

COMP 8006 Assignment 1

Table of Contents

Usage.....	2
Design.....	2
Pseudocode.....	2
Testing.....	2
Nmap.....	2
DNS + WWW	3
Hping - inbound traffic to port 80 (http) from source ports less than 1024.....	3

Usage

```
> ./ez-firewall.sh
```

Design

Pseudocode

Flush all chains

Delete all user chains

Set default policies to DROP for all chains

Create user chain for ssh

Create user chain for www

Drop all packets from port 0

Drop all packets to port 0

Drop inbound traffic to port 80 from source ports 0 to 1023

Jump all packets to and from ports 80 and 443 to www chain

Jump all packets to and from port 22 to ssh chain

Accept all packets to and from port 53

Accept all packets to www chain

Accept all packets to ssh chain

Testing

Testing done with test.sh

Usage:

```
> ./test.sh &> <filename>
```

Nmap

Used for testing inbound packets to port 80,443,53,22,0 with both tcp and udp Protocol

```
# Nmap done at Mon Jan 29 13:43:50 2018 -- 1 IP address (1 host up) scanned  
in 1.51 seconds
```

```
# Nmap 7.60 scan initiated Mon Jan 29 13:46:09 2018 as: nmap -oA results --  
append-output -p 80,443,53,22,0 192.168.0.5
```


```
Nmap scan report for 192.168.0.5
```

```
Host is up (0.00028s latency).
```

PORT	STATE	SERVICE
0/tcp	filtered	unknown
22/tcp	filtered	ssh
53/tcp	closed	domain
80/tcp	closed	http
443/tcp	closed	https

MAC Address: 98:90:96:DC:EB:26 (Dell)

DNS + WWW



Hping - inbound traffic to port 80 (http) from source ports less than 1024

--- 192.168.0.5 hping statistic ---

10 packets transmitted, 0 packets received, 100% packet loss

round-trip min/avg/max = 0.0/0.0/0.0 ms

HPING 192.168.0.5 (eno1 192.168.0.5): S set, 40 headers + 0 data bytes