

# COMP 7402 Assignment 5 Design

Peyman / Dimitry

# Design

This application was written in C and is compiled with cmake. For ease of use two scripts “compile.sh” and “run.sh” which are very self explanatory. The compilation script uses cmake to compile the code correctly while the runner script executes the program on a project file and tests for differences. The runner encrypts and decrypts the input file in both the ECB and CBC modes. The code uses bitwise rotation to permute the initial key passed in through the command line. The key “abcd” which is 32 bits becomes “0x64636261” initially. Here are the permutations of this key:

1. 0x64636261
2. 0xc8c6c4c2
3. 0x918d8985
4. 0x231b130b
5. 0x46362616
6. 0x8c6c4c2c
7. 0x18d89859
8. 0x31b130b2

As you can see, with this method a rather great degree of randomness is added to each round. The function  $f(x,k)$  from the feistel documentation was implemented by using xor on the key and the right section. The blocks of data were originally 8 byte long character arrays but upon further research they were changed to the type `uint64_t` for ease of computation.

# Pseudocode

```
main(Arguments) {
    Parse Arguments
    Validate_inputs()
    Open Input file
    Open Output file
    Generate_keys()
    If (encryption selected) {
        If (ECB selected)
            encrypt_ecb(input, output, keys)
        Else if (CBC selected)
            encrypt_cbc(input, output, keys)
    }else if (decryption selected) {
        If (ECB selected)
            decrypt_ecb(input, output, keys)
        Else if (CBC selected)
            decrypt_cbc(input, output, keys)
    }
}
```

```
encrypt_ecb(input, output, keys) {
    Instantiate 64bit Block
    Instantiate 32 bit sections Left, Right
    While (input not done) {
        Read ( block, 64 bits, from input)
        If ( read error) {
            exit()
        }
        Left = first 32 bits of block
        Right = last 32 bits of block
        Left = xor (Left , xor ( Right , keys) )
        Block = Right + Left // swapped
        Write( Block, 64 bits, into output)
    }
}
```

```
decrypt_ecb(input, output, keys) {
    Instantiate 64bit Block
    Instantiate 32 bit sections Left, Right
    While (input not done) {
        Read ( block, 64 bits, from input)
```

```

        If ( read error) {
            exit()
        }
        Left = first 32 bits of block
        Right = last 32 bits of block
        Left = xor (Left , xor ( Right , keys) ) //keys read in inverse
        Block = Right + Left // swapped
        Write( Block, 64 bits, into output)
    }

}

encrypt_cbc(input, output, keys) {
    Instantiate 64bit Block, Previous_Block
    Instantiate 32 bit sections Left, Right
    Set Previous_Block = 0xFFFFFFFF // for initial value
    While (input not done) {
        Read ( block, 64 bits, from input)
        If ( read error) {
            exit()
        }
        Block = xor(Block, Previous_Block)
        Left = first 32 bits of block
        Right = last 32 bits of block
        Left = xor (Left , xor ( Right , keys) )
        Block = Right + Left // swapped
        Previous_Block = Block
        Write( Block, 64 bits, into output)
    }

}

decrypt_cbc(input, output, keys) {
    Instantiate 64bit Block, Previous_Block, Saved_Block
    Instantiate 32 bit sections Left, Right
    Set First = 1
    While (input not done) {
        Read ( block, 64 bits, from input)
        If ( read error) {
            exit()
        }
        Saved_Block = Block
        Block = xor(Block, Previous_Block)
    }
}

```

```

Left = first 32 bits of block
Right = last 32 bits of block
Left = xor (Left , xor ( Right , keys) ) // Keys in reverse
Block = Right + Left // swapped
If (First is 1) {
    Block = xor( Block, 0xFFFFFFFF) // because of initial value of prev block
    First = 0
} else {
    Block = xor(Block, Previous_Block)
}
Previous_Block = Saved_Block
Write( Block, 64 bits, into output)
}
}

```

# Usage

## Compiling

1. `chmod +x compile.sh`
2. `./compile.sh`

## Testing

1. `chmod +x run.sh`
2. `./run.sh`

## Encrypting

- `./bin/fiestel -e -i <infile> -o <outfile> -k <32bitkey (4chars)>`

## Decrypting

- `./bin/fiestel -d -i <infile> -o <outfile> -k <32bitkey (4chars)>`