Erebus Match Studio

Match Studio 26.2 · Webots R2023b · RoboCupJunior Rescue Simulation 2026



Quick start · Install & run

Branch guide · Features · Changelog · Report an issue

Match Studio combines the Erebus competition environment with an updated supervisor interface, interactive replays and submitted-map review. This **26.2 edition** uses **Webots R2023b** and the **2026 competition rules**.


Match controls Score, clocks, events and referee actions in one compact window.	**Setup and world selection** Organized Robot Setup, Advanced Setup and field previews.
Interactive 3D replays Playback, timeline seeking, camera controls and a final score breakdown.	**Submitted-map review** Compare reported and expected cells, inspect errors and export a PNG or the original matrix.
Events and HUD Timestamped match history, CSV export and events synchronized with replay playback.	**Controller file handling** Keep uploaded files after Reset and optionally reload local source before each match.

Branch guide

Choose the branch that matches your competition and Webots installation.

Branch	Rules	Webots	Use this for
`2026_webots2023b` (this branch)	2026	R2023b	Match Studio 26.2: match supervision, replay and map review.
`2027_webots2025a`	2027 draft	R2025a	Match Studio with battery consumption, cyan contact tiles and smiley victims.
`2028_webots2025a`	Future development	R2025a	Robot Designer and component library; under development.

Quick start · Features · Match files · PDF guide



Match supervision, interactive replay and submitted-map review

Example views of the supervisor, replay and map-review tools. Setup screenshots and the sample map use illustrative data.

Match Studio features

Feature	What you can do
Interactive HTML replay	Replay a saved match in 3D, seek through the timeline and change the camera view.
Match results	Review the final score breakdown, remaining time and playback-synchronized events.
Webots HUD	Show score, time and the latest three events independently of recording.
Submitted-map review	Inspect the accepted map and compare reported and expected values for each cell.
Supervisor interface	View match controls and readouts together, and open setup panels as needed.
Controller source refresh	Reload a local controller from its original file before starting a new match.
File handling	Retain loaded files after Reset and receive clear messages for missing files or invalid robot JSON.
External controllers	Connect using Remote mode or the Docker controls.
Event export	Save the complete timestamped event history as CSV.

Recording, the HUD and map review work with your existing robot controller. Scoring follows the 2026 Erebus rules.

Quick start

What you need

Software	Version	Download / setup
Webots	**R2023b**	Download · Setup
Erebus Match Studio	**2026**	Download ZIP
Python	**3.10 · 64-bit**	Download · Select in Webots
Python packages	requirements.txt	Install below

On Windows, enable **Add Python to PATH** during installation. Select Python 3.10 in **Webots preferences → General → Python command**.

Install Python packages

Extract the Erebus ZIP. Open a terminal in the extracted folder.

Windows

```
py -3.10 -m pip install -r requirements.txt
```

macOS / Linux

```
python3.10 -m pip install -r requirements.txt
```

Packages: NumPy · Requests · termcolor · overrides · Pillow · OpenCV

Start Erebus


1. Open a world file from **game/worlds** in Webots.
2. If Match Studio does not open automatically, right-click **Main Supervisor** in the Webots toolbar and select **Show Robot Window**. Match Studio opens in your default browser.
3. In **Match Studio → Robot Setup**, load your robot program and robot JSON.
4. Press **Run match**.

Example programs · Robot customizer

Match-focused supervisor


Score, clocks, match controls and events stay together on the main page. Robot Setup, Advanced Setup and Worlds share a connected selector row; setup starts collapsed and only one panel opens at a time.

- Read the score with decimal precision.
- Monitor remaining simulation time and the real-world time allowance.
- Resize the window to keep match controls and events visible alongside Webots.
- The battery display stays at **100%** in this edition. Battery consumption is available in the 2027 branch.
- **Open Compact Window** opens a separate, resizable browser window. Allow browser popups if it does not open.



Keep Files and Reload Before Run

Keep Files controls whether the loaded controller and robot JSON copies survive Reset. **Reload Before Run** reads a saved controller program from the manually entered original-file path before a new local match.



Keep Files	Reload Before Run	Behavior
Off	Off	Reset removes loaded copies. Load the controller and JSON again before the next match.
On	Off	Retained copies are used. Editing the original controller does not update the loaded copy.
Off	On	The controller can be copied from its original path for the next match, but robot JSON still needs normal loading after Reset.
On	On	Copies are retained; the controller is refreshed from the original path for each new local match.

The path is on the **computer running Webots**. Relative paths start in the Erebus project folder. Browser file pickers supply file contents, not a portable original full path, so enter the source path manually when using refresh.


The same formats are supported by browser upload and source refresh: `.py`, `.exe`, `.class`, `.jar`, `.bsg`, `.m`, or an executable without an extension. C/C++ programs must already be compiled. **Pause/resume, Remote mode and Docker do not use local source refresh. Robot JSON keeps its normal browser loading workflow.**

If a file or source path is missing, follow the error message in Robot Setup before starting the match. Check controller errors in the Webots console.

Advanced Setup

Use Advanced Setup to configure display, exports and diagnostics. Default settings:

Option	Default
Keep Files	On
Reload Before Run	Off
HTML replay recording	On
Webots HUD	On
Automatically save/open map result	Off
Automatic camera	Off
Keep Remote on Reset	Off
Disable automatic LoP / Enable debugging	Off / Off



Automatic HTML recording

Record an interactive 3D match, then rotate the scene, zoom in or out and replay it in a browser. Recording size depends on the scene assets, movement and match duration.


Replay uses a WebGL-capable browser and loads the viewer from Cyberbotics. See the Webots animation viewer documentation.

Enable **HTML replay recording** before starting the match. Recording starts after the robot and initial HUD are ready. On completion, give-up, timeout or reset, the supervisor finalizes the recording before removing the robot.

Recordings are saved as interactive HTML replays, including the final score and event history.

The recording contains:

- Interactive 3D playback, with play/pause, timeline seeking and camera movement.
- Final score, field score, exit bonus, map bonus and remaining match time.
- Timestamped events. Events follow the playback position when seeking forward or backward.
- A ZIP archive beside the unpacked replay files.



`replay.html` can be opened directly from disk in a supported browser. Keep the complete recording folder for archival and upload. The exported page embeds its scene, animation and local assets; it still needs internet access to load the Webots viewer and a working WebGL implementation.

Embed a replay on a website

Upload the recording folder, preserve its filenames, and serve its `replay.html` over HTTP(S):


```
<iframe
  src="/matches/example/recording/replay.html"
  title="Erebus match replay"
  loading="lazy"
  allowfullscreen
  style="width:100%; height:720px; border:0">
</iframe>
```

The final score and synchronized event display are part of the replay page itself. A website may additionally read `match-result.json` for its own score cards. The ZIP contains a `recording/` directory; extract it without flattening that structure. Configure access permissions on the website where you publish recordings.

Webots HUD

Show head-up display controls the simulation's score, elapsed/maximum match time and latest three events. An event stays visible until newer events replace it. The same labels are captured by HTML recording, while final result metadata includes the completed score and event history.

The HUD and recording switches are independent. Replay events stay synchronized with playback even when the visible HUD is off.




Submitted-map review

At the end of a match, inspect the actual map data submitted by the robot, its correctness result and exactly which reported cells are wrong. Compare reported and expected values, then export the review and raw matrix for further development. The review is available after the supervisor evaluates a submitted map.

The review shows the correctness result used for match scoring.

- **Correct cells fade; incorrect reports stay prominent.**
- **Select a cell** for its raw matrix position, **reported value**, **expected value** and comparison status.
- Rotate left/right in 90° steps, zoom, fit the map or drag to pan.
- Save a PNG of the review, or export the original reported matrix as JSON.
- The initial view fits the useful map automatically. Only an outer margin that is zero in **both** the reference and reported map is cropped.
- Nonzero content in either map remains visible. Cells outside the scorer's comparison are marked separately as **outside comparison**, not silently counted as scored errors.




Automatic map result saves and opens the review when a map is accepted. With that option off, **Save map** still saves and opens the accepted result, including after the robot is removed. The button is unavailable until an evaluated map exists. Repeated saves use the same match folder, and later rejected submissions do not replace the accepted map.

The saved map-review page includes its data and interface assets, so you can reopen it independently.

Export match events as CSV

Press **Export CSV** in Match Events to download the complete history with `Timestamp` and `Event` columns, oldest first.

Export is available during and after the match when events exist. Reset clears the history and disables export until new events arrive. The timestamp is match time, not wall-clock time.



Match files

Each match uses one start-time folder under the project root:

```
match-results/
└── 2026-10-29_14-30-00-123456/
    ├── recording/                  # When HTML recording is enabled
    │   ├── replay.html
    │   ├── replay.json
    │   ├── replay.x3d
    │   ├── replay.css
    │   ├── replay.jpg
    │   ├── match-result.json
    │   ├── textures/               # Exported local assets, when present
    │   └── 2026-10-29_14-30-00-123456.zip
    └── map/                        # When automatic or manual map save is used
        ├── map-review.html
        ├── map-result.json
        └── reported-map.json
```

Other scene dependencies may also be exported. The recording ZIP packages the recording, not the separate map-review directory. Map reviews and recordings are saved independently when their respective options are used.

Credits and licensing

- **Original simulator:** RoboCupJunior Erebus and its contributors.
- **Fork modifications and maintenance:** Peyman Yousefi.
- **Simulation platform:** Webots by Cyberbotics.
- **Competition rules:** RoboCupJunior Rescue Simulation.
- **Interface assets:** IBM Plex Sans, DSEG, Lucide and original upstream fonts, with their bundled notices retained.

This is an independent edition of Erebus maintained by Peyman Yousefi. See NOTICE.md for source and asset licensing, including the bundled IBM Plex Sans, DSEG and Lucide/Feather notices.

See the changelog, release notes and contributing guide. Include your Webots version, operating system and steps to reproduce when reporting an issue.