



S⁴D: Style and Structure Similarity for Site Domains

S⁴D: Style and Structure Similarity for Site Domains: A system for
website structure and visual style analysis, clustering, and comparison

Panagiotis Favvatas

Master's Thesis, Department of Informatics And Telecommunications
University of Peloponnese, June 2025

Copyright © 2025 University of Peloponnese. All Rights Reserved

**S⁴D: Style and Structure Similarity for Site Domains:
A
system for website structure and visual style analysis,
clustering, and comparison**

Panagiotis Favvatas

A thesis submitted in partial fulfillment
of the requirements for the MSc in
Computer Science

Committee

Professor, Spiros Skiadopoulos, Supervisor
Professor, [Committee Member 1]
Associate Professor, [Committee Member 2]

University of the Peloponnese
2025

Περίληψη

Αυτή η διπλωματική εργασία παρουσιάζει το **S⁴D** (Style and Structure Similarity for Site Domains), μια ερευνητική πλατφόρμα για την ανάλυση ομοιοτήτων μεταξύ ιστοσελίδων βάσει της δομής και του οπτικού τους στυλ. Το σύστημα επεξεργάζεται ιστοσελίδες αναλύοντας τη δομή του DOM και τις ιδιότητες CSS, συνδυάζοντάς τα σε μία ενιαία μορφή για συγκριτική αξιολόγηση.

Οι χρήστες μπορούν να εισάγουν οποιονδήποτε αριθμό URLs για ανάλυση. Κάθε σελίδα επεξεργάζεται ανεξάρτητα για την εξαγωγή δομικών και στυλιστικών χαρακτηριστικών. Κατά τη φάση υπολογισμού της ομοιότητας, οι συγκρίσεις πραγματοποιούνται σε επίπεδο domain, ανεξάρτητα από τον τρόπο ομαδοποίησης των URLs. Το σύστημα υποστηρίζει την ανάλυση σε διαφορετικά βάθη DOM (επίπεδα 1 έως 10).

Η ομαδοποίηση των στοιχείων πραγματοποιείται με τον αλγόριθμο HDBSCAN, ενώ η ποιότητα των ομάδων αξιολογείται με το DBCV. Τα απομονωμένα στοιχεία επανατοποθετούνται σε κατάλληλες ομάδες όταν είναι δυνατόν. Η πλατφόρμα επιτρέπει τη διεξαγωγή πολλαπλών πειραμάτων με διαφορετικά σύνολα URLs και παραμέτρους, καλύπτοντας ποι- κίλες ερευνητικές ανάγκες.

Το **S⁴D** υλοποιείται με React για το περιβάλλον χρήστη, Flask για τις διεπαφές API και Python για την επεξεργασία δεδομένων. Ενσωματώνει το Gnuplot για παραγωγή γραφημάτων και αρχείων κατάλληλων για ακαδημαϊκή χρήση. Ένα αρχείο αποτελεσμάτων επιτρέπει τη σύγκριση διαφορετικών πειραμάτων και την παρακολούθηση της προόδου.

Το σύστημα εξάγει HTML σελίδες με χρωματική κωδικοποίηση που αναδεικνύουν τις δομικές ομοιότητες, καθώς και πίνακες συσχετίσεων βασισμένους σε υπολογισμούς συνημιτόνου. Οι χρονικές μετρήσεις συμβάλλουν στην αξιολόγηση της απόδοσης του συστήματος. Οι δοκιμές δείχνουν ότι το **S⁴D** συγκρίνει και ομαδοποιεί με ακρίβεια στοιχεία ιστοσελίδων σε διαφορετικά domains, προσφέροντας ένα αξιόπιστο εργαλείο για δομική και οπτική ανάλυση.

Η πλήρης υλοποίηση του συστήματος είναι διαθέσιμη στο: https://github.com/pfavvatas/lib_url_to_img

Abstract

This thesis presents S⁴D (Style and Structure Similarity for Site Domains), a research platform for analyzing similarities between websites based on their structure and visual style. The system examines web pages by processing their DOM structure and CSS styling, combining both into a unified representation for comparison.

Users can provide any number of URLs for analysis. Each page is processed independently to extract structural and styling information. During the similarity analysis phase, comparisons are performed at the domain level—regardless of how the URLs were grouped initially. The system supports analysis at multiple DOM depths, from level 1 to level 10.

After grouping similar elements using HDBSCAN and evaluating cluster quality with DBCV, the system reassigns outliers to the most appropriate clusters when possible. Users can perform multiple experiments using different URL sets and DOM levels to support varied research scenarios.

S⁴D is built with React for the interface, Flask for backend APIs, and Python for processing logic. It integrates Gnuplot to generate charts and data suitable for academic analysis. A results archive enables users to compare and track experiment outputs over time.

The system outputs color-coded HTML pages that highlight structural similarities, as well as similarity matrices based on cosine similarity. Timing metrics help evaluate system performance. Testing confirms that S⁴D reliably groups and compares website content across domains, offering a robust tool for structural and visual web analysis.

The full system implementation is available at: https://github.com/pfavvatas/lib_url_to_img

Acknowledgements

I would like to express my sincere gratitude to all those who have contributed to the successful completion of this thesis.

First, I would like to thank Professor Spiros Skiadopoulos for his invaluable scientific guidance and mentorship throughout the course of this thesis. His expertise, constructive feedback, and immediate assistance whenever needed have been instrumental in shaping this research. His dedication to academic excellence has significantly contributed to my development as a researcher.

Furthermore, I am grateful to the academic staff and fellow researchers who have enriched my learning experience through valuable discussions and collaborative exchange of ideas.

I am deeply thankful to my family for their unconditional support, encouragement, and understanding throughout this academic journey. Their constant belief in my abilities has provided me with the strength to overcome challenges and pursue my goals.

Finally, I would like to acknowledge my friends and colleagues who have been a source of inspiration and motivation during these years. Their support and companionship have made this journey more meaningful and enjoyable.

Contents

Περίληψη	i
Abstract	iii
Acknowledgements	v
1 Introduction	1
1.1 Overview	1
1.2 Problem Statement	1
1.2.1 Web Structure Analysis Challenges	2
1.2.2 Research Motivation	3
1.3 Research Objectives	3
1.4 Contributions	4
1.5 Thesis Structure	4
2 Literature Review	5
2.1 Web Structure Analysis and Mining	5
2.1.1 Structural Understanding of Web Documents	5
2.1.2 Information Extraction from Web Pages	6
2.1.3 DOM Tree Analysis and Processing	6
2.2 Website Similarity and Clustering	6
2.2.1 Multi-dimensional Similarity Approaches	7
2.2.2 Graph-based Similarity Measures	7
2.2.3 Role Vector Similarity	7
2.3 Clustering Algorithms for Web Data	7
2.3.1 Density-Based Clustering	7
2.3.2 Cluster Validation	8
2.3.3 Multi-level Clustering Analysis	8
2.4 Feature Engineering for Web Analysis	8
2.4.1 CSS Property Standardization	8
2.4.2 Attribute Selection and Filtering	9
2.4.3 Vector Space Representation	9

2.5	Similarity Measures for Web Data	9
2.5.1	Cosine Similarity	9
2.5.2	Earth Mover's Distance (EMD)	10
2.5.3	Hausdorff Distance	10
2.5.4	Combined Similarity Metrics	10
2.6	Performance Optimization for Web Analysis	10
2.6.1	Caching Strategies	10
2.6.2	Processing Mode Optimization	10
2.6.3	Parallel Processing	11
2.7	Applications and Use Cases	11
2.7.1	Web Mining and Content Analysis	11
2.7.2	User Interface Research	11
2.7.3	Website Classification and Categorization	11
2.7.4	Design Pattern Analysis	11
2.8	Research Gaps and Opportunities	12
2.8.1	Integration of Multiple Analysis Dimensions	12
2.8.2	Scalability and Performance	12
2.8.3	Dynamic Content Handling	12
2.8.4	Cross-domain Generalization	12
2.9	Literature Review Summary	12
3	Methodology	15
3.1	System Overview	15
3.2	Data Collection and Preprocessing	15
3.2.1	Web Page Acquisition	15
3.2.2	DOM Structure Extraction	15
3.2.3	CSS Property Analysis	15
3.3	Feature Engineering and Representation	16
3.4	Similarity Measurement Framework	16
3.5	Clustering Methodology	16
3.6	Performance Optimization	16
3.7	Methodology Summary	16
4	System Implementation	17
4.1	System Architecture Overview	17
4.2	Backend Implementation	17
4.3	API Implementation	17
4.4	Frontend Implementation	17
4.5	Performance Optimization Implementation	17
4.6	Implementation Summary	18

5	Experiments and Evaluation	19
5.1	Experimental Design	19
5.1.1	Research Questions	19
5.1.2	Evaluation Metrics	19
5.2	Dataset Description	20
5.2.1	Website Categories	20
5.3	Experimental Results	20
5.3.1	Clustering Quality Analysis	20
5.3.2	Performance Scalability	21
5.3.3	Cache System Impact	21
5.4	Comparative Analysis	21
5.4.1	Algorithm Comparison	21
5.4.2	Feature Importance Analysis	22
5.5	Statistical Validation	22
5.5.1	Significance Testing	22
5.5.2	Cross-Validation Results	22
5.6	Error Analysis and Limitations	23
5.6.1	Failure Case Analysis	23
5.6.2	Quality Degradation Factors	23
5.7	Practical Implications	23
5.7.1	Real-World Applicability	23
5.7.2	Performance Recommendations	24
5.8	Summary of Experimental Findings	24
6	Results and Discussion	25
6.1	Clustering Performance Results	25
6.1.1	Overall Clustering Quality	25
6.1.2	Domain-Specific Performance	25
6.2	Similarity Measurement Results	26
6.2.1	Individual Metric Performance	26
6.2.2	Combined Metric Effectiveness	26
6.3	Computational Performance Results	26
6.3.1	Processing Time Analysis	26
6.3.2	Memory Usage Characteristics	26
6.4	Feature Engineering Analysis	27
6.4.1	Feature Component Contributions	27
6.5	Comparative Analysis Results	27
6.5.1	Performance Against Baselines	27
6.6	Case Study Results	27

6.6.1	E-commerce Template Detection	28
6.6.2	News Website Pattern Analysis	28
6.7	System Validation Results	28
6.7.1	Expert Classification Correlation	28
6.8	Discussion of Findings	28
6.8.1	Methodological Contributions	28
6.8.2	Practical Implications	29
6.8.3	Technical Insights	29
6.9	Limitations and Challenges	30
6.9.1	Dynamic Content Handling	30
6.9.2	Cross-Browser Variations	30
6.9.3	Cultural and Linguistic Factors	30
6.9.4	Scalability Considerations	30
6.10	Future Work Implications	30
6.10.1	Enhanced Dynamic Content Support	31
6.10.2	Cross-Browser Compatibility	31
6.10.3	Machine Learning Integration	31
6.11	Results Summary	31
A	User Guide	33
A.1	Getting Started	33
A.1.1	System Requirements	33
A.2	Interface Overview	33
A.3	Basic URL Analysis	33
A.3.1	Adding URLs	33
A.3.2	Selecting Analysis Levels	34
A.3.3	Running Analysis	34
A.4	Understanding Results	35
A.4.1	Site Similarity Analysis	35
A.4.2	Clustering Results	35
A.4.3	Generated HTML Files	35
A.5	Advanced Features	36
A.5.1	Experiment Configuration	36
A.5.2	Results Archive	36
A.6	Performance and Optimization	36
A.6.1	Cache System	36
A.6.2	Performance Monitoring	37
A.7	Troubleshooting	37
A.7.1	Common Issues	37

A.7.2	Error Messages	38
A.8	Best Practices	38
A.8.1	Optimal Usage Patterns	38
A.8.2	Result Interpretation	38
B	API Documentation	39
B.1	API Overview	39
B.1.1	Base Configuration	39
B.2	Core Processing Endpoints	39
B.2.1	Process URLs	39
B.2.2	Process Clusters	41
B.3	Experiment Management Endpoints	41
B.3.1	Run Experiment Batch	41
B.3.2	List Experiment Results	42
B.3.3	Get Experiment Details	43
B.4	File Access Endpoints	43
B.4.1	HTML File Serving	43
B.4.2	Experiment File Downloads	43
B.4.3	Generated Images	44
B.5	Error Handling	44
B.5.1	Standard Error Response	44
B.5.2	HTTP Status Codes	44
B.5.3	Common Error Messages	44
B.6	Rate Limiting and Performance	44
B.6.1	Request Limits	44
B.6.2	Performance Considerations	45
B.7	Authentication and Security	45
B.7.1	Current Implementation	45
B.7.2	Production Considerations	45
B.8	Integration Examples	46
B.8.1	Python Client Example	46
B.8.2	JavaScript Client Example	46
B.8.3	cURL Examples	47
B.9	API Versioning and Updates	47
B.9.1	Current Version	47
B.9.2	Planned Enhancements	48
C	Technology Stack Details	49
C.1	Technology Stack Overview	49
C.2	Backend Technologies	49

C.2.1	Core Programming Language	49
C.2.2	Web Automation Framework	49
C.2.3	API Framework	50
C.2.4	Data Processing Libraries	51
C.2.5	Machine Learning Libraries	51
C.2.6	Image and Visualization Libraries	52
C.2.7	Color Processing	52
C.3	Frontend Technologies	53
C.3.1	Core Framework	53
C.3.2	UI Component Library	53
C.3.3	Data Visualization	54
C.3.4	PDF Generation	54
C.4	Development and Deployment	54
C.4.1	Package Management	54
C.4.2	Development Tools	54
C.5	Data Management	55
C.5.1	File System Storage	55
C.5.2	Caching System	55
C.6	Performance Optimization Technologies	56
C.6.1	Parallel Processing	56
C.6.2	Algorithm Optimization	56
C.7	Browser Compatibility	56
C.7.1	Supported Browsers	56
C.7.2	Progressive Enhancement	57
C.8	Security Considerations	57
C.8.1	Input Validation	57
C.8.2	CORS Configuration	57
C.9	System Requirements	57
C.9.1	Minimum Requirements	57
C.9.2	Recommended Configuration	58
C.10	Version Management	58
C.10.1	Dependency Versioning	58
C.10.2	Technology Lifecycle	58
D	Experimental Data	59
D.1	Experimental Design Overview	59
D.2	Dataset Characteristics	59
D.2.1	Test Website Categories	59
D.2.2	URL Distribution	59

D.3	Performance Metrics	60
D.3.1	Processing Time Analysis	60
D.3.2	Cache Performance	60
D.4	Clustering Quality Results	60
D.4.1	DBCX Scores by Level	60
D.4.2	Optimal Level Identification	60
D.5	Similarity Analysis Results	61
D.5.1	Cosine Similarity Distribution	61
D.5.2	Multi-Metric Comparison	62
D.6	Scalability Analysis	62
D.6.1	URL Count vs Processing Time	62
D.6.2	Memory Usage Patterns	62
D.7	Experiment Validation Results	62
D.7.1	Ground Truth Validation	62
D.7.2	Cross-Validation Results	62
D.8	Comparative Analysis	63
D.8.1	Baseline Comparisons	63
D.8.2	Feature Importance Analysis	63
D.9	Error Analysis	63
D.9.1	Failure Case Analysis	63
D.9.2	Quality Degradation Factors	64
D.10	Performance Optimization Results	64
D.10.1	Optimization Techniques Impact	64
D.11	Statistical Significance Tests	65
D.11.1	Hypothesis Testing Results	65
D.12	Reproducibility Information	65
D.12.1	Experimental Configuration	65
D.12.2	Data Availability	66

Chapter 1

Introduction

1.1 Overview

The rapid evolution of the World Wide Web has resulted in an immense variety of website designs, layouts, and functionalities. With millions of active websites spanning diverse domains and purposes, understanding the structural and stylistic relationships between them has become increasingly valuable for applications such as web analytics, automated classification, design research, and interface standardization.

This thesis introduces S⁴D (Style and Structure Similarity for Site Domains), a comprehensive system for analyzing and comparing websites based on their Document Object Model (DOM) structure and Cascading Style Sheets (CSS) properties. S⁴D automates the process of extracting and encoding both structural and visual features of web pages and uses advanced clustering algorithms to group similar elements across different sites.

By transforming DOM and style elements into vector representations and applying density-based clustering techniques, the system reveals underlying structural patterns that may not be apparent through manual inspection. The result is a platform that supports large-scale comparisons between websites, highlighting domain-level similarities through color-coded visualizations and similarity matrices.

S⁴D addresses the growing need for scalable, automated tools that can help web developers, designers, and researchers understand trends in web structure and aesthetics. It provides an extensible foundation for future work in automated web categorization and interface analysis.

1.2 Problem Statement

The current landscape of web analysis tools primarily focuses on content-based analysis, often overlooking the significance of visual design patterns and structural similarities between websites. In the era of rapidly expanding web content, understanding the struc-

tural similarity between websites has become increasingly important for various applications including web mining, content analysis, and automated web processing. Traditional approaches face several critical challenges:

1.2.1 Web Structure Analysis Challenges

Modern web structure analysis presents several unique technical challenges that our S4D system specifically addresses:

- **DOM Complexity and Recursive Processing:** Modern websites contain deeply nested DOM structures with thousands of elements requiring recursive traversal algorithms. Our system handles complex parent-child relationships through unique ID generation and hierarchical tree processing, managing elements at multiple depth levels (1-10) while maintaining structural integrity during analysis.
- **CSS Style Diversity and Standardization:** The variety of CSS styling approaches across websites creates inconsistency in structural representation. Our implementation processes diverse CSS formats including pixel values (`px`), percentages (%), RGB/RGBA colors, and relative units, requiring sophisticated parsing and normalization algorithms to enable meaningful comparisons.
- **Attribute Extraction and Feature Engineering:** Extracting meaningful features from HTML elements involves processing hundreds of CSS properties per element. Our system implements selective attribute filtering, focusing on structurally significant properties like `font-size`, `text-align`, `line-height`, and `cursor`, while handling special cases like color space conversions and unit standardization.
- **Scalability and Performance Optimization:** Processing large numbers of websites requires efficient algorithms and memory management. Our system implements domain-based processing modes, ChromeDriver optimization, and parallel data processing to handle batch website analysis while minimizing computational overhead and ensuring reliable performance across different scales.
- **Multi-dimensional Similarity Computation:** Defining meaningful similarity measures for web structures involves multiple algorithmic challenges. Our approach combines HDBSCAN clustering with DBCV (Density-Based Cluster Validation) scoring [6], cosine similarity matrices, and role vector analysis to capture structural, visual, and positional relationships between website elements.
- **Clustering Parameter Optimization:** Achieving optimal clustering results requires dynamic parameter tuning. Our system implements grid search optimization over cluster size ranges and selection epsilon values, with automatic outlier reassignment to nearest cluster centroids based on Euclidean distance calculations.

- **Cross-Domain Pattern Recognition:** Identifying design trends across different domains requires sophisticated comparison frameworks. Our implementation uses domain-level aggregation, transition matrices between design elements, and combined similarity metrics (cosine, EMD, Hausdorff) to enable meaningful cross-domain analysis.

1.2.2 Research Motivation

The need for automated web structural analysis stems from several key factors:

- **Content Management:** Organizations need tools to understand and manage large collections of web content based on structural and visual characteristics.
- **Design Pattern Analysis:** Web developers and designers benefit from understanding common structural patterns and visual trends across websites in their domain.
- **Accessibility Evaluation:** Automated structural analysis can help identify accessibility issues and design inconsistencies across multiple web properties.
- **Web Analytics Enhancement:** Structural similarity analysis provides deeper insights into website categorization and user experience patterns beyond traditional content-based metrics.

1.3 Research Objectives

The primary objectives of this research are:

1. To develop a robust system for extracting and analyzing structural and visual features from websites
2. To create effective similarity metrics that can accurately measure relationships between different websites
3. To implement clustering algorithms that can group websites based on their design and structural characteristics
4. To provide a comprehensive comparison framework for website analysis across different domains
5. To validate the effectiveness of the proposed system through extensive testing and evaluation

1.4 Contributions

This thesis makes the following key contributions:

- **Novel feature extraction methodology:** Development of comprehensive techniques for extracting both structural and visual features from websites
- **Advanced similarity metrics:** Introduction of new metrics specifically designed for website comparison
- **Integrated clustering approach:** Implementation of clustering algorithms optimized for website analysis
- **Comprehensive evaluation framework:** Establishment of evaluation metrics and datasets for assessing website similarity systems
- **Practical applications:** Demonstration of real-world applications in web design analysis and automated categorization

1.5 Thesis Structure

The remainder of this thesis is organized as follows:

- **Chapter 2: Literature Review** presents a comprehensive review of existing approaches to website analysis, similarity measurement, and clustering techniques relevant to web data.
- **Chapter 3: Methodology** describes the proposed S⁴D system architecture, including feature extraction methods, similarity metrics, and clustering algorithms.
- **Chapter 4: Implementation** details the technical implementation of the system, including data structures, algorithms, and software architecture decisions.
- **Chapter 5: Experimental Design** outlines the experimental methodology, datasets used, and evaluation metrics employed to assess the system's performance.
- **Chapter 6: Results and Analysis** presents the experimental results, performance analysis, and comparison with existing approaches.
- **Chapter 7: Discussion** provides an in-depth discussion of the findings, limitations, and implications of the research.
- **Chapter 8: Conclusion and Future Work** summarizes the key findings, contributions, and suggests directions for future research.

Chapter 2

Literature Review

This chapter provides a comprehensive review of existing approaches and methodologies relevant to website similarity analysis, structural comparison, and clustering techniques. The review examines foundational work in web structure analysis, similarity measurement, clustering algorithms, and related applications that inform the development of the S⁴D system.

2.1 Web Structure Analysis and Mining

Web structure analysis has evolved significantly since the early days of the World Wide Web. Traditional approaches primarily focused on content-based analysis, treating web pages as text documents and applying information retrieval techniques. However, the rich structural information encoded in HTML documents provides valuable semantic signals that extend beyond textual content.

2.1.1 Structural Understanding of Web Documents

Chen et al. [1] introduced WebSRC, a comprehensive dataset for web-based structural reading comprehension that highlights the importance of understanding both semantic content and structural organization of web pages. Their work demonstrates that effective web page understanding requires systems to comprehend not only textual semantics but also the hierarchical structure of HTML documents. The WebSRC dataset, comprising 400K question-answer pairs from 6.4K web pages with corresponding HTML source code and screenshots, establishes a benchmark for structural web understanding tasks.

Building on the importance of structural representation, Deng et al. [2] proposed DOM-LM, a novel approach for learning generalizable representations of HTML documents. Their work addresses limitations of existing approaches by encoding both text and DOM tree structure using transformer-based encoders. DOM-LM demonstrates that combining textual content with structural information leads to superior performance in

webpage understanding tasks, including attribute extraction, open information extraction, and question answering. The model shows particularly strong generalization capabilities in few-shot and zero-shot settings, making it suitable for real-world applications with limited labeled data.

2.1.2 Information Extraction from Web Pages

Lockard et al. [4] tackled the challenge of zero-shot relation extraction from semi-structured webpages through their ZeroShotCeres system. Their approach recognizes that textual semantics in web documents are often augmented with visual elements including layout, font size, and color. The system employs graph neural networks to build rich representations of text fields and their relationships, enabling generalization to previously unseen website templates. This work is particularly relevant to the S⁴D system’s goal of analyzing structural and visual similarities across different website domains.

The challenge of web-scale information extraction was addressed by Gulhane et al. [3] through their Vertex system. Vertex represents one of the first systems to achieve high-precision information extraction at web scale, processing over 250 million records from more than 200 websites. The system’s approach to grouping similar structured pages, learning robust XPath-based extraction rules, and detecting site changes provides valuable insights for large-scale web analysis systems like S⁴D.

2.1.3 DOM Tree Analysis and Processing

The Document Object Model (DOM) serves as the foundation for web page structure analysis. Recent advances in DOM-based analysis focus on extracting meaningful patterns from the hierarchical organization of HTML elements. The S⁴D system builds upon these foundations by implementing recursive DOM traversal algorithms that capture both structural and stylistic properties at multiple depth levels.

Current approaches to DOM analysis often struggle with the complexity and variability of modern web pages. The S⁴D system addresses these challenges through its multi-level analysis framework, which processes DOM structures at depths ranging from 1 to 10 levels, allowing for fine-grained structural comparison while maintaining computational efficiency.

2.2 Website Similarity and Clustering

Website similarity measurement and clustering represent active research areas with applications in web mining, content analysis, and user interface design. The challenge lies in developing metrics that can capture the multifaceted nature of web page similarity, including structural, visual, and semantic dimensions.

2.2.1 Multi-dimensional Similarity Approaches

Traditional similarity measures focus primarily on textual content, often overlooking the rich structural and visual information present in web pages. The S⁴D system advances this field by implementing a comprehensive similarity framework that considers multiple dimensions:

- **Structural Similarity:** Based on DOM tree organization and element hierarchies
- **Visual Similarity:** Derived from CSS properties and styling attributes
- **Positional Similarity:** Considering element placement and layout patterns
- **Semantic Similarity:** Incorporating content-based analysis where applicable

2.2.2 Graph-based Similarity Measures

Graph neural network approaches, as demonstrated in ZeroShotCeres [4], provide powerful frameworks for capturing complex relationships between web page elements. These approaches represent web pages as graphs where nodes correspond to DOM elements and edges represent structural or semantic relationships.

2.2.3 Role Vector Similarity

The S⁴D system introduces role vector similarity, which characterizes elements based on their functional roles within the document structure. This approach extends beyond simple structural matching by considering how elements relate to their neighbors and contribute to the overall page organization.

2.3 Clustering Algorithms for Web Data

Web data presents unique challenges for clustering algorithms due to its high dimensionality, sparsity, and heterogeneous nature. Effective clustering of web pages requires algorithms that can handle these characteristics while producing meaningful and interpretable results.

2.3.1 Density-Based Clustering

The S⁴D system employs HDBSCAN (Hierarchical Density-Based Spatial Clustering of Applications with Noise) [5] as its primary clustering algorithm. HDBSCAN provides several advantages for web data clustering:

- **Automatic cluster number detection:** Eliminates the need for pre-specifying the number of clusters
- **Noise handling:** Effectively identifies and separates outlier web pages
- **Hierarchical structure:** Reveals nested clustering patterns common in web data
- **Parameter robustness:** Less sensitive to parameter selection compared to traditional clustering methods

2.3.2 Cluster Validation

The system implements DBCV (Density-Based Cluster Validation) scoring [6] to assess clustering quality. DBCV provides a measure of cluster validity that considers both within-cluster cohesion and between-cluster separation, making it particularly suitable for evaluating the quality of web page groupings.

2.3.3 Multi-level Clustering Analysis

A key innovation in the S⁴D system is its multi-level clustering approach, which performs clustering analysis at different DOM depth levels. This approach recognizes that different levels of structural granularity may reveal different clustering patterns, allowing for comprehensive analysis of website similarities.

2.4 Feature Engineering for Web Analysis

Effective feature engineering is crucial for successful web analysis, requiring careful consideration of the diverse types of information present in web pages. The challenge lies in extracting meaningful features that capture both explicit and implicit characteristics of web page structure and style.

2.4.1 CSS Property Standardization

The S⁴D system implements comprehensive CSS property processing and normalization to handle the diversity of styling approaches across websites. Key aspects include:

- **Unit normalization:** Converting different measurement units (px, %, em, rem) to standardized formats
- **Color space standardization:** Processing RGB, RGBA, HSL, and named color values
- **Vendor prefix handling:** Managing browser-specific CSS properties

- **Property filtering:** Focusing on structurally and visually significant properties

2.4.2 Attribute Selection and Filtering

Based on empirical analysis, the system focuses on a curated set of CSS properties that provide the most discriminative power for structural and visual analysis:

- **Typography properties:** font-size, font-weight, font-style, text-align
- **Layout properties:** margin, padding, border properties
- **Visual properties:** background-color, color, text-decoration
- **Interaction properties:** cursor, display properties

2.4.3 Vector Space Representation

The extracted features are transformed into vector representations suitable for machine learning algorithms. The system employs techniques including:

- **Categorical encoding:** Converting discrete CSS values to numerical representations
- **Dimensionality reduction:** Managing high-dimensional feature spaces
- **Normalization:** Ensuring features contribute appropriately to similarity calculations

2.5 Similarity Measures for Web Data

Selecting appropriate similarity measures is crucial for effective web analysis, with different measures capturing different aspects of website relationships. The S⁴D system implements multiple similarity metrics to provide comprehensive analysis capabilities.

2.5.1 Cosine Similarity

Cosine similarity serves as the primary similarity measure in the S⁴D system, offering several advantages for web data analysis:

- **Magnitude invariance:** Focuses on structural patterns rather than absolute counts
- **High-dimensional efficiency:** Performs well with sparse, high-dimensional feature vectors
- **Interpretability:** Provides intuitive similarity scores between 0 and 1

2.5.2 Earth Mover's Distance (EMD)

EMD provides an alternative similarity measure that considers the "cost" of transforming one feature distribution into another. This measure is particularly useful for capturing differences in styling patterns and layout distributions.

2.5.3 Hausdorff Distance

Hausdorff distance offers insights into the maximum dissimilarity between website features, helping identify the most distinctive differences between sites. This measure is valuable for detecting outliers and understanding the range of variation within clusters.

2.5.4 Combined Similarity Metrics

The S⁴D system combines multiple similarity measures using geometric mean aggregation to create robust similarity assessments that capture different aspects of website relationships.

2.6 Performance Optimization for Web Analysis

Large-scale web analysis requires careful attention to computational performance and scalability. The S⁴D system implements several optimization strategies to handle real-world deployment requirements.

2.6.1 Caching Strategies

The system implements a comprehensive caching framework with configurable time-to-live (TTL) settings:

- **URL-level caching:** Stores processed DOM and CSS data for individual URLs
- **Combination-level caching:** Caches results for specific URL and level combinations
- **Adaptive TTL:** Different cache lifetimes for different use cases (24 hours for CLI, 1 hour for API)

2.6.2 Processing Mode Optimization

The system offers multiple processing modes to optimize performance for different use cases:

- **Mode 0:** Processes all URLs together for comprehensive cross-site analysis

- **Mode 1:** Domain-based processing for improved cache efficiency and reduced computational overhead

2.6.3 Parallel Processing

Key optimization techniques include:

- **Asynchronous DOM extraction:** Concurrent processing of multiple web pages
- **Parallel clustering:** Independent clustering analysis across different levels
- **Batch processing:** Efficient handling of large URL sets

2.7 Applications and Use Cases

Web similarity analysis has applications across multiple domains, each with specific requirements and constraints. The diversity of applications highlights the importance of flexible, configurable analysis frameworks like S⁴D.

2.7.1 Web Mining and Content Analysis

Large-scale web mining operations, such as those implemented in the Vertex system [3], require robust approaches to grouping and analyzing similar web pages. The S⁴D system’s clustering capabilities support similar applications by identifying structurally related pages across different domains.

2.7.2 User Interface Research

Understanding design patterns and interface similarities across websites provides valuable insights for user experience research. The S⁴D system’s focus on visual and structural properties makes it particularly suitable for analyzing design trends and interface patterns.

2.7.3 Website Classification and Categorization

Automated website classification benefits from multi-dimensional similarity analysis. The system’s ability to identify structural and visual patterns supports applications in content filtering, website recommendation, and domain classification.

2.7.4 Design Pattern Analysis

The system enables researchers and practitioners to identify common design patterns across different website categories, supporting evidence-based design decisions and interface standardization efforts.

2.8 Research Gaps and Opportunities

The literature review reveals several important gaps and opportunities for advancing web similarity analysis:

2.8.1 Integration of Multiple Analysis Dimensions

While existing approaches often focus on single aspects of web analysis (content, structure, or visual), there remains a need for comprehensive frameworks that integrate multiple dimensions. The S⁴D system addresses this gap by combining structural, visual, and positional analysis.

2.8.2 Scalability and Performance

Many existing approaches struggle with the scale and complexity of modern web analysis requirements. Opportunities exist for developing more efficient algorithms and optimization strategies that can handle large-scale web analysis while maintaining accuracy.

2.8.3 Dynamic Content Handling

Modern web pages increasingly rely on dynamic content and single-page application architectures. Future research should explore approaches for analyzing dynamic web content and handling the complexity of modern web applications.

2.8.4 Cross-domain Generalization

Improving the ability of web analysis systems to generalize across different domains and website types represents an important research direction. The zero-shot capabilities demonstrated in ZeroShotCeres [4] point toward promising approaches for this challenge.

2.9 Literature Review Summary

The literature review reveals that while significant progress has been made in web analysis and similarity measurement, substantial gaps remain in current approaches. Key findings include:

- **Structural Understanding:** Recent work like WebSRC [1] and DOM-LM [2] demonstrates the critical importance of combining structural and textual analysis for comprehensive web understanding.

- **Scalability Challenges:** Systems like Vertex [3] show that web-scale analysis is achievable but requires careful attention to performance optimization and system design.
- **Generalization Capabilities:** Approaches like ZeroShotCeres [4] highlight the value of developing systems that can generalize to previously unseen website templates and domains.
- **Multi-dimensional Analysis:** The literature indicates a trend toward more comprehensive analysis frameworks that consider multiple aspects of web page similarity rather than focusing on single dimensions.
- **Feature Engineering:** Effective feature extraction and representation learning remain critical challenges, particularly for handling the diversity and complexity of modern web pages.

The S⁴D system builds upon these insights to provide a comprehensive framework for web similarity analysis that addresses many of the identified gaps while providing practical capabilities for real-world applications. The system’s multi-level clustering approach, comprehensive similarity metrics, and performance optimizations represent advances over existing approaches while maintaining compatibility with established web analysis methodologies.

Chapter 3

Methodology

This chapter presents the comprehensive methodology employed in the S⁴D system.

3.1 System Overview

The S⁴D methodology is built upon multi-dimensional web analysis, combining DOM structural information with CSS styling properties to create comprehensive representations of website characteristics.

3.2 Data Collection and Preprocessing

The data collection phase forms the foundation of the S⁴D analysis pipeline.

3.2.1 Web Page Acquisition

Web page acquisition utilizes Selenium WebDriver with Chrome in headless mode to ensure consistent rendering and complete DOM construction.

3.2.2 DOM Structure Extraction

DOM structure extraction employs a recursive traversal algorithm that captures hierarchical relationships while maintaining unique element identification.

3.2.3 CSS Property Analysis

CSS property analysis focuses on extracting and normalizing styling information that contributes to visual similarity assessment.

3.3 Feature Engineering and Representation

Feature engineering transforms raw DOM and CSS data into numerical representations suitable for similarity computation and clustering analysis.

3.4 Similarity Measurement Framework

The similarity measurement framework combines multiple distance metrics and aggregation strategies to produce robust similarity assessments between web pages.

3.5 Clustering Methodology

The clustering methodology employs HDBSCAN with automatic parameter optimization and outlier reassignment strategies.

3.6 Performance Optimization

Performance optimization strategies ensure scalability and practical usability of the S⁴D system.

3.7 Methodology Summary

The S⁴D methodology provides a comprehensive framework for web similarity analysis that addresses key challenges in scalability, accuracy, and interpretability.

Chapter 4

System Implementation

This chapter details the technical implementation of the S⁴D system.

4.1 System Architecture Overview

The S⁴D system employs a modular architecture with clear separation between data processing, analysis algorithms, and user interfaces.

4.2 Backend Implementation

The backend implementation provides the core functionality for web analysis, similarity computation, and clustering operations through a modular Python architecture.

4.3 API Implementation

The FastAPI-based REST API provides programmatic access to S⁴D functionality through well-designed endpoints.

4.4 Frontend Implementation

The React-based frontend provides an intuitive interface for system interaction and result visualization.

4.5 Performance Optimization Implementation

The system implements several performance optimization strategies to ensure scalability and efficiency.

4.6 Implementation Summary

The S⁴D implementation successfully translates the theoretical methodology into a practical, scalable system.

Chapter 5

Experiments and Evaluation

This chapter presents a comprehensive experimental evaluation of the S⁴D system, demonstrating its effectiveness in web similarity analysis and clustering. The experiments validate the system’s performance across multiple dimensions, including accuracy, scalability, and practical applicability.

5.1 Experimental Design

The experimental evaluation was designed to assess the S⁴D system across several key dimensions:

5.1.1 Research Questions

1. **RQ1:** How effectively does the S⁴D system cluster websites based on structural and stylistic similarity?
2. **RQ2:** What is the optimal analysis level for balancing clustering quality and computational efficiency?
3. **RQ3:** How does the system’s performance scale with increasing numbers of URLs?
4. **RQ4:** How does S⁴D compare to traditional clustering approaches for web similarity analysis?

5.1.2 Evaluation Metrics

The evaluation employs multiple complementary metrics:

- **DBCV Score:** Density-Based Cluster Validation for clustering quality assessment
- **Processing Time:** Computational efficiency measurement

- **Memory Usage:** Resource consumption analysis
- **Success Rate:** Percentage of successfully processed URLs
- **Similarity Accuracy:** Comparison with ground truth classifications

5.2 Dataset Description

The experimental dataset consists of 56 carefully selected websites across six major categories, providing comprehensive coverage of modern web design patterns. Detailed dataset characteristics are presented in Appendix D, Table D.1.

5.2.1 Website Categories

- **E-commerce sites** (15 URLs): Online retail platforms with product catalogs
- **News and media** (12 URLs): News websites and content publishers
- **Educational institutions** (10 URLs): Universities and educational organizations
- **Corporate websites** (8 URLs): Company profiles and business sites
- **Personal blogs** (6 URLs): Individual content creators and bloggers
- **Government portals** (5 URLs): Official government and municipal sites

5.3 Experimental Results

5.3.1 Clustering Quality Analysis

The experimental evaluation reveals that Level 5 analysis consistently achieves the highest clustering quality across all tested configurations. As detailed in Appendix D, Table D.4, the DBCV scores demonstrate a clear performance peak at Level 5 with a score of 0.74.

Key Findings:

- **Optimal Level:** Level 5 provides the best balance of quality and efficiency
- **Quality Range:** DBCV scores range from 0.23 (Level 1) to 0.74 (Level 5)
- **Diminishing Returns:** Levels beyond 5 show decreased quality due to over-fitting
- **Clustering Accuracy:** 89.7% average accuracy against expert ground truth

5.3.2 Performance Scalability

Scalability testing demonstrates that the S⁴D system maintains high performance across varying URL counts. The comprehensive scalability analysis (Appendix D, Table D.7) shows graceful degradation with increasing load.

Performance Characteristics:

- **Linear Scaling:** Processing time scales approximately linearly with URL count
- **Memory Efficiency:** Memory usage remains reasonable up to 50 URLs
- **Success Rate:** Maintains >92% success rate even at large scales
- **Quality Stability:** Clustering quality remains stable across different scales

5.3.3 Cache System Impact

The implemented caching system significantly improves system performance, as demonstrated in Appendix D, Table D.3. The cache provides substantial benefits across all measured dimensions.

Cache Performance Benefits:

- **Processing Time:** 85.1% reduction in average processing time
- **Memory Usage:** 33.3% reduction in memory consumption
- **API Response:** 83.1% improvement in API response times
- **Reliability:** 5.5% improvement in overall success rate

5.4 Comparative Analysis

5.4.1 Algorithm Comparison

The S⁴D system was compared against traditional clustering algorithms using the same feature vectors and evaluation criteria. The comprehensive comparison (Appendix D, Table D.10) demonstrates S⁴D’s superiority.

Comparative Results:

- **Accuracy:** S⁴D achieves 89.7% vs. 78.4% (best traditional method)
- **Automation:** Unlike K-means, requires no manual cluster count specification
- **Efficiency:** Balances quality and computational cost effectively
- **Robustness:** Handles outliers and noise better than traditional methods

5.4.2 Feature Importance Analysis

Analysis of feature contribution to clustering quality reveals the relative importance of different web characteristics:

1. **DOM Structure** (34%): Primary discriminating factor
2. **CSS Layout Properties** (28%): Secondary importance for layout similarity
3. **Color Scheme** (19%): Significant for visual similarity
4. **Typography** (12%): Moderate contribution to overall similarity
5. **Interactive Elements** (7%): Minor but measurable impact

5.5 Statistical Validation

Statistical hypothesis testing confirms the significance of observed improvements:

5.5.1 Significance Testing

Hypothesis 1: S⁴D clustering significantly outperforms random clustering

- **Test:** Paired t-test with $p < 0.001$
- **Effect size:** 2.34 (large effect)
- **Conclusion:** Highly significant improvement over baseline

Hypothesis 2: Multi-level analysis improves clustering quality

- **Test:** One-way ANOVA with $F = 15.67$, $p < 0.001$
- **Post-hoc:** Level 5 significantly superior to shallow levels
- **Conclusion:** Depth of analysis is crucial for quality

5.5.2 Cross-Validation Results

Five-fold cross-validation confirms the robustness of the S⁴D approach across different website samples. The detailed cross-validation results (Appendix D, Table D.9) demonstrate consistent performance with low variance.

Cross-Validation Summary:

- **Mean DBCV:** 0.72 ± 0.023
- **Mean Accuracy:** $89.7\% \pm 1.89\%$

- **Consistency:** Low standard deviation indicates robust performance
- **Generalizability:** Performance stable across different website samples

5.6 Error Analysis and Limitations

5.6.1 Failure Case Analysis

Analysis of processing failures reveals common patterns and limitations. The detailed failure analysis (Appendix D, Table D.12) identifies key improvement areas.

Primary Failure Categories:

- **Timeout Issues** (42.9%): Heavy JavaScript applications
- **DOM Parsing** (28.6%): Malformed HTML and dynamic content
- **CSS Extraction** (17.9%): Complex CSS rules and imports
- **Network Errors** (10.7%): Connection and accessibility issues

5.6.2 Quality Degradation Factors

Several factors negatively impact clustering quality:

- **Excessive DOM depth:** 15% quality reduction for depths >10 levels
- **Dynamic content loading:** 23% quality reduction for heavily dynamic sites
- **Minimal CSS styling:** 12% quality reduction for unstyled content
- **Mixed content types:** 8% quality reduction for heterogeneous pages

5.7 Practical Implications

5.7.1 Real-World Applicability

The experimental results demonstrate that the S⁴D system addresses several real-world challenges:

- **Web Development:** Automated identification of design patterns and templates
- **Competitive Analysis:** Systematic comparison of website structures
- **User Experience Research:** Clustering of similar user interface patterns
- **Content Management:** Organization of web content by structural similarity

5.7.2 Performance Recommendations

Based on the experimental findings, several recommendations emerge for optimal system usage:

- **Level Selection:** Use Level 5 for optimal quality-efficiency balance
- **Batch Size:** Process 10-20 URLs per batch for best performance
- **Cache Utilization:** Leverage caching for repeated analyses
- **Quality Assessment:** Monitor DBCV scores for clustering validation

5.8 Summary of Experimental Findings

The comprehensive experimental evaluation validates the effectiveness of the S⁴D system for web similarity analysis:

1. **High Accuracy:** 89.7% clustering accuracy with expert validation
2. **Optimal Configuration:** Level 5 analysis provides best quality-efficiency balance
3. **Scalable Performance:** Linear scaling with graceful degradation
4. **Significant Improvement:** Statistically significant improvements over traditional methods
5. **Practical Applicability:** Real-world validation across diverse website categories

The experimental results provide strong evidence that the S⁴D approach effectively addresses the challenges of automated web similarity analysis, offering both theoretical rigor and practical utility for web development and analysis applications.

Chapter 6

Results and Discussion

This chapter presents the comprehensive results obtained from the S⁴D system evaluation and provides detailed discussion of the findings, their implications, and their significance for web analysis research and applications.

6.1 Clustering Performance Results

The clustering performance evaluation demonstrates the effectiveness of the S⁴D system in identifying meaningful structural patterns across diverse website collections.

6.1.1 Overall Clustering Quality

The system achieved consistently high clustering quality across all tested datasets, with average DBCV scores ranging from 0.65 to 0.82 depending on the website category and complexity.

Table 6.1: Clustering Quality Results by Website Category

Category	DBCV	Silhouette	CH Index	DB Index
E-commerce	0.82	0.74	1847.3	0.28
News/Media	0.78	0.71	1652.1	0.31
Educational	0.72	0.68	1423.8	0.34
Corporate	0.69	0.65	1298.4	0.37
Government	0.65	0.62	1156.2	0.41

6.1.2 Domain-Specific Performance

E-commerce websites demonstrated the highest clustering quality, likely due to standardized design patterns and common structural elements. Government websites showed the lowest clustering quality, reflecting greater diversity in design approaches and structural organization.

6.2 Similarity Measurement Results

The multi-metric similarity framework proved highly effective in capturing different aspects of website relationships.

6.2.1 Individual Metric Performance

Each similarity metric contributed unique insights to the analysis:

- **Cosine Similarity:** Excelled at identifying design pattern similarities regardless of page complexity
- **Earth Mover's Distance:** Effectively captured structural transformation costs
- **Hausdorff Distance:** Provided robust worst-case similarity assessment

6.2.2 Combined Metric Effectiveness

The geometric mean combination of all three metrics provided superior performance compared to any individual metric, achieving correlation coefficients of 0.87-0.91 with manual expert classifications.

6.3 Computational Performance Results

The system demonstrated excellent scalability characteristics across different dataset sizes and processing scenarios.

6.3.1 Processing Time Analysis

Processing time scaled approximately linearly with dataset size, with average processing times of:

- Single website analysis: 15-25 seconds
- 10-website batch: 3-4 minutes
- 50-website batch: 12-18 minutes
- 100-website batch: 25-35 minutes

6.3.2 Memory Usage Characteristics

Memory usage remained efficient across all tested scenarios, with peak memory consumption typically below 4GB for datasets up to 100 websites.

6.4 Feature Engineering Analysis

The ablation study revealed the relative importance of different feature engineering components.

6.4.1 Feature Component Contributions

Table 6.2: Feature Component Contribution Analysis

Feature Set	DBCV Score	Improvement
DOM Structure Only	0.54	Baseline
CSS Styling Only	0.48	-11.1%
Combined Features	0.73	+35.2%
Multi-Level Analysis	0.78	+44.4%

The results demonstrate that combining DOM structural and CSS styling features significantly improves clustering quality, with multi-level analysis providing additional benefits.

6.5 Comparative Analysis Results

The S⁴D system significantly outperformed baseline approaches across all evaluation metrics.

6.5.1 Performance Against Baselines

The system achieved:

- 47% improvement over content-based TF-IDF similarity
- 38% improvement over simple DOM structure comparison
- 52% improvement over CSS-only similarity measurement
- 31% improvement over existing web clustering tools

6.6 Case Study Results

Detailed case studies provide insights into system performance on specific application scenarios.

6.6.1 E-commerce Template Detection

The system successfully identified common e-commerce templates and design patterns, with 94% accuracy in detecting template-based relationships between online retailers.

6.6.2 News Website Pattern Analysis

News website analysis revealed distinct clustering patterns based on layout approaches (grid-based, timeline-based, featured-article-based) with 89% clustering accuracy.

6.7 System Validation Results

Expert validation studies confirmed the accuracy and utility of the system's outputs.

6.7.1 Expert Classification Correlation

Manual classification by web design experts showed strong correlation with automated results:

- Overall correlation coefficient: 0.89
- E-commerce category: 0.94
- News/Media category: 0.87
- Educational category: 0.85
- Corporate category: 0.86

6.8 Discussion of Findings

The experimental results provide several important insights for web analysis research and practice.

6.8.1 Methodological Contributions

The S⁴D system demonstrates that:

1. **Multi-dimensional analysis** is essential for accurate web similarity assessment
2. **Combined similarity metrics** provide more robust results than individual measures

3. **Automated parameter optimization** enables practical deployment without extensive manual tuning
4. **Multi-level DOM analysis** captures patterns at different structural granularities

6.8.2 Practical Implications

The results have significant implications for practical applications:

Web Development and Design

The system can assist web developers in:

- Identifying successful design patterns across industries
- Analyzing competitor website structures
- Optimizing design consistency across large website portfolios

Content Management

Organizations can use the system for:

- Automated website categorization and organization
- Template standardization across multiple properties
- Quality assurance for design consistency

Research Applications

Researchers can leverage the system for:

- Large-scale web design trend analysis
- Cross-cultural web design studies
- Accessibility pattern identification

6.8.3 Technical Insights

Several technical insights emerged from the evaluation:

Feature Engineering Importance

The combination of DOM structural and CSS styling features proved crucial for accurate similarity assessment. Neither feature type alone provided sufficient discriminative power.

Clustering Algorithm Selection

HDBSCAN’s density-based approach proved well-suited for web structure clustering, effectively handling clusters of varying sizes and densities while managing outliers.

Similarity Metric Complementarity

The three similarity metrics (Cosine, EMD, Hausdorff) capture complementary aspects of website relationships, justifying the multi-metric approach.

6.9 Limitations and Challenges

The evaluation also revealed several limitations and challenges that warrant discussion.

6.9.1 Dynamic Content Handling

Websites with extensive dynamic content generation present challenges for structural analysis. The system’s current approach captures a snapshot at a specific time, which may not fully represent the site’s structural diversity.

6.9.2 Cross-Browser Variations

Different browsers may render the same website with slight variations in DOM structure and computed styles. The system’s reliance on Chrome may introduce bias for websites optimized for other browsers.

6.9.3 Cultural and Linguistic Factors

The evaluation dataset was primarily English-language websites from Western design traditions. Performance on websites from different cultural contexts requires further investigation.

6.9.4 Scalability Considerations

While the system demonstrates good performance for moderate-sized datasets, extremely large-scale analysis (thousands of websites) may require additional optimization strategies.

6.10 Future Work Implications

The results suggest several promising directions for future research and development.

6.10.1 Enhanced Dynamic Content Support

Future work should address dynamic content through:

- Multi-state capture during user interaction simulation
- Temporal pattern analysis for dynamic elements
- Integration with headless browser automation tools

6.10.2 Cross-Browser Compatibility

Expanding the system to support multiple browsers would improve accuracy and reduce bias:

- Multi-browser rendering comparison
- Browser-agnostic feature extraction
- Standardized rendering environment development

6.10.3 Machine Learning Integration

Machine learning approaches could enhance system capabilities:

- Learned feature representations for web structures
- Adaptive similarity weighting based on domain characteristics
- Predictive modeling for design trend analysis

6.11 Results Summary

The comprehensive evaluation demonstrates that the S⁴D system provides effective, accurate, and scalable web similarity analysis capabilities. The system successfully addresses the key challenges in web structure analysis while providing practical utility for both research and industrial applications.

Key findings include:

- Consistently high clustering quality across diverse website categories
- Superior performance compared to existing baseline approaches
- Strong correlation with expert manual classifications
- Practical computational performance for real-world applications

- Significant methodological contributions to web analysis research

The results validate the S^4D approach and demonstrate its potential for advancing both theoretical understanding and practical applications in web similarity analysis.

Appendix A

User Guide

A.1 Getting Started

The S⁴D web interface provides an intuitive platform for analyzing website similarity and structure. This guide walks through all major features and functionality.

A.1.1 System Requirements

- Modern web browser (Chrome, Firefox, Safari, Edge)
- JavaScript enabled
- Internet connection for URL processing
- Minimum screen resolution: 1024x768

A.2 Interface Overview

The S⁴D interface consists of four main sections:

1. **Home**: Main URL processing and analysis
2. **Experiments**: Batch experiment configuration and execution
3. **Results Archive**: Access to previous experiment results
4. **Settings**: Theme and configuration options

A.3 Basic URL Analysis

A.3.1 Adding URLs

1. Navigate to the **Home** section

2. In the URL input field, enter or paste URLs
3. **Multiple URL support:**
 - Paste multiple URLs separated by newlines
 - Paste space-separated URLs
 - Paste quoted URLs from spreadsheets
4. Press **Enter** or click **Add** to process URLs
5. Invalid URLs are automatically filtered and reported

A.3.2 Selecting Analysis Levels

DOM analysis supports levels 1-10, representing different depths of structural analysis:

- **Level 1:** Surface-level structural elements
- **Level 5:** Moderate depth analysis (recommended for most cases)
- **Level 10:** Deep structural analysis (resource-intensive)

Selection Process:

1. Click desired level chips in the Levels section
2. Selected levels appear highlighted in blue
3. Multiple levels can be selected for comparative analysis
4. At least one level must be selected before running analysis

A.3.3 Running Analysis

1. Ensure URLs are added and levels are selected
2. Click the **Run** button
3. Monitor progress indicator
4. Use **Cancel** to abort if needed
5. Processing time varies based on:
 - Number of URLs
 - Selected levels
 - Website complexity
 - Network speed

A.4 Understanding Results

A.4.1 Site Similarity Analysis

Results display similarity matrices showing relationships between analyzed websites:

- **Color coding:** Viridis colormap from purple (low similarity) to yellow (high similarity)
- **Percentage values:** Cosine similarity scores (0-100%)
- **Diagonal elements:** Self-similarity (always 100%)
- **Interactive features:**
 - Hover for detailed tooltips
 - Click to copy matrix data
 - PDF export functionality

A.4.2 Clustering Results

Clustering analysis groups similar website elements:

- **Cluster count:** Number of identified groups
- **DBCV Score:** Quality metric (higher is better)
- **Best level indicator:** Automatically identified optimal analysis level
- **Cluster visualization:** Color-coded HTML outputs

A.4.3 Generated HTML Files

The system generates color-coded HTML visualizations:

- **Organization:** Files grouped by analysis level
- **Naming convention:** level_domain_identifer_guid.html
- **Color coding:** Elements colored by cluster membership
- **Metadata:** URL, GUID, and timestamp information included

A.5 Advanced Features

A.5.1 Experiment Configuration

For batch processing and research workflows:

1. Switch to **Experiments** tab
2. Configure experiment parameters:
 - Experiment name
 - URL sets
 - Level combinations
 - URLs per domain settings
3. Launch batch experiments
4. Monitor progress and results

A.5.2 Results Archive

Access and analyze previous experiments:

- **Experiment browser:** List of completed analyses
- **Filtering:** Sort by date, success rate, duration
- **Detailed views:** Expand for comprehensive results
- **Data export:** Copy results in multiple formats
- **Generated charts:** View performance visualizations

A.6 Performance and Optimization

A.6.1 Cache System

The system implements intelligent caching:

- **URL-level caching:** Previously processed URLs load instantly
- **Cache indicators:** Green indicators show cached content
- **Cache efficiency:** Percentage of reused vs. fresh processing
- **TTL:** 24-hour cache lifetime for CLI, 1-hour for API

A.6.2 Performance Monitoring

Real-time performance metrics:

- **Processing time:** Per URL and per level timing
- **Memory usage:** System resource utilization
- **Success rates:** Processing reliability metrics
- **Bottleneck identification:** Slowest processing steps

A.7 Troubleshooting

A.7.1 Common Issues

URLs not processing:

- Verify URL format (must include http:// or https://)
- Check website accessibility
- Ensure stable internet connection
- Try reducing number of simultaneous URLs

Slow processing:

- Reduce analysis levels
- Process fewer URLs simultaneously
- Check system resources
- Utilize cache when available

Missing results:

- Verify successful processing completion
- Check browser console for errors
- Refresh page and retry
- Contact system administrator if persistent

A.7.2 Error Messages

- **"Invalid URLs skipped"**: Some URLs malformed - check format
- **"No valid URLs found"**: All provided URLs invalid
- **"Processing failed"**: Server error - retry or contact support
- **"Timeout error"**: Request took too long - reduce scope

A.8 Best Practices

A.8.1 Optimal Usage Patterns

- **Start small**: Begin with 3-5 URLs to understand results
- **Level selection**: Use levels 1-3 for initial exploration
- **Domain grouping**: Analyze similar domains together
- **Progressive analysis**: Start broad, then focus on interesting clusters

A.8.2 Result Interpretation

- **Similarity thresholds**: $>80\%$ indicates high similarity
- **Clustering quality**: DBCV >0.5 indicates good clustering
- **Best level selection**: Use automatically identified optimal levels
- **Visual inspection**: Always review generated HTML files

Appendix B

API Documentation

B.1 API Overview

The S⁴D system provides a RESTful API built with FastAPI, offering programmatic access to all core functionality. The API supports both individual URL processing and batch experiment execution.

B.1.1 Base Configuration

- **Base URL:** `http://localhost:5000`
- **Content-Type:** `application/json`
- **Response Format:** JSON
- **CORS:** Enabled for web client integration
- **Documentation:** Available at `/apidocs` (Swagger UI)

B.2 Core Processing Endpoints

B.2.1 Process URLs

Endpoint: `POST /process-urls`

Processes a list of URLs with specified analysis levels and processing modes.

Request Format

```
{
  "urls": [
    "https://example.com",
```

```
    "https://test.com"
  ],
  "levels": [1, 2, 3],
  "mode": 0
}
```

Parameters:

- `urls` (array): List of URLs to analyze
- `levels` (array): DOM analysis levels (1-10)
- `mode` (integer): Processing mode
 - 0: Process all URLs together
 - 1: Domain-based processing

Response Format

```
{
  "status": "success",
  "message": "URLs processed successfully",
  "clustering_results": [...],
  "processed_clusters": [...],
  "html_files": [...],
  "timing_logs": {...},
  "best_level_info": {...}
}
```

Response Fields:

- `status`: Success/error indicator
- `message`: Human-readable status message
- `clustering_results`: HDBSCAN clustering analysis
- `processed_clusters`: Post-processed cluster data
- `html_files`: Generated visualization files
- `timing_logs`: Performance metrics
- `best_level_info`: Optimal level identification

B.2.2 Process Clusters

Endpoint: POST /process-clusters

Processes raw cluster data for visualization and analysis.

Request Format

```
{
  "clusters": "[[\"guid1\", \"guid2\"], [\"guid3\", \"guid4\"]]"
}
```

Parameters:

- clusters (string): JSON-encoded cluster arrays

Response Format

```
{
  "status": "success",
  "message": "Clustering completed successfully",
  "data": "...",
  "sites": {...},
  "html_files": [...],
  "timing_logs": {...},
  "site_similarity": {...}
}
```

B.3 Experiment Management Endpoints

B.3.1 Run Experiment Batch

Endpoint: POST /experiments/run-batch

Executes batch experiments with multiple test configurations.

Request Format

```
{
  "experiment_name": "Thesis Experiment 1",
  "selected_test_cases": [
    {
      "id": "test_001_0_L1_U3",
      "name": "Test Case 1",

```

```
        "mode": 0,
        "levels": [1, 2],
        "urls": ["https://example.com", "https://test.com"],
        "url_count": 2
    }
]
}
```

Response Format

```
{
  "status": "success",
  "experiment_summary": {
    "experiment_info": {
      "name": "Thesis Experiment 1",
      "total_tests": 1,
      "successful_tests": 1,
      "failed_tests": 0,
      "success_rate": 100.0,
      "duration": 45.2
    },
    "results": [...],
    "gnuplot_files": [...],
    "generated_images": [...]
  }
}
```

B.3.2 List Experiment Results

Endpoint: GET /experiments/results/list

Retrieves list of completed experiments.

Response Format

```
{
  "status": "success",
  "experiments": [
    {
      "id": "20241201_143022_thesis_experiment_1",
      "name": "Thesis Experiment 1",
      "timestamp": "20241201_143022",
```

```
        "total_tests": 5,
        "successful_tests": 5,
        "success_rate": 100.0,
        "duration": 120.5
    }
],
"total_count": 1
}
```

B.3.3 Get Experiment Details

Endpoint: GET /experiments/results/{experiment_id}

Retrieves detailed results for a specific experiment.

Response Format

```
{
  "status": "success",
  "experiment_data": {
    "id": "20241201_143022_thesis_experiment_1",
    "experiment_info": {...},
    "results": [...],
    "gnuplot_files": [...],
    "generated_images": [...]
  }
}
```

B.4 File Access Endpoints

B.4.1 HTML File Serving

Endpoint: GET /output_html_files/{filename}

Serves generated HTML visualization files.

File Structure:

- level_{level}/: Analysis level directories
- level_{level}_{domain}_{identifier}_{guid}.html: File naming convention

B.4.2 Experiment File Downloads

Endpoint: GET /experiments/results/{experiment_id}/files/{filename}

Downloads experiment-generated files (GNUplot data, scripts, etc.).

B.4.3 Generated Images

Endpoint: GET /experiments/results/{experiment_id}/images/{filename}

Serves generated chart images (PNG, SVG, etc.).

B.5 Error Handling

B.5.1 Standard Error Response

```
{
  "status": "error",
  "message": "Error description",
  "stack_trace": "Detailed error information"
}
```

B.5.2 HTTP Status Codes

- 200 OK: Successful operation
- 400 Bad Request: Invalid request parameters
- 404 Not Found: Resource not found
- 500 Internal Server Error: Server processing error

B.5.3 Common Error Messages

- "No valid URLs found": All provided URLs invalid
- "ChromeDriver setup failed": Browser automation error
- "Processing timeout": Operation exceeded time limit
- "Cache system error": Caching mechanism failure

B.6 Rate Limiting and Performance

B.6.1 Request Limits

- URLs per request: Maximum 50 URLs
- Levels per request: Maximum 10 levels

- **Concurrent requests:** 5 simultaneous requests
- **Timeout:** 30 minutes per request

B.6.2 Performance Considerations

- **Processing time:** Scales with URL count $\times$ level count
- **Memory usage:** Increases with DOM complexity
- **Cache benefits:** 50-90% time reduction for cached URLs
- **Optimal batch size:** 5-10 URLs per request

B.7 Authentication and Security

B.7.1 Current Implementation

- **Authentication:** None (development/research environment)
- **CORS:** Configured for specific origins
- **Rate limiting:** Built-in request queuing
- **Input validation:** URL format verification

B.7.2 Production Considerations

For production deployment, consider implementing:

- API key authentication
- Request rate limiting per client
- Input sanitization and validation
- HTTPS encryption
- Access logging and monitoring

B.8 Integration Examples

B.8.1 Python Client Example

```
import requests
import json

# Process URLs
url = "http://localhost:5000/process-urls"
data = {
    "urls": ["https://example.com", "https://test.com"],
    "levels": [1, 2, 3],
    "mode": 0
}

response = requests.post(url, json=data)
result = response.json()

if result["status"] == "success":
    print(f"Processed {len(data['urls'])} URLs")
    print(f"Generated {len(result['html_files'])} visualizations")
else:
    print(f"Error: {result['message']}")
```

B.8.2 JavaScript Client Example

```
async function processUrls(urls, levels, mode = 0) {
    const response = await fetch('http://localhost:5000/process-urls', {
        method: 'POST',
        headers: {
            'Content-Type': 'application/json',
        },
        body: JSON.stringify({
            urls: urls,
            levels: levels,
            mode: mode
        })
    });
};
```

```
const result = await response.json();

if (result.status === 'success') {
  console.log('Processing completed successfully');
  return result;
} else {
  throw new Error(result.message);
}
}

// Usage
processUrls(['https://example.com'], [1, 2])
  .then(result => console.log(result))
  .catch(error => console.error(error));
```

B.8.3 cURL Examples

Basic URL Processing:

```
curl -X POST "http://localhost:5000/process-urls" \
  -H "Content-Type: application/json" \
  -d '{
    "urls": ["https://example.com"],
    "levels": [1, 2],
    "mode": 0
  }'
```

List Experiments:

```
curl -X GET "http://localhost:5000/experiments/results/list"
```

B.9 API Versioning and Updates

B.9.1 Current Version

- **Version:** v1.0
- **Compatibility:** Backward compatible within major version
- **Updates:** Non-breaking changes for minor versions
- **Documentation:** Always reflects current implementation

B.9.2 Planned Enhancements

Future API improvements may include:

- WebSocket support for real-time progress updates
- Batch processing status endpoints
- Advanced filtering and query parameters
- Result export in multiple formats (CSV, XML)
- Clustering algorithm parameter customization

Appendix C

Technology Stack Details

C.1 Technology Stack Overview

The S⁴D system leverages a comprehensive technology stack designed for scalability, performance, and maintainability. This appendix provides detailed information about each technology component and its role in the system.

C.2 Backend Technologies

C.2.1 Core Programming Language

Python 3.8+

- **Purpose:** Primary backend development language
- **Advantages:**
 - Rich ecosystem for data science and web development
 - Excellent libraries for machine learning and clustering
 - Strong web automation capabilities
 - Readable and maintainable code structure
- **Usage in S4D:** All core processing, clustering algorithms, API development

C.2.2 Web Automation Framework

Selenium WebDriver 4.x

- **Purpose:** Web page automation and DOM extraction
- **Configuration:**

- Chrome browser in headless mode
- Window size: 1920x1080 for consistent rendering
- No sandbox mode for Linux compatibility
- GPU disabled for server environments
- **Features Used:**
 - DOM tree traversal
 - CSS property extraction
 - JavaScript execution for computed styles
 - Element bounding box calculations
- **Usage in S4D:** URL processing, HTML structure extraction, CSS analysis

C.2.3 API Framework

FastAPI 0.100+

- **Purpose:** REST API development and documentation
- **Key Features:**
 - Automatic OpenAPI/Swagger documentation
 - Type hints and validation
 - Async/await support
 - High performance (comparable to NodeJS)
- **Configuration:**
 - CORS enabled for React frontend
 - JSON request/response handling
 - Error handling middleware
 - Request timeout management
- **Usage in S4D:** All API endpoints, experiment management, file serving

C.2.4 Data Processing Libraries

NumPy 1.24+

- **Purpose:** Numerical computing and array operations
- **Usage:** Vector operations, similarity matrix calculations, data normalization

Pandas 2.0+

- **Purpose:** Data manipulation and analysis
- **Usage:** Role vector computation, similarity data organization, result aggregation

SciPy 1.10+

- **Purpose:** Scientific computing algorithms
- **Usage:** Distance calculations, statistical functions, sparse matrix operations

C.2.5 Machine Learning Libraries

Scikit-learn 1.3+

- **Purpose:** Machine learning algorithms and preprocessing
- **Components Used:**
 - StandardScaler for data normalization
 - Cosine similarity calculations
 - PCA for dimensionality reduction
 - Various distance metrics
- **Usage in S4D:** Data preprocessing, similarity computation, feature scaling

HDBSCAN 0.8+

- **Purpose:** Density-based clustering algorithm
- **Key Features:**
 - Hierarchical clustering
 - Automatic cluster count determination
 - Outlier detection and handling
 - DBCV quality scoring

- **Configuration:**
 - Dynamic min_cluster_size optimization
 - Cluster selection epsilon tuning
 - Outlier reassignment to nearest clusters
- **Usage in S4D:** Primary clustering algorithm, quality assessment

DBCV (Density-Based Cluster Validation)

- **Purpose:** Clustering quality evaluation
- **Features:** Density-aware cluster validation metric
- **Usage in S4D:** Clustering quality scoring, parameter optimization

C.2.6 Image and Visualization Libraries

Matplotlib 3.7+

- **Purpose:** Statistical plotting and visualization
- **Usage:** Performance charts, clustering visualizations, result plotting

Seaborn 0.12+

- **Purpose:** Statistical data visualization
- **Usage:** Enhanced matplotlib plots, statistical distributions

Pillow (PIL) 10.0+

- **Purpose:** Image processing and manipulation
- **Usage:** HTML visualization generation, image format conversion

C.2.7 Color Processing

ColorMath 3.0+

- **Purpose:** Color space conversions and analysis
- **Usage:** RGB to LAB color conversion, color similarity analysis

D3 Scale Chromatic (via interpolation)

- **Purpose:** Scientific color mapping
- **Usage:** Viridis colormap for similarity matrix visualization

C.3 Frontend Technologies

C.3.1 Core Framework

React 18.x

- **Purpose:** User interface development
- **Key Features:**
 - Component-based architecture
 - State management with hooks
 - Virtual DOM for performance
 - Hot reload for development
- **Components Developed:**
 - URLChipForm: Main analysis interface
 - Experiment configuration builders
 - Result visualization components
 - Archive browsers and viewers

C.3.2 UI Component Library

Material-UI (MUI) 5.x

- **Purpose:** React component library and design system
- **Components Used:**
 - Form controls (TextField, Button, Chip)
 - Layout components (Grid, Box, Card)
 - Navigation (Accordion, Tabs)
 - Feedback (Snackbar, Progress indicators)
 - Data display (Typography, Tables)
- **Theming:**
 - Dark/light mode support
 - Custom color schemes
 - Responsive breakpoints
 - Consistent spacing system

C.3.3 Data Visualization

D3.js (d3-scale-chromatic) 7.x

- **Purpose:** Scientific color scales for data visualization
- **Usage:** Viridis colormap implementation for similarity matrices

C.3.4 PDF Generation

html2pdf.js 0.10+

- **Purpose:** Client-side PDF generation
- **Features:**
 - HTML to PDF conversion
 - Custom page formatting
 - Vector graphics support
 - Print optimization
- **Usage in S4D:** Similarity matrix PDF export, result documentation

C.4 Development and Deployment

C.4.1 Package Management

Python: pip + requirements.txt

- **Purpose:** Python dependency management
- **Configuration:** Version-pinned dependencies for reproducibility

Node.js: npm + package.json

- **Purpose:** JavaScript dependency management
- **Configuration:** Semantic versioning, dev/prod dependency separation

C.4.2 Development Tools

Chrome DevTools

- **Purpose:** Frontend debugging and performance analysis
- **Usage:** Network monitoring, DOM inspection, performance profiling

Browser Developer Tools

- **Purpose:** Cross-browser testing and debugging
- **Usage:** Compatibility testing, responsive design validation

C.5 Data Management

C.5.1 File System Storage

JSON Data Format

- **Purpose:** Structured data storage and exchange
- **Usage:**
 - URL processing results
 - Clustering outputs
 - Experiment configurations
 - Performance metrics
- **Benefits:** Human-readable, language-agnostic, schema-flexible

HTML File Generation

- **Purpose:** Visual clustering results
- **Structure:** Organized by analysis level and domain
- **Features:** Color-coded elements, metadata inclusion, responsive design

C.5.2 Caching System

File-based Caching

- **Purpose:** Performance optimization through result reuse
- **Implementation:**
 - SHA-256 hash-based cache keys
 - TTL-based expiration (24h CLI, 1h API)
 - Partial and complete cache support
 - Cache statistics and monitoring
- **Benefits:** 50-90% processing time reduction for cached URLs

C.6 Performance Optimization Technologies

C.6.1 Parallel Processing

Python Threading

- **Purpose:** Concurrent URL processing
- **Implementation:** Thread-safe data structures, queue-based processing

Process Optimization

- **Browser Reuse:** Single Chrome instance for multiple URLs
- **Memory Management:** Garbage collection optimization
- **Resource Pooling:** Connection and process pooling

C.6.2 Algorithm Optimization

Vectorized Operations

- **NumPy:** SIMD-optimized mathematical operations
- **SciPy:** Optimized distance calculations
- **Scikit-learn:** Efficient similarity computations

Memory Efficiency

- **Sparse Matrices:** For high-dimensional feature vectors
- **Streaming Processing:** Large dataset handling
- **Data Compression:** JSON minification, binary formats when needed

C.7 Browser Compatibility

C.7.1 Supported Browsers

- **Chrome 90+:** Primary development and testing browser
- **Firefox 88+:** Full feature compatibility
- **Safari 14+:** WebKit compatibility testing
- **Edge 90+:** Chromium-based compatibility

C.7.2 Progressive Enhancement

- **Core Functionality:** Works without JavaScript
- **Enhanced Experience:** Rich interactions with JavaScript enabled
- **Responsive Design:** Mobile and tablet compatibility
- **Accessibility:** ARIA labels, keyboard navigation support

C.8 Security Considerations

C.8.1 Input Validation

- **URL Validation:** Regex-based URL format checking
- **Parameter Sanitization:** Input cleaning and bounds checking
- **File Path Security:** Path traversal prevention
- **Rate Limiting:** Request frequency controls

C.8.2 CORS Configuration

- **Origin Control:** Specific allowed origins
- **Method Restrictions:** Limited to required HTTP methods
- **Header Policies:** Controlled header access
- **Credential Handling:** Secure credential policies

C.9 System Requirements

C.9.1 Minimum Requirements

Backend Server:

- **OS:** Linux, macOS, or Windows
- **Python:** 3.8 or higher
- **Memory:** 4GB RAM minimum, 8GB recommended
- **Storage:** 2GB free space for cache and results

- **Network:** Stable internet connection

Frontend Client:

- **Browser:** Modern browser with JavaScript support
- **Resolution:** 1024x768 minimum
- **Network:** Stable connection to backend API
- **Memory:** 2GB RAM for complex visualizations

C.9.2 Recommended Configuration

Production Server:

- **CPU:** Multi-core processor (4+ cores)
- **Memory:** 16GB+ RAM for large-scale processing
- **Storage:** SSD for improved I/O performance
- **Network:** High-bandwidth connection
- **Browser:** Chrome installed for Selenium automation

C.10 Version Management

C.10.1 Dependency Versioning

- **Python Packages:** Pinned versions in requirements.txt
- **Node.js Packages:** Semantic versioning in package.json
- **Browser Versions:** Tested compatibility ranges
- **API Versions:** Backward compatibility maintenance

C.10.2 Technology Lifecycle

- **Regular Updates:** Security patches and feature updates
- **LTS Support:** Long-term support version preferences
- **Migration Planning:** Gradual technology stack updates
- **Compatibility Testing:** Cross-version validation

Appendix D

Experimental Data

D.1 Experimental Design Overview

This appendix provides comprehensive experimental data, performance metrics, and result visualizations for the S⁴D system evaluation. The experiments were designed to validate the system’s effectiveness across multiple dimensions of web similarity analysis.

D.2 Dataset Characteristics

D.2.1 Test Website Categories

The experimental evaluation utilized websites from the following categories:

Table D.1: Test Website Categories and Characteristics

Category	Count	Avg. DOM Depth	Characteristics
E-commerce	15	8.2	Product listings, shopping carts
News/Media	12	6.7	Article layouts, navigation menus
Educational	10	7.4	Course listings, institutional pages
Corporate	8	5.9	Company profiles, service pages
Blog/Personal	6	4.3	Content-focused, minimal structure
Government	5	6.1	Official pages, form-heavy
Total	56	6.8	Mixed complexity

D.2.2 URL Distribution

Domain Diversity Metrics:

- **Total unique domains:** 42
- **Geographic distribution:** 15 countries

- **Language coverage:** 8 languages
- **Page complexity range:** 150-2,500 DOM elements

D.3 Performance Metrics

D.3.1 Processing Time Analysis

Table D.2: Processing Time by Analysis Level

Level	Mean (s)	Median (s)	Std Dev	Max (s)
1	2.34	2.12	0.58	4.21
2	3.87	3.45	0.92	6.78
3	5.91	5.32	1.34	9.12
4	8.45	7.89	2.01	13.56
5	12.78	11.23	3.45	21.34
6	18.92	16.87	4.92	29.87
7	26.45	23.12	6.78	41.23
8	37.89	34.56	9.12	58.45
9	52.34	47.89	12.45	78.92
10	71.23	65.34	16.78	102.45

D.3.2 Cache Performance

Table D.3: Cache Performance Statistics

Metric	Without Cache	With Cache	Improvement
Average processing time	15.67s	2.34s	85.1%
Memory usage	1.2GB	0.8GB	33.3%
API response time	18.45s	3.12s	83.1%
Success rate	92.3%	97.8%	5.5%

D.4 Clustering Quality Results

D.4.1 DBCV Scores by Level

D.4.2 Optimal Level Identification

Based on the comprehensive analysis, Level 5 consistently achieved the highest clustering quality:

- **DBCV Score:** 0.74 (Excellent)

Table D.4: DBCV Clustering Quality Scores

Level	DBCV Score	Cluster Count	Noise Points	Quality Rating
1	0.23	3	12	Poor
2	0.41	4	8	Fair
3	0.58	5	6	Good
4	0.67	6	4	Good
5	0.74	7	3	Excellent
6	0.71	8	5	Good
7	0.68	9	7	Good
8	0.62	11	9	Fair
9	0.55	13	12	Fair
10	0.48	16	15	Poor

- **Cluster Count:** 7 (Optimal separation)
- **Noise Points:** 3 (Minimal outliers)
- **Processing Time:** 12.78s (Reasonable)
- **Memory Usage:** 0.9GB (Acceptable)

D.5 Similarity Analysis Results

D.5.1 Cosine Similarity Distribution

Table D.5: Cosine Similarity Statistics by Website Category

Category Pair	Mean Similarity	Std Dev	Min	Max
E-commerce vs E-commerce	0.78	0.12	0.52	0.94
News vs News	0.71	0.15	0.43	0.89
Educational vs Educational	0.69	0.13	0.48	0.87
Corporate vs Corporate	0.65	0.11	0.46	0.83
Blog vs Blog	0.58	0.18	0.31	0.79
Government vs Government	0.72	0.09	0.58	0.85
Cross-category	0.34	0.16	0.12	0.67

Table D.6: Comparison of Similarity Metrics

Metric	Cosine	EMD	Hausdorff	Weighted
Intra-category similarity	0.69	0.72	0.65	0.71
Inter-category similarity	0.34	0.29	0.31	0.32
Separation ratio	2.03	2.48	2.10	2.22
Computational cost (ms)	45	127	89	98

Table D.7: Scalability Analysis Results

URL Count	Processing Time	Memory Usage	Success Rate	Avg. Quality
5	1.2 min	0.4 GB	100%	0.72
10	2.8 min	0.7 GB	98%	0.74
20	6.4 min	1.2 GB	95%	0.71
50	18.7 min	2.8 GB	92%	0.68
100	41.2 min	5.1 GB	87%	0.65

D.5.2 Multi-Metric Comparison

D.6 Scalability Analysis

D.6.1 URL Count vs Processing Time

D.6.2 Memory Usage Patterns

Memory Usage Breakdown:

- **DOM Storage:** 45% of total memory
- **Feature Vectors:** 30% of total memory
- **Similarity Matrices:** 15% of total memory
- **Clustering Data:** 10% of total memory

D.7 Experiment Validation Results

D.7.1 Ground Truth Validation

Manual evaluation of clustering results against expert judgment:

D.7.2 Cross-Validation Results

5-fold cross-validation results across different website datasets:

Table D.8: Clustering Accuracy vs Ground Truth

Category	Expert Clusters	S4D Clusters	Accuracy	F1-Score
E-commerce	3	3	92.3%	0.89
News/Media	2	3	87.5%	0.85
Educational	2	2	95.0%	0.93
Corporate	2	2	88.9%	0.87
Blog/Personal	1	2	83.3%	0.81
Government	1	1	100%	1.00
Overall	11	13	91.0%	0.89

Table D.9: Cross-Validation Performance

Fold	DBCV Score	Accuracy	Precision	Recall
1	0.72	89.2%	0.91	0.87
2	0.75	92.1%	0.93	0.91
3	0.69	87.5%	0.89	0.85
4	0.74	90.8%	0.92	0.89
5	0.71	88.9%	0.90	0.88
Mean	0.72	89.7%	0.91	0.88
Std	0.023	1.89%	0.016	0.023

D.8 Comparative Analysis

D.8.1 Baseline Comparisons

Comparison with traditional clustering approaches:

Table D.10: Algorithm Performance Comparison

Algorithm	Accuracy	Processing Time	Memory Usage	Scalability
S4D (HDBSCAN)	89.7%	12.8s	0.9GB	Excellent
K-Means	67.2%	3.2s	0.4GB	Good
Hierarchical	72.8%	45.6s	2.1GB	Poor
DBSCAN	78.4%	8.9s	0.7GB	Good
Spectral	71.5%	67.3s	3.2GB	Poor

D.8.2 Feature Importance Analysis

Analysis of which features contribute most to clustering quality:

D.9 Error Analysis

D.9.1 Failure Case Analysis

Analysis of URLs that failed to process correctly:

Table D.11: Feature Importance Rankings

Feature Category	Importance Score	Variance Explained	Ranking
DOM Structure	0.34	28.7%	1
CSS Layout Properties	0.28	23.1%	2
Color Scheme	0.19	15.8%	3
Typography	0.12	9.9%	4
Interactive Elements	0.07	5.8%	5

Table D.12: Failure Analysis

Failure Type	Count	Percentage	Common Causes
Timeout	12	42.9%	Heavy JavaScript, slow servers
DOM Parsing	8	28.6%	Malformed HTML, dynamic content
CSS Extraction	5	17.9%	Complex CSS rules, imports
Network Error	3	10.7%	Connection issues, blocked requests
Total	28	100%	Various technical issues

D.9.2 Quality Degradation Factors

Factors that negatively impact clustering quality:

- **Excessive DOM depth** (>10 levels): 15% quality reduction
- **Dynamic content loading**: 23% quality reduction
- **Minimal CSS styling**: 12% quality reduction
- **Mixed content types**: 8% quality reduction
- **Responsive design variations**: 6% quality reduction

D.10 Performance Optimization Results

D.10.1 Optimization Techniques Impact

Table D.13: Performance Optimization Impact

Optimization	Before	After	Improvement
Browser instance reuse	25.6s	12.8s	50.0%
Vectorized operations	18.9s	9.4s	50.3%
Cache implementation	15.2s	2.3s	84.9%
Parallel processing	14.7s	8.9s	39.5%
Memory optimization	2.1GB	0.9GB	57.1%

D.11 Statistical Significance Tests

D.11.1 Hypothesis Testing Results

H1: S4D clustering is significantly better than random clustering

- **Test:** Paired t-test with $p < 0.001$
- **Effect size:** 2.34 (large effect)
- **Conclusion:** Highly significant improvement over baseline

H2: Multi-level analysis improves clustering quality

- **Test:** One-way ANOVA with $F = 15.67$, $p < 0.001$
- **Post-hoc:** Level 5 significantly superior to shallow levels
- **Conclusion:** Depth of analysis is crucial for quality

H3: Cache system significantly improves performance

- **Test:** Wilcoxon signed-rank test
- **W-statistic:** 1,247
- **p-value:** < 0.001
- **Conclusion:** Highly significant performance improvement

D.12 Reproducibility Information

D.12.1 Experimental Configuration

System Configuration:

- **OS:** Ubuntu 20.04 LTS
- **Python:** 3.9.7
- **Chrome:** 96.0.4664.45
- **Memory:** 16GB RAM
- **CPU:** Intel i7-10700K

Random Seeds:

- **NumPy:** 42
- **Scikit-learn:** 42
- **HDBSCAN:** 42

D.12.2 Data Availability

All experimental data, configurations, and results are available in the project repository:

- **Raw data:** experiments/data/
- **Processed results:** experiments/results/
- **Analysis scripts:** experiments/analysis/
- **Visualization code:** experiments/visualizations/

Bibliography

- [1] Xingyu Chen, Zihan Zhao, Lu Chen, JiaBao Ji, Danyang Zhang, Ao Luo, Yuxuan Xiong, and Kai Yu. Websrc: A dataset for web-based structural reading comprehension. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 4173–4185, Online and Punta Cana, Dominican Republic, 2021. Association for Computational Linguistics.
- [2] Xiang Deng, Prashant Shiralkar, Colin Lockard, Binxuan Huang, and Huan Sun. Dom-lm: Learning generalizable representations for html documents. *arXiv preprint arXiv:2201.10608*, 2022. cs.CL.
- [3] Pankaj Gulhane, Amit Madaan, Rupesh Mehta, Jeyashankher Ramamirtham, Rajeev Rastogi, Sandeep Satpal, Srinivasan H Sengamedu, Ashwin Tengli, and Charu Tiwari. Web-scale information extraction with vertex. In *2011 IEEE 27th International Conference on Data Engineering*, pages 1209–1220. IEEE, 2011.
- [4] Colin Lockard, Prashant Shiralkar, Xin Luna Dong, and Hannaneh Hajishirzi. Zeroshotceres: Zero-shot relation extraction from semi-structured webpages. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8105–8117, Online, 2020. Association for Computational Linguistics.
- [5] Leland McInnes, John Healy, and Steve Astels. hdbscan: Hierarchical density based clustering. *Journal of Open Source Software*, 2(11):205, 2017. Software Repository: <https://github.com/scikit-learn-contrib/hdbscan>, Software Archive: <http://dx.doi.org/10.5281/zenodo.401403>.
- [6] Davoud Moulavi, Pablo Andretta Jaskowiak, Ricardo J. G. B. Campello, Arthur Zimek, and Jörg Sander. Density-based clustering validation. In *Proceedings of the 2014 SIAM International Conference on Data Mining*, pages 839–847. SIAM, 2014. Introduces DBCV (Density-Based Cluster Validation) index for evaluating density-based clustering results.