



# S<sup>4</sup>D: Style and Structure Similarity for Site Domains

S<sup>4</sup>D: Style and Structure Similarity for Site Domains: A system for  
website structure and visual style analysis, clustering, and comparison

Panagiotis Favvatas

Master's Thesis, Department of Informatics And Telecommunications  
University of Peloponnese, June 2025

Copyright © 2025 University of Peloponnese. All Rights Reserved

**S<sup>4</sup>D: Style and Structure Similarity for Site Domains:  
A  
system for website structure and visual style analysis,  
clustering, and comparison**

Panagiotis Favvatas

A thesis submitted in partial fulfillment  
of the requirements for the MSc in  
Computer Science

**Committee**

Professor, Spiros Skiadopoulos, Supervisor  
Professor, [Committee Member 1]  
Associate Professor, [Committee Member 2]

University of the Peloponnese  
2025

---

# Περίληψη

Αυτή η διπλωματική εργασία παρουσιάζει το **S<sup>4</sup>D** (Style and Structure Similarity for Site Domains), μια ερευνητική πλατφόρμα για την ανάλυση ομοιοτήτων μεταξύ ιστοσελίδων βάσει της δομής και του οπτικού τους στυλ. Το σύστημα επεξεργάζεται ιστοσελίδες αναλύοντας τη δομή του DOM και τις ιδιότητες CSS, συνδυάζοντάς τα σε μία ενιαία μορφή για συγκριτική αξιολόγηση.

Οι χρήστες μπορούν να εισάγουν οποιονδήποτε αριθμό URLs για ανάλυση. Κάθε σελίδα επεξεργάζεται ανεξάρτητα για την εξαγωγή δομικών και στυλιστικών χαρακτηριστικών. Κατά τη φάση υπολογισμού της ομοιότητας, οι συγκρίσεις πραγματοποιούνται σε επίπεδο domain, ανεξάρτητα από τον τρόπο ομαδοποίησης των URLs. Το σύστημα υποστηρίζει την ανάλυση σε διαφορετικά βάθη DOM (επίπεδα 1 έως 10).

Η ομαδοποίηση των στοιχείων πραγματοποιείται με τον αλγόριθμο HDBSCAN, ενώ η ποιότητα των ομάδων αξιολογείται με το DBCV. Τα απομονωμένα στοιχεία επανατοποθετούνται σε κατάλληλες ομάδες όταν είναι δυνατόν. Η πλατφόρμα επιτρέπει τη διεξαγωγή πολλαπλών πειραμάτων με διαφορετικά σύνολα URLs και παραμέτρους, καλύπτοντας ποι- κίλες ερευνητικές ανάγκες.

Το **S<sup>4</sup>D** υλοποιείται με React για το περιβάλλον χρήστη, Flask για τις διεπαφές API και Python για την επεξεργασία δεδομένων. Ενσωματώνει το Gnuplot για παραγωγή γραφημάτων και αρχείων κατάλληλων για ακαδημαϊκή χρήση. Ένα αρχείο αποτελεσμάτων επιτρέπει τη σύγκριση διαφορετικών πειραμάτων και την παρακολούθηση της προόδου.

Το σύστημα εξάγει HTML σελίδες με χρωματική κωδικοποίηση που αναδεικνύουν τις δομικές ομοιότητες, καθώς και πίνακες συσχετίσεων βασισμένους σε υπολογισμούς συνημιτόνου. Οι χρονικές μετρήσεις συμβάλλουν στην αξιολόγηση της απόδοσης του συστήματος. Οι δοκιμές δείχνουν ότι το **S<sup>4</sup>D** συγκρίνει και ομαδοποιεί με ακρίβεια στοιχεία ιστοσελίδων σε διαφορετικά domains, προσφέροντας ένα αξιόπιστο εργαλείο για δομική και οπτική ανάλυση.

Η πλήρης υλοποίηση του συστήματος είναι διαθέσιμη στο: [https://github.com/pfavvatas/lib\\_url\\_to\\_img](https://github.com/pfavvatas/lib_url_to_img)

---

# Abstract

This thesis presents S<sup>4</sup>D (Style and Structure Similarity for Site Domains), a research platform for analyzing similarities between websites based on their structure and visual style. The system examines web pages by processing their DOM structure and CSS styling, combining both into a unified representation for comparison.

Users can provide any number of URLs for analysis. Each page is processed independently to extract structural and styling information. During the similarity analysis phase, comparisons are performed at the domain level—regardless of how the URLs were grouped initially. The system supports analysis at multiple DOM depths, from level 1 to level 10.

After grouping similar elements using HDBSCAN and evaluating cluster quality with DBCV, the system reassigns outliers to the most appropriate clusters when possible. Users can perform multiple experiments using different URL sets and DOM levels to support varied research scenarios.

S<sup>4</sup>D is built with React for the interface, Flask for backend APIs, and Python for processing logic. It integrates Gnuplot to generate charts and data suitable for academic analysis. A results archive enables users to compare and track experiment outputs over time.

The system outputs color-coded HTML pages that highlight structural similarities, as well as similarity matrices based on cosine similarity. Timing metrics help evaluate system performance. Testing confirms that S<sup>4</sup>D reliably groups and compares website content across domains, offering a robust tool for structural and visual web analysis.

The full system implementation is available at: [https://github.com/pfavvatas/lib\\_url\\_to\\_img](https://github.com/pfavvatas/lib_url_to_img)

---



# Acknowledgements

I would like to express my sincere gratitude to all those who have contributed to the successful completion of this thesis.

First, I would like to thank Professor Spiros Skiadopoulos for his invaluable scientific guidance and mentorship throughout the course of this thesis. His expertise, constructive feedback, and immediate assistance whenever needed have been instrumental in shaping this research. His dedication to academic excellence has significantly contributed to my development as a researcher.

Furthermore, I am grateful to the academic staff and fellow researchers who have enriched my learning experience through valuable discussions and collaborative exchange of ideas.

I am deeply thankful to my family for their unconditional support, encouragement, and understanding throughout this academic journey. Their constant belief in my abilities has provided me with the strength to overcome challenges and pursue my goals.

Finally, I would like to acknowledge my friends and colleagues who have been a source of inspiration and motivation during these years. Their support and companionship have made this journey more meaningful and enjoyable.

---

# Contents

|                                                           |            |
|-----------------------------------------------------------|------------|
| <b>Περίληψη</b>                                           | <b>i</b>   |
| <b>Abstract</b>                                           | <b>iii</b> |
| <b>Acknowledgements</b>                                   | <b>v</b>   |
| <b>1 Introduction</b>                                     | <b>1</b>   |
| 1.1 Overview . . . . .                                    | 1          |
| 1.2 Problem Statement . . . . .                           | 1          |
| 1.2.1 Web Structure Analysis Challenges . . . . .         | 2          |
| 1.2.2 Research Motivation . . . . .                       | 3          |
| 1.3 Research Objectives . . . . .                         | 3          |
| 1.4 Contributions . . . . .                               | 4          |
| 1.5 Thesis Structure . . . . .                            | 4          |
| <b>2 Literature Review</b>                                | <b>5</b>   |
| 2.1 Web Structure Analysis and Mining . . . . .           | 5          |
| 2.1.1 Structural Understanding of Web Documents . . . . . | 5          |
| 2.1.2 Information Extraction from Web Pages . . . . .     | 6          |
| 2.1.3 DOM Tree Analysis and Processing . . . . .          | 6          |
| 2.2 Website Similarity and Clustering . . . . .           | 6          |
| 2.2.1 Multi-dimensional Similarity Approaches . . . . .   | 7          |
| 2.2.2 Graph-based Similarity Measures . . . . .           | 7          |
| 2.2.3 Role Vector Similarity . . . . .                    | 7          |
| 2.3 Clustering Algorithms for Web Data . . . . .          | 7          |
| 2.3.1 Density-Based Clustering . . . . .                  | 7          |
| 2.3.2 Cluster Validation . . . . .                        | 8          |
| 2.3.3 Multi-level Clustering Analysis . . . . .           | 8          |
| 2.4 Feature Engineering for Web Analysis . . . . .        | 8          |
| 2.4.1 CSS Property Standardization . . . . .              | 8          |
| 2.4.2 Attribute Selection and Filtering . . . . .         | 9          |
| 2.4.3 Vector Space Representation . . . . .               | 9          |

|          |                                                       |           |
|----------|-------------------------------------------------------|-----------|
| 2.5      | Similarity Measures for Web Data . . . . .            | 9         |
| 2.5.1    | Cosine Similarity . . . . .                           | 9         |
| 2.5.2    | Earth Mover's Distance (EMD) . . . . .                | 10        |
| 2.5.3    | Hausdorff Distance . . . . .                          | 10        |
| 2.5.4    | Combined Similarity Metrics . . . . .                 | 10        |
| 2.6      | Performance Optimization for Web Analysis . . . . .   | 10        |
| 2.6.1    | Caching Strategies . . . . .                          | 10        |
| 2.6.2    | Processing Mode Optimization . . . . .                | 10        |
| 2.6.3    | Parallel Processing . . . . .                         | 11        |
| 2.7      | Applications and Use Cases . . . . .                  | 11        |
| 2.7.1    | Web Mining and Content Analysis . . . . .             | 11        |
| 2.7.2    | User Interface Research . . . . .                     | 11        |
| 2.7.3    | Website Classification and Categorization . . . . .   | 11        |
| 2.7.4    | Design Pattern Analysis . . . . .                     | 11        |
| 2.8      | Research Gaps and Opportunities . . . . .             | 12        |
| 2.8.1    | Integration of Multiple Analysis Dimensions . . . . . | 12        |
| 2.8.2    | Scalability and Performance . . . . .                 | 12        |
| 2.8.3    | Dynamic Content Handling . . . . .                    | 12        |
| 2.8.4    | Cross-domain Generalization . . . . .                 | 12        |
| 2.9      | Literature Review Summary . . . . .                   | 12        |
| <b>3</b> | <b>Methodology</b>                                    | <b>15</b> |
| 3.1      | System Overview . . . . .                             | 15        |
| 3.2      | Data Collection and Preprocessing . . . . .           | 15        |
| 3.2.1    | Web Page Acquisition . . . . .                        | 15        |
| 3.2.2    | DOM Structure Extraction . . . . .                    | 15        |
| 3.2.3    | CSS Property Analysis . . . . .                       | 15        |
| 3.3      | Feature Engineering and Representation . . . . .      | 16        |
| 3.4      | Similarity Measurement Framework . . . . .            | 16        |
| 3.5      | Clustering Methodology . . . . .                      | 16        |
| 3.6      | Performance Optimization . . . . .                    | 16        |
| 3.7      | Methodology Summary . . . . .                         | 16        |
| <b>4</b> | <b>System Implementation</b>                          | <b>17</b> |
| 4.1      | System Architecture Overview . . . . .                | 17        |
| 4.2      | Backend Implementation . . . . .                      | 17        |
| 4.2.1    | Core Processing Engine . . . . .                      | 17        |
| 4.2.2    | Multi-Level Analysis Implementation . . . . .         | 18        |
| 4.3      | API Implementation . . . . .                          | 18        |
| 4.3.1    | FastAPI Server Architecture . . . . .                 | 18        |

|          |                                                   |           |
|----------|---------------------------------------------------|-----------|
| 4.3.2    | File Serving Infrastructure . . . . .             | 19        |
| 4.4      | Frontend Implementation . . . . .                 | 19        |
| 4.4.1    | React Application Architecture . . . . .          | 19        |
| 4.4.2    | User Interface Features . . . . .                 | 20        |
| 4.4.3    | Integration with Backend Services . . . . .       | 20        |
| 4.5      | Performance Optimization Implementation . . . . . | 20        |
| 4.5.1    | Caching Strategy . . . . .                        | 20        |
| 4.5.2    | Scalability Optimizations . . . . .               | 20        |
| 4.6      | Deployment and Configuration . . . . .            | 21        |
| 4.6.1    | Development Environment Setup . . . . .           | 21        |
| 4.6.2    | Production Deployment Considerations . . . . .    | 21        |
| 4.7      | Implementation Summary . . . . .                  | 21        |
| <b>5</b> | <b>Experiments and Evaluation</b>                 | <b>23</b> |
| 5.1      | Experimental Design . . . . .                     | 23        |
| 5.1.1    | Research Questions . . . . .                      | 23        |
| 5.1.2    | Evaluation Metrics . . . . .                      | 23        |
| 5.2      | Dataset Description . . . . .                     | 24        |
| 5.2.1    | Website Categories . . . . .                      | 24        |
| 5.3      | Experimental Results . . . . .                    | 24        |
| 5.3.1    | Clustering Quality Analysis . . . . .             | 24        |
| 5.3.2    | Performance Scalability . . . . .                 | 25        |
| 5.3.3    | Cache System Impact . . . . .                     | 25        |
| 5.4      | Comparative Analysis . . . . .                    | 25        |
| 5.4.1    | Algorithm Comparison . . . . .                    | 25        |
| 5.4.2    | Feature Importance Analysis . . . . .             | 26        |
| 5.5      | Statistical Validation . . . . .                  | 26        |
| 5.5.1    | Significance Testing . . . . .                    | 26        |
| 5.5.2    | Cross-Validation Results . . . . .                | 26        |
| 5.6      | Error Analysis and Limitations . . . . .          | 27        |
| 5.6.1    | Failure Case Analysis . . . . .                   | 27        |
| 5.6.2    | Quality Degradation Factors . . . . .             | 27        |
| 5.7      | Practical Implications . . . . .                  | 27        |
| 5.7.1    | Real-World Applicability . . . . .                | 27        |
| 5.7.2    | Performance Recommendations . . . . .             | 28        |
| 5.8      | Summary of Experimental Findings . . . . .        | 28        |
| <b>6</b> | <b>Results and Discussion</b>                     | <b>29</b> |
| 6.1      | Clustering Performance Results . . . . .          | 29        |
| 6.1.1    | Overall Clustering Quality . . . . .              | 29        |

|          |                                             |           |
|----------|---------------------------------------------|-----------|
| 6.1.2    | Domain-Specific Performance . . . . .       | 29        |
| 6.2      | Similarity Measurement Results . . . . .    | 30        |
| 6.2.1    | Individual Metric Performance . . . . .     | 30        |
| 6.2.2    | Combined Metric Effectiveness . . . . .     | 30        |
| 6.3      | Computational Performance Results . . . . . | 30        |
| 6.3.1    | Processing Time Analysis . . . . .          | 30        |
| 6.3.2    | Memory Usage Characteristics . . . . .      | 30        |
| 6.4      | Feature Engineering Analysis . . . . .      | 31        |
| 6.4.1    | Feature Component Contributions . . . . .   | 31        |
| 6.5      | Comparative Analysis Results . . . . .      | 31        |
| 6.5.1    | Performance Against Baselines . . . . .     | 31        |
| 6.6      | Case Study Results . . . . .                | 31        |
| 6.6.1    | E-commerce Template Detection . . . . .     | 32        |
| 6.6.2    | News Website Pattern Analysis . . . . .     | 32        |
| 6.7      | System Validation Results . . . . .         | 32        |
| 6.7.1    | Expert Classification Correlation . . . . . | 32        |
| 6.8      | Discussion of Findings . . . . .            | 32        |
| 6.8.1    | Methodological Contributions . . . . .      | 32        |
| 6.8.2    | Practical Implications . . . . .            | 33        |
| 6.8.3    | Technical Insights . . . . .                | 33        |
| 6.9      | Limitations and Challenges . . . . .        | 34        |
| 6.9.1    | Dynamic Content Handling . . . . .          | 34        |
| 6.9.2    | Cross-Browser Variations . . . . .          | 34        |
| 6.9.3    | Cultural and Linguistic Factors . . . . .   | 34        |
| 6.9.4    | Scalability Considerations . . . . .        | 34        |
| 6.10     | Future Work Implications . . . . .          | 34        |
| 6.10.1   | Enhanced Dynamic Content Support . . . . .  | 35        |
| 6.10.2   | Cross-Browser Compatibility . . . . .       | 35        |
| 6.10.3   | Machine Learning Integration . . . . .      | 35        |
| 6.11     | Results Summary . . . . .                   | 35        |
| <b>A</b> | <b>User Guide</b>                           | <b>37</b> |
| A.1      | Getting Started . . . . .                   | 37        |
| A.1.1    | System Requirements . . . . .               | 37        |
| A.2      | Interface Overview . . . . .                | 37        |
| A.3      | Basic URL Analysis . . . . .                | 37        |
| A.3.1    | Adding URLs . . . . .                       | 37        |
| A.3.2    | Selecting Analysis Levels . . . . .         | 38        |
| A.3.3    | Running Analysis . . . . .                  | 38        |

|          |                                           |           |
|----------|-------------------------------------------|-----------|
| A.4      | Understanding Results . . . . .           | 39        |
| A.4.1    | Site Similarity Analysis . . . . .        | 39        |
| A.4.2    | Clustering Results . . . . .              | 39        |
| A.4.3    | Generated HTML Files . . . . .            | 39        |
| A.5      | Advanced Features . . . . .               | 40        |
| A.5.1    | Experiment Configuration . . . . .        | 40        |
| A.5.2    | Results Archive . . . . .                 | 40        |
| A.6      | Performance and Optimization . . . . .    | 40        |
| A.6.1    | Cache System . . . . .                    | 40        |
| A.6.2    | Performance Monitoring . . . . .          | 41        |
| A.7      | Troubleshooting . . . . .                 | 41        |
| A.7.1    | Common Issues . . . . .                   | 41        |
| A.7.2    | Error Messages . . . . .                  | 42        |
| A.8      | Best Practices . . . . .                  | 42        |
| A.8.1    | Optimal Usage Patterns . . . . .          | 42        |
| A.8.2    | Result Interpretation . . . . .           | 42        |
| <b>B</b> | <b>API Documentation</b>                  | <b>43</b> |
| B.1      | API Overview . . . . .                    | 43        |
| B.1.1    | Base Configuration . . . . .              | 43        |
| B.2      | Core Processing Endpoints . . . . .       | 43        |
| B.2.1    | Process URLs . . . . .                    | 43        |
| B.2.2    | Process Clusters . . . . .                | 45        |
| B.3      | Experiment Management Endpoints . . . . . | 45        |
| B.3.1    | Run Experiment Batch . . . . .            | 45        |
| B.3.2    | List Experiment Results . . . . .         | 46        |
| B.3.3    | Get Experiment Details . . . . .          | 47        |
| B.4      | File Access Endpoints . . . . .           | 47        |
| B.4.1    | HTML File Serving . . . . .               | 47        |
| B.4.2    | Experiment File Downloads . . . . .       | 47        |
| B.4.3    | Generated Images . . . . .                | 48        |
| B.5      | Error Handling . . . . .                  | 48        |
| B.5.1    | Standard Error Response . . . . .         | 48        |
| B.5.2    | HTTP Status Codes . . . . .               | 48        |
| B.5.3    | Common Error Messages . . . . .           | 48        |
| B.6      | Rate Limiting and Performance . . . . .   | 48        |
| B.6.1    | Request Limits . . . . .                  | 48        |
| B.6.2    | Performance Considerations . . . . .      | 49        |
| B.7      | Authentication and Security . . . . .     | 49        |

|          |                                                 |           |
|----------|-------------------------------------------------|-----------|
| B.7.1    | Current Implementation . . . . .                | 49        |
| B.7.2    | Production Considerations . . . . .             | 49        |
| B.8      | Primary API Usage Examples . . . . .            | 49        |
| B.8.1    | URL Processing API . . . . .                    | 50        |
| B.8.2    | Experiment Batch Processing API . . . . .       | 54        |
| B.8.3    | Experiment Results Listing API . . . . .        | 56        |
| B.8.4    | Experiment Details Retrieval API . . . . .      | 58        |
| B.9      | Integration Examples . . . . .                  | 60        |
| B.9.1    | Python Client Example . . . . .                 | 60        |
| B.9.2    | JavaScript Client Example . . . . .             | 61        |
| B.9.3    | cURL Examples . . . . .                         | 61        |
| B.10     | API Versioning and Updates . . . . .            | 62        |
| B.10.1   | Current Version . . . . .                       | 62        |
| B.10.2   | Planned Enhancements . . . . .                  | 62        |
| <b>C</b> | <b>Technology Stack Details</b>                 | <b>63</b> |
| C.1      | Technology Stack Overview . . . . .             | 63        |
| C.2      | Backend Technologies . . . . .                  | 63        |
| C.2.1    | Core Programming Language . . . . .             | 63        |
| C.2.2    | Web Automation Framework . . . . .              | 63        |
| C.2.3    | API Framework . . . . .                         | 64        |
| C.2.4    | Data Processing Libraries . . . . .             | 65        |
| C.2.5    | Machine Learning Libraries . . . . .            | 65        |
| C.2.6    | Image and Visualization Libraries . . . . .     | 66        |
| C.2.7    | Color Processing . . . . .                      | 66        |
| C.3      | Frontend Technologies . . . . .                 | 67        |
| C.3.1    | Core Framework . . . . .                        | 67        |
| C.3.2    | UI Component Library . . . . .                  | 67        |
| C.3.3    | Data Visualization . . . . .                    | 68        |
| C.3.4    | PDF Generation . . . . .                        | 68        |
| C.4      | Development and Deployment . . . . .            | 68        |
| C.4.1    | Package Management . . . . .                    | 68        |
| C.4.2    | Development Tools . . . . .                     | 68        |
| C.5      | Data Management . . . . .                       | 69        |
| C.5.1    | File System Storage . . . . .                   | 69        |
| C.5.2    | Caching System . . . . .                        | 69        |
| C.6      | Performance Optimization Technologies . . . . . | 70        |
| C.6.1    | Parallel Processing . . . . .                   | 70        |
| C.6.2    | Algorithm Optimization . . . . .                | 70        |



|          |                                          |           |
|----------|------------------------------------------|-----------|
| C.7      | Browser Compatibility . . . . .          | 70        |
| C.7.1    | Supported Browsers . . . . .             | 70        |
| C.7.2    | Progressive Enhancement . . . . .        | 71        |
| C.8      | Security Considerations . . . . .        | 71        |
| C.8.1    | Input Validation . . . . .               | 71        |
| C.8.2    | CORS Configuration . . . . .             | 71        |
| C.9      | System Requirements . . . . .            | 71        |
| C.9.1    | Minimum Requirements . . . . .           | 71        |
| C.9.2    | Recommended Configuration . . . . .      | 72        |
| C.10     | Version Management . . . . .             | 72        |
| C.10.1   | Dependency Versioning . . . . .          | 72        |
| C.10.2   | Technology Lifecycle . . . . .           | 72        |
| <b>D</b> | <b>Experimental Data</b>                 | <b>73</b> |
| D.1      | Experimental Design Overview . . . . .   | 73        |
| D.2      | Dataset Characteristics . . . . .        | 73        |
| D.2.1    | Test Website Categories . . . . .        | 73        |
| D.2.2    | URL Distribution . . . . .               | 73        |
| D.3      | Performance Metrics . . . . .            | 74        |
| D.3.1    | Processing Time Analysis . . . . .       | 74        |
| D.3.2    | Cache Performance . . . . .              | 74        |
| D.4      | Clustering Quality Results . . . . .     | 74        |
| D.4.1    | DBCW Scores by Level . . . . .           | 74        |
| D.4.2    | Optimal Level Identification . . . . .   | 74        |
| D.5      | Similarity Analysis Results . . . . .    | 75        |
| D.5.1    | Cosine Similarity Distribution . . . . . | 75        |
| D.5.2    | Multi-Metric Comparison . . . . .        | 76        |
| D.6      | Scalability Analysis . . . . .           | 76        |
| D.6.1    | URL Count vs Processing Time . . . . .   | 76        |
| D.6.2    | Memory Usage Patterns . . . . .          | 76        |
| D.7      | Experiment Validation Results . . . . .  | 76        |
| D.7.1    | Ground Truth Validation . . . . .        | 76        |
| D.7.2    | Cross-Validation Results . . . . .       | 76        |
| D.8      | Comparative Analysis . . . . .           | 77        |
| D.8.1    | Baseline Comparisons . . . . .           | 77        |
| D.8.2    | Feature Importance Analysis . . . . .    | 77        |
| D.9      | Error Analysis . . . . .                 | 77        |
| D.9.1    | Failure Case Analysis . . . . .          | 77        |
| D.9.2    | Quality Degradation Factors . . . . .    | 78        |

---

|                                                 |    |
|-------------------------------------------------|----|
| D.10 Performance Optimization Results . . . . . | 78 |
| D.10.1 Optimization Techniques Impact . . . . . | 78 |
| D.11 Statistical Significance Tests . . . . .   | 79 |
| D.11.1 Hypothesis Testing Results . . . . .     | 79 |
| D.12 Reproducibility Information . . . . .      | 79 |
| D.12.1 Experimental Configuration . . . . .     | 79 |
| D.12.2 Data Availability . . . . .              | 80 |

# Chapter 1

## Introduction

### 1.1 Overview

The rapid evolution of the World Wide Web has resulted in an immense variety of website designs, layouts, and functionalities. With millions of active websites spanning diverse domains and purposes, understanding the structural and stylistic relationships between them has become increasingly valuable for applications such as web analytics, automated classification, design research, and interface standardization.

This thesis introduces S<sup>4</sup>D (Style and Structure Similarity for Site Domains), a comprehensive system for analyzing and comparing websites based on their Document Object Model (DOM) structure and Cascading Style Sheets (CSS) properties. S<sup>4</sup>D automates the process of extracting and encoding both structural and visual features of web pages and uses advanced clustering algorithms to group similar elements across different sites.

By transforming DOM and style elements into vector representations and applying density-based clustering techniques, the system reveals underlying structural patterns that may not be apparent through manual inspection. The result is a platform that supports large-scale comparisons between websites, highlighting domain-level similarities through color-coded visualizations and similarity matrices.

S<sup>4</sup>D addresses the growing need for scalable, automated tools that can help web developers, designers, and researchers understand trends in web structure and aesthetics. It provides an extensible foundation for future work in automated web categorization and interface analysis.

### 1.2 Problem Statement

The current landscape of web analysis tools primarily focuses on content-based analysis, often overlooking the significance of visual design patterns and structural similarities between websites. In the era of rapidly expanding web content, understanding the struc-

tural similarity between websites has become increasingly important for various applications including web mining, content analysis, and automated web processing. Traditional approaches face several critical challenges:

### 1.2.1 Web Structure Analysis Challenges

Modern web structure analysis presents several unique technical challenges that our S4D system specifically addresses:

- **DOM Complexity and Recursive Processing:** Modern websites contain deeply nested DOM structures with thousands of elements requiring recursive traversal algorithms. Our system handles complex parent-child relationships through unique ID generation and hierarchical tree processing, managing elements at multiple depth levels (1-10) while maintaining structural integrity during analysis.
- **CSS Style Diversity and Standardization:** The variety of CSS styling approaches across websites creates inconsistency in structural representation. Our implementation processes diverse CSS formats including pixel values (`px`), percentages (%), RGB/RGBA colors, and relative units, requiring sophisticated parsing and normalization algorithms to enable meaningful comparisons.
- **Attribute Extraction and Feature Engineering:** Extracting meaningful features from HTML elements involves processing hundreds of CSS properties per element. Our system implements selective attribute filtering, focusing on structurally significant properties like `font-size`, `text-align`, `line-height`, and `cursor`, while handling special cases like color space conversions and unit standardization.
- **Scalability and Performance Optimization:** Processing large numbers of websites requires efficient algorithms and memory management. Our system implements domain-based processing modes, ChromeDriver optimization, and parallel data processing to handle batch website analysis while minimizing computational overhead and ensuring reliable performance across different scales.
- **Multi-dimensional Similarity Computation:** Defining meaningful similarity measures for web structures involves multiple algorithmic challenges. Our approach combines HDBSCAN clustering with DBCV (Density-Based Cluster Validation) scoring [6], cosine similarity matrices, and role vector analysis to capture structural, visual, and positional relationships between website elements.
- **Clustering Parameter Optimization:** Achieving optimal clustering results requires dynamic parameter tuning. Our system implements grid search optimization over cluster size ranges and selection epsilon values, with automatic outlier reassignment to nearest cluster centroids based on Euclidean distance calculations.

- **Cross-Domain Pattern Recognition:** Identifying design trends across different domains requires sophisticated comparison frameworks. Our implementation uses domain-level aggregation, transition matrices between design elements, and combined similarity metrics (cosine, EMD, Hausdorff) to enable meaningful cross-domain analysis.

### 1.2.2 Research Motivation

The need for automated web structural analysis stems from several key factors:

- **Content Management:** Organizations need tools to understand and manage large collections of web content based on structural and visual characteristics.
- **Design Pattern Analysis:** Web developers and designers benefit from understanding common structural patterns and visual trends across websites in their domain.
- **Accessibility Evaluation:** Automated structural analysis can help identify accessibility issues and design inconsistencies across multiple web properties.
- **Web Analytics Enhancement:** Structural similarity analysis provides deeper insights into website categorization and user experience patterns beyond traditional content-based metrics.

## 1.3 Research Objectives

The primary objectives of this research are:

1. To develop a robust system for extracting and analyzing structural and visual features from websites
2. To create effective similarity metrics that can accurately measure relationships between different websites
3. To implement clustering algorithms that can group websites based on their design and structural characteristics
4. To provide a comprehensive comparison framework for website analysis across different domains
5. To validate the effectiveness of the proposed system through extensive testing and evaluation

## 1.4 Contributions

This thesis makes the following key contributions:

- **Novel feature extraction methodology:** Development of comprehensive techniques for extracting both structural and visual features from websites
- **Advanced similarity metrics:** Introduction of new metrics specifically designed for website comparison
- **Integrated clustering approach:** Implementation of clustering algorithms optimized for website analysis
- **Comprehensive evaluation framework:** Establishment of evaluation metrics and datasets for assessing website similarity systems
- **Practical applications:** Demonstration of real-world applications in web design analysis and automated categorization

## 1.5 Thesis Structure

The remainder of this thesis is organized as follows:

- **Chapter 2: Literature Review** presents a comprehensive review of existing approaches to website analysis, similarity measurement, and clustering techniques relevant to web data.
- **Chapter 3: Methodology** describes the proposed S<sup>4</sup>D system architecture, including feature extraction methods, similarity metrics, and clustering algorithms.
- **Chapter 4: Implementation** details the technical implementation of the system, including data structures, algorithms, and software architecture decisions.
- **Chapter 5: Experimental Design** outlines the experimental methodology, datasets used, and evaluation metrics employed to assess the system's performance.
- **Chapter 6: Results and Analysis** presents the experimental results, performance analysis, and comparison with existing approaches.
- **Chapter 7: Discussion** provides an in-depth discussion of the findings, limitations, and implications of the research.
- **Chapter 8: Conclusion and Future Work** summarizes the key findings, contributions, and suggests directions for future research.

# Chapter 2

## Literature Review

This chapter provides a comprehensive review of existing approaches and methodologies relevant to website similarity analysis, structural comparison, and clustering techniques. The review examines foundational work in web structure analysis, similarity measurement, clustering algorithms, and related applications that inform the development of the S<sup>4</sup>D system.

### 2.1 Web Structure Analysis and Mining

Web structure analysis has evolved significantly since the early days of the World Wide Web. Traditional approaches primarily focused on content-based analysis, treating web pages as text documents and applying information retrieval techniques. However, the rich structural information encoded in HTML documents provides valuable semantic signals that extend beyond textual content.

#### 2.1.1 Structural Understanding of Web Documents

Chen et al. [1] introduced WebSRC, a comprehensive dataset for web-based structural reading comprehension that highlights the importance of understanding both semantic content and structural organization of web pages. Their work demonstrates that effective web page understanding requires systems to comprehend not only textual semantics but also the hierarchical structure of HTML documents. The WebSRC dataset, comprising 400K question-answer pairs from 6.4K web pages with corresponding HTML source code and screenshots, establishes a benchmark for structural web understanding tasks.

Building on the importance of structural representation, Deng et al. [2] proposed DOM-LM, a novel approach for learning generalizable representations of HTML documents. Their work addresses limitations of existing approaches by encoding both text and DOM tree structure using transformer-based encoders. DOM-LM demonstrates that combining textual content with structural information leads to superior performance in

webpage understanding tasks, including attribute extraction, open information extraction, and question answering. The model shows particularly strong generalization capabilities in few-shot and zero-shot settings, making it suitable for real-world applications with limited labeled data.

### 2.1.2 Information Extraction from Web Pages

Lockard et al. [4] tackled the challenge of zero-shot relation extraction from semi-structured webpages through their ZeroShotCeres system. Their approach recognizes that textual semantics in web documents are often augmented with visual elements including layout, font size, and color. The system employs graph neural networks to build rich representations of text fields and their relationships, enabling generalization to previously unseen website templates. This work is particularly relevant to the S<sup>4</sup>D system’s goal of analyzing structural and visual similarities across different website domains.

The challenge of web-scale information extraction was addressed by Gulhane et al. [3] through their Vertex system. Vertex represents one of the first systems to achieve high-precision information extraction at web scale, processing over 250 million records from more than 200 websites. The system’s approach to grouping similar structured pages, learning robust XPath-based extraction rules, and detecting site changes provides valuable insights for large-scale web analysis systems like S<sup>4</sup>D.

### 2.1.3 DOM Tree Analysis and Processing

The Document Object Model (DOM) serves as the foundation for web page structure analysis. Recent advances in DOM-based analysis focus on extracting meaningful patterns from the hierarchical organization of HTML elements. The S<sup>4</sup>D system builds upon these foundations by implementing recursive DOM traversal algorithms that capture both structural and stylistic properties at multiple depth levels.

Current approaches to DOM analysis often struggle with the complexity and variability of modern web pages. The S<sup>4</sup>D system addresses these challenges through its multi-level analysis framework, which processes DOM structures at depths ranging from 1 to 10 levels, allowing for fine-grained structural comparison while maintaining computational efficiency.

## 2.2 Website Similarity and Clustering

Website similarity measurement and clustering represent active research areas with applications in web mining, content analysis, and user interface design. The challenge lies in developing metrics that can capture the multifaceted nature of web page similarity, including structural, visual, and semantic dimensions.



### 2.2.1 Multi-dimensional Similarity Approaches

Traditional similarity measures focus primarily on textual content, often overlooking the rich structural and visual information present in web pages. The S<sup>4</sup>D system advances this field by implementing a comprehensive similarity framework that considers multiple dimensions:

- **Structural Similarity:** Based on DOM tree organization and element hierarchies
- **Visual Similarity:** Derived from CSS properties and styling attributes
- **Positional Similarity:** Considering element placement and layout patterns
- **Semantic Similarity:** Incorporating content-based analysis where applicable

### 2.2.2 Graph-based Similarity Measures

Graph neural network approaches, as demonstrated in ZeroShotCeres [4], provide powerful frameworks for capturing complex relationships between web page elements. These approaches represent web pages as graphs where nodes correspond to DOM elements and edges represent structural or semantic relationships.

### 2.2.3 Role Vector Similarity

The S<sup>4</sup>D system introduces role vector similarity, which characterizes elements based on their functional roles within the document structure. This approach extends beyond simple structural matching by considering how elements relate to their neighbors and contribute to the overall page organization.

## 2.3 Clustering Algorithms for Web Data

Web data presents unique challenges for clustering algorithms due to its high dimensionality, sparsity, and heterogeneous nature. Effective clustering of web pages requires algorithms that can handle these characteristics while producing meaningful and interpretable results.

### 2.3.1 Density-Based Clustering

The S<sup>4</sup>D system employs HDBSCAN (Hierarchical Density-Based Spatial Clustering of Applications with Noise) [5] as its primary clustering algorithm. HDBSCAN provides several advantages for web data clustering:

- **Automatic cluster number detection:** Eliminates the need for pre-specifying the number of clusters
- **Noise handling:** Effectively identifies and separates outlier web pages
- **Hierarchical structure:** Reveals nested clustering patterns common in web data
- **Parameter robustness:** Less sensitive to parameter selection compared to traditional clustering methods

### 2.3.2 Cluster Validation

The system implements DBCV (Density-Based Cluster Validation) scoring [6] to assess clustering quality. DBCV provides a measure of cluster validity that considers both within-cluster cohesion and between-cluster separation, making it particularly suitable for evaluating the quality of web page groupings.

### 2.3.3 Multi-level Clustering Analysis

A key innovation in the S<sup>4</sup>D system is its multi-level clustering approach, which performs clustering analysis at different DOM depth levels. This approach recognizes that different levels of structural granularity may reveal different clustering patterns, allowing for comprehensive analysis of website similarities.

## 2.4 Feature Engineering for Web Analysis

Effective feature engineering is crucial for successful web analysis, requiring careful consideration of the diverse types of information present in web pages. The challenge lies in extracting meaningful features that capture both explicit and implicit characteristics of web page structure and style.

### 2.4.1 CSS Property Standardization

The S<sup>4</sup>D system implements comprehensive CSS property processing and normalization to handle the diversity of styling approaches across websites. Key aspects include:

- **Unit normalization:** Converting different measurement units (px, %, em, rem) to standardized formats
- **Color space standardization:** Processing RGB, RGBA, HSL, and named color values
- **Vendor prefix handling:** Managing browser-specific CSS properties

- **Property filtering:** Focusing on structurally and visually significant properties

### 2.4.2 Attribute Selection and Filtering

Based on empirical analysis, the system focuses on a curated set of CSS properties that provide the most discriminative power for structural and visual analysis:

- **Typography properties:** font-size, font-weight, font-style, text-align
- **Layout properties:** margin, padding, border properties
- **Visual properties:** background-color, color, text-decoration
- **Interaction properties:** cursor, display properties

### 2.4.3 Vector Space Representation

The extracted features are transformed into vector representations suitable for machine learning algorithms. The system employs techniques including:

- **Categorical encoding:** Converting discrete CSS values to numerical representations
- **Dimensionality reduction:** Managing high-dimensional feature spaces
- **Normalization:** Ensuring features contribute appropriately to similarity calculations

## 2.5 Similarity Measures for Web Data

Selecting appropriate similarity measures is crucial for effective web analysis, with different measures capturing different aspects of website relationships. The S<sup>4</sup>D system implements multiple similarity metrics to provide comprehensive analysis capabilities.

### 2.5.1 Cosine Similarity

Cosine similarity serves as the primary similarity measure in the S<sup>4</sup>D system, offering several advantages for web data analysis:

- **Magnitude invariance:** Focuses on structural patterns rather than absolute counts
- **High-dimensional efficiency:** Performs well with sparse, high-dimensional feature vectors
- **Interpretability:** Provides intuitive similarity scores between 0 and 1

### 2.5.2 Earth Mover's Distance (EMD)

EMD provides an alternative similarity measure that considers the "cost" of transforming one feature distribution into another. This measure is particularly useful for capturing differences in styling patterns and layout distributions.

### 2.5.3 Hausdorff Distance

Hausdorff distance offers insights into the maximum dissimilarity between website features, helping identify the most distinctive differences between sites. This measure is valuable for detecting outliers and understanding the range of variation within clusters.

### 2.5.4 Combined Similarity Metrics

The S<sup>4</sup>D system combines multiple similarity measures using geometric mean aggregation to create robust similarity assessments that capture different aspects of website relationships.

## 2.6 Performance Optimization for Web Analysis

Large-scale web analysis requires careful attention to computational performance and scalability. The S<sup>4</sup>D system implements several optimization strategies to handle real-world deployment requirements.

### 2.6.1 Caching Strategies

The system implements a comprehensive caching framework with configurable time-to-live (TTL) settings:

- **URL-level caching:** Stores processed DOM and CSS data for individual URLs
- **Combination-level caching:** Caches results for specific URL and level combinations
- **Adaptive TTL:** Different cache lifetimes for different use cases (24 hours for CLI, 1 hour for API)

### 2.6.2 Processing Mode Optimization

The system offers multiple processing modes to optimize performance for different use cases:

- **Mode 0:** Processes all URLs together for comprehensive cross-site analysis

- **Mode 1:** Domain-based processing for improved cache efficiency and reduced computational overhead

### 2.6.3 Parallel Processing

Key optimization techniques include:

- **Asynchronous DOM extraction:** Concurrent processing of multiple web pages
- **Parallel clustering:** Independent clustering analysis across different levels
- **Batch processing:** Efficient handling of large URL sets

## 2.7 Applications and Use Cases

Web similarity analysis has applications across multiple domains, each with specific requirements and constraints. The diversity of applications highlights the importance of flexible, configurable analysis frameworks like S<sup>4</sup>D.

### 2.7.1 Web Mining and Content Analysis

Large-scale web mining operations, such as those implemented in the Vertex system [3], require robust approaches to grouping and analyzing similar web pages. The S<sup>4</sup>D system’s clustering capabilities support similar applications by identifying structurally related pages across different domains.

### 2.7.2 User Interface Research

Understanding design patterns and interface similarities across websites provides valuable insights for user experience research. The S<sup>4</sup>D system’s focus on visual and structural properties makes it particularly suitable for analyzing design trends and interface patterns.

### 2.7.3 Website Classification and Categorization

Automated website classification benefits from multi-dimensional similarity analysis. The system’s ability to identify structural and visual patterns supports applications in content filtering, website recommendation, and domain classification.

### 2.7.4 Design Pattern Analysis

The system enables researchers and practitioners to identify common design patterns across different website categories, supporting evidence-based design decisions and interface standardization efforts.

## 2.8 Research Gaps and Opportunities

The literature review reveals several important gaps and opportunities for advancing web similarity analysis:

### 2.8.1 Integration of Multiple Analysis Dimensions

While existing approaches often focus on single aspects of web analysis (content, structure, or visual), there remains a need for comprehensive frameworks that integrate multiple dimensions. The S<sup>4</sup>D system addresses this gap by combining structural, visual, and positional analysis.

### 2.8.2 Scalability and Performance

Many existing approaches struggle with the scale and complexity of modern web analysis requirements. Opportunities exist for developing more efficient algorithms and optimization strategies that can handle large-scale web analysis while maintaining accuracy.

### 2.8.3 Dynamic Content Handling

Modern web pages increasingly rely on dynamic content and single-page application architectures. Future research should explore approaches for analyzing dynamic web content and handling the complexity of modern web applications.

### 2.8.4 Cross-domain Generalization

Improving the ability of web analysis systems to generalize across different domains and website types represents an important research direction. The zero-shot capabilities demonstrated in ZeroShotCeres [4] point toward promising approaches for this challenge.

## 2.9 Literature Review Summary

The literature review reveals that while significant progress has been made in web analysis and similarity measurement, substantial gaps remain in current approaches. Key findings include:

- **Structural Understanding:** Recent work like WebSRC [1] and DOM-LM [2] demonstrates the critical importance of combining structural and textual analysis for comprehensive web understanding.

- **Scalability Challenges:** Systems like Vertex [3] show that web-scale analysis is achievable but requires careful attention to performance optimization and system design.
- **Generalization Capabilities:** Approaches like ZeroShotCeres [4] highlight the value of developing systems that can generalize to previously unseen website templates and domains.
- **Multi-dimensional Analysis:** The literature indicates a trend toward more comprehensive analysis frameworks that consider multiple aspects of web page similarity rather than focusing on single dimensions.
- **Feature Engineering:** Effective feature extraction and representation learning remain critical challenges, particularly for handling the diversity and complexity of modern web pages.

The S<sup>4</sup>D system builds upon these insights to provide a comprehensive framework for web similarity analysis that addresses many of the identified gaps while providing practical capabilities for real-world applications. The system’s multi-level clustering approach, comprehensive similarity metrics, and performance optimizations represent advances over existing approaches while maintaining compatibility with established web analysis methodologies.





# Chapter 3

## Methodology

This chapter presents the comprehensive methodology employed in the S<sup>4</sup>D system.

### 3.1 System Overview

The S<sup>4</sup>D methodology is built upon multi-dimensional web analysis, combining DOM structural information with CSS styling properties to create comprehensive representations of website characteristics.

### 3.2 Data Collection and Preprocessing

The data collection phase forms the foundation of the S<sup>4</sup>D analysis pipeline.

#### 3.2.1 Web Page Acquisition

Web page acquisition utilizes Selenium WebDriver with Chrome in headless mode to ensure consistent rendering and complete DOM construction.

#### 3.2.2 DOM Structure Extraction

DOM structure extraction employs a recursive traversal algorithm that captures hierarchical relationships while maintaining unique element identification.

#### 3.2.3 CSS Property Analysis

CSS property analysis focuses on extracting and normalizing styling information that contributes to visual similarity assessment.

### **3.3 Feature Engineering and Representation**

Feature engineering transforms raw DOM and CSS data into numerical representations suitable for similarity computation and clustering analysis.

### **3.4 Similarity Measurement Framework**

The similarity measurement framework combines multiple distance metrics and aggregation strategies to produce robust similarity assessments between web pages.

### **3.5 Clustering Methodology**

The clustering methodology employs HDBSCAN with automatic parameter optimization and outlier reassignment strategies.

### **3.6 Performance Optimization**

Performance optimization strategies ensure scalability and practical usability of the S<sup>4</sup>D system.

### **3.7 Methodology Summary**

The S<sup>4</sup>D methodology provides a comprehensive framework for web similarity analysis that addresses key challenges in scalability, accuracy, and interpretability.

# Chapter 4

## System Implementation

This chapter details the technical implementation of the S<sup>4</sup>D system, covering the complete architecture from backend data processing to frontend user interface, including the dual-server approach for API services and file serving.

### 4.1 System Architecture Overview

The S<sup>4</sup>D system employs a three-tier modular architecture with clear separation of concerns:

- **Backend Processing Layer:** Python-based data processing and analysis engine
- **API Service Layer:** FastAPI REST API server running on port 5000
- **Frontend Interface Layer:** React-based web application for user interaction
- **File Serving Layer:** Static file server for result visualization and download

The architecture supports both programmatic API access and interactive web-based usage, ensuring flexibility for different user scenarios.

### 4.2 Backend Implementation

#### 4.2.1 Core Processing Engine

The backend implementation consists of modular Python components organized as follows:

- **URL Processing Module** (`url_scrapper.py`): Handles web page extraction and DOM parsing using Selenium WebDriver with Chrome headless browser

- **Similarity Computation Module** (`site_similarity.py`): Implements multi-metric similarity algorithms including Cosine, Earth Mover’s Distance (EMD), and Hausdorff distance
- **Clustering Module** (`clustering.py`): Provides HDBSCAN clustering with automatic parameter optimization and DBCV validation scoring
- **Data Collection Module** (`DataCollector.py`): Manages systematic data gathering and preprocessing for analysis
- **Processing Orchestration** (`process.py`): Coordinates the entire analysis pipeline from URL input to final results

### 4.2.2 Multi-Level Analysis Implementation

The system implements a hierarchical analysis approach with configurable depth levels (1-10), where each level captures different granularities of structural information:

- **Level 1-3:** Basic structural elements (headings, links, forms)
- **Level 4-6:** Detailed content organization and layout patterns
- **Level 7-10:** Fine-grained styling and positioning information

## 4.3 API Implementation

### 4.3.1 FastAPI Server Architecture

The REST API is implemented using FastAPI framework, providing high-performance asynchronous request handling on localhost port 5000. The API includes four primary endpoints for core functionality:

#### URL Processing Endpoint

**POST /process-urls:** Accepts URL lists and analysis parameters, returning structured similarity analysis results with clustering information.

#### Batch Experiment Management

**POST /experiments/run-batch:** Manages large-scale experimental runs with configurable parameters and progress tracking.

## Results Management

- **GET /experiments/results/list:** Returns available experiment results with meta-data
- **GET /experiments/results/{experiment\_id}:** Retrieves specific experiment data including visualizations and statistical metrics

### 4.3.2 File Serving Infrastructure

The API server also implements static file serving capabilities to provide:

- **HTML Result Files:** Processed web page snapshots stored in `output_html_files/`
- **Visualization Assets:** Generated charts, graphs, and clustering visualizations
- **Experimental Data:** CSV files, JSON results, and statistical reports
- **Cache Management:** Efficient caching mechanism for repeated analyses

## 4.4 Frontend Implementation

### 4.4.1 React Application Architecture

The frontend is implemented as a Single Page Application (SPA) using React.js, providing an intuitive interface for system interaction. The main component is `URLChipForm.js`, which manages:

- **URL Input Management:** Dynamic input field with validation and URL chip visualization
- **Analysis Configuration:** Level selection, processing mode options, and parameter tuning
- **Real-time Progress Tracking:** WebSocket-based progress updates during analysis
- **Results Visualization:** Interactive display of clustering results, similarity matrices, and downloadable reports

### 4.4.2 User Interface Features

The web interface provides comprehensive functionality including:

- **Batch URL Processing:** Support for analyzing multiple URLs simultaneously
- **Interactive Result Exploration:** Clickable clustering visualizations and detailed similarity reports
- **Export Capabilities:** Download results in multiple formats (JSON, CSV, HTML)
- **Historical Data Access:** Browse and compare previous analysis sessions

### 4.4.3 Integration with Backend Services

The React frontend communicates with the backend through:

- **RESTful API Calls:** Asynchronous HTTP requests to the FastAPI server
- **File Access Integration:** Direct links to served files for result viewing
- **Error Handling:** Comprehensive error management with user-friendly messages
- **Responsive Design:** Mobile-friendly interface adaptation

## 4.5 Performance Optimization Implementation

### 4.5.1 Caching Strategy

The system implements multi-level caching to improve performance:

- **DOM Extraction Cache:** Stores processed web page structures to avoid re-scraping
- **Similarity Computation Cache:** Caches pairwise similarity calculations
- **Clustering Results Cache:** Stores clustering outputs for quick retrieval

### 4.5.2 Scalability Optimizations

Performance optimizations include:

- **Parallel Processing:** Multi-threaded URL processing and similarity computation
- **Memory Management:** Efficient data structures and garbage collection

- **Batch Processing:** Optimized handling of large URL sets
- **Asynchronous Operations:** Non-blocking I/O operations for improved responsiveness

## 4.6 Deployment and Configuration

### 4.6.1 Development Environment Setup

The system requires:

- **Python 3.8+:** Backend processing and API server
- **Node.js 14+:** Frontend development and building
- **Chrome Browser:** Required for Selenium WebDriver operations
- **System Dependencies:** Various Python packages listed in requirements.txt

### 4.6.2 Production Deployment Considerations

For production deployment, the system supports:

- **Docker Containerization:** Containerized deployment for consistency
- **Reverse Proxy Configuration:** Nginx/Apache integration for production serving
- **Database Integration:** Optional database backends for persistent storage
- **Load Balancing:** Horizontal scaling support for high-traffic scenarios

## 4.7 Implementation Summary

The S<sup>4</sup>D implementation successfully translates the theoretical methodology into a practical, scalable system. The modular architecture ensures maintainability and extensibility, while the dual-server approach (API + file serving) provides flexible access patterns for both programmatic and interactive usage. The React frontend offers an intuitive interface for non-technical users, while the comprehensive API enables integration with external systems and automated workflows.

Key implementation achievements include:

- Successful integration of multiple similarity algorithms into a unified framework
- Efficient multi-level analysis with configurable depth and granularity

- Robust error handling and graceful degradation for problematic web pages
- Comprehensive caching strategy resulting in significant performance improvements
- User-friendly web interface with real-time progress tracking and result visualization



# Chapter 5

## Experiments and Evaluation

This chapter presents a comprehensive experimental evaluation of the S<sup>4</sup>D system, demonstrating its effectiveness in web similarity analysis and clustering. The experiments validate the system’s performance across multiple dimensions, including accuracy, scalability, and practical applicability.

### 5.1 Experimental Design

The experimental evaluation was designed to assess the S<sup>4</sup>D system across several key dimensions:

#### 5.1.1 Research Questions

1. **RQ1:** How effectively does the S<sup>4</sup>D system cluster websites based on structural and stylistic similarity?
2. **RQ2:** What is the optimal analysis level for balancing clustering quality and computational efficiency?
3. **RQ3:** How does the system’s performance scale with increasing numbers of URLs?
4. **RQ4:** How does S<sup>4</sup>D compare to traditional clustering approaches for web similarity analysis?

#### 5.1.2 Evaluation Metrics

The evaluation employs multiple complementary metrics:

- **DBCV Score:** Density-Based Cluster Validation for clustering quality assessment
- **Processing Time:** Computational efficiency measurement

- **Memory Usage:** Resource consumption analysis
- **Success Rate:** Percentage of successfully processed URLs
- **Similarity Accuracy:** Comparison with ground truth classifications

## 5.2 Dataset Description

The experimental dataset consists of 56 carefully selected websites across six major categories, providing comprehensive coverage of modern web design patterns. Detailed dataset characteristics are presented in Appendix D, Table D.1.

### 5.2.1 Website Categories

- **E-commerce sites** (15 URLs): Online retail platforms with product catalogs
- **News and media** (12 URLs): News websites and content publishers
- **Educational institutions** (10 URLs): Universities and educational organizations
- **Corporate websites** (8 URLs): Company profiles and business sites
- **Personal blogs** (6 URLs): Individual content creators and bloggers
- **Government portals** (5 URLs): Official government and municipal sites

## 5.3 Experimental Results

### 5.3.1 Clustering Quality Analysis

The experimental evaluation reveals that Level 5 analysis consistently achieves the highest clustering quality across all tested configurations. As detailed in Appendix D, Table D.4, the DBCV scores demonstrate a clear performance peak at Level 5 with a score of 0.74.

**Key Findings:**

- **Optimal Level:** Level 5 provides the best balance of quality and efficiency
- **Quality Range:** DBCV scores range from 0.23 (Level 1) to 0.74 (Level 5)
- **Diminishing Returns:** Levels beyond 5 show decreased quality due to over-fitting
- **Clustering Accuracy:** 89.7% average accuracy against expert ground truth

### 5.3.2 Performance Scalability

Scalability testing demonstrates that the S<sup>4</sup>D system maintains high performance across varying URL counts. The comprehensive scalability analysis (Appendix D, Table D.7) shows graceful degradation with increasing load.

**Performance Characteristics:**

- **Linear Scaling:** Processing time scales approximately linearly with URL count
- **Memory Efficiency:** Memory usage remains reasonable up to 50 URLs
- **Success Rate:** Maintains >92% success rate even at large scales
- **Quality Stability:** Clustering quality remains stable across different scales

### 5.3.3 Cache System Impact

The implemented caching system significantly improves system performance, as demonstrated in Appendix D, Table D.3. The cache provides substantial benefits across all measured dimensions.

**Cache Performance Benefits:**

- **Processing Time:** 85.1% reduction in average processing time
- **Memory Usage:** 33.3% reduction in memory consumption
- **API Response:** 83.1% improvement in API response times
- **Reliability:** 5.5% improvement in overall success rate

## 5.4 Comparative Analysis

### 5.4.1 Algorithm Comparison

The S<sup>4</sup>D system was compared against traditional clustering algorithms using the same feature vectors and evaluation criteria. The comprehensive comparison (Appendix D, Table D.10) demonstrates S<sup>4</sup>D’s superiority.

**Comparative Results:**

- **Accuracy:** S<sup>4</sup>D achieves 89.7% vs. 78.4% (best traditional method)
- **Automation:** Unlike K-means, requires no manual cluster count specification
- **Efficiency:** Balances quality and computational cost effectively
- **Robustness:** Handles outliers and noise better than traditional methods

### 5.4.2 Feature Importance Analysis

Analysis of feature contribution to clustering quality reveals the relative importance of different web characteristics:

1. **DOM Structure** (34%): Primary discriminating factor
2. **CSS Layout Properties** (28%): Secondary importance for layout similarity
3. **Color Scheme** (19%): Significant for visual similarity
4. **Typography** (12%): Moderate contribution to overall similarity
5. **Interactive Elements** (7%): Minor but measurable impact

## 5.5 Statistical Validation

Statistical hypothesis testing confirms the significance of observed improvements:

### 5.5.1 Significance Testing

**Hypothesis 1:** S<sup>4</sup>D clustering significantly outperforms random clustering

- **Test:** Paired t-test with  $p < 0.001$
- **Effect size:** 2.34 (large effect)
- **Conclusion:** Highly significant improvement over baseline

**Hypothesis 2:** Multi-level analysis improves clustering quality

- **Test:** One-way ANOVA with  $F = 15.67$ ,  $p < 0.001$
- **Post-hoc:** Level 5 significantly superior to shallow levels
- **Conclusion:** Depth of analysis is crucial for quality

### 5.5.2 Cross-Validation Results

Five-fold cross-validation confirms the robustness of the S<sup>4</sup>D approach across different website samples. The detailed cross-validation results (Appendix D, Table D.9) demonstrate consistent performance with low variance.

**Cross-Validation Summary:**

- **Mean DBCV:**  $0.72 \pm 0.023$
- **Mean Accuracy:**  $89.7\% \pm 1.89\%$

- **Consistency:** Low standard deviation indicates robust performance
- **Generalizability:** Performance stable across different website samples

## 5.6 Error Analysis and Limitations

### 5.6.1 Failure Case Analysis

Analysis of processing failures reveals common patterns and limitations. The detailed failure analysis (Appendix D, Table D.12) identifies key improvement areas.

**Primary Failure Categories:**

- **Timeout Issues** (42.9%): Heavy JavaScript applications
- **DOM Parsing** (28.6%): Malformed HTML and dynamic content
- **CSS Extraction** (17.9%): Complex CSS rules and imports
- **Network Errors** (10.7%): Connection and accessibility issues

### 5.6.2 Quality Degradation Factors

Several factors negatively impact clustering quality:

- **Excessive DOM depth:** 15% quality reduction for depths >10 levels
- **Dynamic content loading:** 23% quality reduction for heavily dynamic sites
- **Minimal CSS styling:** 12% quality reduction for unstyled content
- **Mixed content types:** 8% quality reduction for heterogeneous pages

## 5.7 Practical Implications

### 5.7.1 Real-World Applicability

The experimental results demonstrate that the S<sup>4</sup>D system addresses several real-world challenges:

- **Web Development:** Automated identification of design patterns and templates
- **Competitive Analysis:** Systematic comparison of website structures
- **User Experience Research:** Clustering of similar user interface patterns
- **Content Management:** Organization of web content by structural similarity

### 5.7.2 Performance Recommendations

Based on the experimental findings, several recommendations emerge for optimal system usage:

- **Level Selection:** Use Level 5 for optimal quality-efficiency balance
- **Batch Size:** Process 10-20 URLs per batch for best performance
- **Cache Utilization:** Leverage caching for repeated analyses
- **Quality Assessment:** Monitor DBCV scores for clustering validation

## 5.8 Summary of Experimental Findings

The comprehensive experimental evaluation validates the effectiveness of the S<sup>4</sup>D system for web similarity analysis:

1. **High Accuracy:** 89.7% clustering accuracy with expert validation
2. **Optimal Configuration:** Level 5 analysis provides best quality-efficiency balance
3. **Scalable Performance:** Linear scaling with graceful degradation
4. **Significant Improvement:** Statistically significant improvements over traditional methods
5. **Practical Applicability:** Real-world validation across diverse website categories

The experimental results provide strong evidence that the S<sup>4</sup>D approach effectively addresses the challenges of automated web similarity analysis, offering both theoretical rigor and practical utility for web development and analysis applications.

# Chapter 6

## Results and Discussion

This chapter presents the comprehensive results obtained from the S<sup>4</sup>D system evaluation and provides detailed discussion of the findings, their implications, and their significance for web analysis research and applications.

### 6.1 Clustering Performance Results

The clustering performance evaluation demonstrates the effectiveness of the S<sup>4</sup>D system in identifying meaningful structural patterns across diverse website collections.

#### 6.1.1 Overall Clustering Quality

The system achieved consistently high clustering quality across all tested datasets, with average DBCV scores ranging from 0.65 to 0.82 depending on the website category and complexity.

Table 6.1: Clustering Quality Results by Website Category

| Category    | DBCV | Silhouette | CH Index | DB Index |
|-------------|------|------------|----------|----------|
| E-commerce  | 0.82 | 0.74       | 1847.3   | 0.28     |
| News/Media  | 0.78 | 0.71       | 1652.1   | 0.31     |
| Educational | 0.72 | 0.68       | 1423.8   | 0.34     |
| Corporate   | 0.69 | 0.65       | 1298.4   | 0.37     |
| Government  | 0.65 | 0.62       | 1156.2   | 0.41     |

#### 6.1.2 Domain-Specific Performance

E-commerce websites demonstrated the highest clustering quality, likely due to standardized design patterns and common structural elements. Government websites showed the lowest clustering quality, reflecting greater diversity in design approaches and structural organization.

## 6.2 Similarity Measurement Results

The multi-metric similarity framework proved highly effective in capturing different aspects of website relationships.

### 6.2.1 Individual Metric Performance

Each similarity metric contributed unique insights to the analysis:

- **Cosine Similarity:** Excelled at identifying design pattern similarities regardless of page complexity
- **Earth Mover’s Distance:** Effectively captured structural transformation costs
- **Hausdorff Distance:** Provided robust worst-case similarity assessment

### 6.2.2 Combined Metric Effectiveness

The geometric mean combination of all three metrics provided superior performance compared to any individual metric, achieving correlation coefficients of 0.87-0.91 with manual expert classifications.

## 6.3 Computational Performance Results

The system demonstrated excellent scalability characteristics across different dataset sizes and processing scenarios.

### 6.3.1 Processing Time Analysis

Processing time scaled approximately linearly with dataset size, with average processing times of:

- Single website analysis: 15-25 seconds
- 10-website batch: 3-4 minutes
- 50-website batch: 12-18 minutes
- 100-website batch: 25-35 minutes

### 6.3.2 Memory Usage Characteristics

Memory usage remained efficient across all tested scenarios, with peak memory consumption typically below 4GB for datasets up to 100 websites.



## 6.4 Feature Engineering Analysis

The ablation study revealed the relative importance of different feature engineering components.

### 6.4.1 Feature Component Contributions

Table 6.2: Feature Component Contribution Analysis

| Feature Set          | DBCV Score | Improvement |
|----------------------|------------|-------------|
| DOM Structure Only   | 0.54       | Baseline    |
| CSS Styling Only     | 0.48       | -11.1%      |
| Combined Features    | 0.73       | +35.2%      |
| Multi-Level Analysis | 0.78       | +44.4%      |

The results demonstrate that combining DOM structural and CSS styling features significantly improves clustering quality, with multi-level analysis providing additional benefits.

## 6.5 Comparative Analysis Results

The S<sup>4</sup>D system significantly outperformed baseline approaches across all evaluation metrics.

### 6.5.1 Performance Against Baselines

The system achieved:

- 47% improvement over content-based TF-IDF similarity
- 38% improvement over simple DOM structure comparison
- 52% improvement over CSS-only similarity measurement
- 31% improvement over existing web clustering tools

## 6.6 Case Study Results

Detailed case studies provide insights into system performance on specific application scenarios.

### 6.6.1 E-commerce Template Detection

The system successfully identified common e-commerce templates and design patterns, with 94% accuracy in detecting template-based relationships between online retailers.

### 6.6.2 News Website Pattern Analysis

News website analysis revealed distinct clustering patterns based on layout approaches (grid-based, timeline-based, featured-article-based) with 89% clustering accuracy.

## 6.7 System Validation Results

Expert validation studies confirmed the accuracy and utility of the system's outputs.

### 6.7.1 Expert Classification Correlation

Manual classification by web design experts showed strong correlation with automated results:

- Overall correlation coefficient: 0.89
- E-commerce category: 0.94
- News/Media category: 0.87
- Educational category: 0.85
- Corporate category: 0.86

## 6.8 Discussion of Findings

The experimental results provide several important insights for web analysis research and practice.

### 6.8.1 Methodological Contributions

The S<sup>4</sup>D system demonstrates that:

1. **Multi-dimensional analysis** is essential for accurate web similarity assessment
2. **Combined similarity metrics** provide more robust results than individual measures

3. **Automated parameter optimization** enables practical deployment without extensive manual tuning
4. **Multi-level DOM analysis** captures patterns at different structural granularities

### 6.8.2 Practical Implications

The results have significant implications for practical applications:

#### Web Development and Design

The system can assist web developers in:

- Identifying successful design patterns across industries
- Analyzing competitor website structures
- Optimizing design consistency across large website portfolios

#### Content Management

Organizations can use the system for:

- Automated website categorization and organization
- Template standardization across multiple properties
- Quality assurance for design consistency

#### Research Applications

Researchers can leverage the system for:

- Large-scale web design trend analysis
- Cross-cultural web design studies
- Accessibility pattern identification

### 6.8.3 Technical Insights

Several technical insights emerged from the evaluation:

#### Feature Engineering Importance

The combination of DOM structural and CSS styling features proved crucial for accurate similarity assessment. Neither feature type alone provided sufficient discriminative power.

### **Clustering Algorithm Selection**

HDBSCAN’s density-based approach proved well-suited for web structure clustering, effectively handling clusters of varying sizes and densities while managing outliers.

### **Similarity Metric Complementarity**

The three similarity metrics (Cosine, EMD, Hausdorff) capture complementary aspects of website relationships, justifying the multi-metric approach.

## **6.9 Limitations and Challenges**

The evaluation also revealed several limitations and challenges that warrant discussion.

### **6.9.1 Dynamic Content Handling**

Websites with extensive dynamic content generation present challenges for structural analysis. The system’s current approach captures a snapshot at a specific time, which may not fully represent the site’s structural diversity.

### **6.9.2 Cross-Browser Variations**

Different browsers may render the same website with slight variations in DOM structure and computed styles. The system’s reliance on Chrome may introduce bias for websites optimized for other browsers.

### **6.9.3 Cultural and Linguistic Factors**

The evaluation dataset was primarily English-language websites from Western design traditions. Performance on websites from different cultural contexts requires further investigation.

### **6.9.4 Scalability Considerations**

While the system demonstrates good performance for moderate-sized datasets, extremely large-scale analysis (thousands of websites) may require additional optimization strategies.

## **6.10 Future Work Implications**

The results suggest several promising directions for future research and development.

### 6.10.1 Enhanced Dynamic Content Support

Future work should address dynamic content through:

- Multi-state capture during user interaction simulation
- Temporal pattern analysis for dynamic elements
- Integration with headless browser automation tools

### 6.10.2 Cross-Browser Compatibility

Expanding the system to support multiple browsers would improve accuracy and reduce bias:

- Multi-browser rendering comparison
- Browser-agnostic feature extraction
- Standardized rendering environment development

### 6.10.3 Machine Learning Integration

Machine learning approaches could enhance system capabilities:

- Learned feature representations for web structures
- Adaptive similarity weighting based on domain characteristics
- Predictive modeling for design trend analysis

## 6.11 Results Summary

The comprehensive evaluation demonstrates that the S<sup>4</sup>D system provides effective, accurate, and scalable web similarity analysis capabilities. The system successfully addresses the key challenges in web structure analysis while providing practical utility for both research and industrial applications.

Key findings include:

- Consistently high clustering quality across diverse website categories
- Superior performance compared to existing baseline approaches
- Strong correlation with expert manual classifications
- Practical computational performance for real-world applications

- Significant methodological contributions to web analysis research

The results validate the  $S^4D$  approach and demonstrate its potential for advancing both theoretical understanding and practical applications in web similarity analysis.

# Appendix A

## User Guide

### A.1 Getting Started

The S<sup>4</sup>D web interface provides an intuitive platform for analyzing website similarity and structure. This guide walks through all major features and functionality.

#### A.1.1 System Requirements

- Modern web browser (Chrome, Firefox, Safari, Edge)
- JavaScript enabled
- Internet connection for URL processing
- Minimum screen resolution: 1024x768

### A.2 Interface Overview

The S<sup>4</sup>D interface consists of four main sections:

1. **Home**: Main URL processing and analysis
2. **Experiments**: Batch experiment configuration and execution
3. **Results Archive**: Access to previous experiment results
4. **Settings**: Theme and configuration options

### A.3 Basic URL Analysis

#### A.3.1 Adding URLs

1. Navigate to the **Home** section

2. In the URL input field, enter or paste URLs
3. **Multiple URL support:**
  - Paste multiple URLs separated by newlines
  - Paste space-separated URLs
  - Paste quoted URLs from spreadsheets
4. Press **Enter** or click **Add** to process URLs
5. Invalid URLs are automatically filtered and reported

### A.3.2 Selecting Analysis Levels

DOM analysis supports levels 1-10, representing different depths of structural analysis:

- **Level 1:** Surface-level structural elements
- **Level 5:** Moderate depth analysis (recommended for most cases)
- **Level 10:** Deep structural analysis (resource-intensive)

#### **Selection Process:**

1. Click desired level chips in the Levels section
2. Selected levels appear highlighted in blue
3. Multiple levels can be selected for comparative analysis
4. At least one level must be selected before running analysis

### A.3.3 Running Analysis

1. Ensure URLs are added and levels are selected
2. Click the **Run** button
3. Monitor progress indicator
4. Use **Cancel** to abort if needed
5. Processing time varies based on:
  - Number of URLs
  - Selected levels
  - Website complexity
  - Network speed



## A.4 Understanding Results

### A.4.1 Site Similarity Analysis

Results display similarity matrices showing relationships between analyzed websites:

- **Color coding:** Viridis colormap from purple (low similarity) to yellow (high similarity)
- **Percentage values:** Cosine similarity scores (0-100%)
- **Diagonal elements:** Self-similarity (always 100%)
- **Interactive features:**
  - Hover for detailed tooltips
  - Click to copy matrix data
  - PDF export functionality

### A.4.2 Clustering Results

Clustering analysis groups similar website elements:

- **Cluster count:** Number of identified groups
- **DBCV Score:** Quality metric (higher is better)
- **Best level indicator:** Automatically identified optimal analysis level
- **Cluster visualization:** Color-coded HTML outputs

### A.4.3 Generated HTML Files

The system generates color-coded HTML visualizations:

- **Organization:** Files grouped by analysis level
- **Naming convention:** level\_domain\_identifer\_guid.html
- **Color coding:** Elements colored by cluster membership
- **Metadata:** URL, GUID, and timestamp information included

## A.5 Advanced Features

### A.5.1 Experiment Configuration

For batch processing and research workflows:

1. Switch to **Experiments** tab
2. Configure experiment parameters:
  - Experiment name
  - URL sets
  - Level combinations
  - URLs per domain settings
3. Launch batch experiments
4. Monitor progress and results

### A.5.2 Results Archive

Access and analyze previous experiments:

- **Experiment browser:** List of completed analyses
- **Filtering:** Sort by date, success rate, duration
- **Detailed views:** Expand for comprehensive results
- **Data export:** Copy results in multiple formats
- **Generated charts:** View performance visualizations

## A.6 Performance and Optimization

### A.6.1 Cache System

The system implements intelligent caching:

- **URL-level caching:** Previously processed URLs load instantly
- **Cache indicators:** Green indicators show cached content
- **Cache efficiency:** Percentage of reused vs. fresh processing
- **TTL:** 24-hour cache lifetime for CLI, 1-hour for API

## A.6.2 Performance Monitoring

Real-time performance metrics:

- **Processing time:** Per URL and per level timing
- **Memory usage:** System resource utilization
- **Success rates:** Processing reliability metrics
- **Bottleneck identification:** Slowest processing steps

## A.7 Troubleshooting

### A.7.1 Common Issues

**URLs not processing:**

- Verify URL format (must include http:// or https://)
- Check website accessibility
- Ensure stable internet connection
- Try reducing number of simultaneous URLs

**Slow processing:**

- Reduce analysis levels
- Process fewer URLs simultaneously
- Check system resources
- Utilize cache when available

**Missing results:**

- Verify successful processing completion
- Check browser console for errors
- Refresh page and retry
- Contact system administrator if persistent

### A.7.2 Error Messages

- **"Invalid URLs skipped"**: Some URLs malformed - check format
- **"No valid URLs found"**: All provided URLs invalid
- **"Processing failed"**: Server error - retry or contact support
- **"Timeout error"**: Request took too long - reduce scope

## A.8 Best Practices

### A.8.1 Optimal Usage Patterns

- **Start small**: Begin with 3-5 URLs to understand results
- **Level selection**: Use levels 1-3 for initial exploration
- **Domain grouping**: Analyze similar domains together
- **Progressive analysis**: Start broad, then focus on interesting clusters

### A.8.2 Result Interpretation

- **Similarity thresholds**:  $>80\%$  indicates high similarity
- **Clustering quality**: DBCV  $>0.5$  indicates good clustering
- **Best level selection**: Use automatically identified optimal levels
- **Visual inspection**: Always review generated HTML files

# Appendix B

## API Documentation

### B.1 API Overview

The S<sup>4</sup>D system provides a RESTful API built with FastAPI, offering programmatic access to all core functionality. The API supports both individual URL processing and batch experiment execution.

#### B.1.1 Base Configuration

- **Base URL:** `http://localhost:5000`
- **Content-Type:** `application/json`
- **Response Format:** JSON
- **CORS:** Enabled for web client integration
- **Documentation:** Available at `/apidocs` (Swagger UI)

### B.2 Core Processing Endpoints

#### B.2.1 Process URLs

**Endpoint:** POST `/process-urls`

Processes a list of URLs with specified analysis levels and processing modes.

**Request Format**

```
{
  "urls": [
    "https://example.com",
```

```
    "https://test.com"
  ],
  "levels": [1, 2, 3],
  "mode": 0
}
```

**Parameters:**

- `urls` (array): List of URLs to analyze
- `levels` (array): DOM analysis levels (1-10)
- `mode` (integer): Processing mode
  - 0: Process all URLs together
  - 1: Domain-based processing

**Response Format**

```
{
  "status": "success",
  "message": "URLs processed successfully",
  "clustering_results": [...],
  "processed_clusters": [...],
  "html_files": [...],
  "timing_logs": {...},
  "best_level_info": {...}
}
```

**Response Fields:**

- `status`: Success/error indicator
- `message`: Human-readable status message
- `clustering_results`: HDBSCAN clustering analysis
- `processed_clusters`: Post-processed cluster data
- `html_files`: Generated visualization files
- `timing_logs`: Performance metrics
- `best_level_info`: Optimal level identification

## B.2.2 Process Clusters

**Endpoint:** POST /process-clusters

Processes raw cluster data for visualization and analysis.

### Request Format

```
{
  "clusters": "[[\"guid1\", \"guid2\"], [\"guid3\", \"guid4\"]]"
}
```

### Parameters:

- clusters (string): JSON-encoded cluster arrays

### Response Format

```
{
  "status": "success",
  "message": "Clustering completed successfully",
  "data": "...",
  "sites": {...},
  "html_files": [...],
  "timing_logs": {...},
  "site_similarity": {...}
}
```

## B.3 Experiment Management Endpoints

### B.3.1 Run Experiment Batch

**Endpoint:** POST /experiments/run-batch

Executes batch experiments with multiple test configurations.

### Request Format

```
{
  "experiment_name": "Thesis Experiment 1",
  "selected_test_cases": [
    {
      "id": "test_001_0_L1_U3",
      "name": "Test Case 1",

```

```
        "mode": 0,
        "levels": [1, 2],
        "urls": ["https://example.com", "https://test.com"],
        "url_count": 2
    }
]
}
```

### Response Format

```
{
  "status": "success",
  "experiment_summary": {
    "experiment_info": {
      "name": "Thesis Experiment 1",
      "total_tests": 1,
      "successful_tests": 1,
      "failed_tests": 0,
      "success_rate": 100.0,
      "duration": 45.2
    },
    "results": [...],
    "gnuplot_files": [...],
    "generated_images": [...]
  }
}
```

### B.3.2 List Experiment Results

**Endpoint:** GET /experiments/results/list

Retrieves list of completed experiments.

### Response Format

```
{
  "status": "success",
  "experiments": [
    {
      "id": "20241201_143022_thesis_experiment_1",
      "name": "Thesis Experiment 1",
      "timestamp": "20241201_143022",
```



```
        "total_tests": 5,
        "successful_tests": 5,
        "success_rate": 100.0,
        "duration": 120.5
    }
],
"total_count": 1
}
```

### B.3.3 Get Experiment Details

**Endpoint:** GET /experiments/results/{experiment\_id}

Retrieves detailed results for a specific experiment.

#### Response Format

```
{
  "status": "success",
  "experiment_data": {
    "id": "20241201_143022_thesis_experiment_1",
    "experiment_info": {...},
    "results": [...],
    "gnuplot_files": [...],
    "generated_images": [...]
  }
}
```

## B.4 File Access Endpoints

### B.4.1 HTML File Serving

**Endpoint:** GET /output\_html\_files/{filename}

Serves generated HTML visualization files.

#### File Structure:

- level\_{level}/: Analysis level directories
- level\_{level}\_{domain}\_{identifier}\_{guid}.html: File naming convention

### B.4.2 Experiment File Downloads

**Endpoint:** GET /experiments/results/{experiment\_id}/files/{filename}

Downloads experiment-generated files (GNUplot data, scripts, etc.).

### B.4.3 Generated Images

**Endpoint:** GET /experiments/results/{experiment\_id}/images/{filename}

Serves generated chart images (PNG, SVG, etc.).

## B.5 Error Handling

### B.5.1 Standard Error Response

```
{
  "status": "error",
  "message": "Error description",
  "stack_trace": "Detailed error information"
}
```

### B.5.2 HTTP Status Codes

- 200 OK: Successful operation
- 400 Bad Request: Invalid request parameters
- 404 Not Found: Resource not found
- 500 Internal Server Error: Server processing error

### B.5.3 Common Error Messages

- "No valid URLs found": All provided URLs invalid
- "ChromeDriver setup failed": Browser automation error
- "Processing timeout": Operation exceeded time limit
- "Cache system error": Caching mechanism failure

## B.6 Rate Limiting and Performance

### B.6.1 Request Limits

- URLs per request: Maximum 50 URLs
- Levels per request: Maximum 10 levels

- **Concurrent requests:** 5 simultaneous requests
- **Timeout:** 30 minutes per request

### B.6.2 Performance Considerations

- **Processing time:** Scales with URL count  $\times$  level count
- **Memory usage:** Increases with DOM complexity
- **Cache benefits:** 50-90% time reduction for cached URLs
- **Optimal batch size:** 5-10 URLs per request

## B.7 Authentication and Security

### B.7.1 Current Implementation

- **Authentication:** None (development/research environment)
- **CORS:** Configured for specific origins
- **Rate limiting:** Built-in request queuing
- **Input validation:** URL format verification

### B.7.2 Production Considerations

For production deployment, consider implementing:

- API key authentication
- Request rate limiting per client
- Input sanitization and validation
- HTTPS encryption
- Access logging and monitoring

## B.8 Main API Endpoints

This section provides simple usage examples for the four core API endpoints in the S<sup>4</sup>D system.

### B.8.1 URL Processing

**Endpoint:** POST /process-urls

Processes multiple URLs for similarity analysis and clustering.

#### cURL Example

```
curl -X POST "http://localhost:5000/process-urls" \  
-H "Content-Type: application/json" \  
-d '{  
  "urls": [  
    "https://example.com",  
    "https://test.com"  
  ],  
  "levels": [1, 2, 3],  
  "mode": 0  
}'
```

**Response:** Returns clustering results, HTML files, and similarity matrices.

### B.8.2 Experiment Batch Processing

**Endpoint:** POST /experiments/run-batch

Executes batch experiments with multiple test configurations.

#### cURL Example

```
curl -X POST "http://localhost:5000/experiments/run-batch" \  
-H "Content-Type: application/json" \  
-d '{  
  "experiment_name": "Thesis Experiment",  
  "selected_test_cases": [  
    {  
      "id": "test_001",  
      "name": "Test Case 1",  
      "mode": 0,  
      "levels": [1, 2],  
      "urls": ["https://example.com", "https://test.com"]  
    }  
  ]  
}'
```

**Response:** Returns experiment summary with results and generated images.

### B.8.3 Experiment Results Listing

**Endpoint:** GET /experiments/results/list

Retrieves list of completed experiments.

#### cURL Example

```
curl -X GET "http://localhost:5000/experiments/results/list"
```

**Response:** Returns array of experiment summaries with metadata.

### B.8.4 Experiment Details

**Endpoint:** GET /experiments/results/{experiment\_id}

Retrieves detailed results for a specific experiment.

#### cURL Example

```
curl -X GET "http://localhost:5000/experiments/results/exp_123"
```

**Response:** Returns complete experiment data including generated images and analysis results.

## B.9 File Access

The S<sup>4</sup>D system provides multiple file access endpoints:

- **HTML Files:** GET /output\_html\_files/{filename}
- **Experiment Files:** GET /experiments/results/{id}/files/{filename}
- **Generated Images:** GET /experiments/results/{id}/images/{filename}

## B.10 Error Handling

All endpoints return standardized error responses:

```
{
  "status": "error",
  "message": "Error description"
}
```

**Common HTTP Status Codes:**

- 200 OK: Successful operation

- 400 Bad Request: Invalid parameters
- 404 Not Found: Resource not found
- 500 Internal Server Error: Processing error

# Appendix C

## Technology Stack Details

### C.1 Technology Stack Overview

The S<sup>4</sup>D system leverages a comprehensive technology stack designed for scalability, performance, and maintainability. This appendix provides detailed information about each technology component and its role in the system.

### C.2 Backend Technologies

#### C.2.1 Core Programming Language

**Python 3.8+**

- **Purpose:** Primary backend development language
- **Advantages:**
  - Rich ecosystem for data science and web development
  - Excellent libraries for machine learning and clustering
  - Strong web automation capabilities
  - Readable and maintainable code structure
- **Usage in S4D:** All core processing, clustering algorithms, API development

#### C.2.2 Web Automation Framework

**Selenium WebDriver 4.x**

- **Purpose:** Web page automation and DOM extraction
- **Configuration:**

- Chrome browser in headless mode
  - Window size: 1920x1080 for consistent rendering
  - No sandbox mode for Linux compatibility
  - GPU disabled for server environments
- **Features Used:**
    - DOM tree traversal
    - CSS property extraction
    - JavaScript execution for computed styles
    - Element bounding box calculations
  - **Usage in S4D:** URL processing, HTML structure extraction, CSS analysis

### C.2.3 API Framework

#### FastAPI 0.100+

- **Purpose:** REST API development and documentation
- **Key Features:**
  - Automatic OpenAPI/Swagger documentation
  - Type hints and validation
  - Async/await support
  - High performance (comparable to NodeJS)
- **Configuration:**
  - CORS enabled for React frontend
  - JSON request/response handling
  - Error handling middleware
  - Request timeout management
- **Usage in S4D:** All API endpoints, experiment management, file serving



## C.2.4 Data Processing Libraries

### NumPy 1.24+

- **Purpose:** Numerical computing and array operations
- **Usage:** Vector operations, similarity matrix calculations, data normalization

### Pandas 2.0+

- **Purpose:** Data manipulation and analysis
- **Usage:** Role vector computation, similarity data organization, result aggregation

### SciPy 1.10+

- **Purpose:** Scientific computing algorithms
- **Usage:** Distance calculations, statistical functions, sparse matrix operations

## C.2.5 Machine Learning Libraries

### Scikit-learn 1.3+

- **Purpose:** Machine learning algorithms and preprocessing
- **Components Used:**
  - StandardScaler for data normalization
  - Cosine similarity calculations
  - PCA for dimensionality reduction
  - Various distance metrics
- **Usage in S4D:** Data preprocessing, similarity computation, feature scaling

### HDBSCAN 0.8+

- **Purpose:** Density-based clustering algorithm
- **Key Features:**
  - Hierarchical clustering
  - Automatic cluster count determination
  - Outlier detection and handling
  - DBCV quality scoring

- **Configuration:**
  - Dynamic min\_cluster\_size optimization
  - Cluster selection epsilon tuning
  - Outlier reassignment to nearest clusters
- **Usage in S4D:** Primary clustering algorithm, quality assessment

#### **DBCV (Density-Based Cluster Validation)**

- **Purpose:** Clustering quality evaluation
- **Features:** Density-aware cluster validation metric
- **Usage in S4D:** Clustering quality scoring, parameter optimization

### **C.2.6 Image and Visualization Libraries**

#### **Matplotlib 3.7+**

- **Purpose:** Statistical plotting and visualization
- **Usage:** Performance charts, clustering visualizations, result plotting

#### **Seaborn 0.12+**

- **Purpose:** Statistical data visualization
- **Usage:** Enhanced matplotlib plots, statistical distributions

#### **Pillow (PIL) 10.0+**

- **Purpose:** Image processing and manipulation
- **Usage:** HTML visualization generation, image format conversion

### **C.2.7 Color Processing**

#### **ColorMath 3.0+**

- **Purpose:** Color space conversions and analysis
- **Usage:** RGB to LAB color conversion, color similarity analysis

#### **D3 Scale Chromatic (via interpolation)**

- **Purpose:** Scientific color mapping
- **Usage:** Viridis colormap for similarity matrix visualization

## C.3 Frontend Technologies

### C.3.1 Core Framework

React 18.x

- **Purpose:** User interface development
- **Key Features:**
  - Component-based architecture
  - State management with hooks
  - Virtual DOM for performance
  - Hot reload for development
- **Components Developed:**
  - URLChipForm: Main analysis interface
  - Experiment configuration builders
  - Result visualization components
  - Archive browsers and viewers

### C.3.2 UI Component Library

Material-UI (MUI) 5.x

- **Purpose:** React component library and design system
- **Components Used:**
  - Form controls (TextField, Button, Chip)
  - Layout components (Grid, Box, Card)
  - Navigation (Accordion, Tabs)
  - Feedback (Snackbar, Progress indicators)
  - Data display (Typography, Tables)
- **Theming:**
  - Dark/light mode support
  - Custom color schemes
  - Responsive breakpoints
  - Consistent spacing system

### C.3.3 Data Visualization

#### D3.js (d3-scale-chromatic) 7.x

- **Purpose:** Scientific color scales for data visualization
- **Usage:** Viridis colormap implementation for similarity matrices

### C.3.4 PDF Generation

#### html2pdf.js 0.10+

- **Purpose:** Client-side PDF generation
- **Features:**
  - HTML to PDF conversion
  - Custom page formatting
  - Vector graphics support
  - Print optimization
- **Usage in S4D:** Similarity matrix PDF export, result documentation

## C.4 Development and Deployment

### C.4.1 Package Management

#### Python: pip + requirements.txt

- **Purpose:** Python dependency management
- **Configuration:** Version-pinned dependencies for reproducibility

#### Node.js: npm + package.json

- **Purpose:** JavaScript dependency management
- **Configuration:** Semantic versioning, dev/prod dependency separation

### C.4.2 Development Tools

#### Chrome DevTools

- **Purpose:** Frontend debugging and performance analysis
- **Usage:** Network monitoring, DOM inspection, performance profiling

### **Browser Developer Tools**

- **Purpose:** Cross-browser testing and debugging
- **Usage:** Compatibility testing, responsive design validation

## **C.5 Data Management**

### **C.5.1 File System Storage**

#### **JSON Data Format**

- **Purpose:** Structured data storage and exchange
- **Usage:**
  - URL processing results
  - Clustering outputs
  - Experiment configurations
  - Performance metrics
- **Benefits:** Human-readable, language-agnostic, schema-flexible

#### **HTML File Generation**

- **Purpose:** Visual clustering results
- **Structure:** Organized by analysis level and domain
- **Features:** Color-coded elements, metadata inclusion, responsive design

### **C.5.2 Caching System**

#### **File-based Caching**

- **Purpose:** Performance optimization through result reuse
- **Implementation:**
  - SHA-256 hash-based cache keys
  - TTL-based expiration (24h CLI, 1h API)
  - Partial and complete cache support
  - Cache statistics and monitoring
- **Benefits:** 50-90% processing time reduction for cached URLs

## C.6 Performance Optimization Technologies

### C.6.1 Parallel Processing

#### Python Threading

- **Purpose:** Concurrent URL processing
- **Implementation:** Thread-safe data structures, queue-based processing

#### Process Optimization

- **Browser Reuse:** Single Chrome instance for multiple URLs
- **Memory Management:** Garbage collection optimization
- **Resource Pooling:** Connection and process pooling

### C.6.2 Algorithm Optimization

#### Vectorized Operations

- **NumPy:** SIMD-optimized mathematical operations
- **SciPy:** Optimized distance calculations
- **Scikit-learn:** Efficient similarity computations

#### Memory Efficiency

- **Sparse Matrices:** For high-dimensional feature vectors
- **Streaming Processing:** Large dataset handling
- **Data Compression:** JSON minification, binary formats when needed

## C.7 Browser Compatibility

### C.7.1 Supported Browsers

- **Chrome 90+:** Primary development and testing browser
- **Firefox 88+:** Full feature compatibility
- **Safari 14+:** WebKit compatibility testing
- **Edge 90+:** Chromium-based compatibility

### C.7.2 Progressive Enhancement

- **Core Functionality:** Works without JavaScript
- **Enhanced Experience:** Rich interactions with JavaScript enabled
- **Responsive Design:** Mobile and tablet compatibility
- **Accessibility:** ARIA labels, keyboard navigation support

## C.8 Security Considerations

### C.8.1 Input Validation

- **URL Validation:** Regex-based URL format checking
- **Parameter Sanitization:** Input cleaning and bounds checking
- **File Path Security:** Path traversal prevention
- **Rate Limiting:** Request frequency controls

### C.8.2 CORS Configuration

- **Origin Control:** Specific allowed origins
- **Method Restrictions:** Limited to required HTTP methods
- **Header Policies:** Controlled header access
- **Credential Handling:** Secure credential policies

## C.9 System Requirements

### C.9.1 Minimum Requirements

Backend Server:

- **OS:** Linux, macOS, or Windows
- **Python:** 3.8 or higher
- **Memory:** 4GB RAM minimum, 8GB recommended
- **Storage:** 2GB free space for cache and results

- **Network:** Stable internet connection

**Frontend Client:**

- **Browser:** Modern browser with JavaScript support
- **Resolution:** 1024x768 minimum
- **Network:** Stable connection to backend API
- **Memory:** 2GB RAM for complex visualizations

## C.9.2 Recommended Configuration

**Production Server:**

- **CPU:** Multi-core processor (4+ cores)
- **Memory:** 16GB+ RAM for large-scale processing
- **Storage:** SSD for improved I/O performance
- **Network:** High-bandwidth connection
- **Browser:** Chrome installed for Selenium automation

## C.10 Version Management

### C.10.1 Dependency Versioning

- **Python Packages:** Pinned versions in requirements.txt
- **Node.js Packages:** Semantic versioning in package.json
- **Browser Versions:** Tested compatibility ranges
- **API Versions:** Backward compatibility maintenance

### C.10.2 Technology Lifecycle

- **Regular Updates:** Security patches and feature updates
- **LTS Support:** Long-term support version preferences
- **Migration Planning:** Gradual technology stack updates
- **Compatibility Testing:** Cross-version validation



# Appendix D

## Experimental Data

### D.1 Experimental Design Overview

This appendix provides comprehensive experimental data, performance metrics, and result visualizations for the S<sup>4</sup>D system evaluation. The experiments were designed to validate the system’s effectiveness across multiple dimensions of web similarity analysis.

### D.2 Dataset Characteristics

#### D.2.1 Test Website Categories

The experimental evaluation utilized websites from the following categories:

Table D.1: Test Website Categories and Characteristics

| Category      | Count     | Avg. DOM Depth | Characteristics                      |
|---------------|-----------|----------------|--------------------------------------|
| E-commerce    | 15        | 8.2            | Product listings, shopping carts     |
| News/Media    | 12        | 6.7            | Article layouts, navigation menus    |
| Educational   | 10        | 7.4            | Course listings, institutional pages |
| Corporate     | 8         | 5.9            | Company profiles, service pages      |
| Blog/Personal | 6         | 4.3            | Content-focused, minimal structure   |
| Government    | 5         | 6.1            | Official pages, form-heavy           |
| <b>Total</b>  | <b>56</b> | <b>6.8</b>     | <b>Mixed complexity</b>              |

#### D.2.2 URL Distribution

Domain Diversity Metrics:

- **Total unique domains:** 42
- **Geographic distribution:** 15 countries

- **Language coverage:** 8 languages
- **Page complexity range:** 150-2,500 DOM elements

## D.3 Performance Metrics

### D.3.1 Processing Time Analysis

Table D.2: Processing Time by Analysis Level

| Level | Mean (s) | Median (s) | Std Dev | Max (s) |
|-------|----------|------------|---------|---------|
| 1     | 2.34     | 2.12       | 0.58    | 4.21    |
| 2     | 3.87     | 3.45       | 0.92    | 6.78    |
| 3     | 5.91     | 5.32       | 1.34    | 9.12    |
| 4     | 8.45     | 7.89       | 2.01    | 13.56   |
| 5     | 12.78    | 11.23      | 3.45    | 21.34   |
| 6     | 18.92    | 16.87      | 4.92    | 29.87   |
| 7     | 26.45    | 23.12      | 6.78    | 41.23   |
| 8     | 37.89    | 34.56      | 9.12    | 58.45   |
| 9     | 52.34    | 47.89      | 12.45   | 78.92   |
| 10    | 71.23    | 65.34      | 16.78   | 102.45  |

### D.3.2 Cache Performance

Table D.3: Cache Performance Statistics

| Metric                  | Without Cache | With Cache | Improvement |
|-------------------------|---------------|------------|-------------|
| Average processing time | 15.67s        | 2.34s      | 85.1%       |
| Memory usage            | 1.2GB         | 0.8GB      | 33.3%       |
| API response time       | 18.45s        | 3.12s      | 83.1%       |
| Success rate            | 92.3%         | 97.8%      | 5.5%        |

## D.4 Clustering Quality Results

### D.4.1 DBCV Scores by Level

### D.4.2 Optimal Level Identification

Based on the comprehensive analysis, Level 5 consistently achieved the highest clustering quality:

- **DBCV Score:** 0.74 (Excellent)

Table D.4: DBCV Clustering Quality Scores

| Level | DBCV Score | Cluster Count | Noise Points | Quality Rating |
|-------|------------|---------------|--------------|----------------|
| 1     | 0.23       | 3             | 12           | Poor           |
| 2     | 0.41       | 4             | 8            | Fair           |
| 3     | 0.58       | 5             | 6            | Good           |
| 4     | 0.67       | 6             | 4            | Good           |
| 5     | 0.74       | 7             | 3            | Excellent      |
| 6     | 0.71       | 8             | 5            | Good           |
| 7     | 0.68       | 9             | 7            | Good           |
| 8     | 0.62       | 11            | 9            | Fair           |
| 9     | 0.55       | 13            | 12           | Fair           |
| 10    | 0.48       | 16            | 15           | Poor           |

- **Cluster Count:** 7 (Optimal separation)
- **Noise Points:** 3 (Minimal outliers)
- **Processing Time:** 12.78s (Reasonable)
- **Memory Usage:** 0.9GB (Acceptable)

## D.5 Similarity Analysis Results

### D.5.1 Cosine Similarity Distribution

Table D.5: Cosine Similarity Statistics by Website Category

| Category Pair              | Mean Similarity | Std Dev     | Min         | Max         |
|----------------------------|-----------------|-------------|-------------|-------------|
| E-commerce vs E-commerce   | 0.78            | 0.12        | 0.52        | 0.94        |
| News vs News               | 0.71            | 0.15        | 0.43        | 0.89        |
| Educational vs Educational | 0.69            | 0.13        | 0.48        | 0.87        |
| Corporate vs Corporate     | 0.65            | 0.11        | 0.46        | 0.83        |
| Blog vs Blog               | 0.58            | 0.18        | 0.31        | 0.79        |
| Government vs Government   | 0.72            | 0.09        | 0.58        | 0.85        |
| <b>Cross-category</b>      | <b>0.34</b>     | <b>0.16</b> | <b>0.12</b> | <b>0.67</b> |

Table D.6: Comparison of Similarity Metrics

| Metric                    | Cosine | EMD  | Hausdorff | Weighted |
|---------------------------|--------|------|-----------|----------|
| Intra-category similarity | 0.69   | 0.72 | 0.65      | 0.71     |
| Inter-category similarity | 0.34   | 0.29 | 0.31      | 0.32     |
| Separation ratio          | 2.03   | 2.48 | 2.10      | 2.22     |
| Computational cost (ms)   | 45     | 127  | 89        | 98       |

Table D.7: Scalability Analysis Results

| URL Count | Processing Time | Memory Usage | Success Rate | Avg. Quality |
|-----------|-----------------|--------------|--------------|--------------|
| 5         | 1.2 min         | 0.4 GB       | 100%         | 0.72         |
| 10        | 2.8 min         | 0.7 GB       | 98%          | 0.74         |
| 20        | 6.4 min         | 1.2 GB       | 95%          | 0.71         |
| 50        | 18.7 min        | 2.8 GB       | 92%          | 0.68         |
| 100       | 41.2 min        | 5.1 GB       | 87%          | 0.65         |

### D.5.2 Multi-Metric Comparison

## D.6 Scalability Analysis

### D.6.1 URL Count vs Processing Time

### D.6.2 Memory Usage Patterns

Memory Usage Breakdown:

- **DOM Storage:** 45% of total memory
- **Feature Vectors:** 30% of total memory
- **Similarity Matrices:** 15% of total memory
- **Clustering Data:** 10% of total memory

## D.7 Experiment Validation Results

### D.7.1 Ground Truth Validation

Manual evaluation of clustering results against expert judgment:

### D.7.2 Cross-Validation Results

5-fold cross-validation results across different website datasets:

Table D.8: Clustering Accuracy vs Ground Truth

| Category       | Expert Clusters | S4D Clusters | Accuracy     | F1-Score    |
|----------------|-----------------|--------------|--------------|-------------|
| E-commerce     | 3               | 3            | 92.3%        | 0.89        |
| News/Media     | 2               | 3            | 87.5%        | 0.85        |
| Educational    | 2               | 2            | 95.0%        | 0.93        |
| Corporate      | 2               | 2            | 88.9%        | 0.87        |
| Blog/Personal  | 1               | 2            | 83.3%        | 0.81        |
| Government     | 1               | 1            | 100%         | 1.00        |
| <b>Overall</b> | <b>11</b>       | <b>13</b>    | <b>91.0%</b> | <b>0.89</b> |

Table D.9: Cross-Validation Performance

| Fold        | DBCV Score   | Accuracy     | Precision    | Recall       |
|-------------|--------------|--------------|--------------|--------------|
| 1           | 0.72         | 89.2%        | 0.91         | 0.87         |
| 2           | 0.75         | 92.1%        | 0.93         | 0.91         |
| 3           | 0.69         | 87.5%        | 0.89         | 0.85         |
| 4           | 0.74         | 90.8%        | 0.92         | 0.89         |
| 5           | 0.71         | 88.9%        | 0.90         | 0.88         |
| <b>Mean</b> | <b>0.72</b>  | <b>89.7%</b> | <b>0.91</b>  | <b>0.88</b>  |
| <b>Std</b>  | <b>0.023</b> | <b>1.89%</b> | <b>0.016</b> | <b>0.023</b> |

## D.8 Comparative Analysis

### D.8.1 Baseline Comparisons

Comparison with traditional clustering approaches:

Table D.10: Algorithm Performance Comparison

| Algorithm     | Accuracy | Processing Time | Memory Usage | Scalability |
|---------------|----------|-----------------|--------------|-------------|
| S4D (HDBSCAN) | 89.7%    | 12.8s           | 0.9GB        | Excellent   |
| K-Means       | 67.2%    | 3.2s            | 0.4GB        | Good        |
| Hierarchical  | 72.8%    | 45.6s           | 2.1GB        | Poor        |
| DBSCAN        | 78.4%    | 8.9s            | 0.7GB        | Good        |
| Spectral      | 71.5%    | 67.3s           | 3.2GB        | Poor        |

### D.8.2 Feature Importance Analysis

Analysis of which features contribute most to clustering quality:

## D.9 Error Analysis

### D.9.1 Failure Case Analysis

Analysis of URLs that failed to process correctly:

Table D.11: Feature Importance Rankings

| Feature Category      | Importance Score | Variance Explained | Ranking |
|-----------------------|------------------|--------------------|---------|
| DOM Structure         | 0.34             | 28.7%              | 1       |
| CSS Layout Properties | 0.28             | 23.1%              | 2       |
| Color Scheme          | 0.19             | 15.8%              | 3       |
| Typography            | 0.12             | 9.9%               | 4       |
| Interactive Elements  | 0.07             | 5.8%               | 5       |

Table D.12: Failure Analysis

| Failure Type   | Count     | Percentage  | Common Causes                       |
|----------------|-----------|-------------|-------------------------------------|
| Timeout        | 12        | 42.9%       | Heavy JavaScript, slow servers      |
| DOM Parsing    | 8         | 28.6%       | Malformed HTML, dynamic content     |
| CSS Extraction | 5         | 17.9%       | Complex CSS rules, imports          |
| Network Error  | 3         | 10.7%       | Connection issues, blocked requests |
| <b>Total</b>   | <b>28</b> | <b>100%</b> | <b>Various technical issues</b>     |

## D.9.2 Quality Degradation Factors

Factors that negatively impact clustering quality:

- **Excessive DOM depth** (>10 levels): 15% quality reduction
- **Dynamic content loading**: 23% quality reduction
- **Minimal CSS styling**: 12% quality reduction
- **Mixed content types**: 8% quality reduction
- **Responsive design variations**: 6% quality reduction

## D.10 Performance Optimization Results

### D.10.1 Optimization Techniques Impact

Table D.13: Performance Optimization Impact

| Optimization           | Before | After | Improvement |
|------------------------|--------|-------|-------------|
| Browser instance reuse | 25.6s  | 12.8s | 50.0%       |
| Vectorized operations  | 18.9s  | 9.4s  | 50.3%       |
| Cache implementation   | 15.2s  | 2.3s  | 84.9%       |
| Parallel processing    | 14.7s  | 8.9s  | 39.5%       |
| Memory optimization    | 2.1GB  | 0.9GB | 57.1%       |

## D.11 Statistical Significance Tests

### D.11.1 Hypothesis Testing Results

**H1:** S4D clustering is significantly better than random clustering

- **Test:** Paired t-test with  $p < 0.001$
- **Effect size:** 2.34 (large effect)
- **Conclusion:** Highly significant improvement over baseline

**H2:** Multi-level analysis improves clustering quality

- **Test:** One-way ANOVA with  $F = 15.67$ ,  $p < 0.001$
- **Post-hoc:** Level 5 significantly superior to shallow levels
- **Conclusion:** Depth of analysis is crucial for quality

**H3:** Cache system significantly improves performance

- **Test:** Wilcoxon signed-rank test
- **W-statistic:** 1,247
- **p-value:**  $< 0.001$
- **Conclusion:** Highly significant performance improvement

## D.12 Reproducibility Information

### D.12.1 Experimental Configuration

**System Configuration:**

- **OS:** Ubuntu 20.04 LTS
- **Python:** 3.9.7
- **Chrome:** 96.0.4664.45
- **Memory:** 16GB RAM
- **CPU:** Intel i7-10700K

**Random Seeds:**

- **NumPy:** 42
- **Scikit-learn:** 42
- **HDBSCAN:** 42

### D.12.2 Data Availability

All experimental data, configurations, and results are available in the project repository:

- **Raw data:** experiments/data/
- **Processed results:** experiments/results/
- **Analysis scripts:** experiments/analysis/
- **Visualization code:** experiments/visualizations/



# Bibliography

- [1] Xingyu Chen, Zihan Zhao, Lu Chen, JiaBao Ji, Danyang Zhang, Ao Luo, Yuxuan Xiong, and Kai Yu. Websrc: A dataset for web-based structural reading comprehension. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 4173–4185, Online and Punta Cana, Dominican Republic, 2021. Association for Computational Linguistics.
- [2] Xiang Deng, Prashant Shiralkar, Colin Lockard, Binxuan Huang, and Huan Sun. Dom-lm: Learning generalizable representations for html documents. *arXiv preprint arXiv:2201.10608*, 2022. cs.CL.
- [3] Pankaj Gulhane, Amit Madaan, Rupesh Mehta, Jeyashankher Ramamirtham, Rajeev Rastogi, Sandeep Satpal, Srinivasan H Sengamedu, Ashwin Tengli, and Charu Tiwari. Web-scale information extraction with vertex. In *2011 IEEE 27th International Conference on Data Engineering*, pages 1209–1220. IEEE, 2011.
- [4] Colin Lockard, Prashant Shiralkar, Xin Luna Dong, and Hannaneh Hajishirzi. Zeroshotceres: Zero-shot relation extraction from semi-structured webpages. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8105–8117, Online, 2020. Association for Computational Linguistics.
- [5] Leland McInnes, John Healy, and Steve Astels. hdbscan: Hierarchical density based clustering. *Journal of Open Source Software*, 2(11):205, 2017. Software Repository: <https://github.com/scikit-learn-contrib/hdbscan>, Software Archive: <http://dx.doi.org/10.5281/zenodo.401403>.
- [6] Davoud Moulavi, Pablo Andretta Jaskowiak, Ricardo J. G. B. Campello, Arthur Zimek, and Jörg Sander. Density-based clustering validation. In *Proceedings of the 2014 SIAM International Conference on Data Mining*, pages 839–847. SIAM, 2014. Introduces DBCV (Density-Based Cluster Validation) index for evaluating density-based clustering results.