

Additional Resources: Product Page | 3D Model | PCB Footprint

date 09/11/2024

page 1 of 4

## MODEL: CVS-1508 | DESCRIPTION: SPEAKER

#### **FEATURES**

- · plastic frame
- PET cone
- plastic case






### **SPECIFICATIONS**

parameter	conditions/description	min	typ	max	units
diameter			15		mm
depth			7.5		mm
input power	max. power: IEC-60268-5, filter 60 s on / 120 s off, 10 cycles at room temp		0.3	0.5	W
impedance	at 3 kHz, 1 V	6.8	8	9.2	Ω
resonant frequency	at 1 V	1360	1700	2,040	Hz
sound pressure level	0.3 W, 10 cm ave. at 2.0, 2.5, 3.0, 4.0 kHz 1 W, 1 m ave. at 2.0, 2.5, 3.0, 4.0 kHz	84 70	87 73	90 76	dB dB
response				20,000	Hz
distortion	at 3 kHz, 0.3 W			10	%
buzz, rattle, etc.	must be normal at sine wave 1.55 V				
magnet size	ø6.5 x 1.5 mm				
operating temperature		-20		55	°C
weight			2.0		g
material	PBT +20% glass				
washable	yes				
RoHS	yes			·	


#### **SOLDERABILITY**


parameter	conditions/description
hand soldering	350 ±5°C for 3 seconds

### **MECHANICAL DRAWING**




# FREQUENCY RESPONSE CURVE





### **PACKAGING**



Additional Resources: Product Page | 3D Model | PCB Footprint

SAME SKY | MODEL: CVS-1508 | DESCRIPTION: SPEAKER

date 09/11/2024 | page 4 of 4

#### **REVISION HISTORY**

rev.	description	date	
1.0	initial release	11/15/2011	
1.01	changed solder time from 5 seconds to 3 seconds	08/06/2012	
1.02	brand update	01/20/2020	
1.03	logo, datasheet style update	08/05/2022	
1.04	CUI Devices rebranded to Same Sky	09/11/2024	

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Additional Resources: Product Page | 3D Model | PCB Footprint