# API data stubbing done right

With Saray and Node.js

### What is a data stubber?

It's a software that permits to mock data

## Why it is important to stub data?

- for software development
- consistent data for functional tests
- safe environments for product demo

## We can stub data with Saray!

'Yet Another Rest API Stubber'.split(' ').reverse().map(item => item[0].toLowerCase()).join('')

#### /home/paolo/saray/simple.GET.json

#### Saray can transform this...



```
{
    "message": "Hi Milan, I'm a stubbed API call"
}
```

#### ...into this



#### GET <a href="http://locahost:8000/simple">http://locahost:8000/simple</a>

```
HTTP/1.1 200 0K
X-Powered-By: Express
Access-Control-Allow-Origin: *
Access-Control-Allow-Methods: GET, POST, OPTIONS, PUT, PATCH, DELETE
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type, Accept, Authorization
Access-Control-Allow-Credentials: true
Saray-Stubbed: true
Content-Type: application/json; charset=utf-8
Content-Length: 46
ETag: W/"2e-89E9C8HHkWvwlUiWgeXBGIuHeyw"
Date: Sun, 30 Apr 2017 18:14:33 GMT
Connection: keep-alive

{
    "message": "Hi Milan, I'm a stubbed API call"
}
```

### You can also use JS!

```
module.exports = function(req, res, log, next) {
   res.json({key: 'value'});
};
```

## Saray as a proxy

\$ saray -path data -endpoint https://myapi.com

GET <a href="http://locahost:8000/simple">https://myapi.com</a>





## Saray with dynamic paths

\$ saray -path data -dynpath='\_'

GET <a href="http://localhost:8081/simple/salutation/hello">http://localhost:8081/simple/salutation/hello</a>

simple/\_/hello.GET.json



GET <a href="http://localhost:8081/simple/greeting/hello">http://localhost:8081/simple/greeting/hello</a>

GET <a href="http://localhost:8081/simple/curtsy/hello">http://localhost:8081/simple/curtsy/hello</a>

## Thank you!

Saray: <a href="https://github.com/contactlab/saray">https://github.com/contactlab/saray</a>

Saray demo: https://github.com/contactlab/saray-demo