

A decorative graphic on the left side of the slide. It consists of a blue parallelogram and a light green parallelogram, both tilted at an angle. The blue shape is in the foreground, and the green shape is partially behind it. They are set against a dark blue background with faint, lighter blue diagonal stripes.

RUSTikales Rust for beginners



Plan for today



Plan for today

1. Recap



Plan for today

1. Recap
2. Loops



1. Recap



1. Recap

- Integers in Rust: `i8`, `u8`, `i16`, `u16`, ... , `i128`, `u128`



1. Recap

- Integers in Rust: `i8`, `u8`, `i16`, `u16`, ... , `i128`, `u128`
- `let <name> = ...;` to declare an immutable variable
- `let mut <name> = ...;` to declare a mutable variable



1. Recap

- Integers in Rust: `i8`, `u8`, `i16`, `u16`, ... , `i128`, `u128`
- `let <name> = ...;` to declare an immutable variable
- `let mut <name> = ...;` to declare a mutable variable
- `let var: [type; size] = ...;` to declare an array with the given type and size
- `let var: Vec<type> = ...;` to declare a Vector with the given type



1. Recap

- Integers in Rust: `i8`, `u8`, `i16`, `u16`, ... , `i128`, `u128`
- `let <name> = ...;` to declare an immutable variable
- `let mut <name> = ...;` to declare a mutable variable
- `let var: [type; size] = ...;` to declare an array with the given type and size
- `let var: Vec<type> = ...;` to declare a Vector with the given type
- Elements in Arrays and Vectors always have the same type



1. Recap

- Integers in Rust: `i8`, `u8`, `i16`, `u16`, ... , `i128`, `u128`
- `let <name> = ...;` to declare an immutable variable
- `let mut <name> = ...;` to declare a mutable variable
- `let var: [type; size] = ...;` to declare an array with the given type and size
- `let var: Vec<type> = ...;` to declare a Vector with the given type
- Elements in Arrays and Vectors always have the same type
- Arrays have a fixed size, Vectors are resizable



1. Recap

- `var[index]` to access the element at a given index
 - `var[0] = 5;` sets the element at index 0 to 5
 - `let x = var[1];` gets the element at index 1 and stores it in x



1. Recap

- `var[index]` to access the element at a given index
- Arrays and Vectors are **zero-indexed**
 - For size **N**, indices **0 to N-1** are **defined**, anything else results in **Out-Of-Bounds panics**



1. Recap

- `var[index]` to access the element at a given index
- Arrays and Vectors are **zero-indexed**
- `vec![]` is a macro to easily create Vectors



1. Recap

- Important to know:



1. Recap

- Important to know:
 - Many helper methods exist for Arrays and Vectors
 - `name.reverse()` reverses the order of elements in `name`, and stores the result in `name` again
 - `vector.pop()` removes the `last element` of a Vector
 - `name.len()` returns the `number of elements` in your Array/Vector



1. Recap

- Important to know:
 - Many helper methods exist for Arrays and Vectors
 - Array Type Declaration itself is a Type



1. Recap

- Important to know:
 - Many helper methods exist for Arrays and Vectors
 - Array Type Declaration itself is a Type
 - `[i32; 5]` is an **Array of i32**
 - `[[i32; 5]; 5]` is an **Array of Arrays of i32**
 - `Vec<[i32; 5]>` is a **Vector of Arrays of i32**
 - `[Vec<i32>; 5]` is an **Array of Vectors of i32**

1. Recap

```
let multi_arr: [[i32; 4]; 2] = [  
    [1, 2, 3, 4],  
    [5, 6, 7, 8]  
];  
// multi_arr[index] returns an Array  
let e: i32 = multi_arr[1][2]; // sets v to 7  
println!("Element at (1, 2) is {}", e);
```

1. Recap

```
let multi_arr: [[i32; 4]; 2] = [  
    [1, 2, 3, 4],  
    [5, 6, 7, 8]  
];  
// multi_arr[index] returns an Array  
let e: i32 = [5, 6, 7, 8][2]; // sets v to 7  
println!("Element at (1, 2) is {}", e);
```

1. Recap

```
let multi_arr: [[i32; 4]; 2] = [  
    [1, 2, 3, 4],  
    [5, 6, 7, 8]  
];  
// multi_arr[index] returns an Array  
let e: i32 = [5, 6, 7, 8][2]; // sets v to 7  
println!("Element at (1, 2) is {}", e);
```

1. Recap

```
let multi_arr: [[i32; 4]; 2] = [  
    [1, 2, 3, 4],  
    [5, 6, 7, 8]  
];  
// multi_arr[index] returns an Array  
let e: i32 = 7; // sets v to 7  
println!("Element at (1, 2) is {}", e);
```

1. Recap

```
let multi_arr: [[i32; 4]; 2] = [  
    [1, 2, 3, 4],  
    [5, 6, 7, 8]  
];  
// multi_arr[index] returns an Array  
let e: i32 = 7; // sets v to 7  
println!("Element at (1, 2) is {}", e);  
Element at (1, 2) is 7
```



2. Loops

- Note: I will use Arrays and Vectors interchangeably today



2. Loops

- Writing code that fits a single Vector size is easy, but breaks once you modify its size



2. Loops

- Writing code that fits a single Vector size is easy, but breaks once you modify its size

```
fn main() {  
    let vector: Vec<i32> = vec![1, 2, 3, 4, 5];  
    let sum: i32 = vector[0]  
        + vector[1]  
        + vector[2]  
        + vector[3]  
        + vector[4];  
    println!("The sum of the first 5 elements: {}", sum);  
}
```

2. Loops

- Writing code that fits a single Vector size is easy, but breaks once you modify its size

```
fn main() {  
    let vector: Vec<i32> = vec![1, 2, 3, 4, 5];  
    let sum: i32 = vector[0]  
        + vector[1]  
        + vector[2]  
        + vector[3]  
        + vector[4];  
    println!("The sum of the first 5 elements: {}", sum);  
}
```

What happens if we add a 6th element?

2. Loops

- Writing code that fits a single Vector size is easy, but breaks once you modify its size

```
fn main() {  
    let vector: Vec<i32> = vec![1, 2, 3, 4, 5];  
    let sum: i32 = vector[0]  
        + vector[1]  
        + vector[2]  
        + vector[3]  
        + vector[4];  
    println!("The sum of the first 5 elements: {}", sum);  
}
```

What happens if we add a 6th element?

Write another line, easy!

2. Loops

- Writing code that fits a single Vector size is easy, but breaks once you modify its size

```
fn main() {  
    let vector: Vec<i32> = vec![1, 2, 3, 4, 5];  
    let sum: i32 = vector[0]  
        + vector[1]  
        + vector[2]  
        + vector[3]  
        + vector[4];  
    println!("The sum of the first 5 elements: {}", sum);  
}
```

What happens if we add a 6th element?

Write another line, easy!
Now do it for 1000 elements :^)



2. Loops

- Writing code that fits a single Vector size is easy, but breaks once you modify its size
- Sometimes you don't know how big a Vector is, but want to do something for every element in it



2. Loops

- Writing code that fits a single Vector size is easy, but breaks once you modify its size
- Sometimes you don't know how big a Vector is, but want to do something for every element in it
- Sometimes you want to go over a range of numbers, and do something for every number you see



2. Loops

- Writing code that fits a single Vector size is easy, but breaks once you modify its size
- Sometimes you don't know how big a Vector is, but want to do something for every element in it
- Sometimes you want to go over a range of numbers, and do something for every number you see
 - For every number below 1000, print the primes :)



2. Loops

- Writing code that fits a single Vector size is easy, but breaks once you modify its size
- Sometimes you don't know how big a Vector is, but want to do something for every element in it
- Sometimes you want to go over a range of numbers, and do something for every number you see
 - For every number below 1000, print the primes :)
 - Play a game of **FizzBuzz**



2. Loops

- Writing code that fits a single Vector size is easy, but breaks once you modify its size
- Sometimes you don't know how big a Vector is, but want to do something for every element in it
- Sometimes you want to go over a range of numbers, and do something for every number you see
 - For every number below 1000, print the primes :)
 - Play a game of **FizzBuzz**
 - For every number below 100:
 - if number is divisible by 3, print „Fizz“
 - if number is divisible by 5, print „Buzz“
 - if number is divisible by 15, print „FizzBuzz“
 - else print the number

2. Loops

- Writing code that fits a single Vector size is easy, but breaks once you modify its size
- Sometimes you don't know how big a Vector is, but want to do something **for every** element in it
- Sometimes you want to go over a range of numbers, and do something **for every** number you see
 - **For every** number below 1000, print the primes :)
 - Play a game of **FizzBuzz**
 - **For every** number below 100:
 - if number is divisible by 3, print „Fizz“
 - if number is divisible by 5, print „Buzz“
 - if number is divisible by 15, print „FizzBuzz“
 - else print the number



2. Loops

- Writing code that fits a single Vector size is easy, but breaks once you modify its size
- Sometimes you don't know how big a Vector is, but want to do something **for every** element in it
- Sometimes you want to go over a range of numbers, and do something **for every** number you see
- Need to do any of that? Loops are your friend!



2. Loops

- A Loop does exactly what you think it does → It loops a piece of code



2. Loops

- A Loop does exactly what you think it does → It loops a piece of code
- There are many types of loops
 - `loop`
 - `while`
 - `for`



2. Loops

- A Loop does exactly what you think it does → It loops a piece of code
- There are many types of loops

```
loop {  
    println!("Hehe, this will print forever!!!");  
}  
println!("Loops are fun");
```



2. Loops

- A Loop does exactly what you think it does → It loops a piece of code
- There are many types of loops

```
let condition: bool = true;
while condition {
    println!("Do as long as condition is true!");
    // extra code...
}
```



2. Loops

- A Loop does exactly what you think it does → It loops a piece of code
- There are many types of loops

```
for n: i32 in 0..10 {  
    println!("We're currently at number: {}", n);  
}
```




2. Loops

- A Loop does exactly what you think it does → It loops a piece of code
- There are many types of loops
- Each type has their own use cases



2. Loops

- A Loop does exactly what you think it does → It loops a piece of code
- There are many types of loops
- Each type has their own use cases
 - Use `loop` if you know that your loop never stops



2. Loops

- A Loop does exactly what you think it does → It loops a piece of code
- There are many types of loops
- Each type has their own use cases
 - Use `loop` if you know that your loop never stops
 - A server will `never stop` listening to requests



2. Loops

- A Loop does exactly what you think it does → It loops a piece of code
- There are many types of loops
- Each type has their own use cases
 - Use `loop` if you know that your loop never stops
 - Use `while` if you want to loop based on a condition



2. Loops

- A Loop does exactly what you think it does → It loops a piece of code
- There are many types of loops
- Each type has their own use cases
 - Use `loop` if you know that your loop never stops
 - Use `while` if you want to loop based on a condition
 - While there are elements in this set, do X



2. Loops

- A Loop does exactly what you think it does → It loops a piece of code
- There are many types of loops
- Each type has their own use cases
 - Use `loop` if you know that your loop never stops
 - Use `while` if you want to loop based on a condition
 - Use `for` if you want to iterate* over a collection



2. Loops

- A Loop does exactly what you think it does → It loops a piece of code
- There are many types of loops
- Each type has their own use cases
 - Use **loop** if you know that your loop never stops
 - Use **while** if you want to loop based on a condition
 - Use **for** if you want to iterate* over a collection
 - For every number in a range
 - For every element in a Vector
 - For every dog in my local park



2. Loops - loop

- `loop` is the simplest form of loops in Rust



2. Loops - loop

- `loop` is the simplest form of loops in Rust
- It's also pretty dumb, it can not stop, ever*



2. Loops - loop

- `loop` is the simplest form of loops in Rust
- It's also pretty dumb, it can not stop, ever*
- Use cases include:



2. Loops - loop

- `loop` is the simplest form of loops in Rust
- It's also pretty dumb, it can not stop, ever*
- Use cases include:
 - You don't want your code to ever stop
 - Servers listen to requests 24/7



2. Loops - loop

- `loop` is the simplest form of loops in Rust
- It's also pretty dumb, it can not stop, ever*
- Use cases include:
 - You don't want your code to ever stop
 - Your `while-condition` would be too complex to put in one expression
 - Instead, you can split it into sub-expressions and test each of them separately



2. Loops - loop

- `loop` is the simplest form of loops in Rust
- It's also pretty dumb, it can not stop, ever*
- Use cases include:
 - You don't want your code to ever stop
 - Your `while-condition` would be too complex to put in one expression
 - Stress Testing your CPU (simplest way of getting 100% usage)

2. Loops - loop

a `loop` loop may look like this

```
let mut number: i8 = 0;
loop {
    println!("Weeeeee!!!");
    number = number + 1;
}
```

2. Loops - loop

a `loop` loop may look like this


```
let mut number: i8 = 0;  
loop {  
    println!("Weeeeeee!!!");  
    number = number + 1;  
}
```

Body of the loop
→ This part gets repeated

2. Loops - loop

a **loop** loop may look like this

```
let mut number: i8 = 0;  
loop {  
    println!("Weeeeee!!!");  
    number = number + 1;  
}
```



The diagram illustrates a Rust loop structure. A white curved arrow originates from the text "increments this variable" and points to the line `number = number + 1;` within the loop body. The variable `number` is underlined in the original image, and the increment value `1` is highlighted in green.

2. Loops - loop

a `loop` loop may look like this

```
let mut number: i8 = 0;  
loop {  
    println!("Weeeeee!!!");  
    number = number + 1;  
}
```

Debug mode → Crash once number is 127

2. Loops - loop

a `loop` loop may look like this

```
let mut number: i8 = 0;
loop {
    println!("Weeeeeee!!!");
    number = number + 1;
}
```

0/3

Debug mode → Crash once number is 127
Why?

2. Loops - loop

a `loop` loop may look like this

```
let mut number: i8 = 0;
loop {
    println!("Weeeeeee!!!");
    number = number + 1;
}
```

0/3

Debug mode → Crash once number is 127

Why?

→ i8 can only store up to 127, Overflow

2. Loops - loop

a `loop` loop may look like this

```
let mut number: i8 = 0;  
loop {  
    println!("Weeeeeee!!!");  
    number = number + 1;  
}
```

Debug mode → Crash once number is 127
Release mode → Wrap to -128 and continue




2. Loops - while

- `while` is the advanced version of `loop`



2. Loops - while

- `while` is the advanced version of `loop`
- whereas `loop` loops forever, `while` stops once a `condition is no longer satisfied`



Intermission - Conditions

- **Conditions** are expressions which return a **boolean** (either true or false)

Intermission - Conditions

```
let a: i32 = 5;
let b: i32 = 10;
println!("a equals b: {}", a == b);
println!("a does not equal b: {}", a != b);
println!("a is less than b: {}", a < b);
println!("a is less than or equal b: {}", a <= b);
println!("a is greater than b: {}", a > b);
println!("a is greater than or equal b: {}", a >= b);
println!("a is positive: {}", a.is_positive());
```


Intermission - Conditions

```
let a: i32 = 5;
let b: i32 = 10;
println!("a equals b: {}", a == b);
println!("a does not equal b: {}", a != b);
println!("a is less than b: {}", a < b);
println!("a is less than or equal b: {}", a <= b);
println!("a is greater than b: {}", a > b);
println!("a is greater than or equal b: {}", a >= b);
println!("a is positive: {}", a.is_positive());
```

Those expressions return **true** or **false**

Intermission - Conditions

```
let a: i32 = 5;  
let b: i32 = 10;  
println!("a equals b: {}", a == b);  
println!("a does not equal b: {}", a != b);  
println!("a is less than b: {}", a < b);  
println!("a is less than or equal b: {}", a <= b);  
println!("a is greater than b: {}", a > b);  
println!("a is greater than or equal b: {}", a >= b);  
println!("a is positive: {}", a.is_positive());
```

1/3 What does the program output?

Intermission - Conditions

```
let a: i32 = 5;
let b: i32 = 10;
println!("a equals b: {}", a == b);
println!("a does not equal b: {}", a != b);
println!("a is less than b: {}", a < b);
println!("a is less than or equal b: {}", a <= b);
println!("a is greater than b: {}", a > b);
println!("a is greater than or equal b: {}", a >= b);
println!("a is positive: {}", a.is_positive());
```

a equals b: false
a does not equal b: true
a is less than b: true
a is less than or equal b: true
a is greater than b: false
a is greater than or equal b: false
a is positive: true



Intermission - Conditions

```
let c: i32 = 12;
let d: i32 = 20;
if c < d {
    println!("c is smaller than d!");
} else {
    println!("c is not smaller than d!");
}
if c == d {
    println!("c is equal to d!");
}
```

Intermission - Conditions

```
let c: i32 = 12;
let d: i32 = 20;
if c < d {
    println!("c is smaller than d!");
} else {
    println!("c is not smaller than d!");
}
if c == d {
    println!("c is equal to d!");
}
```

if-expression:
if the condition is true, do the thing in the block

Intermission - Conditions

```
let c: i32 = 12;
let d: i32 = 20;
if c < d {
    println!("c is smaller than d!");
} else {
    println!("c is not smaller than d!");
}
if c == d {
    println!("c is equal to d!");
}
```

if-expression:
if the condition is true, do the thing in the block
else, do the thing in the other block

Intermission - Conditions

```
let c: i32 = 12;
let d: i32 = 20;
if c < d {
    println!("c is smaller than d!");
} else {
    println!("c is not smaller than d!");
}
```

else is optional → We simply do nothing if the condition is false

```
if c == d {
    println!("c is equal to d!");
}
```

Intermission - Conditions

1/3

```
let c: i32 = 12;
```

```
let d: i32 = 20;
```

```
if c < d {
```

```
    println!("c is smaller than d!");
```

```
} else {
```

```
    println!("c is not smaller than d!");
```

```
}
```

```
if c == d {
```

```
    println!("c is equal to d!");
```

```
}
```

What does the program print?

Intermission - Conditions

1/3

```
let c: i32 = 12;
```

```
let d: i32 = 20;
```

```
if true {
```

```
    println!("c is smaller than d!");
```

```
} else {
```

```
    println!("c is not smaller than d!");
```

```
}
```

```
if false {
```

```
    println!("c is equal to d!");
```

```
}
```

What does the program print?

Intermission - Conditions

1/3

```
let c: i32 = 12;  
let d: i32 = 20;
```

```
if true {
```

```
    println!("c is smaller than d!");
```

```
} else {
```

```
    println!("c is not smaller than d!");
```

```
}
```

```
if false {
```

```
    println!("c is equal to d!");
```

```
}
```

We only get one line of output

```
for\bool_demo>cargo run  
Finished dev [unopt  
Running `target\de  
c is smaller than d!
```



2. Loops - while

a **while** loop may look like this

```
let mut number: i8 = 0;
while number < 10 {
    println!("Number: {}", number);
    number += 1;
}
println!("The final number is: {}", number);
```

2. Loops - while

a **while** loop may look like this

```
let mut number: i8 = 0;
while number < 10 { while the condition is true (number is smaller than 10),
    println!("Number: {}", number);
    number += 1;
}
println!("The final number is: {}", number);
```

2. Loops - while

a **while** loop may look like this

```
let mut number: i8 = 0;
while number < 10 {
    println!("Number: {}", number);
    number += 1;
}
println!("The final number is: {}", number);
```

while the **condition is true** (number is smaller than 10),
do the **things** in the block

2. Loops - while

a **while** loop may look like this

```
let mut number: i8 = 0;
while number < 10 {
    println!("Number: {}", number);
    number += 1;
}
println!("The final number is: {}", number);
```

```
Number: 0
Number: 1
Number: 2
Number: 3
Number: 4
Number: 5
Number: 6
Number: 7
Number: 8
Number: 9
The final number is: 10
```

2. Loops - while

a **while** loop may look like this

10 is **not** less than 10, so it
does not enter the loop again

```
let mut number: i8 = 0;
while number < 10 {
    println!("Number: {}", number);
    number += 1;
}
println!("The final number is: {}", number);
```

```
Number: 0
Number: 1
Number: 2
Number: 3
Number: 4
Number: 5
Number: 6
Number: 7
Number: 8
Number: 9
The final number is: 10
```



Intermission - Scopes



Intermission - Scopes

- Statements wrapped in curly brackets are called code blocks



Intermission - Scopes

- Statements wrapped in curly brackets are called code blocks
- Each Block has a scope in which it operates



Intermission - Scopes

- Statements wrapped in curly brackets are called code blocks
- Each Block has a scope in which it operates
- Blocks can access variables from outer scopes



Intermission - Scopes

- Statements wrapped in curly brackets are called code blocks
- Each Block has a scope in which it operates
- Blocks can access variables from outer scopes
- Variables can only be used in scopes they're defined in
 - They're **dropped** once we leave the scope

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 0

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 0
B	

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 0
B	y = 1

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 0
B	y = 1

Check current scope
→ No **x** found in **B**
→ Check previous scope

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 0
B	y = 1

Uses **x** from Scope **A**

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 0
B	y = 1
C	

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 0
B	y = 1
C	

Uses **x** from Scope A

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10        } // Scope D
11        let x: i32 = 0;
12        println!("{}", x);
13    }
14 }
15
16 // let z: i32 = y;
17 println!("{}", x);
18 }
```

Scope	Variables
A	x = 0
B	y = 1
C	tmp = 0

Uses **x** from Scope A

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10        } // Scope D
11        let x: i32 = 0;
12        println!("{}", x);
13    }
14 }
15
16 // let z: i32 = y;
17 println!("{}", x);
18 }
```

Scope	Variables
A	x = 1
B	y = 1
C	tmp = 0

Uses **x** from Scope A
Uses **y** from Scope B

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10        } // Scope D
11            let x: i32 = 0;
12            println!("{}", x);
13        }
14    }
15 }
16 // let z: i32 = y;
17 println!("{}", x);
18 }
```

Scope	Variables
A	x = 1
B	y = 0
C	tmp = 0

Uses **x** from Scope A

Uses **y** from Scope B

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10        } // Scope D
11            let x: i32 = 0;
12            println!("{}", x);
13        }
14    }
15 }
16 // let z: i32 = y;
17 println!("{}", x);
18 }
```

Scope	Variables
A	x = 1
B	y = 0
C	tmp = 0
D	

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10        } // Scope D
11        let x: i32 = 0;
12        println!("{}", x);
13    }
14 }
15 }
16 // let z: i32 = y;
17 println!("{}", x);
18 }
```

Scope	Variables
A	x = 1
B	y = 0
C	tmp = 0
D	x = 0

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10        } // Scope D
11            let x: i32 = 0;
12        println!("{}", x);
13    }
14 }
15 }
16 // let z: i32 = y;
17 println!("{}", x);
18 }
```

Scope	Variables
A	x = 1
B	y = 0
C	tmp = 0
D	x = 0

x is defined in the current scope, use this one!
→ Variable shadowing

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 1
B	y = 0
C	tmp = 0

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 1
B	y = 0

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 1
B	y = 0

Check condition again, and repeat until it is no longer true

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 1
B	y = 1

Check condition again, and repeat until it is no longer true

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 2
B	y = 1

Check condition again, and repeat until it is no longer true

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 3
B	y = 2

Check condition again, and repeat until it is no longer true

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 5
B	y = 3

Check condition again, and repeat until it is no longer true

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 8
B	y = 5

Check condition again, and repeat until it is no longer true

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 13
B	y = 8

Check condition again, and repeat until it is no longer true

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 89
B	y = 55

Check condition again, and repeat until it is no longer true
Eventually...

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 144
B	y = 89

Check condition again, and repeat until it is no longer true
Eventually...
144 is not smaller than 100!

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 144

Check condition again, and repeat until it is no longer true
Eventually...
144 is not smaller than 100!
And we continue.

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10        } // Scope D
11        let x: i32 = 0;
12        println!("{}", x);
13    }
14 }
15 }
16 // let z: i32 = y;
17 println!("{}", x);
18 }
```

Scope	Variables
A	x = 144

The only valid Scope is A, which does not have y
→ Scope B did have y, but it ended in line 15
→ Scope B is not a previous scope of A :^)
→ This would be an error

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Scope	Variables
A	x = 144

Prints 144

Intermission - Scopes

Scope	Variables
-------	-----------

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Intermission - Scopes

```
1 fn main() { // Scope A
2     let mut x: i32 = 0;
3     { // Scope B
4         let mut y: i32 = 1;
5         while x < 100 { // Scope C
6             println!("{}", x);
7             let tmp: i32 = x;
8             x = x + y;
9             y = tmp;
10            { // Scope D
11                let x: i32 = 0;
12                println!("{}", x);
13            }
14        }
15    }
16    // let z: i32 = y;
17    println!("{}", x);
18 }
```

Output:

```
0
0
1
0
1
0
2
0
3
0
5
0
8
0
13
0
21
0
34
0
55
0
89
0
144
```



2. Loops - for

- `for` is a very powerful loop



2. Loops - for

- `for` is a very powerful loop
- It allows you to comfortably loop over data collections



2. Loops - for

- `for` is a very powerful loop
- It allows you to comfortably loop over data collections
- However, where power is involved, rules are necessary



2. Loops - for

- `for` is a very powerful loop
- It allows you to comfortably loop over data collections
- However, where power is involved, rules are necessary
 - To be able to use `for` on a collection, it needs to implement an `Iterator-Trait`



2. Loops - for

- `for` is a very powerful loop
- It allows you to comfortably loop over data collections
- However, where power is involved, rules are necessary
 - To be able to use `for` on a collection, it needs to implement an `Iterator-Trait`
 - `for` implicitly turns your collections into iterators



2. Loops - for

- `for` is a very powerful loop
- It allows you to comfortably loop over data collections
- However, where power is involved, rules are necessary
 - To be able to use `for` on a collection, it needs to implement an `Iterator-Trait`
 - `for` implicitly turns your collections into iterators
 - If you're using the original collection, it gets moved and you can't use it anymore
 - You have to borrow the collection to prevent that



2. Loops - for

- **for** is a very powerful loop
- It allows you to comfortably loop over data collections
- However, where power is involved, rules are necessary
 - To be able to use **for** on a collection, it needs to implement an **Iterator-Trait**
 - **for** implicitly turns your collections into iterators
 - If you're using the **original collection**, it gets **moved** and you **can't use it anymore**
 - You have to **borrow the collection** to prevent that
- What this means will be covered next week when we introduce **the Ownership Model**, for now most examples only work as isolated blocks :^)



2. Loops - for

- **for** is a very powerful loop
- It allows you to comfortably loop over data collections
- However, where power is involved, rules are necessary
 - To be able to use **for** on a collection, it needs to implement an **Iterator-Trait**
 - **for** implicitly turns your collections into iterators
 - If you're using the **original collection**, it gets **moved** and you **can't use it anymore**
 - You have to **borrow the collection** to prevent that
- What this means will be covered next week when we introduce **the Ownership Model**, for now most examples only work as isolated blocks :^)
 - If you feel very brave, you can try and slap **&** in front of vectors when you use them in a for loop, and see what happens :^)



2. Loops - for

- **for** is a very powerful loop
- It allows you to comfortably loop over data collections
- However, where power is involved, rules are necessary
 - To be able to use **for** on a collection, it needs to implement an **Iterator-Trait**
 - **for** implicitly turns your collections into iterators
 - If you're using the **original collection**, it gets **moved** and you **can't use it anymore**
 - You have to **borrow the collection** to prevent that
- What this means will be covered next week when we introduce **the Ownership Model**, for now most examples only work as isolated blocks :^)
- Iterators are scary and complex, we'll ignore most of it as long as possible and still have fun with our non-idiomatic code :)



2. Loops - for

a **for** loop may look like this

```
let array: [i32; 5] = [1, 2, 3, 4, 5];  
for element: i32 in array {  
    println!("Current: {}", element);  
}
```



2. Loops - for

a **for** loop may look like this

```
let array: [i32; 5] = [1, 2, 3, 4, 5];  
for element: i32 in array {  
    println!("Current: {}", element);  
}
```

For every element in the array



2. Loops - for

a **for** loop may look like this

```
let array: [i32; 5] = [1, 2, 3, 4, 5];  
for element: i32 in array {  
    println!("Current: {}", element);  
}
```

For every element in the array
do the stuff in the block



2. Loops - for

a **for** loop may look like this

```
let array: [i32; 5] = [1, 2, 3, 4, 5];  
for element: i32 in array {  
    println!("Current: {}", element);  
}
```

Instead of using indices, the **for loop** automatically assigns the element to a variable, here called **element**



2. Loops - for

a **for** loop may look like this

Output:

```
Current: 1  
Current: 2  
Current: 3  
Current: 4  
Current: 5
```

```
let array: [i32; 5] = [1, 2, 3, 4, 5];  
for element: i32 in array {  
    println!("Current: {}", element);  
}
```



2. Loops - for

a **for** loop may look like this

Output:

```
Current: 120
Current: 768
Current: 9021
Current: -4012
```

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];
for blub: i32 in vector { // Note: This moves the vector!
    println!("Current: {}", blub);
}
```



2. Loops - for

a **for** loop may look like this

Output:

```
Current: 120
Current: 768
Current: 9021
Current: -4012
```

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];
for blub: i32 in vector { // Note: This moves the vector!
    println!("Current: {}", blub);
}
```

You can name the variable whatever you want



2. Loops - for

a **for** loop may look like this

```
for n: i32 in 0..10 {  
    println!("Number: {}", n);  
}  
  
for m: i32 in 0..=10 {  
    println!("Mumber: {}", m);  
}
```

2. Loops - for

Range operator

→ Creates a collection of numbers between start and end

a `for` loop may look like this

```
for n: i32 in 0..10 {  
    println!("Number: {}", n);  
}  
  
for m: i32 in 0..=10 {  
    println!("Mumber: {}", m);  
}
```

2. Loops - for

Range operator

→ Creates a collection of numbers between start and end

a for loop may look like this

end is NOT contained in that collection

```
for n: i32 in 0..10 {  
    println!("Number: {}", n);  
}
```

end is contained in that collection

```
for m: i32 in 0..=10 {  
    println!("Mumber: {}", m);  
}
```

2. Loops - for

a **for** loop may look like this

```
for n: i32 in 0..10 {  
    println!("Number: {}", n);  
}  
  
for m: i32 in 0..=10 {  
    println!("Mumber: {}", m);  
}
```

n is in [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
m is in [0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10]



2. Loops - for

a **for** loop may look like this

```
for n: i32 in 0..10 {  
    println!("Number: {}", n);  
}  
for m: i32 in 0..=10 {  
    println!("Number: {}", m);  
}
```

Output:

```
Number: 0  
Number: 1  
Number: 2  
Number: 3  
Number: 4  
Number: 5  
Number: 6  
Number: 7  
Number: 8  
Number: 9  
Number: 0  
Number: 1  
Number: 2  
Number: 3  
Number: 4  
Number: 5  
Number: 6  
Number: 7  
Number: 8  
Number: 9  
Number: 10
```




2. Loops - for

a **for** loop may look like this

```
for n: i32 in 0..10 {  
    println!("Number: {}", n);  
}
```

```
for m: i32 in 0..=10 {  
    println!("Number: {}", m);  
}
```

Output:

```
Number: 0  
Number: 1  
Number: 2  
Number: 3  
Number: 4  
Number: 5  
Number: 6  
Number: 7  
Number: 8  
Number: 9
```

```
Number: 0  
Number: 1  
Number: 2  
Number: 3  
Number: 4  
Number: 5  
Number: 6  
Number: 7  
Number: 8  
Number: 9  
Number: 10
```

2. Loops - for

a **for** loop may look like this

```
for n: i32 in 0..10 {  
    println!("Number: {}", n);  
}
```

```
for m: i32 in 0..=10 {  
    println!("Number: {}", m);  
}
```

Output:

```
Number: 0  
Number: 1  
Number: 2  
Number: 3  
Number: 4  
Number: 5  
Number: 6  
Number: 7  
Number: 8  
Number: 9
```

```
Number: 0  
Number: 1  
Number: 2  
Number: 3  
Number: 4  
Number: 5  
Number: 6  
Number: 7  
Number: 8  
Number: 9  
Number: 10
```



Intermission - Exercises

- Time for exercises!

Intermission - Exercises

2/3

```
fn main() {  
    let mut counter: i32 = 0;  
    for a: i32 in 0..10 {  
        for a: i32 in 0..10 {  
            counter += 1;  
        }  
    }  
    println!("{}", counter);  
}
```

Intermission - Exercises

2/3

```
fn main() {  
    let mut counter: i32 = 0;  
    for a: i32 in 0..10 {  
        for a: i32 in 0..10 {  
            counter += 1;  
        }  
    }  
    println!("{}", counter);  
}
```

Does this code compile?
If yes, what does it print?

Intermission - Exercises

2/3

```
fn main() {  
    let mut counter: i32 = 0;  
    for a: i32 in 0..10 {  
        for a: i32 in 0..10 {  
            counter += 1;  
        }  
    }  
    println!("{}", counter);  
}
```

Does this code compile?
If yes, what does it print?

It does compile!

Intermission - Exercises

2/3

```
fn main() {  
    let mut counter: i32 = 0;  
    for a: i32 in 0..10 {  
        for a: i32 in 0..10 {  
            counter += 1;  
        }  
    }  
    println!("{}", counter);  
}
```

Does this code compile?
If yes, what does it print?

It does compile!

The answer is 100.

Intermission - Exercises

2/3

```
fn main() {  
    let mut counter: i32 = 0;  
    for a: i32 in 0..10 {  
        for a: i32 in 0..10 {  
            counter += 1;  
        }  
    }  
    println!("{}", counter);  
}
```

Does this code compile?
If yes, what does it print?

It does compile!

The answer is 100.

When nesting loops, runtime easily blows up

Intermission - Exercises

2/3

```
fn main() {  
    let mut counter: i32 = 0;  
    for a: i32 in 0..10 {  
        for a: i32 in 0..10 {  
            counter += 1;  
        }  
    }  
    println!("{}", counter);  
}
```

Does this code compile?
If yes, what does it print?

It does compile!

The answer is 100.

When nesting loops, runtime easily blows up
→ For every outer loop you need to run the inner loop 10 times

Intermission - Exercises

2/3

```
fn main() {  
    let mut counter: i32 = 0;  
    for a: i32 in 0..10 {  
        for a: i32 in 0..10 {  
            counter += 1;  
        }  
    }  
    println!("{}", counter);  
}
```

Does this code compile?
If yes, what does it print?

It does compile!

The answer is 100.

When nesting loops, runtime easily blows up
→ For every outer loop you need to run the inner loop 10 times
→ We run the outer loop 10 times

Intermission - Exercises

2/3

```
fn main() {  
    let mut counter: i32 = 0;  
    for a: i32 in 0..10 {  
        for a: i32 in 0..10 {  
            counter += 1;  
        }  
    }  
    println!("{}", counter);  
}
```

Does this code compile?
If yes, what does it print?

It does compile!

The answer is 100.

When nesting loops, runtime easily blows up
→ For every outer loop you need to run the inner loop 10 times
→ We run the outer loop 10 times
→ 10x10 == 100 iterations

Intermission - Exercises

2/3

```
fn main() {  
    let mut counter: i32 = 0;  
    for a: i32 in 0..10 {  
        for a: i32 in 0..10 {  
            counter += 1;  
        }  
    }  
    println!("{}", counter);  
}
```

Does this code compile?
If yes, what does it print?

How often we run through the loop is not linked
to the variable name

Variable shadowing did not matter

Intermission - Exercises

3/3

```
fn main() {  
    let mut vector: Vec<i32> = vec![1, 2, 3, 4];  
    for index: usize in 0..vector.len() {  
        let mut elem: i32 = vector[index];  
        elem *= 2;  
    }  
    println!("{:?}", vector);  
    for prime: i32 in [2, 3, 5, 7] {  
        if vector.contains(&prime) {  
            println!("Vector contains prime {}", prime);  
        }  
    }  
}
```

Intermission - Exercises

3/3

```
fn main() {  
    let mut vector: Vec<i32> = vec![1, 2, 3, 4];  
    for index: usize in 0..vector.len() {  
        let mut elem: i32 = vector[index];  
        elem *= 2;  
    }  
    println!("{:?}", vector);  
    for prime: i32 in [2, 3, 5, 7] {  
        if vector.contains(&prime) {  
            println!("Vector contains prime {}", prime);  
        }  
    }  
}
```

Does this code compile?
If yes, what does it print?

Intermission - Exercises

3/3

```
fn main() {  
    let mut vector: Vec<i32> = vec![1, 2, 3, 4];  
    for index: usize in 0..vector.len() {  
        let mut elem: i32 = vector[index];  
        elem *= 2;  
    }  
    println!("{:?}", vector);  
    for prime: i32 in [2, 3, 5, 7] {  
        if vector.contains(&prime) {  
            println!("Vector contains prime {}", prime);  
        }  
    }  
}
```

Does this code compile?
If yes, what does it print?

It does compile!

However it does not do what you might think it does...

Intermission - Exercises

3/3

```
fn main() {  
    let mut vector: Vec<i32> = vec![1, 2, 3, 4];  
    for index: usize in 0..vector.len() {  
        let mut elem: i32 = vector[index];  
        elem *= 2;  
    }  
    println!("{:?}", vector);  
    for prime: i32 in [2, 3, 5, 7] {  
        if vector.contains(&prime) {  
            println!("Vector contains prime {}", prime);  
        }  
    }  
}
```

We're never actually setting elements in the vector!
We only assign to a local variable.

Does this code compile?
If yes, what does it print?

Intermission - Exercises

3/3

```
fn main() {  
    let mut vector: Vec<i32> = vec![1, 2, 3, 4];  
    for index: usize in 0..vector.len() {  
        let mut elem: i32 = vector[index];  
        elem *= 2;  
    }  
    println!("{:?}", vector); prints [1, 2, 3, 4]  
    for prime: i32 in [2, 3, 5, 7] {  
        if vector.contains(&prime) {  
            println!("Vector contains prime {}", prime);  
        }  
    }  
}
```

Does this code compile?
If yes, what does it print?

Intermission - Exercises

3/3

```
fn main() {  
    let mut vector: Vec<i32> = vec![1, 2, 3, 4];  
    for index: usize in 0..vector.len() {  
        let mut elem: i32 = vector[index];  
        elem *= 2;  
    }  
    println!("{:?}", vector);  
    for prime: i32 in [2, 3, 5, 7] {  
        if vector.contains(&prime) { vector contains 2 and 3, so it prints those two  
            println!("Vector contains prime {}", prime);  
        }  
    }  
}
```

Does this code compile?
If yes, what does it print?

Intermission - Exercises

3/3

```
fn main() {  
    let mut vector: Vec<i32> = vec![1, 2, 3, 4];  
    for index: usize in 0..vector.len() {  
        let mut elem: i32 = vector[index];  
        elem *= 2;  
    }  
    println!("{:?}", vector);  
    for prime: i32 in [2, 3, 5, 7] {  
        if vector.contains(&prime) {  
            println!("Vector contains prime {}", prime);  
        }  
    }  
}
```

```
[1, 2, 3, 4]  
Vector contains prime 2  
Vector contains prime 3
```

Does this code compile?
If yes, what does it print?



3. Next time

- Ownership
- Borrow Checker
- References



4. Loops - Extra



4. Loops - Extra

- You might think that there exists the „most powerful“ loop



4. Loops - Extra

- You might think that there exists the „most powerful“ loop
- Indeed, some loops are more convenient than others, you would not use `loop` to iterate over a collection!



4. Loops - Extra

- You might think that there exists the „most powerful“ loop
- Indeed, some loops are more convenient than others, you would not use `loop` to iterate over a collection!
- However, all loops can be converted to each other → All loops are equally powerful!



4. Loops - Extra

Goal: Convert this **for** loop into a normal **loop** loop

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];  
for element: i32 in vector { // Note: This moves the vector!  
    println!("Current: {}", element);  
}
```



4. Loops - Extra

Goal: Convert this `for` loop into a normal `loop` loop

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];  
for element: i32 in vector { // Note: This moves the vector!  
    println!("Current: {}", element);  
}
```

Normal `loop` can't easily do the assign thing, we need to first desugar this line

4. Loops - Extra

Goal: Convert this **for** loop into a normal **loop** loop

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];  
for element: i32 in vector { // Note: This moves the vector!  
    println!("Current: {}", element);  
}
```

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];  
for index: usize in 0..vector.len() {  
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
}
```

4. Loops - Extra

Goal: Convert this **for** loop into a normal **loop** loop

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];  
for element: i32 in vector { // Note: This moves the vector!  
    println!("Current: {}", element);  
}
```

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];  
for index: usize in 0..vector.len() {  
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
}
```

Those lines are equivalent – We just assign to a variable by hand
→ Added bonus: We no longer move the **vector**!

4. Loops - Extra

Goal: Convert this **for** loop into a normal **loop** loop

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];  
for element: i32 in vector { // Note: This moves the vector!  
    println!("Current: {}", element);  
}
```

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];  
for index: usize in 0..vector.len() {  
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
}
```

We're still using **for** though... We need to go deeper!

4. Loops - Extra

Goal: Convert this **for** loop into a normal **loop** loop

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];
for element: i32 in vector { // Note: This moves the vector!
    println!("Current: {}", element);
}
```

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];
for index: usize in 0..vector.len() {
    let element: i32 = vector[index];
    println!("Current: {}", element);
}
```

We're still using **for** though... We need to go deeper!
We need to understand what the Range does.

4. Loops - Extra

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];  
for index: usize in 0..vector.len() {  
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
}
```

```
let mut index: usize = 0;  
while index < vector.len() {  
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
    index += 1;  
}
```

4. Loops - Extra

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];  
for index: usize in 0..vector.len() {  
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
}
```

Where did our range go?

```
let mut index: usize = 0;  
while index < vector.len() {  
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
    index += 1;  
}
```


4. Loops - Extra

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];  
for index: usize in 0..vector.len() {  
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
}
```

Where did our range go?

```
let mut index: usize = 0;  
while index < vector.len() {  
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
    index += 1;  
}
```

4. Loops - Extra

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];  
for index: usize in 0..vector.len() {  
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
}
```

Where did our range go?

```
let mut index: usize = 0;  
while index < vector.len() {  
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
    index += 1;  
}
```

4. Loops - Extra

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];  
for index usize in 0..vector.len() {  
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
}
```

Where did our range go?

```
let mut index: usize = 0;  
while index < vector.len() {  
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
    index += 1;  
}
```

4. Loops - Extra

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];  
for index in 0..vector.len() {  
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
}
```

Where did our range go?

```
let mut index: usize = 0;  
while index < vector.len() {  
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
    index += 1;  
}
```

4. Loops - Extra

```
let vector: Vec<i32> = vec![120, 768, 9021, -4012];  
for index in 0..vector.len() {  
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
}
```

Where did our range go?

Damn, impressive! But we still didn't find **loop** :(

```
let mut index: usize = 0;  
while index < vector.len() {  
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
    index += 1;  
}
```

4. Loops - Extra

```
let mut index: usize = 0;
while index < vector.len() {
    let element: i32 = vector[index];
    println!("Current: {}", element);
    index += 1;
}

let mut index: usize = 0;
loop {
    if index >= vector.len() {
        break;
    }
    let element: i32 = vector[index];
    println!("Current: {}", element);
    index += 1;
}
```

4. Loops - Extra

```
let mut index: usize = 0;  
while index < vector.len() {  
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
    index += 1;  
}
```

```
let mut index: usize = 0;  
loop {
```

```
    if index >= vector.len() {  
        break;  
    }
```

```
    let element: i32 = vector[index];  
    println!("Current: {}", element);  
    index += 1;  
}
```

in **while** we want to loop as long as the condition is **true**
→ We want to **break** the **loop** once the condition is **false**
→ **not** ($a < b$) → $a \geq b$

4. Loops - Extra

```
let mut index: usize = 0;
while index < vector.len() {
    let element: i32 = vector[index];
    println!("Current: {}", element);
    index += 1;
}
```

break is a special keyword to break out of any **loop**, **while** or **for**
→ Program **continues execution after loop-body**
→ Here: **After the pink brackets**

```
let mut index: usize = 0;
loop {
    if index >= vector.len() {
        break;
    }
    let element: i32 = vector[index];
    println!("Current: {}", element);
    index += 1;
}
```


4. Loops - Extra

```
let mut index: usize = 0;
while index < vector.len() {
    let element: i32 = vector[index];
    println!("Current: {}", element);
    index += 1;
}
```

```
let mut index: usize = 0;
loop {
    if index >= vector.len() {
        break;
    }
    let element: i32 = vector[index];
    println!("Current: {}", element);
    index += 1;
}
```

Here we finally got **loop**!

All the previous loops are **identical in what they do**, just using **different language constructs**.

Exception: **for** moved the **vector**, which was not the case in **while** or **loop**



4. Loops - Extra

- You might think that there exists the „most powerful“ loop
- Indeed, some loops are more convenient than others, you would not use `loop` to iterate over a collection!
- However, all loops can be converted to each other → **All loops are equally powerful!**
- However, as we've seen... It gets quite convoluted. Thank you `for` and `while` for existing :^)



3. Next time

- Ownership
- Borrow Checker
- References