

Reading and writing files

File opening modes

Different modes to open files for specific operations.

Syntax: r (reading) w (writing) a (appending) + (updating: read/write) b (binary, otherwise text)

```
Examples: with open("data.txt", "r") as file: content = file.read() print(content) with open("output.txt", "w") as file: file.write("Hello, world!") with open("log.txt", "a") as file: file.write("Log entry: Something happened.") with open("data.txt", "r+") as file: content = file.read() file.write("Updated content: " + content)
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



File reading methods

Different methods to read file content in various ways.

Syntax:

```
file.readlines() # reads all lines as a list  
readline() # reads the next line as a string  
file.read() # reads the entire file content as a string
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
with open("data.txt", "r") as file:    lines = file.readlines()    next_line = file.readline()  
)    content = file.read()
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



File writing methods

Different write methods to write content to a file.

Syntax:

```
file.write(content) # writes a string to the file
file.writelines(lines) # writes a list of strings to the file
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
lines = ["Hello\n", "World\n"]
with open("output.txt", "w") as file:
    file.writelines(lines)
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Iterating over lines

Iterates through each line in the file using a *loop*.

Syntax:

```
for line in file: # Code to process each line
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
with open("data.txt", "r") as file:
    for line in file:
        print(line)
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



open() and close()

Opens a file, performs operations, and explicitly closes the file using the close() method.

Syntax:

```
file = open(filename, mode) # Code that uses the filefile.close()
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

**Example:**

```
file = open("data.txt", "r")content = file.read()file.close()
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



with open()

Opens a file using a with block, ensuring automatic file closure after usage.

Syntax:

```
with open(filename, mode) as file: # Code that uses the file
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

**Example:**

```
with open("data.txt", "r") as file:content = file.read()
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Pandas

.read_csv()

Reads data from a .csv file and creates a DataFrame.

Syntax:

```
dataframe_name = pd.read_csv("filename.csv") Example: df = pd.read_csv("data.csv")
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



.read_excel()

Reads data from an Excel file and creates a DataFrame.

Syntax:

```
dataframe_name = pd.read_excel("filename.xlsx")
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
df = pd.read_excel("data.xlsx")
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



.to_csv()

Writes DataFrame to a CSV file.

Syntax:

```
dataframe_name.to_csv("output.csv", index=False)
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
df.to_csv("output.csv", index=False)
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Access Columns

Accesses a specific column using `[]` in the DataFrame.

Syntax:

```
dataframe_name["column_name"] # Accesses single column  
dataframe_name[["column1", "column2"]] # Accesses multiple columns
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
df["age"]df[["name", "age"]]
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



describe()

Generates a statistics summary of numeric columns in the DataFrame.

Syntax:

```
dataframe_name.describe()
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

**Example:**

```
df.describe()
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



drop()

Removes specified rows or columns from the DataFrame. axis=1 indicates columns. axis=0 indicates rows.

Syntax:

```
dataframe_name.drop(["column1", "column2"], axis=1, inplace=True)dataframe_name.drop(index=[row1, row2], axis=0, inplace=True)
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

**Example:**

```
df.drop(["age", "salary"], axis=1, inplace=True) # Will drop columns  
df.drop(index=[5, 10], axis=0, inplace=True) # Will drop rows
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



dropna()

Removes rows with missing NaN values from the DataFrame. axis=0 indicates rows.

Syntax:

```
dataframe_name.dropna(axis=0, inplace=True)
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

**Example:**

```
df.dropna(axis=0, inplace=True)
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



uplicated()

Identifies duplicate or repetitive values or records within a dataset.

Syntax:

```
dataframe_name.duplicated()
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

**Example:**

```
duplicate_rows = df[df.duplicated()]
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Filter Rows

Creates a new DataFrame with rows that meet specified conditions.

Syntax:

```
filtered_df = dataframe_name[(Conditional_statements)]
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

**Example:**

```
filtered_df = df[(df["age"] > 30) & (df["salary"] < 50000)]
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



groupby()

Splits a DataFrame into groups based on specified criteria, enabling subsequent aggregation, transformation, or analysis within each group.

Syntax:

```
grouped = dataframe_name.groupby(by, axis=0, level=None, as_index=True, sort=True, group_keys=True, squeeze=False, observed=False, dropna=True)
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
grouped = df.groupby(["category", "region"]).agg({"sales": "sum"})
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



head()

Displays the first n rows of the DataFrame.

Syntax:

```
dataframe_name.head(n)
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
df.head(5)
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Import pandas

Imports the Pandas library with the alias pd.

Syntax:

```
import pandas as pd
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
import pandas as pd
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



info()

Provides information about the DataFrame, including data types and memory usage.

Syntax:

```
dataframe_name.info()
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
df.info()
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



merge()

Merges two DataFrames based on multiple common columns.

Syntax:

```
merged_df = pd.merge(df1, df2, on=["column1", "column2"])
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
merged_df = pd.merge(sales, products, on=["product_id", "category_id"])
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



print DataFrame

Displays the content of the DataFrame.

Syntax:

```
print(df) # or just type df
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

**Example:**

```
print(df)df
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



replace()

Replaces specific values in a column with new values.

Syntax:

```
dataframe_name["column_name"].replace(old_value, new_value, inplace=True)
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

**Example:**

```
df["status"].replace("In Progress", "Active", inplace=True)
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



tail()

Displays the last n rows of the DataFrame.

Syntax:

```
dataframe_name.tail(n)
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
df.tail(5)
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



NumPy

Importing NumPy

Imports the NumPy library.

Syntax:

```
import numpy as np
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
import numpy as np
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



np.array()

Creates a one-dimensional or multi-dimensional array.

Syntax:

```
array_1d = np.array([list1 values]) # 1D Array
array_2d = np.array([[list1 values], [list2 values]]) # 2D Array
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
array_1d = np.array([1, 2, 3]) # 1D Array
array_2d = np.array([[1, 2], [3, 4]]) # 2D Array
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



NumPy Array Attributes

Common NumPy operations on arrays:

- Calculates the mean of array elements
- Calculates the sum of array elements
- Finds the minimum value in the array
- Finds the maximum value in the array
- Computes the dot product of two arrays

Example:

```
np.mean(array)
np.sum(array)
np.min(array)
np.max(array)
np.dot(array_1, array_2)
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

