

Use this cheat sheet for various packages/methods, their descriptions, and examples.

Accessing element attribute

Access the value of a specific attribute of an HTML element.

Syntax:

```
attribute = element[(attribute)]
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
href = link_element[(href)]
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



BeautifulSoup()

Parse the HTML content of a web page using BeautifulSoup. The parser type can vary based on the project.

Syntax:

```
soup = BeautifulSoup(html, (html.parser))
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
html = (https://api.example.com/data) soup = BeautifulSoup(html, (html.parser))
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



delete()

Send a DELETE request to remove data or a resource from the server. DELETE requests delete a specified resource on the server.

Syntax:

```
response = requests.delete(url)
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
response = requests.delete((https://api.example.com/delete))
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



find()

Find the first HTML element that matches the specified tag and attributes.

Syntax:

```
element = soup.find(tag, attrs)
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
first_link = soup.find((a), {(class): (link)}))
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



find_all()

Find all HTML elements that match the specified tag and attributes.

Syntax:

```
elements = soup.find_all(tag, attrs)
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
all_links = soup.find_all((a), {(class): (link)}</td>
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



findChildren()

Find all child elements of an HTML element.

Syntax:

```
children = element.findChildren()
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
child_elements = parent_div.findChildren()
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



get()

Perform a GET request to retrieve data from a specified URL. GET requests are typically used for reading data from an API. The response variable will contain the server's response, which you can process further.

Syntax:

```
response = requests.get(url)
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
response = requests.get((https://api.example.com/data))
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Headers

Include custom headers in the request. Headers can provide additional information to the server, such as authentication tokens or content types.

Syntax:

```
headers = {(HeaderName): (Value)}
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
base_url = (https://api.example.com/data) headers = {(Authorization): (Bearer YOUR_TOKEN)} re  
sponse = requests.get(base_url, headers=headers)
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Import Libraries

Import the necessary Python libraries for web scraping.

Syntax:

```
from bs4 import BeautifulSoup
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



json()

Parse JSON data from the response. This extracts and works with the data returned by the API. The response.json() method converts the JSON response into a Python data structure, usually a dictionary or list.

Syntax:

```
data = response.json()
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

**Example:**

```
response = requests.get((https://api.example.com/data)) data = response.json()
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



next_sibling()

Find the next sibling element in the DOM.

Syntax:

```
sibling = element.find_next_sibling()
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

**Example:**

```
next_sibling = current_element.find_next_sibling()
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



parent

Access the parent element in the Document Object Model (DOM).

Syntax:

```
parent = element.parent
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
parent_div = paragraph.parent
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



post()

Send a POST request to a specified URL with data. Create or update POST requests using resources on the server. The data parameter contains the data to send to the server, often in JSON format.

Syntax:

```
response = requests.post(url, data)
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
response = requests.post((https://api.example.com/submit), data={{(key): (value)}})
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



put()

Send a PUT request to update data on the server. PUT requests are used to update an existing resource on the server with the data provided in the data parameter, typically in JSON format.

Syntax:

```
response = requests.put(url, data)
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

**Example:**

```
response = requests.put((https://api.example.com/update), data={{key): (value}})
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Query parameters

Pass query parameters in the URL to filter or customize the request. Query parameters specify conditions or limits for the requested data.

Syntax:

```
params = {(param_name): (value)}
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
base_url = "https://api.example.com/data"params = {"page": 1, "per_page": 10}response = requests.get(base_url, params=params)
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



select()

Select HTML elements from the parsed HTML using a CSS selector.

Syntax:

```
element = soup.select(selector)
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

**Example:**

```
titles = soup.select('h1')
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



status_code

Check the HTTP status code of the response. The HTTP status code indicates the result of the request (success, error, redirection). It can be used for error handling and decision-making in your code.

Syntax:

```
response.status_code
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

**Example:**

```
url = "https://api.example.com/data"
response = requests.get(url)
status_code = response.status_code
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



tags for find() and find_all()

Specify any valid HTML tag as the tag parameter to search for elements of that type. Here are some common HTML tags that you can use with the tag parameter.

Tag examples:

```
- (a): Find anchor () tags.- (p): Find paragraph ((p)) tags.-
(h1), (h2), (h3), (h4), (h5), (h6): Find heading tags from level 1 to 6 ( (h1),n (h2)).-
(table): Find table () tags.- (tr): Find table row () tags.-
(td): Find table cell ((td)) tags.- (th): Find table header cell ((td))tags.-
(img): Find image ((img)) tags.- (form): Find form ((form)) tags.-
(button): Find button ((button)) tags.
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



text

Retrieve the text content of an HTML element.

Syntax:

```
text = element.text
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

**Example:**

```
title_text = title_element.text
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

