

Use this cheat sheet for various SQL commands and their syntax, descriptions, and examples.

SELECT

SELECT statement is used to fetch data from a database.

Syntax:

```
SELECT column1, column2, ... FROM table_name;
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
SELECT city FROM placeofinterest;
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



WHERE

WHERE clause is used to extract only those records that fulfill a specified condition.

Syntax:

```
SELECT column1, column2, ...FROM table_name WHERE condition;
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
SELECT * FROM placeofinterest WHERE city = 'Rome' ;
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



COUNT

COUNT is a function that takes the name of a column as argument and counts the number of rows when the column is not NULL.

Syntax:

```
SELECT COUNT * FROM table_name ;
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
SELECT COUNT(country) FROM placeofinterest WHERE country='Canada';
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



DISTINCT

DISTINCT function is used to specify that the statement is a query which returns unique values in specified columns.

Syntax:

```
SELECT DISTINCT columnname FROM table_name;
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
SELECT DISTINCT country FROM placeofinterest WHERE type='historical';
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



LIMIT

LIMIT is a clause to specify the maximum number of rows the result set must have.

Syntax:

```
SELECT * FROM table_name LIMIT number;
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

**Example:**

```
SELECT * FROM placeofinterest WHERE airport="pearson" LIMIT 5;
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



INSERT

INSERT is used to insert new rows in the table.

Syntax:

```
INSERT INTO table_name (column1,column2,column3...) VALUES(value1,value2,value3...);
```

**Information:**

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
INSERT INTO placeofinterest (name,type,city,country,airport) VALUES('Niagara Waterfalls','Nature','Toronto','Canada','Pearson');
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



UPDATE

UPDATE used to update the rows in the table.

Syntax:

```
UPDATE table_name SET [[column1]=[VALUES]] WHERE [condition];
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
UPDATE placeofinterest SET name = 'Niagara Falls' WHERE name = "Niagara Waterfalls";
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



DELETE

DELETE statement is used to remove rows from the table which are specified in the WHERE condition.

Syntax:

```
DELETE FROM table_name WHERE [condition];
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.



Example:

```
DELETE FROM placeofinterest WHERE city IN ('Rome', 'Vienna');
```



Information:

Pressing Tab in the current editor will insert the tab character. Toggle this behavior by pressing Control+M.

