3.0 UX Design Brief: Information Architecture & Navigation

Asset Type	Design Brief
Description	IA and navigation decisions for OPAQUE 3.0, covering the Workspace governance model, BYOW/Containers, Trust Center, and role structure.
Last edited	April 24, 2026 1:10 PM
Owner	Trish Avila
Wave	

Context

Replatforming creates the opportunity to rethink the IA, and the 3.0 governance model makes it the right call.

In 2.x, the nav is flat and org-level: workspaces are a destination — something you select from a list and manage from above. Datasets and Integrations are org-wide. There is no persistent sense of operating *within* a workspace.

In 3.0, the workspace is the primary operating context: resources are bound to it, workflows live inside it, and RBAC is scoped to it. A flat org-level nav cannot represent this coherently for Members (Builders), who have no org-level access and operate exclusively within their assigned workspaces.

The job of this IA rethink is to make workspace-as-context the legible, persistent experience — without requiring users to hold the mental model in their heads. Three capabilities introduced or reframed in 3.0 inform the object model and surface design: Workspaces as governance domains (resource binding, RBAC, policy baselines), BYOW (Containers as a registered resource type), and the Trust Center (org-wide attestation proof for every stakeholder in the trust chain, accessible to all roles).

> **Source PRDs:** Workspaces as Governance Domains · Trust Center · BYOW · OOUX Map

---

Definitions

Term	Definition	Reference
Workspace	A governance domain scoped to an org. Contains Workflows, binds passive Resources, scopes members by role, and carries a policy baseline that Workflows inherit. Containers registered at the org level can be permissioned to a workspace, where they appear as studio nodes. The primary operating context for Members. Two distinct categories exist within a workspace: **Deployable things** (Workflows and permissioned Containers) run, have a lifecycle, and produce an attestation chain. **Passive resources** (Data Sources, Agent Tools, Models) are referenced by deployable things and do not run independently.	Workspaces PRD
Workload	Umbrella term for the two deployable types in OPAQUE: **Workflows** (Studio-built graphs) and **Containers** (BYOW deployable units). Both types declare a Manifest, run inside a TEE, and produce an attestation chain at runtime. Workflows are governed by workspace and workload-level policies.	Workspaces PRD · BYOW PRD
Container	A customer-brought containerized workload (BYOW) registered with OPAQUE at the org level. Two-stage lifecycle: **Registration** (org level — OWD submitted, Manifest generated, governance-approved artifact exists in the registry) and **Permissioning** (the Container is permissioned to one or more workspaces, where it appears as a studio node and can be incorporated as a Workflow node).	BYOW PRD · See Appendix
Workflow	A Studio-built graph that runs within a workspace. Can include bound passive Resources and permissioned Containers as nodes. Declares a Manifest and has a status (Draft / Deployed). Governed by workspace and workload-level policies.	Workspaces PRD

Term	Definition	Reference
Resource	A passive data asset or service (Data Sources, Agent Tools, or Models) referenced by Containers and Workflows. Does not run independently and does not produce attestation. Registered at org level and explicitly bound to a workspace before it is available there.	Workspaces PRD
OPAQUE Workload Definition (OWD)	A YAML configuration file authored by the Builder specifying a Container's app name, version, container images, policies, and identities. Submitted to the cluster manager during registration, which returns a Kubernetes deployment spec and generates the Manifest. Not surfaced in the UI in 3.0 Alpha; its role in the GA UI registration flow is an open question.	BYOW PRD
Manifest	The set of expected reference measurements generated from the OWD during Container or Workflow registration. Represents "what should run." Used by the Verifier to assess whether the actual runtime environment matches what was registered.	BYOW PRD · Trust Center PRD
Signed Evidence	The actual measurements of what is running, captured per pod at runtime. Generic term for the EAT (Entity Attestation Token) in attestation standards — terminology not yet finalized. Represents "what is running."	Trust Center PRD
Result	The output of the Verifier comparing the Manifest (expected) against the Signed Evidence (actual). Represents "did they match?" Distinguishes between failure types: infrastructure failure, measurement mismatch, or invalid evidence. Generic term for the EAR (Attestation Result) in attestation standards — terminology not yet finalized.	Trust Center PRD

The attestation chain — **Manifest** → **Signed Evidence** → **Result** — is the conceptual backbone of Trust Center IA. Every Container and Workflow produces this chain at runtime.

Roles

Three roles govern access across the platform in 3.0. A fourth role (Workspace Admin) is planned for a future release. *(Decision: TBD-6, 3.0 GA)*

- **Owner** — all Global Admin capabilities, plus exclusive control over which users hold the Global Admin role. Equivalent to the former Org Admin.
- **Global Admin** — org-wide view and management. Can manage org-level resources through Registry (Containers and passive Resources), org-level configuration through Org Settings, and workspace membership across all workspaces. Can access Trust Center and Settings. Global Admins who need to view and export cross-workspace trust artifacts (the Watchdog use case) are served by this role in 3.0. A dedicated read-only Watchdog role may be introduced in a future release.
- **Member** — limited to their assigned workspaces. Default landing is the Workspaces list scoped to their memberships. Can view Workflows and Resources within assigned workspaces. Can access Trust Center with org-wide content. Accesses Containers only through the Studio node menu — there is no standalone Containers nav item for Members. Can view workspace member list and policies read-only via Workspace Settings. No access to Registry or Org Settings in nav.

Note: Global Admin is org-scoped, not workspace-scoped. There is no concept of being a Global Admin in one workspace and a Member in another — you are either an org-wide Global Admin or a workspace-limited Member.

Navigation Model

Two-group sidebar structure. The sidebar is organized into two groups separated by a divider. The **workspace-scoped group** (top) contains the workspace picker, Workflows, Resources, and Workspace Settings; it appears only when a workspace is actively scoped. The **org-scoped group** (bottom) contains Workspaces, Registry, Trust Center, and Org Settings; it is always visible (role-permitting).

Workspaces is the home surface. First-time Owners and Global Admins land on Workspaces by default; Members land on the list scoped to their own memberships. Clicking Workspaces at any time returns the user to the list — no

separate home screen is needed, and this resolves the "where do I go back to" problem when nothing is scoped. *(Decision: 2026-04-24)*

Workspace picker behavior. Visible when the user has one or more workspaces; hidden entirely when they have zero. When visible, the label swaps with state — "Select a workspace" (placeholder) when the user is on the Workspaces list surface, and the workspace name (e.g. "HR Internal") when scoped into a specific workspace. The workspace-scoped items below the picker collapse when the picker is in placeholder state. *(Decision: 2026-04-24)*

Registry and Org Settings are regular nav items in the org-scoped group. Their sub-sections (Containers / Resources for Registry; Workspaces / Users / Policies / General for Org Settings) are navigated as in-page tabs within their respective surfaces, not as sidebar replacements — the outer sidebar stays stable across surfaces.

Sidebar states

Four primary states cover the role × workspace-count matrix. In every state, the profile footer is pinned to the bottom of the sidebar. The cluster badge (multi-cluster orgs only) sits above the picker and is visible to all roles.

Owner / Global Admin — scoped into a workspace

```
[ Cluster Name ▾ ]          (multi-cluster orgs only — all rol
es)
[ HR Internal ▾ ]
Workflows
Resources                   (Data Sources, Agent Tools, Model
s)
Workspace Settings          (policies + members; editable)
———————————————————
Workspaces                  (home — list of all org workspace
s)
Registry                    (org-wide — Containers + Resource
s)
Trust Center                (org-wide, filterable by workspac
e)
```

```
Org Settings

[ User Name ▾ ]            (Profile Settings, Log out)
```

Owner / Global Admin — on the Workspaces list, or zero workspaces

```
[ Cluster Name ▾ ]         (multi-cluster orgs only — all rol
es)
[ Select a workspace ▾ ]   (hidden entirely when 0 workspaces
exist)
———————————————————
Workspaces                 (list, or empty state if 0)
Registry
Trust Center
Org Settings

[ User Name ▾ ]
```

Member — scoped into a workspace

```
[ Cluster Name ▾ ]         (multi-cluster orgs only — all rol
es)
[ HR Internal ▾ ]
Workflows
Resources
Workspace Settings         (policies + members; read-only)
———————————————————
Workspaces                 (home — scoped to their membership
s)
Trust Center

[ User Name ▾ ]
```

Member — on the Workspaces list, or zero memberships

```
[ Cluster Name ▾ ]          (multi-cluster orgs only — all rol
es)
[ Select a workspace ▾ ]    (hidden entirely when 0 membership
s)
———————————————————
Workspaces                  (list, or informative empty state
if 0)
Trust Center

[ User Name ▾ ]
```

Role-based visibility

The separator is a scope boundary: above it are workspace-scoped items (visible only when a workspace is scoped); below it are org-wide destinations (always visible, role-permitting).

Members never see Registry or Org Settings in nav. Registry is the home for org-level Container and Resource registrations — treated as an admin-only governance surface. Members access workspace-bound resources through the workspace-scoped **Resources** item instead.

Owners and Global Admins see the full org-scoped group: Workspaces, Registry, Trust Center, Org Settings. Workspace-level role differences (editable vs. read-only Policies and Members tabs in Workspace Settings) live inside screens, not in nav presence.

Trust Center is accessible to all roles. It is org-wide by default and filterable by workspace — Members see only workspaces they are assigned to; Global Admins and Owners see all. The primary audience is expected to be Global Admins; Member access is preserved but treated as secondary. Research in Q2/Q3 should validate this assumption.

The profile footer (e.g. Annemarie ▾) is pinned to the very bottom of the sidebar, structurally separate from the nav hierarchy. Visible to all roles; opens a small menu containing Profile Settings and Log out. User-scoped, not workspace-scoped.

Note: "Trust Center" follows the destination-naming pattern used by Registry and Org Settings. The full label is retained in both the nav and all prose references.

Note: "Org Settings" is used rather than "Settings" to signal org-level scope and avoid ambiguity with Profile Settings (the footer item).

Containers does not appear as a standalone workspace nav item for any role. Members encounter Containers only through the Studio node menu when building Workflows. Global Admins and Owners manage Containers through Registry.

Workspace picker dropdown

The workspace picker lists workspaces directly. Clicking the workspace name opens a dropdown showing available workspaces for the active user. A search bar appears when the user has access to 3 or more workspaces; below that threshold it is omitted.

Member (< 3 workspaces)

```
Finance
HR Internal
```

Member (3+ workspaces)

```
[ Search  🔍 ]
Finance
HR Internal
Sales and Marketing
```

Global Admin / Owner

```
[ Search  🔍 ]
──────────────────────
Recents
  Finance
  HR Internal
  Sales and Marketing
```

```
──────────────────────
+  New workspace
```

Search bar threshold: the search box appears for any role when the user has access to 3 or more workspaces. Below that threshold it is omitted. Global Admins and Owners — who can see all workspaces — will almost always exceed the threshold, so they effectively always see search. Members assigned to 1 or 2 workspaces get a clean list with no search overhead.

Key Surfaces

Empty states & first-run

No Default Workspace is auto-created. On first access, the Global Admin or Owner is prompted to create a workspace before any resources or users can be assigned. This is the expected setup flow for an enterprise governance product — an auto-created Default Workspace would add friction later when workflows need to be launched into a properly scoped workspace. *(Decision: TBD-2, 3.0 GA)*

Owner / Global Admin — no workspaces yet. The Workspaces surface shows a simple empty state: a "Create your first workspace" card with brief explanatory copy and a primary "Create a workspace" CTA. The workspace picker is hidden (nothing to select). Nav shows only org-scoped items: Workspaces, Registry, Trust Center, Org Settings.

Member — no workspace memberships yet. The Workspaces surface shows an informative empty state directing the member to contact their admin. Copy direction: "You're not in a workspace yet. A workspace is a dedicated space for your team to build and run workflows on shared data. To get started, ask an Owner or Global Admin in your org to add you to one." Since 3.0 has no product notification system, the empty state cannot fire a request — it points members to contact their admin out-of-band. *(Decision: 2026-04-24)*

Possible enhancement (no new infra required): surface the names and email addresses of the org's Owners and Global Admins in the empty state (read from the Users surface) with mailto: links, turning the copy into an actionable directory rather than a generic "contact your admin" pointer.

Member — with 1+ workspace memberships. Default landing is the scoped Workspaces list showing only the workspaces the member belongs to. Picker is present with "Select a workspace" placeholder until they pick one; the workspace-scoped group (Workflows, Resources, Workspace Settings) appears once they scope into a specific workspace. *(Decision: 2026-04-24)*

Containers

Containers are registered at the **org level** via the BYOW flow and **permissioned to workspaces** — they do not live inside a workspace the way Workflows do. Containers do not appear as a standalone nav item for any role. Members encounter Containers only through the Studio node menu when building Workflows. Global Admins and Owners register and manage Containers through **Registry** (see below).

Within a workspace, Containers behave as composable nodes — they can be incorporated into a Workflow but cannot be invoked standalone from the workspace nav. The Container lifecycle is managed at the org level: **Registration** (OWD submitted, Manifest generated, Container exists in Registry as a governance-approved artifact) and **Permissioning** (Container is granted access to one or more workspaces, where it becomes available as a Studio node).

Resources

Workspace-scoped view of passive resources bound to the current workspace: Data Sources, Agent Tools, Models. These are referenced by Containers and Workflows but do not run independently and do not produce attestation. All users can view. Resource types are tab- or filter-navigated within a single section. When a Builder adds a node in Studio, only resources listed here are surfaced as available — unbound resources are not shown at all.

Resources are not created here. They are registered at the org level in Registry and bound to workspaces from there. Who performs the binding is an open question (see Open Questions).

Workflows

List of workflows in the workspace with status (Draft / Deployed) and a Trust status badge per workflow that links directly to that item's Trust detail. The graph

editor constrains available node types to workspace-bound resources. Studio canvas discoverability (current multi-click friction) is noted but out of scope for 3.0.

Workspace Settings

A workspace-scoped nav item visible to all roles, sitting above the separator. Exposes two tabs:

Policies (default) — the workspace policy baseline and per-workflow inheritance state. Read-only for Members; editable for Global Admins and Owners. *Note: The workspace policy enforcement ceiling model (workspace baseline → per-workflow inheritance) is a GA deliverable and is not in scope for 3.0 Alpha. In Alpha this tab may show limited or placeholder content.*

Members — the member list for the current workspace, with role labels. Read-only for Members; editable for Global Admins and Owners.

Workspace Settings resolves the orientation gap from 2.x: Members can see who is in their workspace and what policies apply without needing access to Org Settings. Policy enforcement was the single most-requested capability in Q1 research (Policy Enforcement experiment, n=7) — surfacing it at the workspace level ensures that visibility is not gated behind an admin role.

Trust Center

Single surface for all attestation and compliance artifacts. Org-wide by default, filterable by workspace. Members see only workspaces they are assigned to; Global Admins and Owners see all workspaces. This is a deliberate departure from a workspace-scoped Trust surface — consolidating into one entry point makes the product's differentiating capability more discoverable and matches the aggregate view buyers expect.

Top-level view shows all Containers and Workflows across visible workspaces with their last enforcement status. The Overview tab carries two filters — **date range** (default: Last 7 days) and **workspace** (default: All workspaces; role-scoped so Members see only assigned workspaces and Global Admins / Owners see all). Policy enforcement covers three dimensions, all surfaced in the drill-down: **Runtime Integrity** (did the workload match its approved configuration?), **Network Policy** (did it only communicate with verified peers?), and **Pod Access Policy**

(were shell and log access restrictions honored?). Each dimension appears as a distinct Policy-column value in both the Blocked executions table and the Active policies table. Drill-down: item → pod → policy type → decision. Failure types are distinguished: infrastructure failure, measurement mismatch, invalid evidence, connection rejection. The Workload attestation table surfaces **Mode** (Production / Dev mode), **Status** (VERIFIED / FAILED / ALL VERIFIED / N FAILED chips, scoped per pod), and **Failure type** as first-class columns. Export of the Governance Record is the primary CTA, accessible from the per-pod row in item detail — not as a single org-wide action.

Dev-mode workloads cannot produce a TRUSTED verdict and must be persistently distinguished from production workloads throughout the Trust Center. Dev-mode records carry a DEV_UNSAFE state and are excluded from compliance exports. All dev-mode workload rows and detail views require a persistent [DEV MODE — NOT TRUSTED] indicator; dev-mode records must not be presented alongside production results without clear visual separation.

Design direction — progressive disclosure

Q1 research (Trust Center + Policy Enforcement experiment, n=7) surfaced a clear hierarchy of what buyers need before the exportable artifact becomes meaningful: **policy summary** → **workload inventory** → **exportable artifact.** Participants who landed on raw attestation data without policy context first were lost. Trust Center should lead with policy enforcement status and workload inventory, not hardware attestation. Platform and Hardware detail are only associated with a workload, no org-level platform or hardware attestation rollup is shown.

Design direction — per-workload Governance Record

Q1 research surfaced a strong hypothesis for a single human-readable exportable artifact per workload, containing the Manifest, Evidence, and Result. The intended use is for Builders to hand to Data Owners as a consent document before authorizing workload access to sensitive data, and to Watchdogs as proof after the fact. Key research finding: self-verification didn’t land — only 2/7 participants would use it themselves; the rest said they would pass it to legal or security. Buyers want a document, not a command to run.

The user-facing label validated in Q2 testing is **Governance Record** (also referred to as OPAQUE Governance Record). Use this label on all user-facing surfaces and

in design documentation. The engineering and PRD term for the same artifact is AEP (Attested Evidence Pack) — use that only in technical/engineering contexts.

The Governance Record includes a **Regulatory Framework Mapping** section between Policies Enforced and Workload Verification. It maps each active policy to the specific regulatory article it satisfies (SOC 2 Art. 9, DORA Art. 30, EU AI Act Art. 15, GDPR Arts. 25 & 32) and points to the document section where supporting evidence lives — so Data Owners, legal, and security reviewers can see at a glance how the artifact satisfies the controls they are responsible for. The Workload Identity block also carries a **TEE mode** field (`Production` / `Dev mode`); dev-mode workloads cannot produce a valid Governance Record.

> *Source: Q1 2026 PMF Experiments — Research Synthesis, Exportable Artifact experiment; label validated Q2 2026 user testing*

Audit Log

The Audit Log is the "After" surface of Trust Center — complementary to attestation (which answers "did the right thing run?") but answering a different question: "what did it do?" It captures all governance-relevant, state-changing platform actions with tamper-evident, append-only records. A key guarantee: if audit logging fails, the corresponding platform action is rejected. Audit is a control boundary, not telemetry.

This capability exists in the current product. The 3.0 design direction is based on a draft PRD (no finished 3.0 spec yet) — treat as directionally correct but subject to revision.

Access control: Global Admins and Owners see all audit logs across the org. Members see only logs scoped to their workspace. Access to the Audit Log (view, filter, export) is itself auditable.

Event categories captured:

- User & org lifecycle — user creation, role changes, workspace membership changes, deactivation
- Workflow events — create, update, delete, launch, stop, export
- Container / Workload events — registration, launch, stop, updates requiring remeasurement, attestation success/failure

- Policy events — creation and modification of workload-level and org-level policies, enforcement metrics

Not captured: Prompt or output content, internal LLM reasoning, internal container business logic. OPAQUE detects enforcement events, not policy violations.

Key capabilities: filter by category, actor, target entity, and timestamp; export for compliance review (SOC2, HIPAA, ISO). Exports are themselves audited.

Placement within Trust Center: The Audit Log is a distinct view alongside the attestation surfaces. It is filterable by workspace but shown org-wide by default, optimized for compliance officer and security engineer use cases.

> 🛡️ **Surface design directions and wireframes:** Trust Center: Surface Design Directions — includes Trust Center landing page wireframe (Overview + Audit Log tabs), exportable artifact (Trust Report) wireframe, WHAT THIS PROVES section mapped to Q1 research concerns, and Q2 PMF experiment alignment notes.

Registry (Global Admins + Owners)

Registry is a first-class nav item for Global Admins and Owners, covering all org-level asset registrations in one place. It is the primary home for the BYOW onboarding flow and resource management — surfaced prominently in the nav rather than buried in Settings to reduce adoption friction for teams new to the product. Registry's sub-sections (Containers, Resources) are navigated as tabs within the Registry surface — the outer sidebar stays stable. Org-level Resources (Data Sources, Agent Tools, Models) live under the Resources tab; they are not a separate top-level nav item.

Containers tab — All registered Containers, their workspace permission assignments, registration status, and last attestation status. This is where the BYOW registration flow lives (CLI in Alpha, UI in GA). Registration is a governance step — the Container exists in the registry but is not available in any workspace until explicitly permissioned. Drilling into a Container links directly to its Trust Center detail.

Resources tab — All registered passive resources (Data Sources, Agent Tools, Models). These are the source pool from which workspaces draw their bound

resources. Registered here at the org level; must be explicitly bound to a workspace before appearing there.

Only Owners can manage which users hold the Global Admin role. This control lives in Org Settings, not Registry.

No landing page — default to Containers list. Entering Registry drops directly into the Containers list view; Containers is the default selected state in the sub-nav. A landing page was considered and set aside: the primary reason Registry exists is to make Container registration frictionless, and an intermediate overview screen adds a click before the user reaches the task they came to do. The sub-nav already signals the full scope of what lives in Registry. Revisit when Global Admins are doing regular cross-section governance sweeps or when registered asset volume makes a cross-type status summary actionable at a glance — neither condition applies in 3.0.

Org Settings (Global Admins + Owners)

Org Settings narrows to workspace-level configuration now that Registry handles org-level asset management. The label “Org Settings” rather than “Settings” signals org-level scope and avoids ambiguity with Profile Settings. Accessible to Global Admins and Owners only; not visible to Members. Like Registry, its sub-sections (Workspaces, Users, Policies, General) are navigated as tabs within the Org Settings surface — the outer sidebar stays stable. Contains:

Workspaces — Org-wide management of all workspaces. Global Admins and Owners use this surface to oversee the full workspace inventory: create and delete workspaces, edit workspace metadata (name, description, cluster assignment), and view high-level state across every workspace in the org. This is the counterpart to Workspace Settings, which is scoped to a single active workspace and visible to all roles. Workspaces leads the Org Settings sub-nav because the workspace is the governance primitive that all other org-level configuration hangs off of.

Users — Org-wide management of all people with access to the platform, regardless of role. Global Admins and Owners use this surface to add and remove users, assign roles (Owner, Global Admin, Member), and manage workspace membership across all workspaces from one place. Label chosen over "Members" because this surface spans all three roles — "Member" is itself a specific role

name in 3.0, and Workspace Settings already has a Members tab scoped to a single workspace. Only Owners can assign or revoke the Global Admin role (see Registry section). A read-only view of the member list for a single workspace is accessible to all roles via Workspace Settings.

Policies — Workspace policy baseline and inheritance state per workflow. A read-only view of workspace policies is also accessible to all roles via Workspace Settings. *Note: The workspace policy enforcement ceiling model is a GA deliverable — not in scope for 3.0 Alpha.*

General — Workspace name, description, deletion. For orgs with more than one cluster, General also surfaces the **cluster selector** — a named list of registered clusters (e.g., "Production US-West", "Sub-prod") that sets the active infrastructure context for the session. Visible and editable by Owners only; not shown to Global Admins or Members. Single-cluster orgs do not see this control at all.

Cluster badge (sidebar) — all roles. When an org has more than one cluster, a compact badge indicating the active cluster appears in the sidebar above the workspace picker, visible to all roles. Clicking it opens a short dropdown listing available clusters. A footer link routes to Org Settings > General for cluster management (Owner-only). The split is intentional: **switch clusters = all roles, manage clusters = Owner only** — the same model as workspace switching (all roles) vs. workspace creation (admin-only). Placement above the workspace picker makes the org → workspace context hierarchy legible to everyone: you are in cluster X, workspace Y. This pattern follows the AWS region selector: a persistent, low-profile indicator that orients all users without disrupting primary nav. *Placement is tentative pending full sidebar layout review.*

Open Design Questions (Logged as Product Decisions)

1. **"Containers" vs. "Workloads" — nav label and route alignment**
    a. "Containers" vs. "Workloads" for nav label and route alignment?
2. **UI-based Container registration at GA (PM + UX + Engineering)**
    a. How does CLI BYOW experience translate to UI?
3. **Containers nav item — Members**

a. Do Members need (or want) have Container visibility outside of the Studio node menu?

Appendix: Container Lifecycle Detail

In the CLI flow (3.0 Alpha), the Builder authors an OPAQUE Workload Definition (YAML file) specifying app name, version, container images, policies, and identities. This is submitted to the cluster manager, which returns a Kubernetes deployment spec that the Builder deploys using standard Kubernetes tooling. The Manifest (expected reference measurements) is generated as part of this process.

Registration (org level): The OWD is submitted, the Manifest is generated, and the Container exists in the org registry as a governance-approved artifact — but it is not yet running anywhere. In 3.0 Alpha, registration is CLI-only. UI-based registration is planned for GA (see Open Design Questions).

Permissioning (workspace level): The Container is permissioned to one or more workspaces. Once permissioned, it appears in those workspaces as a studio node and can be incorporated as a node in a Workflow. A Container that has not been permissioned to a workspace is not available for use in Workflows in that workspace.

Containers are governed by workspace and workload-level policies. Note that policies are also specified within the OWD itself — the relationship between OWD-level policies and the workspace policy baseline is an open question. Open Question · BYOW PRD

Appendix: Object Model

https://www.figma.com/board/MxgjG99YOSqlIThuaDE580/3.0-Information-Architecture?node-id=14-71

The canonical hierarchy from the OOUX map:

Org → Workspace → [Containers, Workflows] + [Data Connectors, Agent Tools, Models]

Trust Center: Surface Design Directions