fodo cheatsheet · per-repo todos, PRPs and decisions as markdown in `docs/todo/`

Claude Code plugin · GTD for repos · github.com/pforret/claude-plugins · MIT

1 · INSTALL ONCE

1. **Marketplace** `/plugin marketplace add pforret/claude-plugins`
2. **Plugin** `/plugin install fodo@pforret-claude`
   updates: `/plugin marketplace update pforret-claude` , or turn on auto-update
3. **Dashboard** `/fodo:web` starts it on `127.0.0.1:7787` (PHP 8.1+; `stop · status · <port>`)
   and/or `/fodo:valet` serves it permanently as `http://fodo.test` with Laravel Valet (macOS, no sudo)
4. **Terminal** `/fodo:cli` puts a `fodo` command on your PATH (asks which directory; never sudo)
   then `fodo list` , `fodo busy --all` , `fodo pick` work in any terminal
5. **Look** on the dashboard open **/config** : header font, body font and color scheme
   Light Colors (default) · Light Monochrome · Dark Colors · Dark Monochrome, saved in `~/.claude/todo/config.json`
6. **Per repo** `/fodo:init` creates `docs/todo/` with its folders
   optional: the first other `/fodo:` command in a repo does it too

2 · HAPPY PATH

1. `/fodo:add` **fix the login redirect**
   bug · change · feature, sized from the code; a trivial item is offered right away (two-minute rule)
2. `/fodo:plan` **1**
   research + clarifying questions until 9/10 confidence → PRP; the item becomes `P1`
3. `/fodo:start` **P1**
   implement the PRP, run its validation loop; the item becomes `B1`
4. `/fodo:done`
   verify every acceptance criterion, write the Result, archive to `done/`
5. `/fodo:commit`
   generated message, semver bump, CHANGELOG, tag `vX.Y.Z` ; you push

Small, clear items skip the plan: `/fodo:start 1` . Blocked? `/fodo:wait B1 <reason>` . Not now? `/fodo:someday 3` . Never? `/fodo:skip 3` . Once a week: `/fodo:review` . Lost? `/fodo:help` . Everything is markdown in `docs/todo/` .

3 · ITEMS · this repo

`/fodo:add [--quick] <text>`	add an item, sized from the code; `--quick` or several lines: capture now, clarify later
`/fodo:list`	backlog (1, 2, …) plus the plan (P) and busy (B) tables
`/fodo:show [id]`	print an item, or a decision (`D2`)
`/fodo:plan <n>`	research, ask, write a PRP; moves to `plan/`
`/fodo:start <n|Pn>`	implement (PRP if present); moves to `busy/` ; resumes a waiting item
`/fodo:done [Bn]`	verify criteria, append the Result, move to `done/`
`/fodo:skip [id]`	drop with a reason; move to `skipped/`
`/fodo:someday [id [note] | Sn back]`	park an idea, list parked ones, bring one back
`/fodo:wait [Bn] <reason> | resume`	mark a busy item as waiting for something, or clear it
`/fodo:busy [--all]`	in progress and planned, here or in every registered repo

4 · MEMORY, REVIEW, GIT

`/fodo:decide <text>`	record a decision as a small ADR in `decisions/` (`D1` …)
`/fodo:decide --gotcha <text>`	one-line gotcha in `gotchas.md` ; start with `path/to/file:` to tie it to a file
`/fodo:decide`	list decisions and gotchas
`/fodo:review [planned-days [busy-days]]`	weekly review of stale items (backlog 30 days, busy 14, PRPs whose files changed): keep, re-plan, park, skip, start
`/fodo:repos [prune]`	the registry of repos; prune drops the gone ones
`/fodo:commit [<message>]`	stage all, generated subject (or yours), bump estimate like setver (`!` major · feat minor · else patch · bookkeeping none), ask once, write the version into VERSION.md, composer/package.json, .env.example, plugin.json, update CHANGELOG.md, commit, tag `vX.Y.Z` ; never pushes

5 · LAYOUT, IDS AND RULES

```
docs/todo/
  index.md + 2026-10-30.feature.slug.md   backlog
  plan/   busy/ (.current = last started)
  done/   skipped/   someday/
  decisions/  one ADR per file + gotchas.md
```

IDs

`1` , `2`	backlog	`S1`	someday
`P1`	planned with a PRP	`D1`	decision (never moved)
`B1`	busy (⏸ waiting)	*empty*	the item you started last

IDs are table positions and shift when items move: re-list after a move; a filename always works. One file per item (Request · Analysis · Impacted files · Plan · Acceptance criteria · PRP · Result); only its folder changes.

Rules

Never hand-edit `index.md` , `.current` or `decisions/` (the helper writes them) · items are never deleted, they end in `done/` or `skipped/` · only `/fodo:commit` commits and tags, nothing in fodo pushes · a SessionStart hook lists the busy items and the gotchas for the files you touch.

6 · TERMINAL · after /fodo:cli

`fodo list` · `fodo busy [--all]`	the same tables, no Claude needed
`fodo pick`	choose an item (fzf) and open Claude Code on it
`fodo path <id>` · `fodo current`	resolve an ID to its file
`fodo move <id> <stage>`	plan · busy · done · skipped · someday · planned
`fodo set|unset <file> <key> [v]`	frontmatter field, then reindex
`fodo wait|resume <file> [reason]`	waiting marker
`fodo decide <title>` · `fodo gotcha <text>`	decision skeleton · append a gotcha
`fodo stale` · `fodo reindex` · `fodo repos`	stale table · rebuild indexes · registry
`semver.sh current|next|files|set|t`	the version helper behind `/fodo:commit`

In a repo without `docs/todo/` , run `fodo init` first.