fodo cheatsheet · per-repo todos, PRPs and decisions as markdown in `docs/todo/`

`/plugin marketplace add pforret/claude-plugins` · `/plugin install fodo@pforret-claude`

HAPPY PATH

`/fodo:add <text>` — bug · change · feature, sized from the code

→ `/fodo:plan 1` — research + questions until 9/10 → PRP; becomes P1

→ `/fodo:start P1` — implement the PRP, run its validation loop; becomes B1

→ `/fodo:done` — verify the acceptance criteria, write the Result, archive

→ `/fodo:commit` — message, semver bump, CHANGELOG, tag; you push

Small, clear items skip the plan: `/fodo:start 1` . Every week: `/fodo:review` . Blocked? `/fodo:wait B1 <reason>` . Not now? `/fodo:someday 3` . Never? `/fodo:skip 3` . Why did we…? `/fodo:decide` .

DAY TO DAY (THIS REPO)

`/fodo:add [--quick] <text>`	add an item, sized from the code; `--quick` : capture now, clarify later
`/fodo:list`	backlog (1, 2, …) plus the plan (P) and busy (B) tables
`/fodo:show [id]`	print an item, or a decision (`D2`)
`/fodo:plan <n>`	research, ask, write a PRP; moves to `plan/`
`/fodo:start <n|Pn>`	implement (PRP if present); moves to `busy/` ; resumes a waiting item
`/fodo:done [Bn]`	verify criteria, append Result, move to `done/`
`/fodo:skip [id]`	drop with a reason; move to `skipped/`
`/fodo:someday [id [note] | Sn back]`	park an idea, list parked ones, bring one back
`/fodo:wait [Bn] <reason> | resume`	mark a busy item as waiting for something, or clear it
`/fodo:decide [<text> | --gotcha <text>]`	record a decision (small ADR, `D1` …) or a gotcha; no args: list them
`/fodo:review [planned-days [busy-days]]`	weekly review of stale items (30 / 14 days): keep, re-plan, park, skip, start
`/fodo:busy`	in progress and planned, with what items wait on
`/fodo:commit [<message>]`	stage all, generated subject, bump estimate like setver (`!` major · feat minor · else patch · bookkeeping none), ask once, write VERSION.md, composer/package.json, .env.example, plugin.json, update CHANGELOG.md, commit, tag `vX.Y.Z` ; never pushes

IDS

`1` , `2`	backlog, `docs/todo/`
`P1`	planned with a PRP, `plan/`
`B1`	busy, `busy/` (⏸ when waiting)
`S1`	someday, `someday/`
`D1`	decision, `decisions/` (never moved)
(empty)	the item you started last

IDs are positions in a table and shift when items move: re-list after a move. A filename always works too.

LAYOUT

```
docs/todo/
  index.md + 2026-10-30.feature.slug.md   backlog
  plan/      PRP written, waiting to start
  busy/      in progress   (.current = last started)
  done/  skipped/  someday/
  decisions/ one ADR per file + gotchas.md
```

Item = one markdown file: Request · Analysis · Impacted files · Plan · Acceptance criteria · PRP · Result. Filenames never change, only the folder. Legend: 🐞 bug 🔧 change ✨ feature · 🟢 small 🟡 medium 🔴 large ❔ unsized.

ONCE

`/fodo:init`	per repo, optional: any other command does it
`/fodo:web [stop|status|port]`	dashboard of all repos, `127.0.0.1:7787`
`/fodo:valet [status|unlink]`	serve it permanently as `http://fodo.test`
`/fodo:cli [status|unlink|dir]`	a `fodo` command on your PATH

ALL REPOS

`/fodo:busy --all`	busy and plan tables of every registered repo
`/fodo:repos [prune]`	the registry (`~/.claude/todo/repos.csv`); prune drops gone repos

TERMINAL, AFTER `/FODO:CLI`

`fodo list` · `fodo busy [--all]`	the same tables, no Claude needed
`fodo pick`	choose an item (fzf) and open Claude Code on it
`fodo path <id>` · `fodo current`	resolve an ID to its file
`fodo move <id> <stage>`	plan · busy · done · skipped · someday · planned
`fodo set|unset <file> <key> [v]`	frontmatter field, then reindex
`fodo wait|resume <file> [reason]`	waiting marker
`fodo decide <title>` · `fodo gotcha <text>`	write a decision skeleton · append a gotcha
`fodo stale` · `fodo reindex` · `fodo repos`	stale table · rebuild indexes · registry
`semver.sh current|next|files|set`	the version helper behind `/fodo:commit`

RULES OF THE GAME

Never hand-edit	`index.md` , `.current` , files in `decisions/` (use the helper)
Never deleted	items end in `done/` or `skipped/`
Git	only `/fodo:commit` commits and tags; nothing pushes
Session start	a hook lists the busy items and gotchas for the files you touch