



UNIVERSITY OF CALGARY
FACULTY OF SCIENCE
Department of Physics and Astronomy

Contents

| | | |
|----------|--|-----------|
| 1 | Lab Information Hub | 5 |
| 1.1 | Introduction | 5 |
| 1.1.1 | High Level Structure | 5 |
| 1.2 | Making Changes to Website | 6 |
| 1.2.1 | Testing changes before updating live version | 6 |
| 1.2.2 | Sync Live Version and Development Space | 6 |
| 2 | Experiment Documents | 7 |
| 2.1 | Introduction | 7 |
| 2.1.1 | Criteria for adding document | 7 |
| 2.1.2 | Directory structure | 7 |
| 2.2 | Adding a new lab to the repository | 8 |
| 2.3 | Adding new version of an existing lab | 8 |
| 2.4 | Editing Experiment Documents | 10 |
| 2.4.1 | Introduction | 10 |
| 2.4.2 | Repository xml template | 10 |
| 3 | Equipment | 13 |
| 3.0.1 | Inventory structure | 13 |
| 3.0.2 | Adding New Equipment | 13 |
| 3.0.3 | Adding photos of equipment | 13 |
| 3.0.4 | Deleting Old Equipment | 14 |
| 4 | Misc | 15 |
| 4.1 | Schedules | 15 |
| 5 | Preparing Experiment Documents | 17 |
| 5.1 | Introduction | 17 |
| 5.2 | Preparing the Documents | 17 |
| 5.3 | Compiling Manuals and PDFs | 17 |
| 5.3.1 | Generating Student PDFs | 18 |
| 6 | Safety | 19 |
| 6.1 | Orientation | 19 |
| 7 | Code | 21 |
| 7.1 | Scripts | 21 |
| 7.1.1 | Add New Lab - addNewLab.py | 21 |

Chapter 1

Lab Information Hub

1.1 Introduction

The purposes of the pjl website is to be the central information hub for the educational physics labs. It is a base of knowledge from which the department can work collaboratively on building the future of education physics labs.

1.1.1 High Level Structure

1.2 Making Changes to Website

All changes to the website should be made on the development space on slug (/usr/local/master/pjl-web). The only exception to this rule is that the equipment database equipmentDB.xml can be modified live by using the inventory website in edit mode. Because of this it is important to sync the development and live version of the website before making changes.

1.2.1 Testing changes before updating live version

In the pjl-web folder run the command.

```
python -m SimpleHTTPServer 8000
```

In a browser open up the page localhost:8000. This will show the development version of the website. Confirm that the changes are as expected before updating the live version.

1.2.2 Sync Live Version and Development Space

The script “liveUpdate.py” (Listing 7.1.1) has been designed to sync the live version of the website with the development space for the website. It is important to run this script before and after making changes to the development space. It is run the first time to make sure that the equipment xml file in development has been updated with the changes that made directly on the pjl website. Once the changes to the development space have been made and tested the changes can be pushed to the web-server by running the same command again.

The content displayed by the website is generated from the content of the xml files labDB.xml and equipmentDB.xml **WHEEL XML FILES**

To sync run...

```
sudo ./liveUpdate.py
```

The command can also be run in test mode by executing...

```
sudo ./liveUpdate.py -t
```

Chapter 2

Experiment Documents

2.1 Introduction

“Experiment Documents” are a collection of documents used by students in the educational labs, as well as all supporting documents. **ADD SOME EXAMPLES**

2.1.1 Criteria for adding document

Documents can only be added to the repository if they meet the following criteria.

1. The files include the pdf given to students to be used in their course work.
2. All files need to generate the pdf are included.

2.1.2 Directory structure

At top most level is a folder called “repository” that contains all experiment related documents.

At the second level all the files are organized by lab experiment. Each experiment has a folder that is labeled with a naming scheme where the first four characters are the unique identifier number, followed by the name of the lab. The lab name should be descriptive of the experiment itself. In this folder is also a folder called “Support.Docs” that contains any documents useful for the experiment, but not actually used to generate the student document.

At the third level files are organized into versions. Each folder follows a naming scheme where the the first four characters are the unique lab identifier number, followed by “PHYS” followed by the Course Number followed by a two character semester identifier, followed by the year. Each folder contains all the file used to generate the pdf given to students in the course, semester, and year as identified in the folder label.

Directory structure sample.

```
/repository
├── 0072-Nuclear-Decay
│   ├── 0001-PHYS123FA2017
│   │   ├── lab.tex
│   │   ├── photo.jpg
│   │   └── student.pdf
│   └── Support.Docs
```

2.2 Adding a new lab to the repository

Before beginning ensure that all equipment used in the new experiment are in the lab inventory, and have equipment ID number.

1. Create a folder for the new lab (example “new-lab-folder”), and place all files for generating student pdf, and the student pdf in new-lab-folder
2. Inside new-lab-folder make a directory called “Support_Docs”, and put all documents relevant to lab, but not needed for generation of pdf into it. This might include research papers, sample data, Excel spreadsheets, etc.

```
sudo ./repositoryEdit -n
```

The command can also be run in test mode by executing...

```
sudo ./repositoryEdit -n -t
```

The script will now take you through several steps to gather the information needed to properly add this new lab to the repository. There are several safeties built into the code, but there will be a request to review the input information and confirm that it is correct. Please take time at this point to carefully review metadata entered.

The disciplines, topics, and software entries must align with the master list contained in /data/valid-Diciplines.txt, /data/validTopics.txt, and /data/validSoftware.txt. New items must be added to these master lists before they can be added to a lab.

- Name, **Name as to be Seen on Website** *Use Standard Title Capitalize Convention.*
- Type, **Type** *Must be either Lab or Labatorial.*
- Disciplines, **Discipline1, Discipline2** *Disciplines must comma separated be taken from the approved list* **Need location of this list.**
- Topics, **Topic1, Topic2** *Topics must comma separated be taken from the approved list* **Need location of this list.**
- Semester, **Semester** *Winter, Spring, Summer, or Fall*
- Year, **Year** : *Four digits.*
- Course, **Course Number** *Three digit number corresponding to the course the experiment was used in.*
- Equipment, **equipID-(Amount)-[alternate equipID], equipID-(Amount)** *equipID is four digit code of equipment in inventory, Amount is how many are needed, alternate ID is the four digit code of equipment in inventory that can be used if the primary unit is not available. IDs amounts and alternate IDs separated by “-”, and items in equipment list separated by “,”*
- Software, **Software1, Software2** *Name of all software needed. Must be software from the list of supported software* **Need location of this list**
- PDF, **PDF exact Name** *This needs to be the exact name of the student pdf*

2.3 Adding new version of an existing lab

Note that a version can only be added once, so make sure that everything outlined below is as desired before proceeding to step 4

1. Make a folder that will contain all file relating to the experiment to add. (ex “0078-PHYS325WI2019” is a suggested name for a folder that would be used to add lab 0078, used in physics 325, for the Winter 2019 semester.)

2. Inside the lab folder make a folder called “Support_Docs”. This folder name is not optional because it will be reference in the scripts used for document and website maintenance.
3. In the main folder place. 2.1
 - Main tex file. (ex, Rutherford-Scattering-FULL-WI2019.tex)
 - Student tex file. (ex, Rutherford-Scattering-ST-WI2019.tex)
 - TA guide if it exists. (ex, Rutherford-Scattering-CG-WI2019.tex)
 - PDF of student version of lab. (ex. Rutherford-Scattering-ST-WI2019.pdf)
 - Any file needed to compile the student version of the pdf. (ex, setup-photo.jpg or standard-preamble.tex)
 - Any file that is particular this version of an experiment. (ex template-WI2019.xlsx)
 - Place any general documents into the folder called “Support_Docs”. (ex, Interesting-Paper.pdf)
4. Run the command.

```
sudo ./repositoryEdit --add
```

Example *I/O* from script when adding experiment version.

Enter lab ID number:

0087

Adding version to “Rutherford Scattering”

Enter absolute path for directory containing lab:

/home/pgimby/labs/under-construction/PHYS325WI2019/0078-PHYS325WI2019

Enter the name of the student version pdf:

Rutherford-Scattering-ST-WI2019.pdf

Enter course number:

325

Enter semester:

Winter

Year

2019

Would you like to edit the equipment list for this lab? y/N

n

Would you like to edit the software list for this lab? y/N

n

Would you like to edit the disciplines list for this lab? y/N

n

Would you like to edit the topics list for this lab? y/N

n

Is this information correct? N/y:

y

Note that the lists of equipment, software, disciplines, and topics can be edited here if desired. For more information on the see **NEED REFERENCE**

5. Sync live version. See section 1.2.2

```

/0078-PHYS325WI2019
├─ Rutherford-Scattering-FULL-WI2019.tex
├─ Rutherford-Scattering-ST-WI2019.tex
├─ Rutherford-Scattering-CG-WI2019.tex
├─ Rutherford-Scattering-ST-WI2019.pdf
├─ setup-photo.jpg
├─ standard-preamble.tex
├─ template-WI2019.xlsx
├─ Support_Docs
└─ Interesting-Paper.pdf

```

Figure 2.1: Directory structure and sample contents.

2.4 Editing Experiment Documents

2.4.1 Introduction

All changes should be made to the fill with the word “FULL” in the title. This is one document should contain everything needed to compile the student version and the TA version of an experiment. Different version of a experiment are compiled using the script `pjldoc.py` **REFERENCE TO HOW TO USE THIS SCRIPT**

2.4.2 Repository xml template

```

<Labs>
  <Lab labId="0001">
    <Name />
    <Disciplines>
      <Discipline />
      ...
    </Disciplines>
    <Topics>
      <Topic />
      ...
    </Topics>
    <Versions>
      <Version>
        <Path />
        <Semester />
        <Year />
        <Course />
        <Directory />
      </Version>
      ...
    </Versions>
    <Equipment>
      <Item id="0001">
        <Name />
        <Amount />
      </Item>
      ...
    <Equipment />
    <Type />
    <SupportDocs>
      <Doc>
        <Name />
        <Path />
      </Doc>
      ...
    </SupportDocs>
    <Software>
      <Name />

```

```
    ...  
  </Software>  
</Lab>  
  ...  
</Labs>
```


Chapter 3

Equipment

3.0.1 Inventory structure

Each item in the inventory should have a unique identifier number, and a unique name. An item can be either a stand alone item, or a kit. If the item is a kit it will need to include a list of the items the kit. If only part of the kit are needed for an experiment the repository xml can reference those items by creating a equipment tag in the labDB.xml that has the id number for the kit, but the name for the individual item(s). Each item has a place for any number of manuals, and one picture.

All changes outlined in this section are made to the development side of the website. Once all changes have been made, and are satisfactory, the live version of documents must be update and the web server must be updated.

3.0.2 Adding New Equipment

From the /dev/python-tools folder, the command,

```
./equipmentEdit.py -n
```

A prompt will appear that will ask for information regarding the new item. Enter all the information available. It is ok to leave some fields blank just as long as there is a name. Once all the available information is added a summary will be displayed as well as a request for confirmation. If the user confirms that the information it will go through a validation process to ensure that the name is unique. If everything checks out it will be added to the /dev version of the equipmentDB.xml file.

Note: To add Greek letters enter them as (ex. {Omega} or {mu}).

3.0.3 Adding photos of equipment

When taking photos note that they will require editing before they are added to the database. The final version of photo will be square, so keep this in mind when taking the photographs. Note that all images must be in jpg format.

1. Place images in /usr/local/master/labs/rawphotos
2. Rename all images using the scheme [idnum]img.jpg where idnum is the id number of the piece of equipment photographed.
3. Run the conversion script

```
./convertImg.py
```

4. Enter angle to rotate photos. Photos from some cameras will look like they are properly orientated until they are posted on the website, at which time they will look like they are sideways. It is recommended that when using a new camera that the first image to add is used as a test case to determine if the images need to be rotated by the conversion script.

Edited version will now appear in /usr/local/master/rawimages/output

5. Visually check all photographs in the output folder to confirm that they are still acceptable after they have been converted.
6. Move all photographs ready to be added to the database to /staffresources/equipment/equipping
7. From /dev/python-tools run the script

```
./equipmentEdit.py -i
```

to update the images in the equipmentDB.xml

8. Check local version of website, and once the photos are acceptable remove all photos from /usr/local/-master/rawimages so that they are not added with the next batch of photos.
9. Update live version.

3.0.4 Deleting Old Equipment

To remove a piece of old equipment run, from the python-tools folder, the command,

```
./equipmentEdit.py -d [idnum]
```

If the piece of equipment is currently listed as part of the equipment list for a current lab the script will prompt you to make sure that you know this. Ideally the equipment list in the lab repository should be updated first before removing the equipment. This will help to keep the lab equipment lists and the equipment database in sync.

Chapter 4

Misc

4.1 Schedules

1. Create spreadsheet of schedules for the semester. (ex, schedule-WI2019.xlsx)
2. Create a PDF of the experiment schedule. (ex, schedule-WI2019.pdf)
3. Create a PDF of the lab room schedule. (ex, rooms-WI2019.pdf)
4. Place spreadsheet and PDFs in to folder /pjl-web/data/schedules
5. Copy /pjl-web/data/schedule-WI2019.pdf to /pjl-web/data/schedule-current.pdf
6. Copy /pjl-web/data/rooms-WI2019.pdf to /pjl-web/data/rooms-current.pdf
7. Add the previous schedule (ex, schedule-FA2018.pdf) to schedule archive

```
nano /pjl-web/data/schedules/schedule-index.html
```

Paste the code...

```
<a href="/data/schedules/schedule-FA2018.pdf" target="_blank">
  <div class="schedule-download" >
    <i class="far fa-calendar" style="font-size: 20px;" aria-hidden=true></i>
    <div>
      <p>Experiment Schedule - Fall 2018</p> <!-- description -->
    </div>
  </div>
</a>
```

...directly before the similar code that exist for the two semesters ago.

8. Add the previous schedule (ex, schedule-FA2018.pdf) to schedule archive

```
nano /pjl-web/data/schedules/room-index.html
```

Paste the code...

```
<a href="/data/schedules/rooms-FA2018.pdf" target="_blank">
  <div class="schedule-download" >
    <i class="far fa-calendar" style="font-size: 20px;" aria-hidden=true></i>
    <div>
      <p>Rooms Schedule - Fall 2018</p> <!-- description -->
    </div>
  </div>
</a>
```

...directly before the similar code that exist for the two semesters ago.

Chapter 5

Preparing Experiment Documents

5.1 Introduction

- All tex in one file (lab and companion guide)
- standard preamble file
- pjldoc script for compiling documents
- documents prepared with a root directory of "under-construction"
- document editing timeline

5.2 Preparing the Documents

The following instructions were made specifically for physics 325 in winter 2019. Adjust the names for course and semester.

1. Create folder for course named in the form similar to **PHYS325WI2019**.
2. Inside course folder place a sub folder for each lab named in the form **0078-PHYS325WI2019**.
3. Inside each lab folder there should be...
 - tex file which include student version and companion guide. Name in the form **NAME-FULL-WI2019.tex** **All edits are made to this file**
 - Any documents referenced in the tex file which are needed for compiling
 - Folder called **Support_Docs** that contain any important documents that are not needed to compile pdfs, such as sample data.
 - File called **standard-preamble.tex**
4. Inside main course folder make a text file called **physics325-lab-order**. Inside this folder list the id numbers of each experiment in the order it should appear in the manual. Be careful not to leave a blank line at the end of the file.

5.3 Compiling Manuals and PDFs

All compiling of standard lab documents can be done with the script **pjldoc.py**.

5.3.1 Generating Student PDFs

To compile all of the student PDFs

```
pjldoc.py PHY325WI2019 -s -c -i 0
```

To compile individual PDF of the second lab listed in physics325-lab-order

```
pjldoc.py PHY325WI2019 -s -c -i 2
```

Chapter 6

Safety

6.1 Orientation

- Located in /pjl-web/data/safety/lab-safety-manual/
- Edit latest tex file and call it Orientation-WI2019.tex (adjusted for current semester and year)
- Overwrite file called Orientation.tex with updated version.
- Compile Orientation.tex
- **THERE IS A SYMLINK IN PARENT DIRECTORY. WHICH FILE DOES PJLDOCS LOOK FOR?**

Chapter 7

Code

7.1 Scripts

7.1.1 Add New Lab - addNewLab.py

```
/usr/bin/python3
,
n be called from the command line to make a wide range of changes to the lab repository xml file.
ange include

ding versions of labs from a new semester
ding a brand new lab to repository
,

port pjlDB
port os, argparse, re

unction that preform safety checks

f testHost(host):
    '''
    Test what computer this being run on. As of now it is machinne specific

    Args:
        host (str) name of host script was designed for

    Return:
        none
    '''
    thishost = os.uname()[1]
    if thishost not in host:
        print("This script is designed to be run on" + host + "Only. Exiting...")
        exit()

f checkTimeStamp(dev, data):
    '''
    Checks that the source files for the databases referenced are the latest. This protects against overwritting change

    Args:
        dev (str) location of a file
        data (str) location of a file

    Return:
```

```

        (bool) True if file at data is newer than the one at dev
    '''
    if os.path.getmtime(data) <= os.path.getmtime(dev):
        return True
    else:
        return False

'''
Functions used to add a new version entry to the repository xml
'''

'''
Creates a new empty lab object '''
def getLabObject(labdb):
    '''
    Used to generate a pjl lab object from the labDB.xml database

    Args:
        labdb (pjlDB.labDB) entire lab database object generated by pjlDB

    Return:
        lab (pjlDB._LabItem) individual lab item generated by pjlDB
    '''
    validID = False
    while not validID:
        idnum = input("Enter lab ID number: ")
        if len(idnum) == 4 and idnum.isdigit() == True:
            try:
                lab = labdb.getLab(idnum)
                validID = True
            except pjlDB.IDDoesNotExist: ### not working properly
                print("Message")
        else:
            print("ID format is not valid. Valid IDs are of the form ####. Please try again")
            validID = False

    return lab

'''
Collects information about new version of an existing lab '''
def getVersionInfo(originalItem, validCourses, validSemesters, semesterKeys, eqdb, disciplineSource, topicSource, softwareSource, testMode):
    '''
    Main function that collects information for new version of lab entry

    Args:
        originalItem (pjlDB._LabItem) individual lab item generated by pjlDB
        validCourses (list) list of valid courses
        validSemesters (list) list of valid semesters
        semesterKeys (dict) dictionary that matches semesters with their abbreviations
        eqdb (pjlDB.EquipDB) entire equipment inventory database object generated by pjlDB
        disciplineSource (str) path of file that contains all valid disciplines
        topicSource (str) path of file that contains all valid topics
        testMode (bool) allows script to be run in testing mode. No output written.

    Return:
        new_version (dict) dictionary that contains information needed for pjlDB package and a version of a lab to
    '''
    print("Adding version to \" + originalItem.name + "\".")
    new_version = {}
    #new_version = {'originalDir': '/home/pgimby/labs/under-construction/211SP2018/lab2/', 'pdf': 'Phys 211-221 - Laba
    new_version["idnum"] = originalItem.id_num
    new_version["name"] = originalItem.name
    new_version["type"] = originalItem.lab_type
    print("")
    new_version["originalDir"] = getOriginalDir()
    print("")
    new_version["pdf"] = getOriginalPdf(new_version["originalDir"])
    print("")
    new_version["course"] = validCourse(validCourses)
    print("")

```

```

new_version["semester"] = validSemester(validSemesters)
print("")
new_version["year"] = validYear()
new_version["directory"], new_version["labFolder"] = validExistingDirectory(new_version, originalItem, semesterKeys)
new_version["path"] = validPdfPath(new_version)
new_version["equipment"] = getEquipList(eqdb, originalItem)
print("")
new_version["software"] = getSoftwareList(originalItem, softwareSource)
print("")
new_version['disciplines'] = getDisciplineList(originalItem, disciplineSource)
print("")
new_version['topics'] = getTopicList(originalItem, topicSource)
return new_version

```

```

def getOriginalDir():
    """
    Asks user for location of folder containing new lab, and check that it exists

    Args:
        none

    Return:
        originalDir (str) location of folder containing new lab
    """
    validDir = False
    while not validDir:
        originalDir = input("Enter absolute path for directory containing lab: ")
        if not originalDir.split("/")[-1] == "":
            originalDir = originalDir + "/"
        print(originalDir)
        if os.path.isdir(originalDir):
            validDir = True
        else:
            print("Directory " + originalDir + " does not exist. Please try again.")
    return originalDir

```

```

def getOriginalPdf(dir):
    """
    Asks user for name of lab pdf file, and check that it exists

    Args:
        dir (str) pathname of the folder that the pdf should be in

    Return:
        pdfName (str) location of pdf file for new lab
    """
    validPath = False
    while not validPath:
        pdfName = input("Enter the name of the student version pdf: ")
        if os.path.isfile(dir + pdfName):
            validPath = True
        else:
            print("PDF does not exist. Please try again.")
    return pdfName

```

```

def validCourse(validCourses):
    """
    Asks user to enter the course the lab was used in, and checks it against a list of valid courses

    Args:
        validCourses (list) list of valid courses

    Return:
        course (str) valid course number
    """

```

```

validCourse = False
while not validCourse:
    courseNum = str(input("Enter course number: "))
    for i in validCourses:
        if courseNum == i:
            course = "PHYS_" + courseNum
            validCourse = True
    if not validCourse:
        print("Invalid Course number")
        print("Valid courses are...")
        for i in validCourses:
            print(i)

return course

f validSemester(validSemesters):
    """
    Asks user to enter the semester the lab was used in, and checks it against a list of valid semesters

    Args:
        validSemesters (list) list of valid courses

    Return:
        semesterName (str) valid semester name
    """
    validSemester = False
    while not validSemester:
        semesterName = str(input("Enter semester: ")).capitalize()
        for i in validSemesters:
            if semesterName == i:
                validSemester = True
        if not validSemester:
            print("Invalid semester")
            print("Valid semesters are...")
            for i in validSemesters:
                print(i)

    return semesterName

f validYear():
    """
    Asks user to enter the year the lab was used in, and checks that it is a valid year

    Args:
        none

    Return:
        year (str) valid 4 digit year
    """
    validYear = False
    while not validYear:
        year = input("Enter year: ")
        if len(year) == 4 and year.isdigit() == True:
            validYear = True
        else:
            print("Year is invalid.")

    return year

f validExistingDirectory(new_version, lab, semesterKeys):
    """
    Takes information entered from user, and determines the name of the folder that will
    contain version of lab that will be added. This uses knowledge of other version folder
    that have already been added. Will not work for a new Lab (see function versionFolder)

    Args:
        new_version (dict) information entered by user
        lab (pjlDB.LabItem) individual lab item generated by pjlDB
        semesterKeys (dict) matches abbreviations for semesters with full name

    Return:

```



```

        directory (str) full path name on new version directory
    """
    samplePath = lab.versions[0]["directory"]
    labFolder = "/" .join(samplePath.split("/")[:-1]) + "/"
    semester = semesterKeys[new_version["semester"]]
    courseNum = new_version["course"].split("_")[-1]
    year = new_version["year"]
    directory = labFolder + lab.id_num + "_PHYS" + courseNum + semester + year + "/"
    return directory, labFolder

def validPdfPath(new_version):
    """
    Asks user to input the path to the pdf to display on the webpage for this version

    Args:
        new_version (dict) information entered by user

    Return:
        path (str) final path to pdf
    """
    validPath = False
    while not validPath:
        pdfName = new_version["pdf"]
        if os.path.isfile(new_version["originalDir"] + pdfName):
            validPath = True
            path = new_version["directory"] + pdfName
        else:
            print("PDF_does_not_exist._Please_try_again.")
    return path

def getEquipList(eqdb, originalItem):
    """
    generates a list of equipment

    Args:
        eqdb (pjlDB.EquipDB) entire equipment inventory database object generated by pjlDB
        originalItem (pjlDB.LabItem) individual lab item generated by pjlDB

    Return:
        equipItems (list of dictionaries)
    """
    print("")
    if input("Would_you_like_to_edit_the_equipments_list_for_this_lab?_y/N_").lower() == "y":
        print("")
        print("Current_Equipment_List")
        print("_____")
        for i in originalItem.equipment:
            # i['alt-name'] = "TEST NAME"
            # i['alt-id'] = "0000"
            print(i['id'] + "_" + i['name'] + "_" + i['alt-id'] + "_" + i['alt-name'] + "_" + i['amount'])
        equipItems = []
        equipItems = equipInfoReview(eqdb, originalItem)
        allItems = False
        while not allItems:
            print("")
            if input("Would_you_like_to_add_a_new_piece_of_equipments_for_this_lab?_y/N_").lower() == "y":
                itemId = input("Enter_the_equipments_id_number:_")
                equipItems.append(addEquipItem(eqdb, itemId))
            else:
                allItems = True
        else:
            equipItems = originalItem.equipment
    return equipItems

def equipInfoReview(eqdb, originalItem):
    """
    Controls the review and editing of equipment list. Asks user to input id numbers and

```

quantity of equipment needed for the new lab. User also can input an alternate/secondary equipment item for each primary item

Input id numbers are check for correctness

Args:

eqdb (*pjlDB.EquipDB*) entire equipment inventory database object generated by *pjlDB*
originalItem (*pjlDB.LabItem*) individual lab item generated by *pjlDB*

Return:

equipItems (list of dictionaries)

```
equipItems = []
if originalItem.equipment:
    for i in originalItem.equipment:
        print("ID_Number[" + i['id'] + "]:_Name_[" + i['name'] + "]:_Alternate_Name:_[" + i['alt-name'] +
        if input("Would_you_like_to_edit_this_entry?_y/N:_").lower() == "y":
            equipID = input("Enter_new_id_number_[" + i['id'] + "],_enter_'delete'_to_remove_this_item_")
            if equipID == "":
                equipID = i['id']
            if not equipID == "delete":
                item = addEquipItem(eqdb, equipID)
                print("enter_editing_code_here")
            else:
                print("deleting_" + i['id'] + "_" + i['name'])
        else:
            equipItems.append(i)
return equipItems
```

f addEquipItem(eqdb, itemId):

Adds a new piece of equipment to a lab object

Args:

eqdb (*pjlDB.EquipDB*) entire equipment inventory database object generated by *pjlDB*
itemId (str) equipment id number entered by user

Return:

equipItem (dict) dictionary for single equipment item

```
equipItem = {}
validItem = False
validAlt = False
validNum = False
itemName = ""
altName = ""
amount = ""
```

adds main item

```
while not validItem:
    if itemId == "retry":
        itemId = input("Enter_the_equipement_id_number:_")
        validItem, itemName, itemError = equipValid(eqdb, itemId)
    if not validItem:
        print(itemError)
        if input("Do_you_wish_to_try_again?_Y/n:_").lower() == "n":
            break
        else:
            itemId = "retry"
    else:
        equipItem['id'] = itemId
        equipItem['name'] = itemName
        validItem = True
```

adds alternate item

```
while not validAlt:
    altId = input("Enter_id_number_of_an_alternate_for_this_item._If_none_hit_Enter._")
    if not altId == "":
```

```

        validAlt, altName, altError = equipValid(eqdb, altId)
        if not validAlt:
            print(altError)
            if input("Do you wish to try again? Y/n: ").lower() == "n":
                break
            else:
                altId = ""
                altName = ""
                validAlt = False
        else:
            equipItem['alt-name'] = altName
            equipItem['alt-id'] = altId
            validAlt = True
    else:
        equipItem['alt-name'] = ""
        equipItem['alt-id'] = ""
        validAlt = True

# adds the number of units needed
while not validNum:
    amount = input("Please enter how many " + itemName + "(s) are needed? ")
    if amount.isdigit():
        equipItem['amount'] = amount
        validNum = True
    else:
        print(amount + " is not a valid number.")
        if input("Do you wish to try again? Y/n: ").lower() == "n":
            break
    equipItem["id"] = itemId
return equipItem

f equipValid(eqdb, itemID):
    """
    Checks if equipment item added by user for new lab is valid

    Args:
        eqdb (pjlDB.EquipDB) entire equipment inventory database object generated by pjlDB
        itemID (str) Id number of equipment item to add

    Return:
        validItem (bool)
        name (str) Name of equipment item
        errorMessage (str) Information on why a equipment entry is invalid
    """
    errorMessage = ""
    if len(itemID) == 4 and itemID.isdigit() == True:
        try:
            item = eqdb.getItem(idnum=itemID)
            name = item.name
            errorMessage = ""
            return True, name, errorMessage
        except pjlDB.EQIDDoesNotExist as e:
            errorMessage = ("Invalid Equipment: Item " + itemID + " does not exist.")
            name = "null"
            return False, name, errorMessage
    else:
        errorMessage = ("Invalid Equipment: Id needs to be a 4 digit number")
        name = "null"
        return False, name, errorMessage

f getSoftwareList(originalItem, softwareSource):
    """
    generates a list of software

    Args:
        originalItem (pjlDB.LabItem) individual lab item generated by pjlDB
        softwareSource (string) path to file containing list of available software
    """

```

Return:

softwareItems (list) valid software

, , ,

```
softwareItems = []
```

```
if input("Would you like to edit the software list for this lab? y/N").lower() == "y":
```

```
    print("")
```

```
    print("Current Software")
```

```
    print("_____")
```

```
    for i in originalItem.software:
```

```
        print(i)
```

```
    print("")
```

```
    softwareItems = []
```

```
    softwareItems = softwareRemove(originalItem)
```

```
    allItems = False
```

```
    while not allItems:
```

```
        if input("Would you like to add a new software for this lab? y/N").lower() == "y":
```

```
            print("")
```

```
            masterList = getValidList(softwareSource)
```

```
            print("")
```

```
            print("Valid Software")
```

```
            printList(masterList)
```

```
            softwareItems.append(getNewSoftware(masterList))
```

```
        else:
```

```
            allItems = True
```

```
    softwareItems = list(set(softwareItems))
```

```
else:
```

```
    softwareItems = originalItem.software
```

```
return softwareItems
```

```
def softwareRemove(originalItem):
```

, , ,

Removes unwanted software

Args:

originalItem (pjlDB.LabItem) individual lab item generated by pjlDB

Return:

softwareItems (list) wanted software

, , ,

```
softwareItems = []
```

```
if originalItem.software:
```

```
    for i in originalItem.software:
```

```
        if not input("Would you like to remove \"" + i + "\" as needed software? If so enter 'delete': ").lower() == "delete":
```

```
            softwareItems.append(i)
```

```
return softwareItems
```

```
def getNewSoftware(masterList):
```

, , ,

Get list of software from user and check if they are valid

Args:

masterList (list) complete pool of valid topics

Return:

software (str) single valid software for new lab

, , ,

```
valid = False
```

```
while not valid:
```

```
    item = input("Enter new software: ")
```

```
    for i in masterList:
```

```
        if i.lower() == item.lower():
```

```
            valid = True
```

```
            item = i
```

```
            print("Adding " + i + " to software")
```

```
            print("")
```

```
    if not valid:
```

```
        print(item + " is invalid software.")
```

```
        if not input("Would you like to try again? Y/n").lower() == "n":
```

```

                continue
            else:
                break

    return item

def getValidList(listSource):
    """
    Generates list of valid selections from file

    Args:
        listSource (string) path to file containing valid list entries

    Return:
        validList (list) list of valid selections

    """
    validList = open(listSource).readlines()
    for i in range(0, len(validList)):
        validList[i] = validList[i].replace('\n', '').strip()
    validList = list(filter(None, validList))
    return validList

def getDisciplineList(originalItem, disciplineSource):
    """
    generates a list of disciplines

    Args:
        originalItem (pjlDB._LabItem) individual lab item generated by pjlDB
        disciplineSource (string) path to file containing list of disciplines

    Return:
        disciplineItems (list) valid disciplines

    """
    disciplineItems = []
    if input("Would you like to edit the disciplines list for this lab? y/N").lower() == "y":
        print("")
        print("Current Disciplines")
        print("_____")
        for i in originalItem.disciplines:
            print(i)
        print("")
        disciplineItems = []
        disciplineItems = disciplineRemove(originalItem)
        allItems = False
        while not allItems:
            if input("Would you like to add a new discipline for this lab? y/N").lower() == "y":
                print("")
                masterList = getValidList(disciplineSource)
                print("")
                print("Valid Disciplines")
                printList(masterList)
                disciplineItems.append(getNewDisciplines(masterList))
            else:
                allItems = True
        disciplineItems = list(set(disciplineItems))
    else:
        disciplineItems = originalItem.disciplines
    return disciplineItems

def disciplineRemove(originalItem):
    """
    Removes unwanted disciplines

    Args:
        originalItem (pjlDB._LabItem) individual lab item generated by pjlDB

    Return:
        disciplineItems (list) wanted disciplines
    """

```

```

'''
disciplineItems = []
if originalItem.disciplines:
    for i in originalItem.disciplines:
        if not input("Would you like to remove \" + i + "\" as a discipline? If so enter 'delete': ").lower() == "delete":
            disciplineItems.append(i)
return disciplineItems

def getNewDisciplines(masterList):
'''
    Get list of disciplines from user and check if they are valid

    Args:
        masterList (list) complete pool of valid topics

    Return:
        disciplines (str) single valid discipline for new lab
'''
valid = False
while not valid:
    item = input("Enter new discipline: ")
    for i in masterList:
        if i.lower() == item.lower():
            valid = True
            item = i
            print("Adding \" + i + \" to disciplines")
            print("")
    if not valid:
        print(item + " is an invalid discipline.")
        if not input("Would you like to try again? Y/n ").lower() == "n":
            continue
        else:
            break
return item

def getTopicList(originalItem, topicSource):
'''
    generates a list of topics

    Args:
        originalItem (pjldb.LabItem) individual lab item generated by pjldb
        topicSource (string) path to file containing list of topics

    Return:
        topicItems (list) valid topics
'''
topicItems = []
if input("Would you like to edit the topics list for this lab? y/N ").lower() == "y":
    print("")
    print("Current Topics")
    print("_____")
    for i in originalItem.topics:
        print(i)
    print("")
    topicItems = []
    topicItems = topicRemove(originalItem)
    print("")
    allItems = False
    while not allItems:
        if input("Would you like to add a new topic for this lab? y/N ").lower() == "y":
            print("")
            masterList = getValidList(topicSource)
            print("")
            print("Valid Topics")
            printList(masterList)
            topicItems.append(getNewTopic(topicSource, masterList))
        else:
            allItems = True

```

```

        topicItems = list(set(topicItems))
    else:
        topicItems = originalItem.topics
    return topicItems

f topicRemove(originalItem):
    """
    Removes unwanted topics

    Args:
        originalItem (pjlDB.LabItem) individual lab item generated by pjlDB

    Return:
        topicItems (list) wanted topics
    """
    topicItems = []
    if originalItem.topics:
        for i in originalItem.topics:
            if not input("Would you like to remove \"" + i + "\" as a topic? If so enter 'delete': ").lower() == "delete":
                topicItems.append(i)
    return topicItems

f getNewTopic(topicSource, masterList):
    """
    Get list of topics from user and check if they are valid

    Args:
        topicSource (string) path to file containing list of disciplines
        masterList (list) complete pool of valid topics

    Return:
        topics (str) single valid topic
    """
    valid = False
    while not valid:
        item = input("Enter new topic: ")
        for i in masterList:
            if i.replace(" ", "").lower() == item.replace(" ", "").lower():
                valid = True
                item = i
                print(item)
                print("Adding " + i + " to topics")
                print("")
        if not valid:
            print(item + " is an invalid topic.")
            if not input("Would you like to try again? Y/n ").lower() == "n":
                continue
        else:
            break
    return item

f printList(lst):
    """
    Prints a list of strings line by line for easy readability

    Args:
        lst (list) list of strings to be printed

    Return:
        none
    """
    print("_____")
    for i in lst:
        print(i)
    print("")

f confirmEntry(new_version):
    """

```

print out what information entered by usee, and asks for confirmation

Args:
new_version (dict) dictionary containing all data in for that pjlDB can enter into database

Return:
(bool) True if information has been confirmed by user
,,,

```
print("")

print("Please_confirm_that_the_information_entered_is_correct")
print("lab_id:_ " + new_version["idnum"])
print("name:_ " + new_version["name"])
print("type:_ " + new_version["type"])
print("original_Directory:_ " + new_version["originalDir"])
print("course:_ " + new_version["course"])
print("semester:_ " + new_version["semester"])
print("year:_ " + new_version["year"])
print("directory:_ " + new_version["directory"])
print("path:_ " + new_version["path"])
print("equipment:_ ")
printList(new_version["equipment"])
print("disciplines:_ ")
printList(new_version["disciplines"])
print("topics:_ ")
printList(new_version["topics"])
if not input("Is_this_information_correct?_N/y:_ ").lower() == "y":
    print("exiting...")
    exit()
```

f validDB(info, lab, labdb):

,,,
adds lab object to database and checks that database is valid

Args:
info (dict) information about new lab object
lab (pjlDB._LabItem) individual lab item generated by pjlDB
labdb (pjlDB.LabDB) entire lab database object generated by pjlDB

Return:
(bool) True if labDB object is valid
,,,

```
lab.id_num = info["idnum"]
lab.name = info["name"]
lab.lab_type = info["type"]
lab.equipment = info["equipment"]
lab.software = info["software"]
lab.disciplines = info["disciplines"]
lab.topics = info["topics"]
lab.addVersion(info)
valid = labdb.validateFull()
if valid:
    return valid
else:
    return False
```

unctions for moving directory into repository

f validDir(info, root):

,,,
checks that the verison has not already been added to repository file structure

Args:
info (dict) information about new lab object
root (str) root path of lab repository

Return:


```

        (bool) True is lab has not already been added to repository file structure
    """
    versionDir = root + info["directory"]
    if not os.path.isdir(versionDir):
        return True
    else:
        print("Lab_folder_" + versionDir + "_Already_Exists.")
        print("Exiting...")
        return False

def moveVersionDir(info, root):
    """
    adds source file to lab repository.
    Makes new directory
    rsyncs files except for contents of Support_Docs folder

    Args:
        info (dict) information about new lab object
        root (str) root path of lab repository

    Return:
        none
    """
    versionDir = root + info["directory"]
    if not os.path.isdir(versionDir):
        os.system("mkdir_" + versionDir)
        #os.system("echo rsync -avz --exclude Support_Docs " + info["originalDir"] + " " + versionDir)
        os.system("sudo_rsync_-avz_--exclude_Support_Docs_" + info["originalDir"] + "_" + versionDir)
    else:
        print("Lab_folder_" + versionDir + "_Already_Exists.")
        print("Exiting...")
        exit()

Functions for updating Support_Docs

def addSupportFolder(info, root):
    """
    adds contents of Support_Docs folder to repository

    Args:
        info (dict) information about new lab object

    Return:
        none
    """
    originDir = info["originalDir"] + "Support_Docs"
    destinationDir = root + info["labFolder"] + "Support_Docs"
    if os.path.isdir(originDir):
        if not os.path.isdir(destinationDir):
            print("Support_Docs_folder_does_not_exist_Adding_new_folder_" + destinationDir)
            os.system("mkdir_" + destinationDir)
        if os.path.isdir(destinationDir):
            os.system("rsync_-avz_" + originDir + "/" + destinationDir)
        else:
            print("Something_when_wrong_Exiting...")
            exit()

Functions for adding a new lab

def getNewLabInfo(originalItem, testMode):
    """
    Main function that collects information for new lab entry

    Args:
        originalItem (pjldb.LabItem) individual lab item generated by pjldb
    """

```

validCourses (list) list of valid courses
validSemesters (list) list of valid semesters
semesterKeys (dict) dictionary that matches semesters with their abbreviations
eqdb (pjlDB.EquipDB) entire equipment inventory database object generated by pjlDB
disciplineSource (str) path of file that contains all valid disciplines
topicSource (str) path of file that contains all valid topics
testMode (bool) allows script to be run in testing mode. No output written.

Return:

new_lab (dict) dictionary that contains information needed for pjlDB package to create new lab object
labFolder (str) path of parent folder to create for new lab

,,,

```

new_lab = {}
new_versions = []
new_version = {}
new_lab["idnum"] = originalItem.id_num
print("Adding new_lab with id number:_" + new_lab["idnum"] + "_")
print("_____")
print("")
new_lab["name"] = getName(originalItem)
print("")
new_lab["type"] = getType()
print("")
new_lab["originalDir"] = getOriginalDir()
print("")
new_lab["pdf"] = getOriginalPdf(new_lab["originalDir"])
print("")
new_lab["course"] = validCourse(validCourses)
print("")
new_lab["semester"] = validSemester(validSemesters)
print("")
new_lab["year"] = validYear()
print("")
new_version
new_lab["labFolder"], new_lab["labFolderPath"] = newLabFolder(new_lab)
print("_____")
print(new_lab["labFolderPath"])
print(new_lab["labFolder"])
new_lab["directory"] = versionFolder(new_lab, semesterKeys)
print(new_lab["directory"])
new_lab["path"] = validPdfPath(new_lab)
new_lab["equipment"] = getEquipList(eqdb, originalItem)
print("")
new_lab["software"] = getSoftwareList(originalItem, softwareSource)
print("")
new_lab['disciplines'] = getDisciplineList(originalItem, disciplineSource)
print("")
new_lab['topics'] = getTopicList(originalItem, topicSource)
new_version["path"] = new_lab["path"]
new_version["year"] = new_lab["year"]
new_version["semester"] = new_lab["semester"]
new_version["course"] = new_lab["course"]
new_version["directory"] = new_lab["directory"]
new_versions.append(new_version)
new_lab["versions"] = new_versions
return new_lab

```

f getName(originalItem):

,,,

Asks user to enter name of new lab, and check that the name is not already used

Args:

originalItem (pjlDB._LabItem) individual lab item generated by pjlDB

Return:

labName (str) name of new lab

,,,

labName = originalItem.name

```

    if originalItem.name == "":
        validName = False
        while not validName:
            labName = str(input("Enter name of the new lab. Please use conventional titlecase (ie. This is a Title)"))
            if input("Is this name entered correctly? N/y: ").lower() == "y":
                validName = True
            elif input("Would you like to try again? Y/n: ").lower() == "n":
                print("Exiting.")
                exit()

    return labName

def getType():
    """
    asks user what type of experiment this is. There are only two options lab or labatorial

    Args:
        none

    Return (str) type experiment. lab or labatorial
    """
    validType = False
    while not validType:
        labType = input("Is this a lab or a labatorial? ").lower()
        if labType == "lab" or labType == "labatorial":
            validType = True
        else:
            if input("Would you like to try again? Y/n: ").lower() == "n":
                exit()
    return labType.capitalize()

def newLabFolder(info):
    """
    determine name of folder for a new lab

    Args:
        info (dict) information about new lab object
    """
    name = "-".join(info["name"].split("_"))
    labFolder = "/data/repository/" + info["idnum"] + "-" + name
    labFolderPath = root + labFolder
    return labFolder, labFolderPath

def versionFolder(info, semesterKeys):
    """
    determine name of folder for a new lab. This is different than the function
    (validExistingDirectory) which uses knowledge of existing version folders.

    Args:
        info (dict) information about new lab object
        labFolder (str) path of the new lab parent folder in repository
        semesterKeys (dict) matches full name semesters with abbreviation

    Return:
        directory (str) path of version directory for a new lab
    """
    semester = semesterKeys[info["semester"]]
    courseNum = info["course"].split("_")[-1]
    directory = info["labFolder"] + "/" + info["idnum"] + "-PHYS" + courseNum + semester + info["year"] + "/"
    return directory

def validNewLab(info, lab, labdb):
    """
    adds lab object to database and checks that database is valid

    Args:
        info (dict) information about new lab object
        lab (pjldb.LabItem) individual lab item generated by pjldb
        labdb (pjldb.LabDB) entire lab database object generated by pjldb

```

Return:
 (bool) True if labDB object is valid
 ,,,

```
lab.id_num = info["idnum"]
lab.name = info["name"]
lab.lab_type = info["type"]
lab.equipment = info["equipment"]
lab.software = info["software"]
lab.disciplines = info["disciplines"]
lab.topics = info["topics"]
lab.versions = info["versions"]
labdb.addLab(lab)
valid = labdb.validateFull()
if valid:
    return valid
else:
    return False
```

```
def getEditInfo(originalItem, eqdb, disciplineSource, topicSource, softwareSource, testMode):
```

 ,,,
 Main function that collects information for new version of lab entry

 Args:
 originalItem (pjlDB._LabItem) individual lab item generated by pjlDB
 eqdb (pjlDB.EquipDB) entire equipment inventory database object generated by pjlDB
 disiplineSource (str) path of file that contains all valid disciplines
 topicSource (str) path of file that contains all valid topics
 testMode (bool) allows script to be run in testing mode. No output written.

Return:
 ,,,
 originalItem (pjlDB._LabItem) updated individual lab item

```
print("Editing_info_for_" + originalItem.name + ".")
print("")
originalItem.equipment = getEquipList(eqdb, originalItem)
print("")
originalItem.software = getSoftwareList(originalItem, softwareSource)
print("")
originalItem.disciplines = getDisciplineList(originalItem, disciplineSource)
print("")
originalItem.topics = getTopicList(originalItem, topicSource)
return originalItem
```

```
def displayLabItem(lab):
    print("")
    print("Please_confirm_that_the_information_entered_is_correct.")
    print("_____")
    print("lab_id:_" + lab.id_num)
    print("")
    print("name:_" + lab.name)
    print("")
    print("type:_" + lab.lab_type)
    print("")
    print("equipment:_")
    print("_____")
    printEquipList(lab.equipment)
    print("")
    print("disciplines:_")
    printList(lab.disciplines)
    print("topics:_")
    printList(lab.topics)
    if input("Is_this_information_correct?_N/y:_").lower() == "y":
        return True
    else:
        print("exiting...")
        return
        exit()
```

```

def printEquipList(equipList):
    for i in equipList:
        print(i["id"] + ": " + i["name"] + " (" + i["amount"] + "), " + i["alt-id"] + ": " + i["alt-name"])

```

Main Script

```

version = "1.1"

```

```

'List of valid courses and semesters'''
validCourses = ["211", "223", "227", "255", "259", "323", "325", "341", "365", "369", "375", "397", "497"]
validSemesters = ["Winter", "Spring", "Summer", "Fall"]
semesterKeys = {"Winter": "WI", "Spring": "SP", "Summer": "SU", "Fall": "FA"}

```

'Define user options'''

```

parser = argparse.ArgumentParser(
    formatter_class=argparse.RawDescriptionHelpFormatter,
    epilog='''

```

Now bugs and other important information:

```

    A) Blank Topics or Disciplines was causing issues. I think
    B) Spaces in the names of folders does not work.
    C) Review does not include software.
    D) Cannot add additional docs.

```

```

    )
    parser.add_argument('-a', '--add', help='Add a new version to an existing lab.', action='store_true')
    parser.add_argument('-e', '--edit', help='Edit the details of a lab.', action='store_true')
    parser.add_argument('-n', '--new', help='Add a brand new lab.', action='store_true')
    parser.add_argument('-t', '--test', help='Debug mode.', action='store_true')
    parser.add_argument('-x', '--validate', help='Disable validation for xml.', action='store_true')
    parser.add_argument('-v', '--version', help='Print current version of script.', action='store_true')

```

```

args = parser.parse_args()
testMode = args.test
validate = args.validate

```

'Paths for files'''

```

root = "/usr/local/master/pjl-web"
labDev = root + "/dev/equipmentDB.xml"
labDBDev = root + "/dev/labDB.xml"
labData = root + "/data/equipmentDB.xml"
labDBData = root + "/data/labDB.xml"
disciplineSource = root + "/data/validDisciplines.txt"
topicSource = root + "/data/validTopics.txt"
softwareSource = root + "/data/validSoftware.txt"

```

'Changes the output to a temporary file if script is run in test mode'''

```

testMode:
    destXML = root + "/dev/test_labDB.xml"
    print("_____Running in test mode._____")

```

```

else:
    destXML= labdbDev

```

'validation disabled warning'''

```

validate:
    print("validation of output file has been disabled. Be Very Careful!")

```

'name of host machine this script was written for'''

```

devhost = "slug"
vhost = ["slug", "fry"]

```

'Confirm that this script won't accidentally run on the wrong machine'''

```

testHost(devhost)

```

```

'''Create pjlDB object of each of the relevent xml files'''
lab = pjlDB.EquipDB(eqdbDev)
labdb = pjlDB.LabDB(labdbDev)

'''prints version'''
args.version:
    print("Version_" + version)
    exit()

'''Checks that the development version of both key DBs are new or as new as the live versions.'''
not checkTimeStamp(eqdbDev,eqdbData) or not checkTimeStamp(labdbDev,labdbData):
    if not checkTimeStamp(eqdbDev,eqdbData):
        print("Equipment_development_database_is_out_of_sync_with_the_live_version._Please_update_the_development_")
    if not checkTimeStamp(labdbDev,labdbData):
        print("Repository_development_database_is_out_of_sync_with_the_live_version._Please_update_the_development_")
    print("Exiting...")
    exit()

'''add a new version of an existing lab'''
args.add:
    print("Adding_new_lab_version.")
    lab = getLabObject(labdb)
    versionInfo = getVersionInfo(lab,validCourses,validSemesters,semesterKeys,eqdb,disciplineSource,topicSource,softwareSource)
    confirmEntry(versionInfo)
    if validDB(versionInfo,lab,labdb) and validDir(versionInfo,root):
        labdb.save(destXML, ignore_validation=validate, error_log=True)
        if not testMode:
            moveVersionDir(versionInfo,root)
            addSupportFolder(versionInfo,root)
    else:
        print("something_when_wrong")
        exit()

'''add a new lab'''
args.new:
    print("Adding_new_lab.")
    lab = labdb.newLab(labdb.new_id)
    newLabInfo = getNewLabInfo(lab,testMode)
    lab.name = newLabInfo["name"]
    lab.type = newLabInfo["type"]
    confirmEntry(newLabInfo)
    if validDB(newLabInfo,lab,labdb):
        if not testMode:
            os.system("mkdir_" + newLabInfo["labFolderPath"])
            moveVersionDir(newLabInfo,root)
            addSupportFolder(newLabInfo,root)
            labdb.addLab(lab)
            labdb.save(destXML, ignore_validation=validate, error_log=True)
        else:
            os.system("echo_mkdir_" + newLabInfo["labFolder"])
            labdb.addLab(lab)
            labdb.save(destXML, ignore_validation=validate, error_log=True)

args.edit:
    print("Editing_existing_lab.")
    lab = getLabObject(labdb)
    lab = getEditInfo(lab,eqdb,disciplineSource,topicSource,softwareSource,testMode)
    if displayLabItem(lab):
        labdb.save(destXML, ignore_validation=validate, error_log=True)

'''confirms that the script has ended properly'''
nt("...and_then_there_will_be_cake")

```

```

/usr/bin/python3

```

Script is to be run on web server to update contents of lab repository used in the live version

Written by Peter Gimby, Nov 17 2017

```
import os, subprocess, argparse, filecmp, time
startTime = time.process_time()

'''define folder locations'''
root = "/usr/local/master/"
webSource = root + "pjl-web"
labSource = root + "labs"
webDest = "/mnt/local/pjl-web"
labDest = "/mnt/local/labs"
webMount = "/mnt/pjl-web-mnt"
labMount = "/mnt/lab-mnt"
EquipXML = webSource + "/dev/equipmentDB.xml"
labEquipXML = webSource + "/data/equipmentDB.xml"
webEquipXML = webMount + "/data/equipmentDB.xml"

webFolders = ["downloads", "equipimg", "equipman", "landingpage", "repository", "safety", "schedules", "web-security"]
labFolders = ["css", "data", "dev", "doc", "fonts", "img", "js", "php", "repository", "staffresources"]
webFiles = ["index.html", "README.md"]
labFileReverse = ["equipmentDB.xml"]
mountInfo = [{"source": webSource, "mountPt": webMount}, {"source": labSource, "mountPt": labMount}]

'''define owners of files and general permissions'''
owner = "pgimby"
group = "pjl_admins"
cacheUser = "www-data"
vhost=["slug","fry"]
webserver="watt.pjl.ualgary.ca"

def testHost(host):
    thishost = os.uname()[1]
    if thishost not in host:
        print("This script is designed to be run on " + thishost + " only. Exiting...")
        gracefullExit(mountInfo)

def mountFolder(source, mountPoint, remote, option):
    fullSource = remote + ":" + source
    os.system("mount -t nfs -o " + option + " " + fullSource + " " + mountPoint)
    if not os.system("mount | grep " + fullSource + " > /dev/null") == 0:
        print(fullSource + " did not mount properly. Exiting...")
        gracefullExit(mountInfo)

def umountFolder(mountPoint):
    os.system("umount " + mountPoint)

def syncFolder(testMode, source, dest):
    print("syning " + source)
    os.system("rsync " + testMode + " " + source + " " + dest)

def getDbFiles(dest, key):
    allFiles = os.listdir(dest)
    dbFiles = []
    for f in allFiles:
        if f.startswith(key) and f.split(".")[0][-1] in ['0','1','2','3','4','5','6','7']:
            dbFiles.append(f)
    return sorted(dbFiles)

def incrementFiles(files, dest, key, source, osTest):
    for i, f in enumerate(files):
        name = f.split(".")[0]
        index = int(name[-1])
```

```

        index += 1
        f = name[: -1] + str(index) + ".xml"
        os.system(osTest + "mv_" + dest + "/" + files[i] + "_" + dest + "/" + f)
os.system(osTest + "mv_" + dest + "/" + key + ".xml_" + dest + "/" + key + "-0.xml")
os.system(osTest + "cp_" + source + "/" + key + ".xml_" + dest + "/" + key + ".xml")

if wheel(dest, key, source, osTest):
    print("updating_equipementDB.xml")
    dbFiles = getDbFiles(dest, key)
    incrementFiles(list(reversed(dbFiles)), dest, key, source, osTest)

def wheel(dbFile, source, dest, key, osTest):
    print("updating_equipementDB.xml")
    dbFiles = getDbFiles(dest, key)
    #incrementFiles(list(reversed(dbFiles)), dest, key, source, osTest)

if changePerm(varDir, owner, group, filePerm, options, osTest):
    processStart = time.process_time()

    print("changing_permissions_of_" + varDir + "_with_find" + options + "._This_may_take_a_minute.")
    os.system(osTest + "find_" + varDir + options + "_-exec_chmod_" + filePerm + "_{}_\\;")
    os.system(osTest + "find_" + varDir + options + "_-exec_chown_" + owner + "." + group + "_{}_\\;")
    print("chargePerm_Time:_" + str(time.process_time() - processStart))

if gracefullExit(mountInfo):
    for i in mountInfo:
        umountFolder(i["mountPt"])
    exit()

'checks that file a is newer than file b''
if whichIsNewer(a, b, testMode):
    if os.path.isfile(a) and os.path.isfile(b):
        if os.path.getmtime(a) > os.path.getmtime(b):
            if testMode:
                print(a + "_is_newer_than_" + b)
                print(a + "_" + str(os.path.getmtime(a)))
                print(b + "_" + str(os.path.getmtime(b)))
            return True
        else:
            if testMode:
                print(b + "_is_newer_than_" + a)
                print(a + "_" + str(os.path.getmtime(a)))
                print(b + "_" + str(os.path.getmtime(b)))
            return False
    else:
        if not os.path.isfile(a):
            print("File_" + a + "_Does_not_exist._Exiting...")
            gracefullExit(mountInfo)
        if not os.path.isfile(b):
            print("File_" + b + "_Does_not_exist._Exiting...")
            gracefullExit(mountInfo)
        # if os.path.getmtime(a) > os.path.getmtime(b):
        #     return True
        # else:
        #     return False

'Main Script''

'User input to allow for a test mode during development''
rser = argparse.ArgumentParser()
rser.add_argument('-t', '--test', help='test_adding_to_xml_without_moving_folders', action='store_true')
args = parser.parse_args()
tMode = args.test

not os.getuid() == 0:
    print("This_script_must_be_run_by_\"The_Great_and_Powerful_Sudo\".")
    exit()

```



```

'Parameters and options for operating in test mode''
testMode == True:
    rsyncOption = "┬-avnz┬─no┬l"
    osTest = "echo┬"
else:
    rsyncOption = "┬-az┬─no┬l"
    osTest = ""

'Confirm that this script won't accidentally run on the wrong machine''
tHost(devhost)

'mounts folder for syncing files and confirms success''
untFolder(webDest,webMount,webserver,"rw")
untFolder(labDest,labMount,webserver,"rw")

'update equipmenDB.xml from web server to development space if it is newer''
whichIsNewer(liveEquipXML,devEquipXML,testMode) and whichIsNewer(liveEquipXML,dataEquipXML,testMode):
    print("The┬live┬version┬of┬equipmentDB.xml┬is┬newer┬than┬the┬dev┬version.")
    if input("Do┬you┬wish┬to┬continue?┬y/N┬") == "y":
        key = "equipmentDB"
        dataFolder = webSource + "/data"
        liveSource = webMount + "/data"
        wheel(dataFolder,key,liveSource,osTest)
        #wheel(i,source,dest,key,osTest)
    else:
        print("Exiting...")
        gracefulExit(mountInfo)

'Set permissions and owners of files and folders''
ngePerm(labSource,owner,group,"644","┬-type┬f",osTest)
ngePerm(labSource,owner,group,"755","┬-type┬d",osTest)
ngePerm(webSource,owner,group,"644","┬-type┬f",osTest)
ngePerm(webSource,owner,group,"755","┬-type┬d",osTest)

'Sets the permission for executable''
ngePerm(webSource,owner,group,"750","┬-type┬f┬-name┬\`*.py\`",osTest)

'rsync lab content folders''
for i in labFolders:
    source = labSource + "/" + i + "/"
    dest = labMount + "/" + i + "/"
    syncFolder(rsyncOption,source,dest)

'rsync webpage folders''
for i in webFolders:
    source = webSource + "/" + i + "/"
    dest = webMount + "/" + i + "/"
    syncFolder(rsyncOption,source,dest)

'rsync webpage files''
for i in webFiles:
    source = webSource + "/" + i
    dest = webMount + "/"
    syncFolder(rsyncOption,source,dest)

'changes the permissions of specific files and folders needed for live update of equipment numbers''
ngePerm(webMount + "/data" ,"root","www-data","660","┬-type┬f┬-name┬equipmentDB.xml",osTest)
ngePerm(webMount + "/data" ,"root","www-data","775","┬-type┬d┬-name┬\`data\`",osTest)

'unmounts folders used for syncing files''
ountFolder(webMount)
ountFolder(labMount)

print("Total┬Time:┬" + str(time.process_time() - startTime))

print("...and┬then┬there┬will┬be┬cake")

```