

Educational Laboratory Website Manual

April 24, 2018

Contents

0.1	Introduction	3
0.2	Making Changes to Website	4
0.2.1	Sync Live Version and Development Space	4
0.3	Repository	4
0.3.1	Directory structure	4
0.3.2	Adding a new lab to the repository	5
0.3.3	Repository xml template	6
0.4	Inventory	7
0.4.1	Inventory structure	7
0.4.2	Deleting Old Equipment	7
0.4.3	Adding New Equipment	7
0.4.4	Adding photos of equipment	8
0.5	Schedules	8
0.6	Scripts	8
0.6.1	Add New Lab - addNewLab.py	8

0.1 Introduction

The purposes of the pjl website is to be the central information hub for the educational physics labs. It is a base of knowledge from which the department can work collaboratively on building the future of education physics labs.

0.2 Making Changes to Website

All changes to the website should be made on the development space on slug (/usr/local/master/pjl-web). The only exception to this rule is that the equipment database equipmentDB.xml can be modified live by using the inventory website in edit mode. Because of this it is important to sync the development and live version of the website before making changes.

0.2.1 Sync Live Version and Development Space

The script “liveUpdate.py” (Listing 0.6.1) has been designed to sync the live version of the website with the development space for the website. It is important to run this script before and after making changes to the development space. It is run the first time to make sure that the equipment xml file in development has been updated with the changes that made directly on the pjl website. Once the changes to the development space have been made and tested the changes can be pushed to the web-server by running the same command again.

To sync run...

```
sudo ./liveUpdate.py
```

The command can also be run in test mode by excecuting...

```
sudo ./liveUpdate.py -t
```

0.3 Repository

0.3.1 Directory structure

At top most level is a folder called “repository” that contains all experiment related documents.

At the second level all the files are organized by lab experiment. Each experiment has a folder that is labeled with a naming scheme where the first four characters are the unique identifier number, followed by the name of the lab. The lab name should be descriptive of the experiment itself. In this folder is also a folder called “Support_Docs” that contains any documents useful for the experiment, but not actually used to generate the student document.

At the third level files are organized into versions. Each folder follows a naming scheme where the the first four characters are the unique lab identifier number, followed by “PHYS” followed by the Course Number followed by a two character semester identifier, followed by the year. Each folder contains all the file used to generate the pdf given to students in the course, semester, and year as identified in the folder label.

Directory structure sample.

```

/repository
├── 0072-Nuclear-Decay
│   └── 0001-PHYS123FA2017
│       ├── lab.tex
│       ├── photo.jpg
│       └── student.pdf
└── Support_Docs

```

Documents can only be added to the repository if they meet the following criteria.

1. The files include the pdf given to students to be used in their course work.
2. All files need to generate the pdf are included.

0.3.2 Adding a new lab to the repository

Before beginning ensure that all equipment used in the new experiment are in the lab inventory, and have equipment ID number.

1. Create a folder for the new lab (example “new-lab-folder”), and place all files for generating student pdf, and the student pdf in new-lab-folder
2. Inside new-lab-folder make a directory called “Support_Docs”, and put all documents relevant to lab, but not needed for generation of pdf into it. This might include research papers, sample data, Excel spreadsheets, etc.
3. Inside new-lab-folder create a file called info.csv and add all relevant information to the file.

Listing 1: The file info.csv needs to be in this form. See below for more details xleftmargin

```

Name, Vectors-in-One-and-Two-Dimensions
Type, Labatorial
Disciplines, Newtonian Mechanics, Optics
Topics, Collisions, Momentum
Semester, Fall
Year, 2017
Course, 325
Equipment, 0004-(1)-[0002], 0050-(4)
Software, ImageJ, Canon
PDF, title.pdf

```

Any text that is **Bold** must be configured for each lab. text in *italic* are notes that must be removed. Standard text must be left as is.

- Name, **Name as to be Seen on Website** *Use Standard Title Capitalize Convention.*
- Type, **Type** *Must be either Lab or Labatorial.*
- Disciplines, **Discipline1, Discipline2** *Disciplines must comma separated be taken from the approved list **Need location of this list.***
- Topics, **Topic1, Topic2** *Topics must comma separated be taken from the approved list **Need location of this list.***
- Semester, **Semester** *Winter, Spring, Summer, or Fall*
- Year, **Year** : *Four digits.*
- Course, **Course Number** *Three digit number corresponding to the course the experiment was used in.*
- Equipment, **equipID-(Amount)-[alternate equipID], equipID-(Amount)** *equipID is four digit code of equipment in inventory, Amount is how many are needed, alternate ID is the four digit code of equipment in inventory that can be used if the primary unit is not available. IDs amounts and alternate IDs separated by “-”, and items in equipment list separated by “,”*
- Software, **Software1, Software2** *Name of all software needed. Must be software from the list of supported software **Need location of this list***
- PDF, **PDF exact Name** *This needs to be the exact name of the student pdf*

4. Run “addNewLab.py /path/to/new-lab-folder” from development space.

0.3.3 Repository xml template

```
<Labs>
  <Lab labId="0001">
    <Name />
    <Disciplines>
      <Discipline />
      ...
    </Disciplines>
    <Topics>
      <Topic />
      ...
    </Topics>
    <Versions>
      <Version>
        <Path />
        <Semester />
        <Year />
        <Course />
        <Directory />
      </Version>
      ...
    
```

```

        </Versions>
        <Equipment>
            <Item id="0001">
                <Name />
                <Amount />
            </Item>
            ...
        </Equipment />
        <Type />
        <SupportDocs>
            <Doc>
                <Name />
                <Path />
            </Doc>
            ...
        </SupportDocs>
        <Software>
            <Name />
            ...
        </Software>
    </Lab>
    ...
</Labs>

```

0.4 Inventory

0.4.1 Inventory structure

Each item in the inventory should have a unique identifier number, and a unique name. Each item has a place for any number of manuals, and one picture.

0.4.2 Deleting Old Equipment

To remove a piece of old equipment run, from the python-tools folder, the command,

```
./equipmentEdit.py -d [idnum]
```

If the piece of equipment is currently listed as part of the equipment list for a current lab the script will prompt you to make sure that you know this. Ideally the equipment list in the lab repository should be updated first before removing the equipment. This will help to keep the lab equipment lists and the equipment database in sync.

0.4.3 Adding New Equipment

There two ways to add a piece of equipment.

- You can add each item individually with just a name only, and then used the “edit mode” on the live site to add further information about the item.
- You can generate a csv file that contains all the relevant information, and then import that information into the database.

Adding each piece individually

To add an individual piece of new equipment to the equipment database.

1. From the /dev/python-tools folder, the command,

```
./equipmentEdit.py -a "Name of equipment"
```

Note that the quotation marks around the name is important, if they are missing the new piece of equipment will be call Name.

2. From the /data folder run the command,

```
./liveUpdate
```

which will replace the equipmentDB.xml file to be served, while backing up the previous versions.

1. Compile all rel

Listing 2: The file info.csv needs to be in this form. language

```
name; Unique Name of Kit, is_kit; False, kit ; item1 ; item2 ; item3 (2)
name; Unique Name of Equipment
```

0.4.4 Adding photos of equipment

0.5 Schedules

The name of the current schedules should be

- schedule-current.pdf
- rooms-current.pdf

0.6 Scripts

0.6.1 Add New Lab - addNewLab.py

```
#!/usr/bin/python3

'''Adds version from a csv file and adds them to the repository'''

from pjlDB import *
import csv, argparse, os, sys
import xml.etree.ElementTree as ET

'''Folders and file used.'''
root = "/usr/local/master"
eqdb = EquipDB(root + "/pjl-web/data/equipmentDB.xml")
```



```

labdb = LabDB(root + "/pjl-web/data/labDB.xml")
infoFile = "info.csv"
semesterDict = {"Winter": "WI", "Spring": "SP", "Summer": "SU", "Fall": "FA" }

'''Collects information on the lab to add, and formats it to be used by pjlDB.py'''
class NewLabInfo():

    def __init__(self, labSource, newLabObj):
        self.id_num = newLabObj.id_num
        self.labFolder = self.id_num + "-" + labSource.split("/)[-2]
        self.rawInfo = self._collectInfo(labSource, infoFile)
        self.name = "_".join(self.rawInfo["name"][0].split("-"))
        self.name = "_".join(self.name.split())
        self.lab_type = self.rawInfo["type"][0].capitalize()
        self.equipment = self.equipInfo()
        self.software = self.rawInfo.get("software", "")
        self.semester = self.rawInfo["semester"][0].capitalize()
        self.semester = "_".join(self.semester.split())
        self.year = self.rawInfo["year"][0]
        self.year = "_".join(self.year.split())
        self.course = self.rawInfo["course"][0]
        self.versionDr = self.id_num + "-PHYS" + self.course + semesterDict[self.semester] + self.year
        self.versions = self.makeVersionDict()
        self.topics = self.optionalTag("topics")
        self.disciplines = self.optionalTag("disciplines")

    def optionalTag(self, typ):
        checkForNone = self.rawInfo.get(typ)
        if checkForNone != None:
            if not len(checkForNone) == 0:
                if not checkForNone[0] == '':
                    checkForNone = [i.strip('_') for i in checkForNone]
                    for i in checkForNone:
                        if i == '':
                            checkForNone.remove(i)
                    return checkForNone
                else:
                    return []
            else:
                return []
        else:
            return []

    '''Checks to see if info.csv file exists'''
    def _collectInfo(self, dr, filename):
        self.infoPath = dr + filename
        if os.path.isfile(self.infoPath):
            csvContents = self._convertCSVtoDic()
        else:
            print(i + "_is_missing_the_configuration_file_info.csv")
            print("exiting...")
            exit()
        return csvContents

```

```

'''Turns data in info.csv into dictionary'''
def _convertCSVtoDic(self):
    labInfoDict = {}
    with open(self.infoPath, "r") as o:
        labInfo = csv.reader(o)
        for i in labInfo:
            category = i[0].lower()
            contents = i[1:]
            labInfoDict[category] = contents
    return labInfoDict

'''Makes a dictionary of version to feed into pjlDB.py'''
def makeVersionDict(self):
    versions = []
    version = {}
    version["path"] = "/data/repository/" + self.labFolder + "/" + self.versionDr \
+ "/" + self.rawInfo["pdf"][0]
    version["semester"] = self.semester
    version["course"] = "PHYS_" + self.course
    version["year"] = self.year
    directory = "/data/repository/" + self.labFolder + "/" + self.versionDr
    version["directory"] = directory
    versions.append(version)
    return versions

'''Finds the name of equipment from inventory, and returns list'''
def equipInfo(self):
    equipItems = []
    equipRawInfo = self.rawInfo["equipment"]
    for i in equipRawInfo:
        itemDict = {}
        eqid = i.split("-")[0].strip()
        if eqdb._idExistsAlready(eqid) == True:
            itemDict["id"] = eqid
            itemDict["name"] = eqdb.getItem(eqid).name
            itemDict["amount"] = i.split("(")[1].split(")")[0]
            if "[" in i:
                altid = (i.split("[")[1].split(")")[0])
                itemDict["alt-name"] = eqdb.getItem(altid).name
                itemDict["alt-id"] = altid
            else:
                itemDict["alt-name"] = ""
                itemDict["alt-id"] = ""
        equipItems.append(itemDict)
    return equipItems

def emptyList(tagInfo):
    for i in tagInfo:
        if i == "":
            tagInfo.remove(i)
    if len(tagInfo) == 0:
        return True

```

```

else:
    return False

'''Adds information to new xml entry'''
def addLabToXML(labInfo, newlab, labdb):
    newlab.name = labInfo.name
    newlab.lab_type = labInfo.lab_type
    #if not emptyList(labInfo.disciplines):
    newlab.disciplines = labInfo.disciplines
    #if not emptyList(labInfo.topics):
    newlab.topics = labInfo.topics
    newlab.equipment = labInfo.equipment
    newlab.software = labInfo.software
    newlab.versions = labInfo.versions
    if testing == True:
        print(newlab.name)
        print(newlab.lab_type)
        print(newlab.disciplines)
        print(newlab.topics)
        print(newlab.equipment)
        print(newlab.software)
        print(newlab.versions)

    labdb.addLab(newlab)

'''Collects info on the source and destination directories of new lab'''
def getDrMoveInfo(labInfo, repository):
    drInfo = {}
    drInfo["originDr"] = i
    drInfo["labDr"] = root + "/labs/repository/" + labInfo.labFolder
    drInfo["versionDr"] = drInfo["labDr"] + "/" + labInfo.versionDr#[0]["directory"]
    return drInfo

def makeDr(newDr):
    print("newDr_is_" + newDr)
    if not os.path.isdir(newDr):
        os.system("mkdir_" + newDr)
    else:
        print("Lab_folder_" + newDr + "_Already_Exists.")
        print("If_this_is_a_new_version_of_an_existing_lab_try_running_addVersions.py")
        print("Exiting...")
        exit()

def checkForDr(existingDr):
    if not os.path.isdir(existingDr):
        print("Source_folder_" + existingDr + "_Does_Not_Exists._Exiting...")
        exit()
    else:
        return True

def moveDr(origin, destination):
    if checkForDr(origin) and checkForDr("/".join(destination.split("/")[:-1])):
        os.system("mv_" + origin + "_" + destination)

'''Reads in location of folder for lab to add'''
parser = argparse.ArgumentParser()

```

```

parser.add_argument('source', nargs='+', help='enter_path_of_lab_folder(s)_to_add.\
.....Ex_addNewLab_/path/to/folder1~/path/to/folder2')
parser.add_argument('-t', '--test', help='test_adding_to_xml_without_moving_folders', action='store_true')
args = parser.parse_args()
labDr = args.source
testing = args.test

'''Adds new lab to labDB.xml'''
newDrInfo = []
for i in labDr:
    newLab = labdb.newLab(labdb.new_id)
    labInfo = NewLabInfo(i, newLab)
    addLabToXML(labInfo, newLab, labdb)
    newDrInfo.append(getDrMoveInfo(labInfo, root))
labdb.save(root + "/pjl-web/dev/labDB.xml", ignore_validation=False)
valid = labdb.validateFull()

if testing != True:
    if valid == True:
        for i in range(0, len(labDr)):
            makeDr(newDrInfo[i]["labDr"])
            moveDr(newDrInfo[i]["originDr"], newDrInfo[i]["versionDr"])
            origin = newDrInfo[i]["versionDr"] + "/" + "Support_Docs"
            destination = newDrInfo[i]["labDr"]
            moveDr(origin, destination)
        else:
            print("something_went_wrong._Exiting...")
            exit()

print("...and_then_there_will_be_cake")

#!/usr/bin/python3
#
# Script is to be run on web server to update contents of lab repository used in the live version
#
# Written by Peter Gimby, Nov 17 2017

import os, subprocess, argparse, filecmp, time

'''define folder locations'''
webSource = "/usr/local/master/pjl-web"
labSource = "/usr/local/master/labs"
webDest = "/mnt/local/pjl-web"
labDest = "/mnt/local/labs"
webMount = "/mnt/pjl-web-mnt"
labMount = "/mnt/lab-mnt"
labFolders = ["downloads", "equipimg", "equipman", "landingpage", "repository", "safety", "schedules", "we
webFolders = ["css", "data", "dev", "doc", "fonts", "img", "js", "php", "repository", "staffresources"]
webFiles = ["index.html", "README.md"]
webFileReverse = ["equipmentDB.xml"]
mountInfo = [{"source": webSource, "mountPt": webMount}, {"source": labSource, "mountPt": labMount}]

'''define owners of files and general permissions'''
owner = "pgimby"
group = "pjl-admins"
apacheUser = "www-data"
devhost="slug"

```

```

webserver="watt"

def testHost(host):
    thishost = os.uname()[1]
    if not host == thishost:
        print("This script is designed to be run on " + thishost + " only. Exiting...")
        gracefulExit(mountInfo)

def mountFolder(source, mountPoint, remote, option):
    fullSource = remote + ":" + source
    os.system("mount -t nfs -o " + option + " " + fullSource + " " + mountPoint)
    if not os.system("mount | grep " + fullSource + " > /dev/null") == 0:
        print(fullSource + " did not mount properly. Exiting...")
        gracefulExit(mountInfo)

def umountFolder(mountPoint):
    os.system("umount " + mountPoint)

def syncFolder(testMode, source, dest):
    print("syncing " + source)
    os.system("rsync " + testMode + " " + source + " " + dest)

def getDbFiles(dest, key):
    allFiles = os.listdir(dest)
    dbFiles = []
    for f in allFiles:
        if f.startswith(key) and f.split(".")[0][-1] in ['0', '1', '2', '3', '4', '5', '6', '7']:
            dbFiles.append(f)
    return sorted(dbFiles)

def incrementFiles(files, dest, key, source, osTest):
    for i, f in enumerate(files):
        name = f.split(".")[0]
        index = int(name[-1])
        index += 1
        f = name[:-1] + str(index) + ".xml"
        os.system(osTest + "mv " + dest + "/" + files[i] + " " + dest + "/" + f)
    os.system(osTest + "mv " + dest + key + ".xml " + dest + "/" + key + "-0.xml")
    os.system(osTest + "cp " + source + " " + dest)

def wheel(dbFile, source, dest, key, osTest):
    print("updating equipmentDB.xml")
    dbFiles = getDbFiles(dest, key)
    incrementFiles(list(reversed(dbFiles)), dest, key, source, osTest)

def changePerm(varDir, owner, group, filePerm, options, osTest):
    print("changing permissions of " + varDir + " with find " + options + ". This may take a minute.")
    os.system(osTest + "find " + varDir + options + " -exec chmod " + filePerm + " {} \;")
    os.system(osTest + "find " + varDir + options + " -exec chown " + owner + "." + group + " {} \;")

def gracefulExit(mountInfo):
    for i in mountInfo:
        umountFolder(i["mountPt"])
    exit()

```

```

'''Main Script'''

'''User input to allow for a test mode during development'''
parser = argparse.ArgumentParser()
parser.add_argument('-t', '--test', help='test adding to xml without moving folders', action='store_true')
args = parser.parse_args()
testMode = args.test

if not os.getuid() == 0:
    print("This script must be run by \"The_Great_and_Powerful_Sudo\".")
    exit()

'''Parameters and options for operating in test mode'''
if testMode == True:
    rsyncOption = "-avz --no-l"
    osTest = "echo_"
else:
    rsyncOption = "-az --no-l"
    osTest = ""

'''Confirm that this script won't accidentally run on the wrong machine'''
testHost(devhost)

'''mounts folder for syncing files and confirms success'''
mountFolder(webDest, webMount, webserver, "rw")
mountFolder(labDest, labMount, webserver, "rw")

'''update equipmentDB.xml from web server to development space if it is newer'''
for i in webFileReverse:
    key = "equipmentDB"
    source = webMount + "/data/" + i
    dest = webSource + "/data/"
    if os.path.getctime(source) > os.path.getctime(dest + "equipmentDB.xml"):
        #if not filecmp.cmp(source, dest + i):
            wheel(i, source, dest, key, osTest)

'''Set permissions and owners of files and folders'''
changePerm(labSource, owner, group, "644", "-type_f", osTest)
changePerm(labSource, owner, group, "755", "-type_d", osTest)
changePerm(webSource, owner, group, "644", "-type_f", osTest)
changePerm(webSource, owner, group, "755", "-type_d", osTest)

'''Sets the permission for executable'''
changePerm(webSource, owner, group, "750", "-type_f --name_ \"*.py\"", osTest)

'''rsync lab content folders'''
for i in labFolders:
    source = labSource + "/" + i + "/"
    dest = labMount + "/" + i + "/"
    print(i)
    syncFolder(rsyncOption, source, dest)

'''rsync webpage folders'''
for i in webFolders:
    source = webSource + "/" + i + "/"
    dest = webMount + "/" + i + "/"
    syncFolder(rsyncOption, source, dest)

```

```
'''rsync webpage files'''
for i in webFiles:
    source = webSource + "/" + i
    dest = webMount + "/"
    syncFolder(rsyncOption, source, dest)

'''changes the permissions of specific files and folders needed for live update of equipment numbers'''
changePerm(webMount + "/data" , "root", "www-data", "660", "└type└f└name└equipmentDB.xml", osTest)
changePerm(webMount + "/data" , "root", "www-data", "775", "└type└d└name└'data\'", osTest)

'''unmounts folders used for syncing files'''
umountFolder(webMount)
umountFolder(labMount)

print(" ... and then there will be cake")
```