

Consistency and classification of metrics for binary classifiers

K. Dirland

<***@***>

A. S. Lundervold

<***@***>

P.G.L. Porta Mana 

<pgl@portamana.org>

(or any permutation thereof)

Draft. 4 March 2022; updated 25 March 2022

abstract

✚ [Luca] I find it very difficult to structure the paper: there seems to be issues at several levels in the development and use of binary classifiers (and classifiers in general) within machine-learning. Here are some relevant points:

- There should be a distinction between “inference” (or forecast, prediction, guess) and “decision” (or action, choice). In particular, the possible situations we may be uncertain about and the possible decisions available may be completely different things. A clinician, for example, may be uncertain about “cancer” vs “non-cancer”, while the choices are about “drug treatment 1” vs “drug treatment 2” vs “surgery”.
- Probability theory & decision theory say that in order to make self-consistent decision we need two things: (a) the probabilities for the possible situations, (b) the utilities of the decisions given each possible situation.
- A useful machine-learning algorithm should therefore give us one of two things:
 - either the *probabilities* of the uncertain situations (“cancer” vs “non-cancer” in the example above),
 - or the final decision (“drug treatment 1” vs “drug treatment 2” vs “surgery” in the example above).

Current machine-learning classifiers do not give us either: the output in the example above would be “cancer” vs “non-cancer”, often without probabilities.

- So there are two possible solutions to the problem above:
 - We must build a classifier that outputs probabilities. The 0–1 outputs of current classifiers cannot properly interpreted as probabilities, for various reasons.
 - We must build a classifier that output *decisions*: so not “cancer” vs “non-cancer”, but “drug treatment 1” vs etc..

1 Valuation metrics, amounts of data, inferences, and decisions

Let’s consider the simple example of a binary classifier and several dilemmas that appear in its development, choice, and use.

At the moment of evaluating different classifier algorithms, or different hyperparameter settings for one algorithm, we are avalanched

by a choice of possible evaluation scales: accuracy, area under curve, F_1 -measure, coefficient of contingency¹ also known as Matthews correlation coefficient², precision, recall, sensitivity, specificity, and many others³. Only vague guidelines are usually given to face this choice. A thorough analysis and discussion of several such scales was given by Goodman & Kruskal (1954; 1959; 1963; 1972).

Regarding such scales, we can also ask: are they all well-founded and self-consistent? is it possible that the use of any of them lead to contradictions? The literature abounds with studies showing that some scale X may imply hidden contradictions with the data or the assumptions used for our inference, and is therefore worse than some other scale Y . See for example Baker & Pinsky (2001), Lobo et al. (2008), Hand & Christen (2018), Zhu (2020) for instances of criticisms of area under the curve, F_1 -measure, and Matthews correlation coefficient, as well as Goodman & Kruskal's papers cited above.

If we have many more data for one class than for the other – a common predicament in medical applications – we must face the “class-imbalance problem”

Bibliography

(“de X ” is listed under D, “van X ” under V, and so on, regardless of national conventions.)

- Baker, S. G., Pinsky, P. F. (2001): *A proposed design and analysis for comparing digital and analog mammography special receiver operating characteristic methods for cancer screening*. J. Am. Stat. Assoc. **96**⁴⁵⁴, 421–428. DOI:10.1198/016214501753168136.
- Goodman, L. A., Kruskal, W. H. (1954): *Measures of association for cross classifications*. J. Am. Stat. Assoc. **49**²⁶⁸, 732–764. DOI:10.1080/01621459.1954.10501231. See corrections Goodman, Kruskal (1957; 1958) and also Goodman, Kruskal (1959; 1963; 1972).
- (1957): *Corrigenda: Measures of association for cross classifications*. J. Am. Stat. Assoc. **52**²⁸⁰, 578. DOI:10.1080/01621459.1957.10501415. See Goodman, Kruskal (1954).
- (1958): *Corrigenda: Measures of association for cross classifications*. J. Am. Stat. Assoc. **53**²⁸⁴, 1031. DOI:10.1080/01621459.1958.10501492. See Goodman, Kruskal (1954).
- (1959): *Measures of association for cross classifications. II: Further discussion and references*. J. Am. Stat. Assoc. **54**²⁸⁵, 123–163. DOI:10.1080/01621459.1959.10501503. See also Goodman, Kruskal (1954; 1963; 1972).
- (1963): *Measures of association for cross classifications. III: Approximate sampling theory*. J. Am. Stat. Assoc. **58**³⁰², 310–364. DOI:10.1080/01621459.1963.10500850. See correction Goodman, Kruskal (1970) and also Goodman, Kruskal (1954; 1959; 1972).

¹ Yule 1912 denoted “ r ” there. ² Matthews 1975. ³ Sammut & Webb 2017.

- Goodman, L. A., Kruskal, W. H. (1970): *Corrigenda: Measures of association for cross classifications. III: Approximate sampling theory.* J. Am. Stat. Assoc. **65**³³⁰, 1011. DOI: [10.1080/01621459.1970.10481142](https://doi.org/10.1080/01621459.1970.10481142). See Goodman, Kruskal (1963).
- (1972): *Measures of association for cross classifications, IV: Simplification of asymptotic variances.* J. Am. Stat. Assoc. **67**³³⁸, 415–421. DOI: [10.1080/01621459.1972.10482401](https://doi.org/10.1080/01621459.1972.10482401). See also Goodman, Kruskal (1954; 1959; 1963).
- Hand, D., Christen, P. (2018): *A note on using the F-measure for evaluating record linkage algorithms.* Stat. Comput. **28**³, 539–547. DOI: [10.1007/s11222-017-9746-6](https://doi.org/10.1007/s11222-017-9746-6).
- Lobo, J. M., Jiménez-Valverde, A., Real, R. (2008): *AUC: a misleading measure of the performance of predictive distribution models.* Glob. Ecol. Biogeogr. **17**², 145–151. DOI: [10.1111/j.1466-8238.2007.00358.x](https://doi.org/10.1111/j.1466-8238.2007.00358.x), <https://www2.unil.ch/biomapper/Download/Lobo-GloEcoBioGeo-2007.pdf>.
- Matthews, B. W. (1975): *Comparison of the predicted and observed secondary structure of T4 phage lysozyme.* Biochim. Biophys. Acta **405**², 442–451. DOI: [10.1016/0005-2795\(75\)90109-9](https://doi.org/10.1016/0005-2795(75)90109-9).
- Sammut, C., Webb, G. I., eds. (2017): *Encyclopedia of Machine Learning and Data Mining*, 2nd ed. (Springer, Boston). DOI: [10.1007/978-1-4899-7687-1](https://doi.org/10.1007/978-1-4899-7687-1). First publ. 2011.
- Yule, G. U. (1912): *On the methods of measuring association between two attributes.* J. R. Stat. Soc. **75**⁶, 579–652. DOI: [10.1111/j.2397-2335.1912.tb00463.x](https://doi.org/10.1111/j.2397-2335.1912.tb00463.x).
- Zhu, Q. (2020): *On the performance of Matthews correlation coefficient (MCC) for imbalanced dataset.* Pattern Recognit. Lett. **136**, 71–80. DOI: [10.1016/j.patrec.2020.03.030](https://doi.org/10.1016/j.patrec.2020.03.030).