

# Identifying Alzheimer patients based on the analysis of graphs constructed from resting state fMRI data

Claudia Bachmann<sup>1</sup>, Heidi Jacobs<sup>2,3,4</sup>, Klm Dillen<sup>5</sup>, PierGianLuca Porta Mana<sup>1</sup>, Simone Buttler<sup>1</sup>, Gereon R. Fink<sup>5,6</sup>, Juraj Kukolja<sup>5,6</sup>, Abigail Morrison<sup>1,7,8</sup>

<sup>1</sup> Institute of Neuroscience and Medicine (INM-6)

<sup>2</sup> Faculty of Health, Medicine and Life Science, School for Mental Health and Neuroscience (MHeNS), Alzheimer Centre Limburg, Maastricht University Medical Centre, PO Box 616, 6200 MD Maastricht, The Netherlands

<sup>3</sup> Department of Radiology & Athinoula A. Martinos Center for Biomedical Imaging, Massachusetts General Hospital, Harvard Medical School, Boston, MA 02114, USA

<sup>4</sup> Faculty of Psychology and Neuroscience, Department of Cognitive Neuroscience, Maastricht University, PO BOX 616, 6200 MD Maastricht, The Netherlands

<sup>5</sup> Institute of Neuroscience and Medicine (INM-3)

<sup>6</sup> Department of Neurology, University Hospital of Cologne, Cologne, Germany

<sup>7</sup> Computational Neuroscience, Bernstein Center Freiburg, Freiburg, 79104, Germany.

<sup>8</sup> Institute of Cognitive Neuroscience, Faculty of Psychology, Ruhr-University Bochum, 44801 Bochum, Germany

**Contact:** c.bachmann@fz-juelich.de

**Keywords:** *Alzheimer's disease; graph theory; fMRI; atlas-based analysis.*

Diagnosing Alzheimer's Disease (AD), especially in the early stage, is costly and burdensome for the patients, since it comprises a battery of psychological tests and an extraction of disease specific biomarkers from the cerebrospinal fluid. A cheaper and more convenient procedure would be a diagnosis based on images obtained through fMRI. Based on previous polymodal studies demonstrating disrupted inter- and intra-cortical connectivity in AD [1], we argue that the functional connectivity of the whole cortex might be a good predictor for the cause of the disease. In resting state fMRI, previous attempts to analyze graph properties of whole brain networks contradict each other [2]. In our opinion there are two general critical points in the methodology of these studies that are likely to contribute to the variability of the results. First, we criticize that the activities of the brain areas (graph nodes) that are used to calculate the functional connectivities (weights of the graph edges) are composed of functionally inhomogeneous signals, as individual brains are often mapped onto a standard atlas brain of known functional coherent areas [2,3]. The second problem consists in converting the resulting weighted graphs into simple graphs, by setting weights above an arbitrary threshold  $w_{\min}$  to 1, and those below it to 0 [2]. The drawback here is that there is no validation for an optimal threshold, and information that might be relevant in AD may be lost. In this work we address the first problem by applying an activity-driven, region-growing clustering algorithm derived from image processing [4]. In order to guarantee functionally homogeneous clusters, the threshold for inclusion of a voxel in a region is regulated by a heterogeneity criterion [3]. Applying this algorithm, we end up with undirected weighted graphs with varying numbers of nodes for three sets of data: healthy elderly controls, mild cognitive impairment and Alzheimer's disease. Targeting the second problem, we analyze the dependence of graph theoretic measures (shortest path length, in- and out-degree distribution, clustering coefficient, modularity and minimal spanning tree [5]) on  $w_{\min}$ . Finally, we investigate the distribution of these measures for each data set to determine candidates for a predictive measure.

**Acknowledgements.** We acknowledge partial support by the Helmholtz Alliance through the Initiative and Networking Fund of the Helmholtz Association and the Helmholtz Portfolio theme "Supercomputing and Modeling for the Human Brain".

## References

- [1] Bokde AL, Ewers M, Hampel H.: Assessing neuronal networks: understanding Alzheimer's disease. *Prog Neurobiol.* 2009, 89: 125-33.
- [2] Tijms BM, Wink AM, de Haan W, van der Flier WM, Stam CJ, Scheltens P, Barkhof F. *Neurobiol : Alzheimer's disease: connecting findings from graph theoretical studies of brain networks.* *Aging* 2013, 34: 2023-36.
- [3] Marrelec G, Fransson P.: Assessing the influence of different ROI selection strategies on functional connectivity analyses of fMRI data acquired during steady-state conditions. *PLoS One* 2011, 6(4): e14788.
- [4] Lu Y, Jiang T, Zang Y.: Region growing method for the analysis of functional MRI data. *Neuroimage.* 2003, 20(1): 455-65.
- [5] Wang J, Zuo X, Dai Z, Xia M, Zhao Z, Zhao X, Jia J, Han Y, He Y.: Disrupted functional brain connectome in individuals at risk for Alzheimer's disease. *Biol Psychiatry* 2013, 73(5):472-81