






GitHub, Inc. github.com/protocol/research/issues/9





This repository Search


[Pull requests](#) [Issues](#) [Marketplace](#) [Explore](#)

 protocol / research

 Watch 30

 Star 16

 Fork 3

[Code](#)

[Issues 7](#)


[Pull requests 1](#)

[Insights](#)


Optimize storage and convergence time in causal CmRDTs

[Edit](#) [New issue](#)

#9

 Open

pgte opened this issue 6 days ago · 0 comments



pgte commented 6 days ago • edited by miyazono

Member + 😊 ✎ 🗨

Optimize storage and convergence time in causal CmRDTs

Context

Eventual consistency

Unlike Strongly Consistent systems, Eventually Consistent (EC) systems don't require synchronization between peers in order to modify data. Changes can be done locally or to a small number of replicas and then asynchronously replicated to others, eventually reaching them. These systems are more resistant to network partitions, and thus are suited to being used in decentralized environments where connectivity can be low. The drawback is that, in a given point in time, data is not guaranteed to be synchronized between peers.

Strong Eventual Consistency

Strong Eventual Consistency (SEC) is a stronger type of EC where some properties are guaranteed: when all the replicas have received all the messages independently of their order, they are guaranteed to reach the same state.

Assignees

No one assigned


Labels

open problem statement

Milestone



No milestone

Notifications

 Unsubscribe

You're receiving notifications because you authored the thread.

2 participants



Access Control > Cryptographic ACL

- What does a C.ACL look like?
- What types of C.ACL, when laced with a CRDT, still provides SEC?