

GETTER IN DART

Getter In Dart

Getter is used to get the value of a property. It is mostly used to access a **private property's** value. Getter provide explicit read access to an object properties.

Syntax

```
return_type get property_name {  
    // Getter body  
}
```



Info

Note: Instead of writing { } after the property name, you can also write **=>** (fat arrow) after the property name.

Example 1: Getter In Dart

In this example below, there is a class named **Person**. The class has two properties **firstName** and **lastName**. There is getter **fullName** which is responsible to get full name of person.

```
class Person {  
    // Properties  
    String? firstName;  
    String? lastName;  
  
    // Constructor  
    Person(this.firstName, this.lastName);  
  
    // Getter  
    String get fullName => "$firstName $lastName";  
}  
  
void main() {
```



```
Person p = Person("John", "Doe");
print(p.fullName);
}
```

[➤ Show Output](#)

[Run Online](#)

Example 2: Getter In Dart

In this example below, there is a class named **NoteBook**. The class has two private properties **_name** and **_prize**. There are two getters **name** and **price** to access the value of the properties.

```
class NoteBook {
  // Private properties
  String? _name;
  double? _prize;

  // Constructor
  NoteBook(this._name, this._prize);

  // Getter method to access private property _name
  String get name => this._name!;

  // Getter method to access private property _prize
  double get price => this._prize!;
}

void main() {
  // Create an object of NoteBook class
  NoteBook nb = new NoteBook("Dell", 500);
  // Display the values of the object
  print(nb.name);
  print(nb.price);
}
```

[➤ Show Output](#)

[Run Online](#)

Info

Note: In the above example, a getter **name** and **price** are used to access the value of the properties **_name** and **_prize**.

Example 3: Getter In Dart With Data Validation

In this example below, there is a class named **NoteBook**. The class has two private properties **_name** and **_prize**. There are two getters **name** and **price** to access the value of the properties. If you provide a blank name, then it will return **No Name**.

```
class NoteBook {
  // Private properties
  String _name;
  double _prize;

  // Constructor
  NoteBook(this._name, this._prize);

  // Getter to access private property _name
  String get name {
    if (_name == "") {
      return "No Name";
    }
    return this._name;
  }

  // Getter to access private property _prize
  double get price {
    return this._prize;
  }
}

void main() {
  // Create an object of NoteBook class
  NoteBook nb = new NoteBook("Apple", 1000);
  print("First Notebook name: ${nb.name}");
  print("First Notebook price: ${nb.price}");
  NoteBook nb2 = new NoteBook("", 500);
  print("Second Notebook name: ${nb2.name}");
  print("Second Notebook price: ${nb2.price}");
}
```

[Show Output](#)

[Run Online](#)

Example 4: Getter In Dart

In this example below, there is a class named **Doctor**. The class has three private properties **_name**, **_age** and **_gender**. There are three getters **name**, **age**, and **gender** to access the value of the properties. It has **map** getter to get **Map** of the object.

```
class Doctor {
  // Private properties
  String _name;
  int _age;
  String _gender;

  // Constructor
  Doctor(this._name, this._age, this._gender);

  // Getters
  String get name => _name;
  int get age => _age;
  String get gender => _gender;

  // Map Getter
  Map<String, dynamic> get map {
    return {"name": _name, "age": _age, "gender": _gender};
  }
}

void main() {
  // Create an object of Doctor class
  Doctor d = Doctor("John", 41, "Male");
  print(d.map);
}
```

[Show Output](#)

[Run Online](#)

Why Is Getter Important In Dart?

- To access the value of private property.
- To restrict the access of data members of a class.

Video

Watch our video on getters in Dart.

Conclusion

In this section, you have learned about **Getter** with the help of examples. In the next section, you will learn about **Setter In Dart**.