

SUPER IN DART

Introduction

In this section, you will learn about Super in Dart programming language with the help of examples. Before learning about Super in Dart, you should have a basic understanding of the [constructor](#) and [inheritance](#) in Dart.

What Is Super In Dart?

Super is used to refer to the parent class. It is used to call the parent class's properties and methods.

Example 1: Super In Dart

In this example below, the **show()** method of the **MacBook** class calls the **show()** method of the parent class using the **super** keyword.

```
class Laptop {
  // Method
  void show() {
    print("Laptop show method");
  }
}

class MacBook extends Laptop {
  void show() {
    super.show(); // Calling the show method of the parent class
    print("MacBook show method");
  }
}

void main() {
  // Creating an object of the MacBook class
  MacBook macbook = MacBook();
  macbook.show();
}
```

[➤ Show Output](#)

Example 2: Accessing Super Properties In Dart

In this example below, the **display()** method of the **Tesla** class calls the **noOfSeats** property of the parent class using the **super** keyword.

```
class Car {
  int noOfSeats = 4;
}

class Tesla extends Car {
  int noOfSeats = 6;

  void display() {
    print("No of seats in Tesla: $noOfSeats");
    print("No of seats in Car: ${super.noOfSeats}");
  }
}

void main() {
  var tesla = Tesla();
  tesla.display();
}
```

[Show Output](#)

Example 3: Super With Constructor In Dart

In this example below, the **Manager** class constructor calls the **Employee** class constructor using the **super** keyword.

```
class Employee {
  // Constructor
  Employee(String name, double salary) {
    print("Employee constructor");
    print("Name: $name");
    print("Salary: $salary");
  }
}

class Manager extends Employee {
  // Constructor
  Manager(String name, double salary) : super(name, salary) {

```

```

    print("Manager constructor");
  }
}

void main() {
  Manager manager = Manager("John", 25000.0);
}

```

[> Show Output](#)

Run Online

Example 4: Super With Named Constructor In Dart

In this example below, the **Manager** class named constructor calls the **Employee** class named constructor using the **super** keyword.

```

class Employee {
  // Named constructor
  Employee.manager() {
    print("Employee named constructor");
  }
}

class Manager extends Employee {
  // Named constructor
  Manager.manager() : super.manager() {
    print("Manager named constructor");
  }
}

void main() {
  Manager manager = Manager.manager();
}

```

[> Show Output](#)

Run Online

Example 5: Super With Multilevel Inheritance In Dart

In this example below, the **MacBookPro** class method **display** calls the **display** method of the parent class **MacBook** using the **super** keyword. The **MacBook** class method **display** calls the **display** method of the parent class **Laptop** using the **super** keyword.

```
class Laptop {
  // Method
  void display() {
    print("Laptop display");
  }
}

class MacBook extends Laptop {
  // Method
  void display() {
    print("MacBook display");
    super.display();
  }
}

class MacBookPro extends MacBook {
  // Method
  void display() {
    print("MacBookPro display");
    super.display();
  }
}

void main() {
  var macbookpro = MacBookPro();
  macbookpro.display();
}
```



[Show Output](#)

Run Online

Key Points To Remember

- The **super** keyword is used to access the parent class members.
- The **super** keyword is used to call the method of the parent class.

Video

Watch our video on super in Dart.