

Gradient Descent Optimization for Variational Quantum Algorithms

Prashant Gupta

Indian Institute of Technology Kharagpur, 721302 India

October 29, 2025

1 Introduction

Variational Quantum Algorithms (VQAs) are a promising approach for near-term quantum computing applications, combining parameterized quantum circuits with classical optimization. This project demonstrates gradient-based optimization of a single-qubit variational circuit using the parameter-shift rule, a fundamental technique for computing exact gradients on quantum hardware. The work is implemented in Qiskit with AerSimulator, providing a clear pedagogical example of VQA optimization principles.

2 Problem Statement

The objective is to minimize the expectation value of the Pauli-Z operator for a parameterized quantum state:

$$|\psi(\theta, \phi)\rangle = R_Y(\phi)R_X(\theta)|0\rangle$$

where $R_X(\theta)$ and $R_Y(\phi)$ are single-qubit rotation gates. The cost function is defined as:

$$C(\theta, \phi) = \langle\psi(\theta, \phi)|Z|\psi(\theta, \phi)\rangle = \langle Z\rangle$$

The expectation value is computed from measurement statistics:

$$\langle Z\rangle = P(|0\rangle) - P(|1\rangle)$$

The goal is to find parameters (θ^*, ϕ^*) that minimize $C(\theta, \phi)$.

3 Methods

3.1 Parameter-Shift Rule

To compute gradients analytically on quantum circuits, we employ the parameter-shift rule. For a parameterized gate $G(\theta)$ generating the cost function $C(\theta)$, the derivative is:

$$\frac{\partial C}{\partial \theta} = \frac{1}{2} \left[C\left(\theta + \frac{\pi}{2}\right) - C\left(\theta - \frac{\pi}{2}\right) \right]$$

This rule requires evaluating the cost function at shifted parameter values, avoiding finite-difference approximations and providing exact gradients suitable for quantum hardware.

For our two-parameter system:

$$\frac{\partial C}{\partial \theta} = \frac{1}{2} [\langle Z \rangle_{\theta+\pi/2, \phi} - \langle Z \rangle_{\theta-\pi/2, \phi}] \quad (1)$$

$$\frac{\partial C}{\partial \phi} = \frac{1}{2} [\langle Z \rangle_{\theta, \phi+\pi/2} - \langle Z \rangle_{\theta, \phi-\pi/2}] \quad (2)$$

3.2 Gradient Descent Optimization

The parameter update rule follows standard gradient descent:

$$\theta_{k+1} = \theta_k - \eta \frac{\partial C}{\partial \theta} \bigg|_{\theta_k, \phi_k} \quad (3)$$

$$\phi_{k+1} = \phi_k - \eta \frac{\partial C}{\partial \phi} \bigg|_{\theta_k, \phi_k} \quad (4)$$

where $\eta = 0.3$ is the learning rate.

3.3 Implementation Details

- **Backend:** Qiskit AerSimulator (noiseless)
- **Shots per circuit:** 8192
- **Iterations:** 10
- **Initial parameters:** Random uniform in $[0, 2\pi]$
- **Seed:** 42 (for reproducibility)

4 Results

4.1 Optimization Trajectory

The optimization proceeded as shown in Table 1.

Table 1: Gradient descent optimization trajectory

Iteration	θ (rad)	ϕ (rad)	Cost $\langle Z \rangle$	$\partial_\theta C$	$\partial_\phi C$
0	2.552	6.031	-0.673	-0.664	-0.193
1	2.716	6.094	-0.805	-0.546	-0.209
2	2.839	6.149	-0.903	-0.408	-0.182
3	2.927	6.182	-0.947	-0.294	-0.111
4	2.993	6.209	-0.973	-0.220	-0.091
5	3.039	6.231	-0.985	-0.156	-0.072
6	3.073	6.246	-0.995	-0.113	-0.052
7	3.096	6.254	-0.998	-0.076	-0.026
8	3.110	6.261	-0.999	-0.047	-0.024
9	3.120	6.267	-0.999	-0.033	-0.017

4.2 Final Results

After 10 iterations:

- Final $\theta = 3.120 \text{ rad} \approx \pi \text{ rad}$
- Final $\phi = 6.267 \text{ rad} \approx 2\pi \text{ rad}$
- Final cost: $\langle Z \rangle = -0.9990 \approx -1.0$

5 Analysis and Discussion

5.1 Convergence Behavior

The optimization exhibits smooth, monotonic convergence toward the theoretical minimum of -1 . The cost function decreases from -0.673 to -0.999 over 10 iterations, demonstrating effective gradient-based optimization.

Gradient magnitudes decrease consistently, indicating approach to a critical point. The final gradient components are $\partial_\theta C = -0.033$ and $\partial_\phi C = -0.017$, both close to zero.

5.2 Theoretical Optimum

The Pauli-Z operator has eigenvalues ± 1 corresponding to eigenstates $|0\rangle$ and $|1\rangle$, respectively. The minimum eigenvalue is -1 , achieved by the state $|1\rangle$. The optimized parameters $\theta \approx \pi$ and $\phi \approx 2\pi$ prepare a state very close to $|1\rangle$:

$$R_Y(2\pi)R_X(\pi)|0\rangle = R_X(\pi)|0\rangle = |1\rangle$$

The small deviation from perfect -1.0 is due to finite shot noise in the quantum measurements.

5.3 Parameter-Shift Rule Effectiveness

The parameter-shift rule provides exact gradients without numerical approximation. This is critical for quantum hardware where finite-difference methods would accumulate measurement errors. The smooth convergence validates the effectiveness of this approach.

6 Visualizations

Two plots were generated:

1. **Cost vs. Iteration:** Shows monotonic decrease of $\langle Z \rangle$ toward -1
2. **Parameter Trajectory:** Displays the path in (θ, ϕ) parameter space from initialization to optimum

7 Limitations

- Noiseless simulation does not capture real hardware errors
- Single-qubit system is pedagogical; scaling to multi-qubit requires more sophisticated techniques
- Fixed learning rate may not be optimal for all cost landscapes
- Barren plateau phenomena not explored (relevant for deeper circuits)

8 Conclusion

This project successfully demonstrates gradient-based optimization for variational quantum algorithms using the parameter-shift rule. The implementation achieves near-optimal results, with the final cost function value within 0.1% of the theoretical minimum. The work provides a foundational understanding of VQA optimization principles applicable to more complex quantum computing tasks, including VQE for molecular systems and quantum machine learning.

9 References

- Qiskit Documentation: <https://qiskit.org/documentation/>
- M. Cerezo et al., "Variational quantum algorithms." *Nature Reviews Physics* **3**, 625–644 (2021).
- J. R. McClean et al., "The theory of variational hybrid quantum-classical algorithms." *New Journal of Physics* **18**, 023023 (2016).
- K. Mitarai et al., "Quantum circuit learning." *Physical Review A* **98**, 032309 (2018).
- M. Schuld, V. Bergholm, C. Gogolin, J. Izaac, N. Killoran, "Evaluating analytic gradients on quantum hardware." *Physical Review A* **99**, 032331 (2019).