

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

# Working with data

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

**So you have some DATA -  
now what?**

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

So you have some DATA - now what?

# Learning objectives for today:

## Starting to work with data:

1. What is a data frame
2. Get the data into R
3. Figure out what's in the dataset
  - ▶ Identifying the unit of analysis
  - ▶ Differentiating between the types of variables
4. Manipulate the data frame using the R package dplyr's main functions:
  - ▶ `rename()`
  - ▶ `select()`
  - ▶ `arrange()`
  - ▶ `filter()`
  - ▶ `mutate()`
  - ▶ `group_by()`
  - ▶ `summarize()`

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

# What is a data frame?

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

- ▶ A data frame or data set is one object that contains rows and columns of data.
- ▶ We read data into R from common sources like Excel spreadsheets (.xls or .xlsx), text files (.txt), comma separate value files (.csv), and other formats.
- ▶ The simplest format of data contains one row for each individual in the study.
- ▶ The first column of the data identifies the **individual** (perhaps by a name or an ID **variable**).
- ▶ Subsequent columns are **variables** that have been recorded or measured.

# Lake data from Baldi and Moore (B&M)

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

- ▶ Exercise 1.25 from Edition 4 of B&M
- ▶ Data from a study of mercury concentration across 53 lakes
- ▶ I've placed these data in my working directory
- ▶ Let's find it there

# readr is a library to import data into R

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

- ▶ To access readr's functions we load the library like this:

```
{, warning=FALSE} library(readr)
```

- ▶ Click the green arrow to run the code
- ▶ A green rectangle that temporarily appears next to the code shows you that it has run.

## `read_csv()` to load the lake data in R

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

- ▶ `read_csv()` is a function from the `readr` library used to import csv files.
- ▶ code template: `your_data <- read_csv("pathway_to_data.csv")`
- ▶ The `<-` is called the **assignment operator**. It says to save the imported data into an object called `your_data`.

```
lake_data <- read_csv("mercury-lake.csv")
```



So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

1. Execute the above code using the green arrow
2. Note that the data appears in the Environment pane in the top right.
  - ▶ Notice the number of **observations** and the number of **variables**.
3. Click the tiny table icon to the right of the `lake_data` in the Environment pane to open the **Viewer** tab and inspect the data.

So you have some DATA -  
now what?

**Describing your data: what  
are you working with?**

dplyr functions for data  
manipulation

Describing your data: what are you working with?

# Four R functions to get to know a dataset

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

- ▶ `head(your_data)`: Shows the first six rows of the supplied dataset
- ▶ `dim(your_data)`: Provides the number of rows by the number of columns
- ▶ `names(your_data)`: Lists the variable names of the columns in the dataset
- ▶ `str(your_data)`: Summarizes the above information and more

*# notice that if I put a # in front of a line of code it will not run*  
*#head(lake\_data)*  
*#dim(lake\_data)*  
*#names(lake\_data)*  
*#str(lake\_data)*

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

The unit of analysis is the major entity you are working with:

- ▶ Bacteria
- ▶ Laboratory test results
- ▶ Individual People
- ▶ Groups of people (couples, households)
- ▶ Villages
- ▶ Countries

Which function in R lets us know how many units we have?

# Type of Variable

- ▶ **Categorical** variable: A variable that has grouping levels. Mathematically you can calculate the proportion (%) of individuals in each level of the category.
  - ▶ **Nominal** variables: have no underlying order or rank. E.g., hospital ID, HIV status (yes/no variables), race
  - ▶ **Ordinal** variables: can be ordered or ranked. E.g., socio-economic status, BMI categories
- ▶ **Quantitative** variable: A continuous, numeric variable that you can perform mathematical operations on. Mathematically, we can you take the median or average of these variables
  - ▶ **Discrete** variables: can be counted. E.g., number of brain lesions, number of previous births
  - ▶ **Continuous** variables: can be measured precisely, with a ruler or scale. E.g., annual income, blood alcohol content, gestational age at birth

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

**dplyr functions for data  
manipulation**

## dplyr functions for data manipulation

# Using dplyr functions for data manipulation

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

**dplyr functions for data  
manipulation**

- ▶ `rename()`
- ▶ `select()`
- ▶ `arrange()`
- ▶ `filter()`
- ▶ `mutate()`
- ▶ `group_by()`
- ▶ `summarize()`

## Load the dplyr library to access the functions

```
library(dplyr)
```

```
##  
## Attaching package: 'dplyr'  
  
## The following objects are masked from 'package:timeSeries':  
##  
##      filter, lag  
  
## The following objects are masked from 'package:stats':  
##  
##      filter, lag  
  
## The following objects are masked from 'package:base':  
##  
##      intersect, setdiff, setequal, union
```

- These messages mean that some functions (e.g., `filter()`) share names with functions from other libraries. So, when we use `filter()` we will now use

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation



## Function 1: rename()

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

What do you think rename does?

First print the names of the variables:

```
names(lake_data)
```

```
## [1] "lakes"          "ph"              "chlorophyll"    "mercury"        "number_fish"
```

```
## [6] "age_data"
```

Run the rename() function and assign it to lake\_data\_tidy:

```
lake_data_tidy <- rename(lake_data, name_of_lake = lakes)
```

## Function 1: rename()

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

Then reprint the variable names:

```
names(lake_data_tidy)
```

```
## [1] "name_of_lake" "ph"
```

```
## [6] "age_data"
```

```
"chlorophyll" "mercury"
```

```
"number_fi"
```

## Function 1: rename() multiple variables at once

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

**dplyr functions for data  
manipulation**

You can rename multiple variables at once:

```
lake_data_tidy <- rename(lake_data,  
                          name_of_lake = lakes,  
                          ph_level = ph)
```

## Code template for rename() function

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

**dplyr functions for data  
manipulation**

```
new_dataset <- rename(old_dataset, new_name = old_name)
```

Another way to write the above code is to use the **pipe** operator: %>%

```
new_dataset <- old_dataset %>% rename(new_name = old_name)
```

The pipe will become very useful in a few slides...

## Function 2: select()

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

**dplyr functions for data  
manipulation**

Based on the output below, what do you think `select()` does?

```
smaller_data <- select(lake_data, lakes, ph, chlorophyll)
names(smaller_data)
```

```
## [1] "lakes"          "ph"             "chlorophyll"
```

## Function 2: `select()`

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

**dplyr functions for data  
manipulation**

- ▶ We use `select()` to select a subset of **variables**.
- ▶ This is very handy if we inherit a large dataset with several variables that we do not need.

## Function 2: “negative select()”

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

We can also use “negative select()” to deselect variables. Suppose we wanted to keep all variables except for age\_data:

```
smaller_data_2 <- select(lake_data, - age_data)  
names(smaller_data_2)
```

```
## [1] "lakes"          "ph"              "chlorophyll"     "mercury"         "number_fish"
```

We place a negative sign in front of age\_data to remove it from the dataset.

## Rewrite using the pipe operator

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

**dplyr** functions for data  
manipulation

```
smaller_data <- lake_data %>% select(lakes, ph, chlorophyll)
smaller_data_2 <- lake_data %>% select(- age_data)
```

- ▶ Going forward, we will use the pipe operator to write code using any dplyr functions
- ▶ This is because we can use the pipe to stack many dplyr functions in a row



## Function 3: arrange()

What does arrange do? First type `View(lake_data)` to look at the original data. Then run the code and examine its output below. What is different?:

```
#View(lake_data)
lake_data %>% arrange(ph)
```

```
## # A tibble: 9 x 6
##   lakes          ph chlorophyll mercury number_fish age_data
##   <chr>        <dbl>      <dbl>    <dbl>      <dbl> <chr>
## 1 Brick         4.6         1.8      1.2         12 year old
## 2 Annie         5.1         3.2     1.33         7 recent
## 3 Catalina      5.5        13.2     0.33         5 recent
## 4 Alligator     6.1         0.7     1.23         5 year old
## 5 Blue Cypress  6.9         3.5     0.44        12 recent
## 6 Bryant       7.3        44.1     0.27        14 year old
## 7 Four Mile    7.3         0.4     0.17         8 recent
## 8 Henry        8.2        12.2     1.87         3 year old
## 9 Apopka       9.1        128.     0.04         6 recent
```

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

## Function 3: arrange() in descending order

```
lake_data %>% arrange(- ph)
```

```
## # A tibble: 9 x 6
##   lakes          ph chlorophyll mercury number_fish age_data
##   <chr>        <dbl>      <dbl>    <dbl>      <dbl> <chr>
## 1 Apopka        9.1      128.     0.04         6 recent
## 2 Henry          8.2      12.2     1.87         3 year old
## 3 Bryant         7.3      44.1     0.27        14 year old
## 4 Four Mile      7.3       0.4     0.17         8 recent
## 5 Blue Cypress   6.9       3.5     0.44        12 recent
## 6 Alligator      6.1       0.7     1.23         5 year old
## 7 Catalina       5.5      13.2     0.33         5 recent
## 8 Annie          5.1       3.2     1.33         7 recent
## 9 Brick          4.6       1.8     1.2        12 year old
```

## Function 3: arrange() by two variables

```
lake_data %>% arrange(age_data, ph)
```

```
## # A tibble: 9 x 6
##   lakes          ph chlorophyll mercury number_fish age_data
##   <chr>        <dbl>      <dbl>    <dbl>      <dbl> <chr>
## 1 Annie          5.1         3.2     1.33         7 recent
## 2 Catalina        5.5        13.2     0.33         5 recent
## 3 Blue Cypress   6.9         3.5     0.44        12 recent
## 4 Four Mile      7.3         0.4     0.17         8 recent
## 5 Apopka         9.1       128.     0.04         6 recent
## 6 Brick          4.6         1.8     1.2        12 year old
## 7 Alligator      6.1         0.7     1.23         5 year old
## 8 Bryant         7.3        44.1     0.27        14 year old
## 9 Henry          8.2        12.2     1.87         3 year old
```

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

## Function 4: mutate()

- ▶ `mutate()` is one of the most useful functions!
- ▶ It is used to add new variables to the dataset. Suppose that someone told you that the number of fish sampled was actually in hundreds, such that 5 is actually 500. You can use `mutate` to add a new variable to your dataset that is in the hundreds:

```
lake_data_new_fish <- lake_data %>%  
  mutate(actual_fish_sampled = number_fish * 100)  
  
#lake_data_new_fish
```

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

## Use %>% to append several lines of code together

- ▶ We have saved many of new datasets in our environment!
- ▶ If these datasets were larger, they would take up a lot of space.
- ▶ Rather than saving a new dataset each time, we can make successive changes to one dataset like this:

```
tidy_lake_data <- lake_data %>%  
  rename(name_of_lake = lakes) %>%  
  mutate(actual_fish_sampled = number_fish * 100) %>%  
  select(- age_data, - number_fish)
```

- ▶ When you see “%>%”, say the words “and then...”. For example, “Take lake\_data and then rename lakes to name\_of\_lake, and then mutate...”

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

## Use %>% to “pipe” several lines of code together

```
tidy_lake_data <- lake_data %>%  
  rename(lake_name = lakes) %>%  
  mutate(actual_fish_sampled = number_fish * 100) %>%  
  select(- age_data, - number_fish)
```

```
tidy_lake_data
```

```
## # A tibble: 9 x 5
```

```
##   lake_name      ph chlorophyll mercury actual_fish_sampled  
##   <chr>        <dbl>      <dbl>    <dbl>          <dbl>  
## 1 Alligator    6.1        0.7      1.23           500  
## 2 Annie        5.1        3.2      1.33           700  
## 3 Apopka       9.1       128.      0.04           600  
## 4 Blue Cypress 6.9        3.5      0.44          1200  
## 5 Brick        4.6        1.8      1.2           1200  
## 6 Bryant       7.3       44.1      0.27          1400  
## 7 Catalina     5.5       13.2      0.33           500
```

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

## Function 5: `filter()`

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

**dplyr functions for data  
manipulation**

Filter is another very useful function! What might `filter()` do?

## Function 5: `filter()`ing on numeric variables

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

**dplyr functions for data  
manipulation**

We use `filter` to select which rows we want to keep in the dataset. Suppose you were only interested in lakes with `ph` levels of 7 or higher.



## Function 5: `filter()`ing on numeric variables

We use `filter` to select which rows we want to keep in the dataset. Suppose you were only interested in lakes with `ph` levels of 7 or higher.

```
lake_data_filtered <- lake_data %>% filter(ph > 7)
lake_data_filtered
```

```
## # A tibble: 4 x 6
##   lakes      ph chlorophyll mercury number_fish age_data
##   <chr>    <dbl>      <dbl>    <dbl>      <dbl> <chr>
## 1 Apopka    9.1      128.     0.04         6 recent
## 2 Bryant    7.3      44.1     0.27        14 year old
## 3 Four Mile  7.3       0.4     0.17         8 recent
## 4 Henry     8.2      12.2     1.87         3 year old
```

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

## Function 5: filter()ing on character/string variables

Let's try a few more ways to filter() the data set since subsetting data is so important:

```
lake_data %>% filter(age_data == "recent")
```

```
## # A tibble: 5 x 6
##   lakes          ph chlorophyll mercury number_fish age_data
##   <chr>      <dbl>      <dbl>    <dbl>      <dbl> <chr>
## 1 Annie        5.1         3.2     1.33         7 recent
## 2 Apopka        9.1        128.     0.04         6 recent
## 3 Blue Cypress  6.9         3.5     0.44        12 recent
## 4 Catalina      5.5        13.2     0.33         5 recent
## 5 Four Mile     7.3         0.4     0.17         8 recent
```

► == is read as “is equal to”

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

## Function 5: filter()ing on character/string variables

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

```
lake_data %>% filter(age_data != "recent")
```

```
## # A tibble: 4 x 6
##   lakes      ph chlorophyll mercury number_fish age_data
##   <chr>    <dbl>      <dbl>    <dbl>      <dbl> <chr>
## 1 Alligator 6.1      0.7      1.23        5 5 year old
## 2 Brick     4.6      1.8      1.2        12 12 year old
## 3 Bryant    7.3     44.1     0.27       14 14 year old
## 4 Henry     8.2     12.2     1.87        3 3 year old
```

► != is read as “is not equal to”

## Function 5: filter()ing on character/string variables

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

```
lake_data %>% filter(lakes %in% c("Alligator", "Blue Cypress"))
```

```
## # A tibble: 2 x 6
```

```
##   lakes          ph chlorophyll mercury number_fish age_data
```

```
##   <chr>         <dbl>         <dbl>    <dbl>         <dbl> <chr>
```

```
## 1 Alligator     6.1           0.7      1.23           5 year old
```

```
## 2 Blue Cypress  6.9           3.5      0.44          12 recent
```

- ▶ %in% is the “in” operator. We are selecting rows where the variable lakes belongs to the specified list.
- ▶ The c() combines “Alligator” and “Blue Cypress” into a list

## Function 5: multiple filter()s at once

```
lake_data %>% filter(ph > 6, chlorophyll > 30)
```

```
## # A tibble: 2 x 6
```

```
##   lakes      ph chlorophyll mercury number_fish age_data
##   <chr>   <dbl>         <dbl>   <dbl>         <dbl> <chr>
## 1 Apopka  9.1          128.     0.04             6 recent
## 2 Bryant  7.3           44.1     0.27            14 year old
```

*#this is the same as:*

```
lake_data %>% filter(ph > 6 & chlorophyll > 30)
```

```
## # A tibble: 2 x 6
```

```
##   lakes      ph chlorophyll mercury number_fish age_data
##   <chr>   <dbl>         <dbl>   <dbl>         <dbl> <chr>
## 1 Apopka  9.1          128.     0.04             6 recent
## 2 Bryant  7.3           44.1     0.27            14 year old
```

- A comma or the “and” operator (&) are equivalent. Here they say, filter the dataset and keep only rows with `ph > 6 AND chlorophyll > 30`

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

## Function 5: filter() using “or”

```
lake_data %>% filter(ph > 6 | chlorophyll > 30)
```

```
## # A tibble: 6 x 6
##   lakes          ph chlorophyll mercury number_fish age_data
##   <chr>      <dbl>      <dbl>    <dbl>      <dbl> <chr>
## 1 Alligator    6.1         0.7     1.23         5 year old
## 2 Apopka       9.1        128.     0.04         6 recent
## 3 Blue Cypress 6.9         3.5     0.44        12 recent
## 4 Bryant       7.3        44.1     0.27        14 year old
## 5 Four Mile    7.3         0.4     0.17         8 recent
## 6 Henry        8.2        12.2     1.87         3 year old
```

- ▶ | is the OR operator. At least one of `ph > 6` or `chlorophyll > 30` needs to be true.

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

## Functions 6 and 7: group\_by() and summarize()

Let's execute the following code and see what it does.

```
lake_data %>%  
  group_by(age_data) %>%  
  summarize(mean_ph = mean(ph))
```

```
## # A tibble: 2 x 2  
##   age_data mean_ph  
##   <chr>      <dbl>  
## 1 recent      6.78  
## 2 year old    6.55
```

What happened?

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

## Functions 6 and 7: group\_by() and summarize()

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

Another one:

```
lake_data %>%  
  group_by(age_data) %>%  
  summarize(mean_ph = mean(ph),  
             standard_deviation_ph = sd(ph))
```

```
## # A tibble: 2 x 3  
##   age_data mean_ph standard_deviation_ph  
##   <chr>      <dbl>                <dbl>  
## 1 recent      6.78                1.59  
## 2 year old    6.55                1.56
```



## Recap: What functions did we use?

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

dplyr functions for data  
manipulation

1. `library()` to load `readr` and `dplyr`.
2. `read_csv()` to read csv files from a directory.
3. `head()`, `str()`, `dim()`, and `names()` to look at our imported data.
4. `rename()` to rename variables in a data frame.
5. `select()` to select a subset of variables.
6. `arrange()` to sort a dataset according to one or more variables.
7. `mutate()` to create new variables.
8. `filter()` to select a subset of rows.
9. `group_by()` and `summarize()` to group the data by a categorical variable and calculate a statistic.
10. `mean()` and `sd()` to calculate the mean and standard deviation of variables.

# Recap: What operators did we use?

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

**dplyr** functions for data  
manipulation

1. Assignment arrow: `<-`: This is our most important operator!
2. Greater than: `>` There are also:
  - ▶ Less than: `<`
  - ▶ Greater than or equal to: `>=`, and,
  - ▶ Less than or equal to: `<=`
3. Is equal to: `==`, and `!=` is not equal to
4. `%in%` to select from a list, where the list is created using `c()`, i.e., `lakes %in% c("Alligator", "Annie")`

# Reference material: Additional material

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

**dplyr functions for data  
manipulation**

- ▶ 15 min intro to dplyr
- ▶ Data wrangling cheat sheet

# How to export from datahub and save onto your own computer

So you have some DATA -  
now what?

Describing your data: what  
are you working with?

**dplyr** functions for data  
manipulation

Some of you may want to edit this file in R markdown by adding notes, etc. In that case, you can make your edits on datahub and save your updated file on the cloud. You can additionally save your updated file locally on your computer. Here's how to do that:

1. In the File view window, click the checkbox beside the file you'd like to export
2. click More > Export.

This will download the file to your computer's downloads folder.