



The SPR-6 is LEGAL WIDTH in transport mode and requires NO PERMITS FOR TRANSPORT DAYS, NIGHTS OR WEEKENDS. The SPR-6 has FRONT WHEEL DRIVE AND STEERING, Modular Strike-off Blades and an 18 in. wide CHAIN DRIVE CONVEYOR and when equipped with the optional HYDRAULIC BLADE EXTENSION can spread from 1 to 6 ft. The SPR-6 is a versatile and productive machine for both contractors and municipalities needing a shoulder spreader machine.

SPECIFICATIONS

Engine:

Model QSF2.8 T4F - 66 HP Turbocharged Cummins
Diesel Engine - Final Tier IV/Stage IIIB
Hydraulic drives,
Front Steering /Drive Axle,
Two speed Hydrostatic Transmission,
Hydraulic/Air brakes,
Spring actuated Emergency/Parking Brake,
Travel Speed: 0 - 8 mph (18 km/hr.)
Working Speed: 0 - 150 ft/min.(46 m/min.)

Receiving Hopper: L.H. Folding

2.5 cubic yards (1.92 cu. m).
10 ft. (3.05 m) inside working width.
Material Bib - 3/4" thick (1.905 cm) Full width,
Reinforced Rubber

Conveyor:

High torque hydraulic motor drive
mounted on conveyor drive roller shaft w/sprockets
18 in. (46 cm) wide, Heat and oil resistant
Conveyor Belt bolted to Drive Chains,
Variable Speed Hydraulic Drive to 300 tph

Strike off Blade:

1 to 6 ft. (1.82 m) spread width, 18 in. (0.46 m) high
1 ft. (30 cm) & 2 ft. (60 cm) modular Blade sections
-Optional Hydraulic Section 1 to 2 ft. (30 to 60 cm)
Hydraulic Grade Control - 12 in. (30.5 cm)
above and below Grade
Hydraulic Slope control +/-16%

Push Rollers: Oscillating, Self cleaning and Hydraulically Extendible by 14 in. (36 cm.)

Specifications subject to change without notice. 3/12

Model SPR-6

SELF-PROPELLED ROAD WIDENER

Compact Folding Hopper design for Transport *without overwidth permits*

- 8 ft. 6 in. (2.6 m) TRANSPORT WIDTH
- RIGHT HAND DISCHARGE
- SPREAD WIDTH: 1 to 6 ft. (.3 m - 2 m)
- VARIABLE SPEED HYDRAULIC/CHAIN DRIVE CONVEYOR 300 TPH
- 66 hp Final Tier IV/Stage IIIB DIESEL HYDRAULIC POWER
- LOW COST OF OPERATION - EASY TO TRANSPORT
- FRONT WHEEL DRIVE AND STEERING

OPTIONAL FEATURES:

Hydraulic Strike-off Blade Extension 1 to 2 ft. (30 - 61 cm)
Hydraulically Extending Truck Push Rollers
Light package - Head and Tail Lights, Warning Beacon
Washdown System - Electric Pump, 20 ft. (6 m) Hose/reel & Hand Nozzle
Trench Fill Strike off Box - Levels Material down to 34 in. (86 cm) below grade



SPR-6 loads easily for transport



SPR-6 handles large loads with ease



SPR-6 can place base or top course, above or below grade

Dimensions

Length: 15 ft. 8 in. (4.8 m.)
Width: Travel - 8 ft. 6 in. (2.6 m)
Working - 10 ft. (3.05 m)
Height: 8 ft. (2.44 m.)
Turning Radius 17 ft. (5.18 m.)
Wheelbase: 8 ft. (2.44 m)


Weight: 12,000 lbs. (5488 kg.)
Track width: 5 ft. (1.52m)
(4) 255/70R 22.5 Pneumatic Tires



Key start and all machine controls on console



Scan to see all Midland Models



CONTACT YOUR AUTHORIZED MIDLAND DEALER

WWW.ROADWIDENER.COM

MIDLAND MACHINERY CO., INC. 716-692-1200
101 CRANBROOK EXT. TONAWANDA, NY 14150
SALES@MIDLANDMACHINERY.COM