

1200 & 1800

HYDRAULIC TRUCK CONVEYORS



INFORMATION ON HTC
ROAD SANDER
SAND BAGGER
LEVELER and
ROAD PATCHER
INCLUDED





MODEL 1200/1800

HYDRAULIC TRUCK CONVEYOR

IT'S A HYDRAULIC CONVEYOR

- **A TRENCH FILLER**
- **A SHOULDERING UNIT**
- **A ROAD SANDER**
- **A SANDBAG FILLER**
- **AN ASPHALT PATCHER**

IT'S A VERSATILE PERFORMER

IT'S HTC



Model 1200

Width	103"
Length	37"
Height	21"
Belt Width	12"
Gate Opening	10" x 10"
Weight	1,000 lbs.
Capacity	approx. 120 T.P.H.

(Dimensions are approximate)



Model 1800

Width	103"
Length	43"
Height	27"
Belt Width	18"
Gate Opening	16" x 16"
Weight	1,160 lbs.
Capacity	approx. 200 T.P.H.

(Dimensions are approximate)

Will fit all standard dump bodies with a maximum width of 96" (outside measurement).

Self-leveling at all positions of the dump box. Handles any material that will pass through the gate. Right or left hand discharge. Whichever model fits your needs, you will find Hydraulic Truck Conveyor has all the quality features you need to deliver the performance you demand.

Conveyor motor requires 2,000 PSI and 10 to 15 GPM.

OPTIONAL ATTACHMENTS

Improve your bottom line and give yourself the competitive edge that is so necessary in today's economy with the Hydraulic Truck Conveyor.

The economical Hydraulic Truck Conveyor mounts quickly and easily on all standard dump boxes to efficiently deliver material like sand, gravel or hot asphalt where you want them, when you want them, without the expensive hand labor.

Operating the HTC is a simple one person job that can be handled from the truck cab.

HTC discharges from either side, making asphalt patching, highway shouldering and ditch filling fast and easy.

OPTIONS

Gate Opener

Fast opening gate for right or left hand discharge. Both gates adjust in 1" increments or can be equipped with optional hydraulic motors.



Rear Reversing Valve

Mounted on the rear of the conveyor, the Rear Reversing Valve allows both belt speed and direction control at the conveyor.



Power Unit

The HTC can be operated without connecting to an existing hydraulic system. The power unit mounts to the rear edge of the conveyor.



Deflector Plate

The quick attaching Deflector Plate can be mounted on either side of the conveyor. It spreads the material as it is conveyed for that finished look. Shown below on right.



4-FOOT EXTENSION

Optional 4-foot extension mounts to Hydraulic Truck Conveyor to give you the extra reach you sometimes need for ditch filling or delivering materials to hard to reach locations. Right hand photo shows the Deflector Plate in use.



ROAD SANDER ATTACHMENT

ADDS YEAR-ROUND VERSATILITY

Now you can convert your Hydraulic Truck Conveyor for year-round use with the addition of the Sander Attachment. Detachable door allows you to sand one or two lanes of highway.

- Better utilization of your truck and conveyor investment.
- Eliminates the need for expensive single-use sand and salt hopper trucks.
- No more costly hand labor for spreading sand and salt.
- Saves changeover downtime on multi-use equipment.



MODEL 1218LA LEVELING ASSEMBLY

Now you can put the finishing touch on your road shouldering operation. The latest attachment for the Models 1200/1800 Hydraulic Truck Conveyors is the Model 1218LA Leveling Assembly. The two foot wide leveling capabilities of this attachment allow you to apply and level the material in one easy step.



Go from retracted to extended in 20 seconds and YES they can be retrofitted to any HTC Conveyor already in use!



The assembly comes in either manual or hydraulic operating systems. The hydraulic unit (not shown) comes with it's own electrically controlled hydraulic manifold. This unit also features an automatic shut-off to maintain an even flow of materials. This allows for control and consistency in your coverage.



This unit moves between sealed cam bearing, with the heavy duty construction you've come to expect from an HTC product.



03"
43"
27"
18"
16"
lbs.
.PH

HOLD THAT WATER BACK!!

WITH



SAND BAGGER PLUS



- ☐ NO MORE HAND SHOVELING
- ☐ FILLS SANDBAGS IN 2 SECONDS
- ☐ FILLS SANDBAGS WHERE & WHEN YOU NEED THEM
- ☐ FULLY PORTABLE - FOR FASTER EMERGENCY RESPONSE
- ☐ AMERICA'S FASTEST, MOST VERSATILE SANDBAG FILLER

FOR USE IN :

- EMERGENCY FLOOD CONTROL
- EROSION CONTROL
- CONTAINMENT BERMS
- SAFETY BARRICADES

With the new Sandbag Attachment installed on the Hydraulic Truck Conveyor, a standard sandbag can be filled in 2 seconds. That kind of performance can actually improve community emergency response effectiveness. And, because the HTC with Sandbag Attachment is fully portable, sandbags can be filled right where you need them, when you need them. No more back-breaking lugging filled sandbags from sandpiles to where they are needed.

One person can easily detach the SandBagger unit and use the Hydraulic Conveyor for:

- Trench Filling
- Shouldering
- Asphalt Patching





PATCHER 48

For Quick, Quality Patching of

- HIGHWAYS • STREETS
- PARKING LOTS • ROADS



**HTC PATCHER 48 turns your truck into
a self-contained Production Patching System**

- Mounts to existing equipment, increasing vehicle versatility.
- Lower capital investment than larger self-contained rollers.
- Raise and lower limits allow for safe travel clearance and below-grade compaction.
- Integral roller wash system eliminates material buildup.

FAST - EASY INSTALLATION

The PATCHER 48 mounts directly to any truck, utilizing either existing plow hitch points and hydraulic control connections, or the factory mounting bracket and hydraulic controls.



H.T.C. Inc.
P.O. Box 131th Street • Milford, OH 45130
Phone: (732) 338-4403

Call Toll Free:
1-800-348-4403
www.htcconveyors.com

For more information please write or call:

METROQUIP
Environmental Equipment Solutions

IDAHO • OREGON • NEVADA
(208) 344-3318