


The 180° Directional Display™ Panel from National Signal is utilized for roof mounted applications to provide advance warning and directional information.

The unique 180° design allows the Directional Display to rotate and face in either direction.



- Sequential chevron right or left mode
- Sequential stem arrow right or left mode
- Single head arrow right or left mode
- Single flashing arrow right or left mode
- Double flashing arrow mode
- Caution rectangular mode
- Caution bar mode
- Alternating diamond caution mode





- Powered by 12VDC
- Meets the MUTCD
- Remote operator control
- Manual and automatic dimming
- Touch sensitive control keys
- LED mode display
- Rugged construction
- Automotive style fuse w/ spares
- Built-in battery indicator w/ auto shut down protecs vehicle battery from discharge
- Slimline control saves valuable dash space
- Rotates to face either direction to reduce repositioning vehicle

# **Control System**

- Sealed, touch sensitive membrane switches
- Power ON/OFF with LED indicator
- Manual/Automatic dimming
- Automotive style fuses (20A) with extra replacements
- LED display on control indicates mode
- · LED battery condition indicator
- Built-in low voltage shut-off protects from excessive battery discharge
- Test mode illuminates all lamps allowing user to spot burned out lamps
- Remote keypad: 3" x 7" x 1"
- Main control: Under seat or remote location

### **Automatic/Manual Dimming**

- Full lamp voltage above approximately 100 foot candles. Below 20 foot candles, lamp voltage set by photo cell located under the panel to protect from vehicle head lights, street lights, etc. Lamp intensity is set by ambient light conditions.
- Four manual brightness settings

#### **Cables**

- Standard power cable is 9'. Standard control cable is 15'. Other cable lengths are optional.
- Multi-conductor with abrasion resistant jacket

#### **Power Lift**

•12VDC high torque electric motor with automatic clutch

# **Display Panel**

- The front and back panels are made from aluminum. Perimeter frame and internal vertical members manufactured from extruded aluminum channel.
- Lamps are 4 in. amber, PAR 36 LED high brightness/low power with three indicator lamps located on the rear.
- Lamp hoods (retainers) are formed of high impact plastic with four indexing mounting holes.
- Panels are etched, painted, and baked using non glare black powder paint. A photo resistor is built into the bottom of the panel to measure the ambient light.

### **Mounting Frame**

- · Mig welded rectangular steel tubing
- Powder coat finish in black and other optional colors
- Electric tilt allows user to reposition the arrow panel from within the vehicle

Panel Size	Number of lamps
30 x 60	13, 15 <sup>1</sup> , 25
36 x 72	15, 25

<sup>1</sup>Optional

Specifications subject to change any time without notice. Copyright 2016 National Signal, Inc. All rights reserved. Printed in the United States.

