

# Modular Responsive Web Design using Element Queries

Lucas Wiener  
EVRY  
Stockholm, Sweden  
lucas.wiener@evry.com

Tomas Ekholm  
KTH Royal Institute of  
Technology  
Stockholm, Sweden  
tomase@kth.se

Philipp Haller  
KTH Royal Institute of  
Technology  
Stockholm, Sweden  
phaller@kth.se

## ABSTRACT

Responsive Web Design (RWD) enables web applications to adapt to the characteristics of different devices such as screen size which is important for mobile browsing. Today, the only W3C standard to support this adaptability is CSS media queries. However, using media queries it is impossible to create applications in a modular way, because responsive elements then always depend on the global context. Hence, responsive elements can only be reused if the global context is exactly the same, severely limiting their reusability. This makes it extremely challenging to develop large responsive applications, because the lack of true modularity makes certain requirement changes either impossible or expensive to realize.

In this paper we extend RWD to also include responsive modules, i.e., modules that adapt their design based on their local context independently of the global context. We present the ELQ project which implements our approach. ELQ is a novel implementation of so-called *element queries* which generalize media queries. Importantly, our design conforms to existing web specifications, enabling adoption on a large scale. ELQ is designed to be heavily extensible using plugins. Experimental results show speed-ups of the core algorithms of up to 37x compared to previous approaches.

## Categories and Subject Descriptors

H.4 [Information Systems Applications]: Miscellaneous;  
D.2.8 [Software Engineering]: Metrics—*complexity measures, performance measures*

## General Terms

Theory

## Keywords

Responsive web design, Element queries, CSS, Modularity, Web

## 1. INTRODUCTION

Responsive Web Design (RWD) is an approach to make an application respond to the viewport size and device characteristics. This is currently achieved by using CSS media queries that are designed to conditionally design content by the media, such as using serif fonts when printed and sans-serif when viewed on a screen [26].

In order to reduce complexity and enable reusability applications are typically composed of modules, i.e., interchangeable and independent parts that have a single and well-defined responsibility [18]. In order for a module to be reusable it must not assume in which context it is being used.

In this paper we focus on the presentation layer of web applications. As it stands, using media queries to make the presentation layer responsive precludes modularity. The problem is that there is no way to make a module responsive without it being context-aware, due to media queries only being able to target the viewport. Thus, a responsive module using media queries is layout dependent and has therefore limited reusability. Therefore, media queries can only be used for RWD of non-modular static applications. In a world where no better solution than media queries exists for RWD, changing the layout of a responsive application becomes a cumbersome task.

### 1.1 The Problem Exemplified

Imagine a single page application that displays the current weather of various cities as widgets, by using a weather widget module. The module should be responsive so that more information, such as a temperature graph over time, is displayed when the widget is big. When the widget is small it should only display the current temperature. Users should also be able to add, remove and resize widgets.

Such application cannot be built with media queries, since the widgets can have varying sizes independent of the viewport (e.g., the width of one widget is 30% while another is 40%). To overcome this problem we must change the application so that widgets always have the same sizes. This implies that the size of the module and the media query breakpoints are coupled/intertwined, i.e. they are proportional to each other. The problem now is that we have removed the reusability of the weather module, since it requires the specific width that is correctly proportional to the media query breakpoints.

Imagine a company working on a big application that uses media queries for responsiveness (i.e., each responsive module assumes to have a specific percentage of the viewport size). The ability to change is desired by both developers and stakeholders, but is limited by this responsive approach. The requirement of changing a menu from being a horizontal top menu to being a vertical side menu implies that all responsive modules break since the assumed proportionality of each module is changed. Even worse, if the menu is also supposed to hide on user input the responsiveness of the module breaks since the layout changes dynamically. The latter requirement is impossible to satisfy without element queries.

Additionally, it is popular to define breakpoints relative to the font size. Media queries can only target the font size of the document root, limiting the functionality drastically. With element queries, breakpoints may be defined relative to the font size of the targeted element.

As we can see, even with limited requirements there still are significant flaws with using media queries for responsive modules.

## 1.2 Requirements

The desired behavior of a responsive module is having its inner design responding to the size of *its container* instead of the viewport. Only then is a responsive module independent of its layout context. Realizing responsive modules requires CSS rules that are conditional upon *elements*, instead of the global viewport. We have identified the following requirements of a solution:

- It must provide a possibility for an element to automatically respond to changes of its parent's properties so that the correct design can be presented.
- It must conform to the syntax of HTML, CSS, and JavaScript so that the compatibility of tools, libraries and existing projects is retained.
- It must have adequate performance for large applications that make heavy use of responsive modules.
- It must enable developers to write encapsulated style rules so that responsive modules may be arbitrarily composed without any conflicting style rules.

## 1.3 Approach

In this paper we extend the concept of RWD to also include responsive modules. The W3C has discussed such a feature under the name of *element queries* given its analogy to media queries [28]. This paper presents a novel implementation of element queries in JavaScript named ELQ that enables new possibilities of GUI design of web applications.

Our approach is implemented as a client side library to be included in applications. One could argue that a solution does not need to be executed on the client side, but instead generate media queries on the server side for all modules with respect to the current application layout. However, this is insufficient due to the modules then being limited to applications with static layouts. Also, the generated media

queries would not be able to respond to the user changing properties of elements such as layout and font size.

## 1.4 Contributions

This paper makes the following contributions:

- A new design that enables responsive modules while conforming to the syntax of HTML, CSS, and JavaScript.
- Our approach is the first to enable nested elements that are responsive in a modular way, i.e., styling required for RWD is fully encapsulated in the module. As a side effect, responsive modules may also be arbitrarily styled with CSS independently of their context.
- An extensible library architecture that enables plugins to significantly extend the behavior of the library. This makes it possible to create plugins in order to enable new features and to ease integration of ELQ into existing modules or libraries.
- A new implementation that offers substantially higher performance than previous approaches. The implementation batch processes DOM operations so that layout thrashing (i.e., forcing the layout engine to perform multiple independent layouts) is avoided.

The rest of the paper is organized as follows: Section 2 introduces ELQ and its API from a user's perspective. In Section 3 we introduce ELQ's plugin architecture. Section 4 provides an overview of the main components of ELQ's implementation. In Section 5 we evaluate the performance of ELQ and report on real-world case studies. Section 6 discusses limitations of ELQ and related libraries, as well as the current state of standardization of element queries. Finally, Section 8 concludes.

## 2. OVERVIEW OF ELQ

Media queries and element queries are similar in the sense that they both enable developers to define conditional designs that are applied by specified criteria. The main difference is the type of criteria that can be used; in media queries device, document, and media criteria are used, while element criteria are used in element queries. It can somewhat simplified be described as that media queries target the document root and up such as viewport, browser, device, and input mechanisms. Element queries target the document root and down, i.e., elements of the document.

To enable element queries, we have developed a novel JavaScript implementation named ELQ. Our implementation satisfied all requirements given in 1.2. The library have been designed to conform to the standards and specifications of the web languages while providing the features required of building advanced constellations of responsive modules. The novelty lies in having significantly improved performance by batch processing DOM operations, and providing an API that enables nesting of modules. ELQ also has excellent browser compatibility as it supports Internet Explorer 8 and upwards.

ELQ is designed to be plugin-based for increased flexibility and extensibility. By providing a good library foundation

and plugins it is up to developers to choose the right plugins for each project. In addition, by letting the plugins satisfy the requirements it is easy to extend the library with new plugins when new requirements arise.

An *element breakpoint* is defined as a point of an element property range which can be used to define conditional behavior, similar to breakpoints of media queries. For example, an element breakpoint of 500 pixels in width enables conditional styling depending on if the element is narrower or wider than 500 pixels. An element may have multiple breakpoints. An *element breakpoint state* is defined as the state of the element breakpoint relative to the current element property value. For example, if an element that is 300 pixels wide has two width breakpoints of 200 and 400 pixels the element breakpoint states are “wider than 200 pixels” and “narrower than 400 pixels”.

When the breakpoint states of an element changes, ELQ performs cycle detection in order to detect and handle possible style cycles. If a cycle is detected, the new element breakpoint states are not applied in order to avoid an infinite loop of layouts. The cycle detection system is implemented as an conservative algorithm, and may in some cases detect false positives.

## 2.1 The API

As CSS3 does not support custom at-rules/selectors [27], responsive elements are annotated in HTML by element attributes. The main idea is to annotate elements with breakpoints of interest so that children can be conditionally styled in CSS by targeting the different element breakpoint states. In this section, we will use the **elq-breakpoints** API (that is bundled with ELQ as default) that observes an element in order to automatically update breakpoint state classes of the element. Although not written in the examples, the library also supports attributes defined with the **data-** prefix to conform to the HTML standard.

The following is example HTML of an element that has two annotated width breakpoints at 300 and 500 pixels:

```
<div class="foo" elq elq-breakpoints
  elq-breakpoints-widths="300 500">

  <p>When in doubt, mumble.</p>
</div>
```

When ELQ has processed the element it will have two classes that reflects each breakpoint state. For instance, if the element is 400 pixels wide, the element has the two classes **elq-min-width-300px** and **elq-max-width-500px**. Similarly, if the element is 200 pixels wide the classes are instead **elq-max-width-300px** and **elq-max-width-500px**. So for each breakpoint only the min/max part changes. It may seem alien that the classes describe that the width of the element is both maximum 300 and 500 pixels. This is because we have taken a user-centric approach so that the CSS usage of the classes is similar to the API of media queries. However, developers are free to change this API by creating plugins.

Now that we have defined the breakpoints of the element, we can conditionally style it in CSS by using the classes as shown in listing 1.

```
.foo.elq-max-width-300px {
  background-color: blue;
}

.foo.elq-min-width-300px.elq-max-width-500px {
  background-color: green;
}

.foo.elq-min-width-500px p {
  color: white;
}
```

### Listing 1: Example usage of the breakpoint state classes in CSS.

In order for the conditional styles to be applied, the elements that have breakpoints must be activated by the ELQ JavaScript runtime. Elq can either be required as a module (by the CommonJS or AMD syntax), or it can be included in a HTML **script** tag which then will expose a global constructor **Elq**. The following is an example of how to create an ELQ instance and activating elements:

```
// Create an instance
var elq = Elq();

// Plugins may be registered
elq.use(myPlugin);
elq.use(myOtherPlugin);

// Activate elements.
var elements = document.querySelectorAll("[elq]");
elq.activate(elements);
```

In this example we created an ELQ instance and registered two plugins to it. Then we queried the document for all elements with an **elq** attribute (as annotated in previous examples) and then passed them as an argument to the activation method of ELQ. It should be noted that it is up developers how to activate elements; annotating elements with **elq** was used for simplicity in these examples. The only requirement is that they in some way gets passed through the activation method at some point. This can for example be achieved with a plugin that listens to DOM mutations and performs the activation automatically, or a plugin that parses CSS and activates all elements that has any conditional style defined.

#### 2.1.1 Nested modules

The **elq-breakpoints** API is sufficient for applications that do not need nested breakpoint elements, and similar features are provided by related libraries such as [20, 29]. However, using such API in responsive modules still limits the reusability since the modules then may not exist in an outer responsive context.

The reason this API is not sufficient for nested modules is because there is no way to limit the CSS matching search of the selectors. The last style rule of the example given in listing 1 specifies that all paragraph elements should have white text if *any* ancestor breakpoints element is wider than 500 pixels. Since the ancestor selector may match elements outside of the module, such selectors are dangerous to use in the context of responsive modules. The problem may be somewhat reduced by more specific selectors and such, but it cannot be fully solved for arbitrary styling.

To solve this problem, we provide a plugin that let us define elements to “mirror” the breakpoints classes of the nearest ancestor breakpoints element. Then, the conditional style of the mirror element may be written as a combinatory selector that is relative to the nearest ancestor breakpoints element. The following is an example usage of the mirror plugin to enable nested modules:

```
<div class="foo" elq elq-breakpoints
  elq-breakpoints-widths="300 500">

  <div class="foo" elq elq-breakpoints
    elq-breakpoints-widths="300 500">

    <p elq elq-mirror >...</p>
  </div>

  <p elq elq-mirror >...</p>
</div>
```

As the paragraph elements are mirroring the nearest `.foo` ancestor, we can now write CSS that does not traverse the ancestor tree:

```
.foo {
  /* So that the nested modules
   have different size */
  width: 50%;
}

.foo p.elq-min-width-500px {
  color: white;
}
```

Since we in the examples given so far have annotated elements breakpoints manually, the power and flexibility of the API have not been properly displayed. In the next Section, we'll present an API that combines JavaScript and generated CSS in order to create a high-level API.

### 2.1.2 A grid API

To further show the potential of ELQ, we have created a plugin that enables a high-level API for responsive modules. The API enables developers to use responsive grids consisting of twelve columns and utility classes very similar to the ones defined by the CSS Bootstrap framework [17].

The following is an example grid:

```
<div class="container">
  <div class="row">
    <div class="col-500-4 col-700-6">
      ...
    </div>
    <div class="col-500-4" col-700-6">
      ...
    </div>
    <div class="col-500-4 hidden-700-up">
      ...
    </div>
  </div>
</div>
```

The example grid is defined to be single columned when the width of the grid is below 500 pixels, triple columned when the width is between 500 and 700 pixels, and double columned for when the width is above 700 pixels. It should be noted that the last column is hidden when the width is above 700 pixels.

The columns of our API respond to the parent `row` instead of the viewport. Therefore, we have altered the column classes to also accept custom breakpoints so that developers have full control of the grid behavior. The `[breakpoint]` part of the column class can be any positive number, and may optionally be postfixed with a unit. Currently, the supported units are `px`, `em`, `rem`. If the unit is omitted, `px` is assumed.

This enables developers to define grid behaviors by pixel precision in nestable modules.

## 3. EXTENSIONS VIA PLUGINS

For example, if annotating HTML is undesired it is possible to create a plugin that instead generates element breakpoints by parsing CSS. Likewise, if adding breakpoint state classes to elements is undesired it is possible to create a plugin that does something else when an element breakpoint state has changed.

A plugin is defined by a *plugin definition object* and has the structure shown in listing 2.

```
var myPluginDefinition = {
  getName: function () {
    return "my-plugin";
  },
  getVersion: function () {
    return "0.0.0";
  },
  isCompatible: function (elq) {
    return true;
  },
  make: function (elq, options) {
    return {
      // Implement plugin instance methods.
      ...
    };
  }
};
```

**Listing 2:** The structure of plugin definition objects.

All of the methods are invoked when registered to an ELQ instance. The `getName` and `getVersion` methods tells the name and version of the plugin. The `isCompatible` tells if the plugin is compatible with the ELQ instance that it is registered to. In the `make` method the plugin may initialize itself to the ELQ instance and return an object that defines the plugin API accessible by ELQ and other plugins.

When necessary, ELQ invokes certain methods of the plugin API, if implemented, to let plugins decide the behavior of the system. Those methods are the following:

- **activate(element)** Called when an element is requested to be activated, in order for plugins to initialize listeners and element properties.
- **getElements(element)** Called in order to let plugins reveal extra elements to be activated in addition to the given element.
- **getBreakpoints(element)** Called to retrieve the current breakpoints of an element.
- **applyBreakpointStates(element, breakpointStates)** Called to apply the given element breakpoint states of an element.

In addition, plugins may also listen to the following ELQ events:

- **resize(element)** Emitted when an ELQ element has changed size.
- **breakpointStatesChanged(element, breakpointStates)** Emitted when an element has changed element breakpoint states (e.g., when the width of an element changed from being narrower than a breakpoint to being wider).

There are two main flows of the ELQ system; activating an element and updating an element. When ELQ is requested to activate an element, the following flow occurs:

1. Initialize the element by installing properties and a system that handles listeners.
2. Call the **getElements** method of all plugins to retrieve any additional elements to activate. Perform an activation flow for all additional elements.
3. Call the **activate** method of all plugins so that plugin-specific initializations may occur.
4. If any plugin has requested ELQ to detect resize events of the element, install an resize detector to the element.
5. Pass the element through the update flow.

The update flow is as follows:

1. Call the **getBreakpoints** method of all plugins to retrieve all breakpoints of the element.
2. Element breakpoint states are calculated.
3. If any state has changed since the previous update:
  - (a) Perform cycle detection. If a cycle is detected, then abort the flow and emit a warning.
  - (b) Call the **applyBreakpointStates** method of all plugins in order for plugins to apply the new element breakpoint states.
  - (c) Emit an **breakpointStatesChanged** event.

Of course, there are options to disable some of the steps such as cycle detection and applying breakpoint states. In addition to being triggered by the activation flow and plugins, it is also triggered by element resize events.

Plugins may also use an extended API of ELQ that offers access to subsystems such as the plugin handler, cycle detector, batch processor, etc. The extended API is given to a plugin as an argument to the **make** method of the plugin definition object. In addition, plugins may set behavior properties of an element by the **element.elq** property. It is also possible for plugins to define own behavior properties for inter-plugin collaboration, or for storing plugin-specific element state. Examples of behavior properties of the ELQ core are:

- **resizeDetection** Tells if resize detection should be performed.
- **cycleDetection** Tells if cycle detection should be performed.
- **updateBreakpoints** Tells if the element should be passed through the update flow.
- **applyBreakpointStates** Tells plugins may apply breakpoint states of the element (it is needed for some elements to only emit element breakpoint states changes, without applying them to the actual element).

### 3.1 Example Plugin Implementation

The **elq-breakpoints** API that enables developers to annotate breakpoints in HTML, as described in Section 2.1, is implemented as two plugins. This shows that even the core functionality of ELQ is implemented in terms of plugins. The first plugin parses the breakpoints of the element attributes. The second plugin applies the breakpoint states as classes.

The following is a simplified implementation of the **make** method (see listing 2) of the parsing plugin:

```
function activate(element) {
  if (!element.hasAttribute("elq-breakpoints")) {
    return;
  }

  element.elq.resizeDetection      = true;
  element.elq.updateBreakpoints    = true;
  element.elq.applyBreakpointStates = true;
  element.elq.cycleDetection        = true;
}

function getBreakpoints(element) {
  // Parse the "elq-breakpoints-*" attributes
  // and retrieve their breakpoints.
  return ...;
}

// Return the plugin API
return {
  activate: activate,
  getBreakpoints: getBreakpoints
};
```

In the **activate** method the plugin registers that resize detection is needed for the element and that it should be passed through the update flow. It also enables the element to have its breakpoint states applied and have cycle detection being performed. Although not shown in the simplified implementation, **applyBreakpointStates** and **cycleDetection** are in some cases disabled.

The plugin that applies the element breakpoint states simply implements the **applyBreakpointStates** method to alter the **className** property of the element by the given element breakpoint states.

## 4. IMPLEMENTATION

### 4.1 Batch Processing

Batch processing is the foundation of the performance gains of our approach, and is therefore used by several subsystems. ELQ uses a leveled batch processor, which is implemented as a stand-alone project. It serves two purposes: to process

batches in different levels to avoid layout thrashing, and to automatically process batches asynchronously for simpler usage.

Being able to process a batch in levels is important when different types of operations, that are to be processed in a specific order (usually to avoid layout thrashing), needs to be grouped together in a batch. For example, a function that doubles an element's width and reads the new calculated height benefits by being batch processed in three levels: reading the width, mutating the width, and reading the height. The following is an example implementation of such function that uses the leveled batch processor:

```
var batchProcessor = ...;

function doubleWidth(element, callback) {
  var width = element.offsetWidth;
  var newWidth = (width * 2) + "px";

  // Implicit level 0 of the batch.
  // Will be processed first.
  batchProcessor.add(function mutateWidth() {
    element.style.width = newWidth;
  });

  // Level 1 of the batch. Will be processed
  // after level 0. Changing the level number
  // from "1" to "0" results in layout thrashing.
  batchProcessor.add(1, function readHeight() {
    var height = element.offsetHeight;
    callback(height);
  });
}
```

From this example it is also clear that automated asynchronous processing of batches is important because the function may be called multiple times synchronously, like so:

```
var elements = [...];
elements.forEach(function (element) {
  doubleWidth(element, function (height) {
    ...
  });
});
```

Since one batch for each function call is processed, layout thrashing occurs which results in a severe performance impact. To solve this, each batch is delayed to execute asynchronously so that all synchronous calls of the method is grouped into a pending batch to be executed asynchronously. This results in a 45-fold speedup when applied to 1000 elements of the function compared to not processing the batch in levels. It also results in a simple API that allows multiple synchronous calls without causing layout thrashing.

The **activate** method of ELQ is implemented similarly so it may also be called multiple times synchronously without performance penalties like the following example:

```
var elements = [...];
elements.forEach(elq.activate);
```

## 4.2 Element Resize Detection

Unfortunately, there is no standardized resize event for arbitrary elements [25]. A naive approach to detecting element resize events is to have a script continuously check elements if they have resized given some interval (polling). This approach is appealing because it does not mutate the DOM,

supports arbitrary elements, and it provides excellent compatibility. However, in order to prevent the responsive elements lagging behind the size changes of the user interface, polling needs to be performed quite frequently. The problem is that each poll would force the layout queue to be flushed since the computed style of elements needs to be retrieved in order to know if elements have resized or not. Since the polling is performed all the time the overall page performance is decreased even if the page is idle, which is undesired especially for mobile devices running on battery.

It is desired to instead have an event-based approach that only performs additional computations when an actual element resize has happened. This is achieved by the resize detection subsystem of ELQ by using two independent injecting approaches, both originally presented by [5]. These approaches are limited to non-void elements, i.e., elements that may have content. It is a reasonable limitation since void elements can easily be wrapped with non-void elements without affecting the page visually.

**Object-based resize detection.** Only documents emit resize events in modern browsers and therefore such events can only be observed for frame elements (since a frame element has its own document). This approach injects **object** elements into the target element, which can be listened to resize events since **object** elements are frames. The **object** is styled so that it always matches the size of the target element and so that it does not affect the page visually. This approach has good browser compatibility and excellent resize detection performance, but imposes severe performance impacts during injection since **object** elements use a significant amount of memory.

**Scroll-based resize detection.** This approach injects an element that contains multiple overflowing elements that listen to scroll events. The overflowing elements are styled so that **scroll** events are emitted when the target element is resized. For detecting when the target element shrinks, two elements are needed; one for handling the scrollbars and one for causing them to scroll. Similarly, for detecting when the target element expands, two elements are needed in the same way. As this solution only injects **div** elements, it offers greater opportunities for optimizations. The main algorithm that is performed when an element *e* is to be observed for resize events is the following:

1. Get the computed style of *e*.
2. If the element is positioned (i.e., **position** is not **static**) the next step is 4.
3. Set the position of *e* to be **relative**. Here additional checks can be performed to warn the developer about unwanted side effects of doing this.
4. Create the four elements needed (two for detecting when *e* shrinks, and two for detecting when *e* expands) and attach event handlers for the **scroll** event of the elements. When the elements have been styled and configured properly, they are added as children to an additional container element that is injected into *e*.

5. The current size of  $e$  is stored and the scrollbars of the injected elements are positioned correctly.
6. The algorithm waits for the `scroll` event handlers to be called asynchronously by the layout engine (they are called since the previous step repositioned the scrollbars). When the handlers have been called, the injection is finished and observers can be notified on resize events of  $e$  when `scroll` events occur.

Layout thrashing can be avoided by using the leveled batch processor described in Section 4.1. The algorithm steps are batch processed in the following levels:

1. **The read level:** Step 1 is performed to obtain all necessary information about  $e$ . The information is stored in a shared state so that all other steps can obtain the information without reading the DOM.
2. **The mutation level:** Steps 2, 3 and 4 are performed, which mutate the DOM. All mutations performed in this level can be queued by layout engines.
3. **The forced layout level:** Step 5 is performed, which forces the layout engine to perform a layout.

Since repositioning a scrollbar in some layout engines forces a layout, such operations need to be performed after that all other queueable operations have been executed. Therefore, step 5 is performed in level 3 as the last step. Even if some layout engines are unable to queue the repositing of scrollbars, it is still beneficial to batch process the algorithm since only pure layouts need to be performed (instead of having to recompute styles and synchronize the DOM and render trees before each layout). As step 6 is performed by the layout engine asynchronously and does not interact with the DOM, it does not need to be batch processed.


## 5. EMPIRICAL EVALUATION

### 5.1 Performance

Only the performance of the element resize detection system has been performed. The reason for this is that this system entails the significant performance penalties of the library. Also, it is hard to compare performance results of related libraries since the functionality is so different. Fortunately, element resize detection is the common denominator of all automatic libraries and the results of this system can be compared faithfully.

Measurements and graphs show evaluations performed in Chrome version 42 unless stated otherwise.

The object-based approach (as presented by [5]) performs well when detecting resize events, which it does with a delay of 30 ms for 100 elements. However, the injection performance is not great as presented in figure 1. As shown by the graphs, the injection can be performed with adequate performance as long as the number of elements is low. The approach does not scale well as the number of elements increases. This is probably due to the fact that the heap memory usage grows roughly by 0.55 MB per element.



**Figure 1: The injection performance of the object-based approach.**

As the scroll-based approach (as presented by [5]) does not inject `object` elements the memory footprint is reduced significantly, which improves the injection performance. The amount of used memory is so low that reliable measurements could not be gathered. Recall from Section 4.2 that the scroll-based approach was heavily optimized for ELQ, which is referred to as the ELQ scroll-based approach. See figure 2 for graphs that show how the ELQ scroll-based approach performs compared to the other two approaches. As evident in the figure, the optimized ELQ approach has significantly reduced injection times. It achieves a 37-fold speedup compared to the object-based approach and a 17-fold speedup compared to the scroll-based approach when preparing 700 elements for resize detection.

TODO: Write about other browsers? Safari 9 and Chrome seem to have similar results. IE and FireFox and legacy version of Safari. Write that ELQ will at worst be as slow as the other ones (since it uses the object-based approach as a fallback).

TODO: Write about resize detection for all approaches?

TODO: Mention the flow-based solution quickly (as we talk about it in the related works section)

### 5.2 Case studies

In this section we aim to provide answers to the following questions:

- How can ELQ be used to modularize existing responsive code bases?
- How much effort is this modularization?

In order to answer the questions, we have adapted the popular Bootstrap framework<sup>1</sup> to use element queries instead of media queries. According to its website, “Bootstrap is the most popular HTML, CSS, and JS framework for developing responsive, mobile first projects on the web.” [17]

<sup>1</sup>This evaluation uses Bootstrap version 3.3.2.




Figure 2: The left graph shows the injection time of the ELQ scroll-based approach. The right graph shows all three approaches, including graph predictions by polynomial regression.

In order to modularize Bootstrap, we redefine the behavior of its responsive elements so that they no longer respond to the viewport but to enclosing container elements. The following observation guides our modularization: all responsive elements should respond to their closest enclosing **container** or **container-fluid** element. Both classes are used in Bootstrap to define new parts of a page (e.g., a grid is required to have a container ancestor). They are also nestable, which is important to satisfy the requirement of composable modules. The breakpoints of the container elements are defined using the **elq-breakpoints** API (see Section 2.1). Since the Bootstrap API uses a predefined set of breakpoints, they are all added to the container elements.

According to this design, we convert all responsive elements of Bootstrap to **elq-mirror** elements, since they need to mirror the breakpoints of the nearest ancestor **elq-breakpoints** element. Since container elements may be nested, they have both the **elq-breakpoints** and **elq-mirror** behavior.

The breakpoints of Bootstrap are defined as the following constants:<sup>2</sup>

```
@screen-sm-min: 480px;
@screen-md-min: 992px;
@screen-lg-min: 1200px;
```

The following example shows how Bootstrap’s style definitions are changed from using media queries to using ELQ’s element queries:

```
/* File "less/grid.less" of Bootstrap. */

// Original Bootstrap using media queries.
.container {
```

<sup>2</sup>The Bootstrap CSS is generated using the LESS preprocessor [1] whose syntax we use.

```
@media (min-width: @screen-sm-min) {
  width: @container-sm;
}
...
}

// ELQ Bootstrap using element queries.
.container {
  &.elq-min-width-@{screen-sm-min} {
    width: @container-sm;
  }
  ...
}
```

By using the power of preprocessors, ELQ element queries become as pleasant to work with as media queries. In fact, only about 0.6% of the style code (LESS syntax) need to be altered. Most changes are similar to the one shown above, which replaces the media query syntax with the ELQ element queries syntax. This is especially advantageous when keeping a forked project up to date with the original project, as fewer diverged lines implies a lowered risk of merge conflicts.

In summary we have shown that it is easy to adapt existing responsive code to use ELQ’s element queries instead of media queries. With only a small number of changes, the widely used Bootstrap framework can be modularized.

**Industrial use of ELQ.** In addition to the Bootstrap case study, we have been gathering experience with the application of ELQ in large financial applications at EVERY. Our practical experience shows that complex applications require a variety of features to be supported by element queries. Such features can be provided effectively by ELQ plugins.



Implementation	Syntax	Resize detection	Page type	Comments
[8] MagicHTML	Invalid	-	Static	Compiles invalid CSS to valid CSS at server side.
[11] EQCSS	Invalid	Viewport only	Dynamic	Flow-based element resizing detection. Polling-based element resizing detection. Using the Cassowary constraints solver. Writes media queries to style on load.
[19] Element Media Queries	Invalid	Non-void elements	Dynamic	
[3] Localised CSS	Invalid	Arbitrary elements	Dynamic	
[7] Grid Style Sheets 2.0	Invalid	Arbitrary elements	Dynamic	
[24] Class Query	Valid	-	Static	
[23] breakpoints.js	Valid	Viewport only	Dynamic	Inline JS syntax.
[15] MediaClass	Valid	Viewport only	Dynamic	
[14] ElementQuery	Valid	Viewport only	Dynamic	
[13] Responsive Elements	Valid	Viewport only	Dynamic	Parses CSS.
[16] SickleS	Valid	Viewport only	Dynamic	
[29] Responsive Elements	Valid	Viewport only	Dynamic	
[10] breaks2000	Valid	Viewport only	Dynamic	Object-based element resizing detection. Scroll-based element resizing detection. Polling-based element resizing detection.
[20] eq.js	Valid	Viewport only	Dynamic	
[6] Element Queries	Valid	Non-void elements	Dynamic	
[22] CSS Element Queries	Valid	Non-void elements	Dynamic	
[12] Selector queries and responsive containers	Valid	Arbitrary elements	Dynamic	

**Table 1: Classification of related approaches to modular RWD.**

## 6. DISCUSSION

### 6.1 Limitations

Inherent to all current implementations of element queries is that the conditional style is applied “one layout behind”. Since a layout pass needs to have been performed in order for an element to change size, the conditional styles defined by the element queries cannot be applied until next layout. Therefore, the element will be display invalid design until another layout has been performed. The flash of invalid design is usually so short that users do not notice it, but in some cases developers need to work around the issue to avoid more apparent results.

Another caveat is presented by the element resize detection approaches, as they mutate the DOM. Developers need to be aware of this as CSS selectors and JavaScript may also match the injected elements. This is easily avoided by good practices.

It should be noted that all limitations described only affects the elements that uses the element queries functionality. ELQ does not impose potential problems to other parts of the DOM other than where applied explicitly.

### 6.2 Standardization

It is stated on the W3C’s www-style mailing list [28] by Zbarsky of Mozilla, Atkins of Google and Sprehn of Google that element queries are infeasible to implement without restricting them. By limiting element queries to specially separated container elements that can only be queried by child elements, many of the problems are resolved [2, 1]. Therefore, the Responsive Issues Community Group (RICG) is currently investigating the possibility of standardizing *container* queries.

Unfortunately, even such limited container queries requires significant effort to implement due to the complex changes to browsers required [1]. Atkins argues that a full implementation that avoids the double layout issue is unlikely to be implemented, and therefore it might be wiser to pursue sub-standards that aids third-party solutions instead.

In the future, we hope that ELQ may use the aiding sub-standards pushed by RICG, to achieve greater flexibility and

performance.

We hope that the supporting standards of element queries discussed by RICG come soon, so that some of the limitations may be resolved. A standardized resize event would enable us to avoid injecting elements, and to reduce the code base of ELQ significantly. Support for custom at-rules/selectors would also enable us to define a more natural API in CSS. Finally, being able to tell elements to ignore children while computing their size would decrease the need for cycle detection.

## 7. RELATED WORK

Table 1 attempts to classify all existing approaches, of modular RWD, known to us. We discuss these approaches according to two different aspects: (a) syntax extensions and (b) resize detection.

*Syntax extensions.* The libraries [8, 11, 19, 3, 7] have in common that they require developers to write custom (invalid) CSS, unlike ELQ. Since they do not conform to the CSS standard, new features are supported through custom CSS parsed using JavaScript. As shown by [11, 7] quite advanced features can be implemented this way. Additionally, adding new CSS features implies that it is possible to implement a solution to element queries that does not require any changes to the HTML, which may be preferable since all styling then can be written in CSS. However, there are numerous drawbacks with libraries that require custom CSS.

TODO: Extended syntax violates the requirement, compilation step performance, cite thesis.

*Resize detection.* Most libraries simply observe the viewport resize event, which may be enough for static pages, but not enough to satisfy the requirements of reusable responsive modules. The libraries [3, 12, 19, 7, 6, 22] have in common that they observe elements for resize events. The libraries [3, 12] use polling to detect element resize. The three remaining libraries use three different injection approaches, as described in Section 4.2, to detect element resize events; [6] uses the object-based solution, [19] uses the flow-based so-

lution, and [22] uses the scroll-based solution. As shown in Section 5.1, all three approaches have significantly less performance than the element resizing detection system used in ELQ.

TODO: Make sure all libs in table are summarized.

**Constraint-based CSS.** CCSS [4] proposes a more general and flexible alternative to CSS. As the name suggests, the idea of CCSS is to layout documents based on constraints. According to its authors, the constraint-based approach provides extended features and reduced complexity compared to CSS. To solve the constraints CCSS uses the Cassowary constraint solving algorithm [?].

The Grid Style Sheets library [7] builds upon the ideas of CCSS and uses a JavaScript port [21] of Cassowary to solve the constraints at runtime. While not directly offering element queries, the library enables the possibility to conditionally style elements by element criteria and thus makes it a good candidate to solve the problem of responsive modules. However, the library has two major issues: performance and browser compatibility [9]. One approach to resolve both issues is to precompute the layout in a compilation step at the server. However, precompiling styles implies static layouts. The authors discuss other approaches [9] that would increase the performance while limiting the dynamism of page layout. In contrast, ELQ only considers element queries, but without these limitations and with higher performance.

## 8. CONCLUSION

Responsive Web Design (RWD) enables web applications to adapt to the characteristics of different devices, which is achieved using CSS media queries. However, using media queries it is impossible to create responsive applications in a modular way, because responsive elements then always depend on the global context.

This paper extends RWD to also include responsive modules through element queries. We present ELQ, an open-source implementation of our approach, that conforms to the current standards of HTML, CSS and JavaScript. It enables developers to create responsive modules that are independent of their context, and a way to encapsulate their conditional style rules. The element resize detection of ELQ, used to automatically evaluate element queries on changes of responsive elements, performs up to 37x better than previous algorithms.

Using a case study based on the popular Bootstrap framework we show that large code bases using media queries can be converted to using ELQ's element queries with little effort. Changing only about 0.6% of the LOC of style related code was sufficient to enable the use of Bootstrap in responsive modules. We also report on first commercial users of ELQ.

We believe ELQ is an important contribution to realizing a *modular* form of element queries, in particular since standardization bodies like the RICG do not intend to standardize a complete solution. In the future we intend to improve ELQ by using forthcoming standards developed by the

RICG to avoid some current limitations.

## 9. ACKNOWLEDGMENTS

The authors would like to thank EVRY for sponsoring the ELQ project, and the supporting projects for element resize detection and batch processing.

## 10. REFERENCES

- [1] CSS containment draft. Retrieved April 29, 2015 from <https://github.com/ResponsiveImagesCG/cq-usecases/issues/7>.
- [2] RICG IRC log. Retrieved April 29, 2015 from <http://ircbot.responsiveimages.org/bot/log/respimg/2015-03-05#T117108>.
- [3] C. Ashton. Localised CSS. Retrieved April 29, 2015 from <https://github.com/ChrisBAShton/localised-css>.
- [4] G. J. Badros, A. Borning, K. Marriott, and P. Stuckey. Constraint cascading style sheets for the web. In *Proceedings of the 12th annual ACM symposium on User interface software and technology*, pages 73–82. ACM, 1999.
- [5] D. Buchner. Backalleycoder. Retrieved March 23, 2015 from <http://www.backalleycoder.com/>.
- [6] D. Buchner. Element Queries. Retrieved April 29, 2015 from <https://github.com/csuwildcat/element-queries>.
- [7] e. a. Dan Tocchini. Grid Style Sheets 2.0. Retrieved April 29, 2015 from <http://gridstylesheets.org/>.
- [8] G. Felipe. MagicHTML. Retrieved April 29, 2015 from <https://github.com/gabriel-felipe/MagicHTML>.
- [9] Grid Style Sheets. Element queries with precompilation. Retrieved June 8, 2015 from <https://github.com/gss/engine/issues/178>.
- [10] D. Hägglund. breaks2000. Retrieved April 29, 2015 from <https://github.com/judas-christ/breaks2000>.
- [11] T. Hodgins and M. Euzière. EQCSS. Retrieved April 29, 2015 from <http://elementqueries.com/>.
- [12] A. Hume. Selector queries and responsive containers. Retrieved April 29, 2015 from <https://github.com/ahume/selector-queries/>.
- [13] K. Hunaid. Responsive Elements. Retrieved April 29, 2015 from <https://github.com/kumailht/responsive-elements>.
- [14] T. Matanich. ElementQuery. Retrieved April 29, 2015 from <https://github.com/tysonmatanich/elementQuery>.
- [15] J. Neal. MediaClass. Retrieved April 29, 2015 from <https://github.com/jonathantneal/MediaClass>.
- [16] T. Nguyen. Sickles. Retrieved April 29, 2015 from <http://singggum3b.github.io/SickleS/>.
- [17] M. Otto and J. Thornton. Bootstrap. Retrieved October 15, 2015 from <http://getbootstrap.com/>.
- [18] D. L. Parnas. On the criteria to be used in decomposing systems into modules. *Communications of the ACM*, 15(12):1053–1058, 1972.
- [19] F. Remy. Element Media Queries. Retrieved April 29, 2015 from <https://github.com/FremyCompany/prollyfill-min-width/>.

- [20] S. Richard. eq.js. Retrieved April 29, 2015 from <https://github.com/Snugug/eq.js>.
- [21] A. Russell. Cassowary/JS. Retrieved April 28, 2015 from <https://github.com/slightlyoff/cassowary.js>.
- [22] M. J. Schmidt. CSS Element Queries. Retrieved April 29, 2015 from <https://github.com/marcj/css-element-queries>.
- [23] J. Stoutenburg. breakpoints.js. Retrieved April 29, 2015 from <https://github.com/reusables/breakpoints.js>.
- [24] M. Stow. Class Query. Retrieved April 29, 2015 from <https://github.com/stowball/Class-Query>.
- [25] W3C. Document object model events. Retrieved March 14, 2015 from <http://www.w3.org/TR/DOM-Level-2/events.html>.
- [26] W3C. Media queries. Retrieved April 19, 2015 from <http://www.w3.org/TR/css3-mediaqueries/>.
- [27] W3C. Selectors level 3. Retrieved March 19, 2015 from <http://www.w3.org/TR/css3-selectors/>.
- [28] W3C. W3C public mail archive: The :min-width/:max-width pseudo-classes. Retrieved April 28, 2015 from <https://lists.w3.org/Archives/Public/www-style/2013Mar/0368.html>.
- [29] C. Worrell. Responsive Elements. Retrieved April 29, 2015 from <https://github.com/coreyworrell/responsive-elements>.