

ADAMKYC REST API

Dev Base URL

Base URL for all endpoints is <https://adamkyc.deltaplata.com>

Authentication

To authenticate a user in production used Nonce:

<https://developer.wordpress.org/apis/security/nonces/>

Authentication is done by setting a header X-WP-Nonce to a value that is present by adamkyc_frontend_nonce JS variable.

Failure Response

```
{
  "status": false,
  "message": string,
}
```

Entity Object

```
interface Entity {
  "id": string           // ID of the Entity
  "caption": string      // Entity name
  "schema": string       // Entity type or category,
  "first_seen": string   // First time when Entity appeared in database
  "last_change": string  // Last time when Entity was updated
  "bookmarked": boolean  // Whether user added this entity to bookmarks
  "referents": string[]  // Referents
  "datasets": string[]   // Entity datasets
  "relations": Entity[]  // Entity relations to other entities
  "properties": {
    "address"? : string[]           // Entity short addresses
    "addressEntity"? : string[]     // Address.ID[] connected to Entity
    "alias"? : string[]            // Entity alternative names
    "amount"? : string[]           // Security field
    "amountUsd"? : string[]        // CryptoWallet field
    "balance"? : string[]          // CryptoWallet field
    "bikCode"? : string[]          // Company Field
    "birthCountry"? : string[]     // Person Field
    "birthDate"? : string[]        // Person field
  }
}
```

```

"birthPlace"?: string[] // Person field
"buildDate"?: string[] // Vessel Field
"callSign"?: string[] // Vessel Field
"city"?: string[] // Address Field
"classification"?: string[] // Company and Security field
"country"?: string[] // Country of the Entity
"createdAt"?: string[] // Entity created at
"currency"?: string[] // CryptoWallet and Security field
"deathDate"?: string[] // Person field
"description"?: string[] // Description of the Entity
"dissolutionDate"?: string[] // Company and Organization field
"dunsCode"?: string[] // Company and Organization field
"education"?: string[] // Person field
"email"?: string[] // Email of the Entity
"ethnicity"?: string[] // Person field
"fatherName"?: string[] // Person field
"firstName"?: string[] // Person field
"flag"?: string[] // Vessel field
"full"?: string[] // Address field
"gender"?: string[] // Person field
"grossRegisteredTonnage"?: string[] // Vessel field
"holder"?: string[] // CryptoWallet field
"iban"?: string[] // BankAccount field
"icijId"?: string[] // ICIJ ID of the Entity
"imoNumber"?: string[] // Vessel field
"incorporationDate"?: string[] // Incorporation date of Entity
"innCode"?: string[] // INN Code of the Entity
"isin"?: string[] // Security field
"issueDate"?: string[] // Security field
"issuer"?: string[] // Security field
"jurisdiction"?: string[] // Company and Organization field
"keywords"?: string[] // Keywords of the Entity
"kppCode"?: string[] // Company field
"lastName"?: string[] // Person field
"legalForm"?: string[] // LegalEntity field
"leiCode"?: string[] // LEI Code of the Entity
"mainCountry"?: string[] // MainCountry of the Entity
"maturityDate"?: string[] // Security field
"middleName"?: string[] // Person field
"mmsi"?: string[] // MMSI number of Vessel
"modifiedAt"?: string[] // ModifiedAt of Entity
"motherName"?: string[] // Person field
"name"?: string[] // Name of the Entity
"nameSuffix"?: string[] // Name of the Entity
"nationality"?: string[] // Name of the Entity
"notes"?: string[] // Notes of the Entity
"ogrnCode"?: string[] // OGRN Code of the Entity
"okpoCode"?: string[] // Company and Organization field
"opencorporatesUrl"?: string[] // Company and Organization field
"passportNumber"?: string[] // Person field
"pastFlags"?: string[] // Vessel field
"phone"?: string[] // Phone of the Entity
"political"?: string[] // Person field
"position"?: string[] // Person field
"postOfficeBox"?: string[] // Address field

```

```

"postalCode"?: string[] // Address field
"previousName"?: string[] // Previous name of the Entity
"program"?: string[] // Company field
"proof"?: string[] // Proof of the Entity
"publicKey"?: string[] // CryptoWallet field
"publisher"?: string[] // Published of the Entity
"region"?: string[] // Address field
"registrationNumber"?: string[] // Registration Number of the Entity
"religion"?: string[] // Person field
"remarks"?: string[] // Address field
"secondName"?: string[] // Person field
"sector"?: string[] // Company and Organization field
"sourceUrl"?: string[] // Source URL of the Entity
"state"?: string[] // Address field
"status"?: string[] // Status of the Entity
"street"?: string[] // Address field
"summary"?: string[] // Summary of the Entity
"swiftBic"?: string[] // Company and Organization field
"taxNumber"?: string[] // TAX Number of the Entity
"ticker"?: string[] // Security field
"title"?: string[] // Person field
"tonnage"?: string[] // Vessel field
"topics"?: string[] // Topics of the Entity
"type"?: string[] // Type of the Entity
"vatCode"?: string[] // Company and Organization field
"weakAlias"?: string[] // Weak Alias of the Entity
"website"?: string[] // Website of the Entity
"wikidataId"?: string[] // Wikidata ID of the Entity
}
}

```

Connect Endpoint

POST /wp-json/adamkyc/v1/connect

Connect plugin to MongoDB with credentials.

Body Parameters

username - [required: string] *Username of the MongoDB connection*
password - [required: string] *Password of the MongoDB connection*
hostname - [required: string] *Hostname of the MongoDB connection*
database - [required: string] *Database name of the MongoDB connection*

Example Response

```

{
  "status": boolean,
  "data": null,
}

```

Connection Endpoint

GET /wp-json/adamkyc/v1/connection

Check whether currently connected to MongoDB.

Example Response

```
{
  "status": boolean,
  "data": {
    "connected": boolean,
    "username": string,
    "hostname": string,
    "database": string,
  }
}
```

Disconnect Endpoint

GET /wp-json/adamkyc/v1/disconnect

Disconnect from the MongoDB.

Example Response

```
{
  "status": boolean,
  "data": null,
}
```

Me Endpoint

GET /wp-json/adamkyc/v1/me

Information about current user

Example Response

```
{
  "status": boolean,
  "data": {
    "is_admin": boolean,
  }
}
```

Bookmarks Endpoint

[GET /wp-json/adamkyc/v1/bookmarks](#)

Return bookmarked entity IDs for current user.

Query Parameters

page - [optional: integer min:1] *Page of the collection*

after - [optional: string date YYYY-MM-DD] *Starting date of the collection*

before - [optional: string date YYYY-MM-DD] *Ending date of the collection*

Example Response

```
{
  "status": boolean,
  "data": {
    "items": Entity[],
    "page": number,
    "totalItems": number,
    "totalPages": number,
  }
}
```

Bookmark Endpoint

[GET /wp-json/adamkyc/v1/bookmark/:id](#)

Create or delete bookmark of entity for current user.

Example Response

```
{
  "status": boolean,
  "data": null,
}
```

Download Endpoint

[GET /wp-json/adamkyc/v1/download/:id](#)

Download information about entity.

Example Response

```
{
  ...EntityFields
}
```

```
}
```

Entity Endpoint

GET /wp-json/adamkyc/v1/entity/:id

Return information about entity.

Example Response

```
{
  "status": boolean,
  "data": Entity,
}
```

Search Endpoint

GET /wp-json/adamkyc/v1/search

Search through collections to find match for given query.

Query Parameters

q - [required: string] *Query to find matches for*

type - [optional: enum(address, bank-account, crypto-wallet, legal-entity, person, security, vessel)] *Type of the collection to search through*

page - [optional: integer min:1] *Page of the collection*

sort - [optional: enum(asc, desc)] *Sorting order of the collection*

topics - [optional: string] *Comma separated topics*

country - [optional: string] *Two letter (in some cases 4 letter) country code in lowercase*

...**properties_*** - [optional: string] *Properties fields (used for Advanced Search). You can pass any property that Entity type has.*

Example Response

```
{
  "status": boolean,
  "data": {
    "items": Entity[],
    "page": number,
    "totalItems": number,
    "totalPages": number,
  }
}
```

Bookmarks Clear Endpoint

GET /wp-json/adamkyc/v1/bookmarks/clear

Removes all bookmarks for current user.

Example Response

```
{
  "status": boolean,
  "data": null,
}
```

Last Viewed Endpoint

GET /wp-json/adamkyc/v1/last-viewed

Returns last ten viewed entities IDs by current user.

Example Response

```
{
  "status": boolean,
  "data": Entity[],
}
```

Recent Search Endpoint

GET /wp-json/adamkyc/v1/recent-search

Returns last ten keywords searched by current user.

Example Response

```
{
  "status": boolean,
  "data": string[],
}
```

History Clear Endpoint

GET /wp-json/adamkyc/v1/history/clear

Removes all history and views analytics for current user.

Example Response

```
{
  "status": boolean,
  "data": null,
}
```

History Endpoint

[GET /wp-json/adamkyc/v1/history](#)

Search history for current user.

Query Parameters

page - [optional: integer min:1] *Page of the collection*

after - [optional: string date YYYY-MM-DD] *Starting date of the collection*

before - [optional: string date YYYY-MM-DD] *Ending date of the collection*

Example Response

```
{
  "status": boolean,
  "data": {
    "items": [
      {
        "search": string,
        "type": string,
        "count": number,
        "created_at": DateTime,
      }
    ],
    "page": number,
    "totalItems": number,
    "totalPages": number,
  }
}
```

Bulk-Upload Endpoint

[POST /wp-json/adamkyc/v1/bulk-upload](#)

Goes through uploaded file and searches for matches in MongoDB.

Body Parameters

data - [required: File] *Uploaded file (CSV, XLSX, XLS)*
type - [required: enum(address, bank-account, crypto-wallet, legal-entity, person, security, vessel)] *Type of the collection to search through*

Example Response

```
{
  "status": boolean,
  "data": null,
}
```

Bulk-Upload History Endpoint

GET /wp-json/adamkyc/v1/bulk-upload/history

Bulk-upload history for current user.

Query Parameters

page - [optional: integer min:1] *Page of the collection*

after - [optional: string date YYYY-MM-DD] *Starting date of the collection*

before - [optional: string date YYYY-MM-DD] *Ending date of the collection*

Example Response

```
{
  "status": boolean,
  "data": {
    "items": [
      {
        "id": number,
        "entity_id?": string,
        "search": string,
        "type": string,
        "created_at": DateTime,
      }
    ],
    "page": number,
    "totalItems": number,
    "totalPages": number,
  }
}
```

Bulk-Upload Delete Endpoint

GET [/wp-json/adamkyc/v1/bulk-upload/delete](#)

Delete bulk-upload history entries for current user.

Query Parameters

identifiers - [required: string] *Comma separated identifiers*

Example Response

```
{
  "status": boolean,
  "data": null,
}
```

Bulk-Upload Download Endpoint

GET [/wp-json/adamkyc/v1/bulk-upload/download](#)

Download bulk-upload history entries for current user.

Query Parameters

identifiers - [required: string] *Comma separated identifiers*

Example Response

ZipStream

Report Endpoint

POST [/wp-json/adamkyc/v1/report/:id](#)

Report entity as current user.

Body Parameters

firstName - [required: string **non-empty**] *First name*

lastName - [required: string **non-empty**] *Last name*

email - [required: string **non-empty**] *Valid email*

phone - [required: string] *Valid phone number*

entityName - [required: string **non-empty**] *Entity name*

registerUrl - [required: string] *Register valid URL*

details - [required: string **non-empty**] *Details*

relationship - [required: string **non-empty**] *Relationship*

Example Response

```
{
  "status": boolean,
  "data": null,
}
```

Datasets Endpoint

[GET /wp-json/adamkyc/v1/datasets](#)

Datasets to be used with details endpoint.

Example Response

```
{
  "status": boolean,
  "data": [
    {
      "id": string,
      "title": string,
      "description": string,
      "country"?: string,
      "publisher_name": string,
      "publisher_url": string,
      "source_url"?: string,
      "tags": string[],
    }
  ]
}
```

Topics Endpoint

[GET /wp-json/adamkyc/v1/topics](#)

Topics to be used in search, details, etc.

Example Response

```
{
  "status": boolean,
  "data": string[string],
}
```

Admin Reports Endpoint

[GET /wp-json/adamkyc/v1/admin-reports](#)

List reports visible to every administrator.

Query Parameters

page - [optional: integer min:1] *Page of the collection*

after - [optional: string date YYYY-MM-DD] *Starting date of the collection*

before - [optional: string date YYYY-MM-DD] *Ending date of the collection*

state - [optional: enum(DELETED)] *State of the report*

status - [optional: enum(APPROVED, DENIED, REVIEWING)] *Status of the report*

type - [optional: enum(address, bank-account, crypto-wallet, legal-entity, person, security, vessel)] *Type of the report's entity*

q - [optional: string] *Query to search through all reports*

Example Response

```
{
  "status": boolean,
  "data": {
    "items": [
      {
        "id": number,
        "entity_id": string,
        "first_name": string,
        "last_name": string,
        "email": string,
        "phone": string,
        "entity_name": string,
        "register_url": string,
        "details": string,
        "relationship": string,
        "created_at": DateTime,
        "state"? : DELETED,
        "status"? : APPROVED | DENIED | REVIEWING,
      }
    ],
    "page": number,
    "totalItems": number,
    "totalPages": number,
  }
}
```

Admin Report View Endpoint

GET /wp-json/adamkyc/v1/admin-report/:id

Get single report visible to every administrator.

Example Response

```
{
  "status": boolean,
  "data": {
    "id": number,
    "entity_id": string,
    "first_name": string,
    "last_name": string,
    "email": string,
    "phone": string,
    "entity_name": string,
    "register_url": string,
    "details": string,
    "relationship": string,
    "created_at": DateTime,
    "state"? : DELETED,
    "status"? : APPROVED | DENIED | REVIEWING,
  }
}
```

Admin Report Update Endpoint

POST /wp-json/adamkyc/v1/admin-report/:id

Update single report visible to every administrator.

Body Parameters

status - [optional: enum(APPROVED, DENIED, REVIEWING)] *Status of the report*

Example Response

```
{
  "status": boolean,
  "data": null
}
```

Admin Report Delete/Trash Endpoint

DELETE [/wp-json/adamkyc/v1/admin-report/:id](#)

Delete/Trash single report visible to every administrator.

Example Response

```
{
  "status": boolean,
  "data": null
}
```

Admin Report Changelog Endpoint

GET [/wp-json/adamkyc/v1/admin-report/:id/changelog](#)

List reports visible to every administrator.

Example Response

```
{
  "status": boolean,
  "data": [
    {
      "id": number,
      "report_id": number,
      "message": string,
      "created_at": DateTime,
      "updated_at": DateTime,
    }
  ]
}
```

Admin Report Notes Endpoint

GET [/wp-json/adamkyc/v1/admin-report/:id/notes](#)

List report's notes visible to every administrator.

Example Response

```
{
```

```
{
  "status": boolean,
  "data": [
    {
      "id": number,
      "report_id": number,
      "subject": string,
      "note": string,
      "created_at": DateTime,
      "updated_at": DateTime,
    }
  ]
}
```

Admin Report Note Create Endpoint

POST [/wp-json/adamkyc/v1/admin-report/:id/note](#)

Create report note visible to every administrator.

Body Parameters

subject - [required: string] *Subject of the note*

note - [required: string] *Note body*

Example Response

```
{
  "status": boolean,
  "data": null
}
```

Admin Report Note Update Endpoint

PUT [/wp-json/adamkyc/v1/admin-report/:id/note/:id](#)

Update report note visible to every administrator.

Body Parameters

subject - [required: string] *Subject of the note*

note - [required: string] *Note body*

Example Response

```
{
```

```
{
  "status": boolean,
  "data": null
}
```

Admin Report Note Delete Endpoint

DELETE [/wp-json/adamkyc/v1/admin-report/:id/note/:id](#)

Delete report note visible to every administrator.

Example Response

```
{
  "status": boolean,
  "data": null
}
```

Admin Report Multiple Delete Endpoint

GET [/wp-json/adamkyc/v1/admin-reports/delete](#)

Delete reports in bulk visible to all administrators.

Query Parameters

indentifiers - [required: string] *Comma separated identifiers*

Example Response

```
{
  "status": boolean,
  "data": null,
}
```

Admin Report Multiple Update Endpoint

POST [/wp-json/adamkyc/v1/admin-reports/update](#)

Update reports in bulk visible to all administrators.

Body Schema

```
{
  "data": [
    {
      "id": number,
```



```

        "status"?: APPROVED | DENIED | REVIEWING
    }
]
}

```

Body Parameters

data.id - [required: string] *ID of Report to update*

data.status - [optional: enum(APPROVED, DENIED, REVIEWING)] *Status of the report*

Example Response

```

{
  "status": boolean,
  "data": null,
}

```

Admin Bulk Upload Endpoint

POST /wp-json/adamkyc/v1/admin-bulk-upload

Bulk upload of entities available only for administrators.

Body Parameters

data - [required: File] *Uploaded file (CSV, XLSX, XLS)*

type - [required: enum(address, bank-account, crypto-wallet, legal-entity, person, security, vessel)] *Type of the collection to do a bulk upload for*

Example Response

```

{
  "status": boolean,
  "data": null,
}

```

Admin Bulk Upload History Endpoint

GET /wp-json/adamkyc/v1/admin-bulk-upload/history

History of all administrators all bulk uploads.

Query Parameters

status - [optional: enum(FAILURE, SUCCESS)] *Status of the bulk upload to search for*

type - [optional: enum(address, bank-account, crypto-wallet, legal-entity, person, security, vessel)] *Type of the collection to do a bulk upload for*
page - [optional: integer min:1] *Page of the collection*
after - [optional: string date YYYY-MM-DD] *Starting date of the collection*
before - [optional: string date YYYY-MM-DD] *Ending date of the collection*

Example Response

```
{
  "status": boolean,
  "data": null,
}
```

Admin Bulk Upload Delete Data Endpoint

DELETE /wp-json/adamkyc/v1/admin-bulk-upload/:id

Delete data for specified bulk uploads done by any of administrators.

Example Response

```
{
  "status": boolean,
  "data": null,
}
```

Admin Entities Endpoint

GET /wp-json/adamkyc/v1/admin-entities

List entities visible to every administrator added through bulk upload.

Query Parameters

page - [optional: integer min:1] *Page of the collection*
after - [optional: string date YYYY-MM-DD] *Starting date of the collection*
before - [optional: string date YYYY-MM-DD] *Ending date of the collection*
state - [optional: enum(DELETED, DRAFT, PRIVATE, PUBLIC)] *State of the entity*
status - [optional: enum(VERIFIED, INCORRECT, UNVERIFIED)] *Status of the entity*
type - [optional: enum(address, bank-account, crypto-wallet, legal-entity, person, security, vessel)] *Type of the entity*
q - [optional: string] *Query to search through all entities*

Example Response

```
{
  "status": boolean,
```

```

"data": {
  "items": [
    {
      "id": number,
      "user_id": string,
      "user": User,
      "data": Entity,
      "state"?: DELETED | DRAFT | PUBLIC | PRIVATE,
      "status"?: VERIFIED | INCORRECT | UNVERIFIED,
      "created_at": DateTime,
      "updated_at": DateTime,
    }
  ],
  "page": number,
  "totalItems": number,
  "totalPages": number,
}
}

```

Admin Entities Multiple Delete Endpoint

GET [/wp-json/adamkyc/v1/admin-entities/delete](#)

Delete entities in bulk visible to all administrators.

Query Parameters

identifiers - [required: string] *Comma separated identifiers*

Example Response

```

{
  "status": boolean,
  "data": null,
}

```

Admin Entities Multiple Patch Endpoint

POST [/wp-json/adamkyc/v1/admin-entities/update](#)

Patch entities in bulk visible to all administrators.

JSON Schema

```
{
  "data": [
    {
      "id": number,
      "status"?: VERIFIED | INCORRECT | UNVERIFIED,
    }
  ]
}
```

JSON Parameters

data.id - [required: string] *ID of entity to patch*

data.status - [optional: enum(VERIFIED, INCORRECT, UNVERIFIED)] *Status of the entity*

Example Response

```
{
  "status": boolean,
  "data": null,
}
```

Admin Entity Create Endpoint

POST /wp-json/adamkyc/v1/admin-entity/create

Create entity visible to all administrators.

JSON Schema

```
{
  "state"?: DRAFT | PRIVATE | PUBLIC,
  "status"?: VERIFIED | INCORRECT | UNVERIFIED,
  "data": Entity,
}
```

JSON Parameters

state - [optional: enum(DRAFT, PRIVATE, PUBLIC)] *State of the entity*

status - [optional: enum(VERIFIED, INCORRECT, UNVERIFIED)] *Status of the entity*

data - [required: Entity] *Data of the entity*

Example Response

```
{
  "status": boolean,
  "data": {
```

```
"id": number,
"user_id": string,
"user": User,
"data": Entity,
"state"?: DELETED | DRAFT | PUBLIC | PRIVATE,
"status"?: VERIFIED | INCORRECT | UNVERIFIED,
"created_at": DateTime,
"updated_at": DateTime,
},
}
```

Admin Entity View Endpoint

GET /wp-json/adamkyc/v1/admin-entity/:id

View entity visible to every administrator.

Example Response

```
{
  "status": boolean,
  "data": {
    "id": number,
    "user_id": string,
    "user": User,
    "data": Entity,
    "state"?: DELETED | DRAFT | PUBLIC | PRIVATE,
    "status"?: VERIFIED | INCORRECT | UNVERIFIED,
    "created_at": DateTime,
    "updated_at": DateTime,
  },
}
```

Admin Entity Delete Endpoint

DELETE /wp-json/adamkyc/v1/admin-entity/:id

Delete entity visible to every administrator.

Example Response

```
{
```

```
"status": boolean,  
"data": null,  
}
```

Admin Entity Patch Endpoint

PATCH `/wp-json/adamkyc/v1/admin-entity/:id`

Patch entity visible to every administrator (used for quick edit).

Body Parameters

status - [optional: enum(VERIFIED, INCORRECT, UNVERIFIED)] *Status of the report*

Example Response

```
{  
  "status": boolean,  
  "data": null,  
}
```

Admin Entity Update Endpoint

PUT `/wp-json/adamkyc/v1/admin-entity/:id`

Update entity visible to every administrator.

JSON Schema

```
{  
  "state"? : DRAFT | PRIVATE | PUBLIC,  
  "status"? : VERIFIED | INCORRECT | UNVERIFIED,  
  "data": Entity,  
}
```

JSON Parameters

state - [optional: enum(DRAFT, PRIVATE, PUBLIC)] *State of the entity*

status - [optional: enum(VERIFIED, INCORRECT, UNVERIFIED)] *Status of the entity*

data - [required: Entity] *Data of the entity*

Example Response

```
{  
  "status": boolean,  
  "data": {  
    "id": number,  
  },  
}
```

```

    "user_id": string,
    "user": User,
    "data": Entity,
    "state"?: DELETED | DRAFT | PUBLIC | PRIVATE,
    "status"?: VERIFIED | INCORRECT | UNVERIFIED,
    "created_at": DateTime,
    "updated_at": DateTime,
  },
}

```

Admin Dataset Create Endpoint

POST /wp-json/adamkyc/v1/admin-dataset

Create dataset that can be used with Entity.

Body Parameters

description - [required: string] *Description of the dataset*
 publisher_name - [required: string] *Publisher name of the dataset*
 publisher_url - [required: string] *Publisher URL of the dataset*
 title - [required: string] *Title of the dataset*
 country - [optional: string] *Two letter (in some cases 4 letter) country code in lowercase*
 source_url - [optional: string] *Source URL of the dataset*
 tags - [optional: string] *Comma separated tags. Any of: external dataset, non-official source.*

Example Response

```

{
  "status": boolean,
  "data": {
    "id": string,
    "title": string,
    "description": string,
    "country"?: string,
    "publisher_name": string,
    "publisher_url": string,
    "source_url"?: string,
    "tags": string[],
  },
}

```

All possible properties.* for each collection

Airplane: ["address", "sourceUrl", "addressEntity", "model", "country", "registrationNumber", "topics", "serialNumber", "name", "buildDate"]
Address: ["region", "street", "state", "summary", "full", "remarks", "postalCode", "country", "city", "postOfficeBox"]
Associate: ["startDate", "endDate", "modifiedAt", "**associate**", "**person**", "relationship"]
BankAccount: ["iban"]
Company: ["ogrnCode", "notes", "status", "alias", "keywords", "publisher", "kppCode", "opencorporatesUrl", "previousName", "addressEntity", "address", "phone", "createdAt", "registrationNumber", "website", "classification", "proof", "innCode", "weakAlias", "name", "leiCode", "summary", "jurisdiction", "incorporationDate", "swiftBic", "dissolutionDate", "okpoCode", "bikCode", "mainCountry", "dunsCode", "icijId", "email", "idNumber", "vatCode", "description", "sourceUrl", "sector", "topics", "country", "legalForm", "taxNumber", "modifiedAt", "program"]
CryptoWallet: ["amountUsd", "modifiedAt", "alias", "balance", "topics", "publicKey", "currency", "**holder**", "createdAt"]
Directorship: ["publisher", "summary", "status", "startDate", "**organization**", "modifiedAt", "**director**", "role", "endDate"]
Employment: ["date", "endDate", "role", "modifiedAt", "summary", "startDate", "**employer**", "**employee**"]
Family: ["startDate", "**relative**", "endDate", "modifiedAt", "relationship", "**person**"]
Identification: ["country", "type", "startDate", "number", "summary", "endDate", "**holder**", "authority", "namesMentioned", "description"]
LegalEntity: ["phone", "sourceUrl", "address", "addressEntity", "country", "legalForm", "createdAt", "topics", "registrationNumber", "name", "website", "innCode", "modifiedAt", "previousName", "incorporationDate", "mainCountry", "notes", "status", "icijId", "email", "alias", "publisher"]
Membership: ["date", "role", "summary", "endDate", "modifiedAt", "**organization**", "startDate", "**member**"]
Occupancy: ["startDate", "description", "**post**", "status", "**holder**", "endDate"]
Organization: ["createdAt", "registrationNumber", "email", "icijId", "dunsCode", "idNumber", "okpoCode", "dissolutionDate", "modifiedAt", "ogrnCode", "description", "sourceUrl", "vatCode", "country", "legalForm", "sector", "taxNumber", "topics", "alias", "summary", "publisher", "keywords", "opencorporatesUrl", "phone", "proof", "notes", "status", "weakAlias", "name", "leiCode", "innCode", "jurisdiction", "swiftBic", "incorporationDate", "wikidataId", "address", "previousName", "addressEntity", "website"]
Ownership: ["status", "modifiedAt", "date", "role", "sharesValue", "percentage", "recordId", "sharesCount", "sharesCurrency", "startDate", "publisher", "**asset**", "summary", "**owner**", "endDate"]
Passport: ["type", "startDate", "number", "summary", "**holder**", "endDate", "authority", "country"]
Person: ["nationality", "createdAt", "email", "middleName", "deathDate", "website", "idNumber", "birthPlace", "icijId", "registrationNumber", "title", "birthCountry", "gender", "birthDate", "modifiedAt", "motherName", "ogrnCode", "description", "sourceUrl", "fatherName", "country", "lastName", "political", "topics", "taxNumber", "ethnicity", "legalForm", "alias", "summary", "keywords", "phone", "publisher", "nameSuffix", "education", "proof", "notes", "status", "passportNumber", "weakAlias", "name", "secondName", "innCode", "leiCode", "wikidataId", "religion", "address", "firstName", "addressEntity", "previousName", "position"]
Representation: ["publisher", "endDate", "role", "summary", "**client**", "startDate", "status", "**agent**"]


```
Sanction: ["date", "provisions", "unscId", "entity", "program", "authorityId",  
"modifiedAt", "recordId", "country", "authority", "reason", "description",  
"sourceUrl", "listingDate", "publisher", "endDate", "summary", "duration",  
"startDate", "status"]  
Security: ["country", "classification", "type", "maturityDate", "currency", "amount",  
"ticker", "name", "registrationNumber", "isin", "issuer", "issueDate", "createdAt",  
"topics", "sourceUrl"]  
UnknownLink: ["endDate", "publisher", "summary", "status", "modifiedAt", "object",  
"subject", "startDate", "role"]  
Vessel: ["tonnage", "callSign", "pastFlags", "name", "modifiedAt", "buildDate",  
"country", "createdAt", "registrationNumber", "topics", "sourceUrl",  
"grossRegisteredTonnage", "imoNumber", "description", "address", "proof", "type",  
"alias", "notes", "flag", "mmsi"]
```