

Checkers Design Document

2me3

Contents

1	Introduction	2
2	Requirements of Checkers	2
3	Module Guide	3
3.1	Hardware Hiding Module	3
3.1.1	Input Module	3
3.2	Behaviour Hiding Module	3
3.2.1	Piece Module	3
3.3	Software Decision Hiding Module	4
3.3.1	Game1 Module	4
3.3.2	Board Module	4
3.3.3	FileIO Module	4
4	Uses Relationship	5
5	Changelog from Assignment 1 to Current	6
5.1	Board	6
5.2	Piece	6
5.3	Game1	6
6	Module Design (MIS and MID)	7
6.1	Piece Module	7
6.1.1	Interface	7
6.1.2	Implementation	7
6.2	Board Module	8
6.2.1	Interface	8
6.2.2	Implementation	9
6.3	Game1 Module	10
6.3.1	Interface	10
6.3.2	Implementation	10
6.4	FileIO Module	11
6.4.1	Interface	11
6.4.2	Implementation	11
6.5	Input Module	11
6.5.1	Interface	11
6.5.2	Implementation	12
7	Internal Evaluation	12

1 Introduction

This document contains the decomposition, uses relationship, traceability, and internal evaluation. Note: Red links and the Uses diagram are clickable hyperlinks (depending on your PDF reader).

2 Requirements of Checkers

1. Assignment 1 Requirements
 - 1.1. Must set up an 8x8 checkers board
 - 1.1.1. Squares will be either light or dark
 - 1.1.2. The Bottom right square must be light
 - 1.2. User must be able to choose the standard set up
 - 1.3. Board Rules
 - 1.3.1. User must be able to specify starting position of each piece
 - 1.3.2. Notation for specifying piece location must use standard form (A7 = B)
 - 1.3.3. User should be able to specify type (normal or king)
 - 1.3.4. If they specified every pieces starting position, user must be able to indicate if the set up is complete
 - 1.3.5. User should be able to clear the board
 - 1.4. Maximum of 12 white and 12 black pieces can be placed on the board
 - 1.5. Illegal placement notification:
 - 1.5.1. User should be notified if a piece choice is illegal
 - 1.5.2. A piece on a light square
 - 1.5.3. Exceeding the maximum number
 - 1.5.4. Spelling/ typing error
 - 1.5.5. There is already a piece there
 - 1.6. User should be notified if there in an inappropriate number of pieces on the board
Inappropriate includes:
 - 1.6.1. Blank board
2. Assignment 2 Requirements
 - 2.1. Load Saves
 - 2.1.1. Start Game from original starting positions
 - 2.1.2. Start a game from a previously stored state from a within a file
 - 2.1.3. Save a game to be resumed later
 - 2.2. Legal Moves and Crowning
 - 2.2.1. Make moves from one position to another, while making sure the move made is legal.

- 2.2.2. Simply move a piece to another square; jump the opponents piece (so that piece is removed from the board).
- 2.2.3. Crowning a piece to king
- 2.2.4. move kings in both directions (forwards and backwards).
- 2.2.5. Graphically or through code indicate possible movements.

3 Module Guide

3.1 Hardware Hiding Module

3.1.1 Input Module

Type	Hardware Module
Secret	This module translates mouse clicks and keyboard presses to be used by the rest of the software.
Requirements	None
Responsibilities	This module will take mouse and keyboard input and convert it to software usable states.
Uses	None
Design	6.5
Code File	Inside Game1.cs, and built into C#.
Explanation	The input module is a hardware hiding module since it translates hardware inputs to software.

3.2 Behaviour Hiding Module

3.2.1 Piece Module

Type	Software Module
Secret	This module hides and separates specific piece information.
Requirements	1.3.3.
Responsibilities	This will hold the necessary components to describe what a game piece will contain, which will be separate from the game board.
Uses	None
Design	6.1
Code File	Piece.cs
Explanation	The piece is a part of behaviour hiding since the piece module holds specific piece information and outputs values needed by other modules.

3.3 Software Decision Hiding Module

3.3.1 Game1 Module

Type	Software Module
Secret	This module hides how the graphics are displayed and how we switch between states of the game.
Requirements	1.2. 1.3.1. 1.3.2. 1.3.4. 1.3.4. 2.2.
Responsibilities	This module will be the responsible for the initial execution of the game, this class connects and launches critical components together.
Uses	3.3.2, 3.2.1, 3.1.1
Design	6.3
Code File	Game1.cs
Explanation	The module is a part of software decision hiding since it determines how we draw the graphics and what to do when we switch between states of the game.


3.3.2 Board Module

Type	Software Module
Secret	This module serves to hide the secret of how the board is defined internally.
Requirements	1.1. 1.3.1. 1.3.2. 1.3.3. 1.3.5. 1.4. 1.5. 1.6.
Responsibilities	This module is responsible for holding the necessary components and attributes to setup the board and describe piece locations.
Uses	3.2.1
Design	6.2
Code File	Board.cs
Explanation	The board is a part of software decision hiding since the board implements a data structure that holds the placement of the pieces, this data structure might be changed for increased performance. Another software decision is deciding how to take user input to parse the placement of pieces.

3.3.3 FileIO Module

Type	Software Module
Secret	This module allows the user to save the current game session as a plain text file and also load previous games by parsing the plain text file into a representation of the board.
Requirements	1.3.2. 2.1.
Responsibilities	This module is responsible for the load and saving of the current game
Uses	none
Design	6.4
Code File	FileIO.cs
Explanation	The module is a part of software decision hiding since it determines how the game will be saved and represented in a text file, and also how the file is parsed to reload a saved game file.

4 Uses Relationship



5 Changelog from Assignment 1 to Current

5.1 Board

- if statements modified to switch colours of pieces
- new getPiece that takes a vector argument so that mouse clicks can be used
- getPiece modified to throw an exception if the piece is not found
- getPieceArray added to return the entire array of pieces
- movePiece function added

5.2 Piece

- added a validMovements struct that holds all of the information about a pieces valid movement
- added an enumerated variable containing the valid movement directions
- added a getValidMovement function that returns the array of valid movements
- added a setValidMovements function that gives a piece the squares it is able to move to

5.3 Game1

- new enumerated variable added: PLAYER_TURN
- new variables added: currentPlayerTurn, fileIO
- new Texture2D variables: Menu.ButtonLoad, Playing.ButtonSave
- new View_Clickable: Playing.ButtonSave, clickable_SaveButton
- board.SquareSize has been changed into a constant
- new Vector2 variable: mouseBoardPosition
- graphics changed to include new load button
- switching of players turn added
- new restrictions on dragging ability so that pieces only moved correctly
- added more detailed clicking ability to restrict the movement of pieces on the correct turn
- actions upon clicking updated to allow for full playing
- takeInput function added that sets up the board if there is a file to open
- added setValidMovements functions to give every piece on the board the squares they can move to

Added Module

- added a new module FileIO to match requirement of being able to save and load games

6 Module Design (MIS and MID)

6.1 Piece Module

6.1.1 Interface

Types	
typeState	enumerate if the piece is normal or king
player	enumerate if piece owned by Black or White
Constants	
None	
Access Programs	
getType() : typeState	Retrieves the piece's current type.
setType(newType : typeState)	Changes the piece's type.
getOwner() : player	Says who owns the piece.

6.1.2 Implementation

Variables	
pieceType : typeState	holds current piece type
owner : player	holds information of the piece's owner
Access Programs	
getType() : typeState	
Inputs	None
Updates	None
Outputs	pieceType
Description	Returns the current type of the piece.
setType(newType : typeState)	
Inputs	newType
Updates	None
Outputs	pieceType
Description	Changes the type of piece to the type given.
getOwner() : player	
Inputs	None
Updates	None
Outputs	owner
Description	Returns which player the piece is owned by.

6.2 Board Module

6.2.1 Interface

Types

None

Constants

None

Access Programs

setUpBoard()	Sets up board based on user input.
getPiece(col : int, row : int) : Piece	This method is used to determine if a piece exists on a square of the board. If the piece does exist, we pass it along to the caller.
placePiece(col : int, row : int, piece : Piece)	Places the piece on the board while checking if the placement is legal (in terms of checkers).
movePiece(fromCol : int, fromRow : int, toCol : int, toRow : int)	Moves the piece from starting to end positions while checking if the movement is valid (in terms of checkers).
clear()	Removes all pieces from the board.

6.2.2 Implementation

Types

None

Constants

None

Variables

pieceArray : array	Contains all the Piece objects currently on the board in an array.
numWhitePieces : int	Holds the number of white pieces on the board as an integer.
numBlackPieces : int	Holds the number of black pieces on the board as an integer.

Access Programs

setUpBoard(input : string)

Inputs	input
Outputs	pieceArray, numWhitePieces, numBlackPieces
Updates	None
Description	Parses input to be interpreted as Piece locations. Place Piece on correct Piece location using the PlacePiece() access program. numWhitePieces' = numWhitePieces + c and numBlackPieces' = numBlackPieces + d where c and d are between 0 and 12. pieceArray' = pieceArray with c + d more PieceObjects.

getPiece(col : int, row : int) : Piece

Inputs	col, row
Outputs	piece
Updates	None
Description	Returns the piece currently at the location specified.

placePiece(col : int, row : int, piece : Piece)

Inputs	col, row, piece
Outputs	None
Updates	pieceArray, numWhitePieces, numBlackPieces
Description	If piece placement is valid, it will put it there in the data structure. Either numWhitePieces' = numWhitePieces + 1 or numBlackPieces' = numWhitePieces + 1. pieceArray' = pieceArray with one more Piece object.

movePiece(fromCol : int, fromRow : int, toCol : int, toRow : int)

Inputs	None
Outputs	None
Updates	None
Description	Moves piece at said location to the location specified.

clear()

Inputs	None
Outputs	pieceArray, numWhitePieces, numBlackPieces
Updates	None
Description	Clears the board of all pieces. pieceArray' = Array of null objects, numWhitePieces' = 0 or numBlackPieces' = 0.

6.3 Game1 Module

6.3.1 Interface

Types	
state	enumerate if the game is in Menu, Setup, or Playing
Constants	
	None
Access Programs	
Update()	Allows the game to run logic such as switching state, updating the game, and gathering input.
Draw()	Draws the correct graphics on screen depending on the state.
takeInput()	Takes user input for setting up a board.

6.3.2 Implementation

Variables	
currentState : state	holds information of the current state
input : string	holds board setup from user
board : Board	
pieceList : List	Holds information of where to graphically place each piece.
Access Programs	
Update()	
Inputs	None
Updates	currentState
Outputs	None
Description	Changes the state based on keyboard press or mouse presses on graphical buttons.
Draw()	
Inputs	board
Updates	pieceList
Outputs	None
Description	Draws the buttons, board tiles and pieces in proper place on the screen. The piece locations are stored in pieceList. And we just loop through the graphics objects to draw them each frame.
takeInput()	
Inputs	input
Updates	None
Outputs	board
Description	Takes user input and sends it to the board using board.SetupBoard().

6.4 FileIO Module

6.4.1 Interface

Types	None
Constants	None
Access Programs	
	Save(Board : Board, Turn : Piece.player) : void Saves the current board state
	Load(Board : Board) : String Loads the board with a previous board state

6.4.2 Implementation

Variables	
	path : String holds the path to the location of where the save file is to be placed
Access Programs	
	Save(Board : Board) : typeState
	Inputs Board, Turn
	Updates None
	Outputs None
	Description Saves the current game session, it parses the current board state and saves it to a file.
	Load(Board : Board)
	Inputs Board
	Updates None
	Outputs None
	Description Loads a new game with a previous save file. This will return the board state and the current turn.

6.5 Input Module

6.5.1 Interface

Types	
	Mouse enumeration of mouse button states
	Keys enumerates keyboard buttons
Constants	None
Access Programs	
	GetState() : Mouse Gets if mouse button is pressed.
	IsKeyDown(key : Keys) : bool Checks if the key is pressed.

6.5.2 Implementation

Variables

mouseState : Mouse	Holds if mouse is pressed.
mouseClickedPiece	Holds the graphical object the mouse is clicking on.
mousePos	Stores current mouse position.

Access Programs

GetState()

Inputs	None
Updates	None
Outputs	mouseState

IsKeyDown(key : Keys)

Inputs	None
Updates	None
Outputs	None

7 Internal Evaluation