

Introduction to CSS

Selecting Elements to Apply a Style

greenwich.edu.vn



Alliance with  Education


Table of Contents



PRIMARY SELECTORS



NESTED SELECTORS



PSEUDO SELECTORS

Relative to Element Content or State




Alliance with  Education

PRIMARY SELECTORS

Primary Selectors: Select by Tag

```
<span>Here's a span with some text.</span>  
  <p>Here's a p with some text.</p>  
<span>Here's a span with more text.</span>
```




Select all
 elements

```
span {  
  background: DodgerBlue;  
  color: #ffffff;  
}
```

Primary Selectors: Select by ID

```
<span id="top">Here's a span with some text.</span>  
<span>Here's another.</span>
```




Select ``
with `id="top"`

```
span#top {  
    background: DodgerBlue;  
}
```

Primary Selectors: Select by Class

```
<span class="sky">Here's a span with some text.</span>  
<span>  
  Another <span class="code">&lt;span&gt;</span>.&br/></span>
```




```
span.sky {  
  background: DodgerBlue;  
}  
.code {  
  font-family:  
    Consolas;  
}
```

** with
class="sky"**

**Elements with
class="code"**



Alliance with **FPT** Education




NESTED SELECTORS

Nested Selectors: Descendant

```
div.items a {  
  color: green;  
  font-weight: bold;  
}
```


<a> inside <div class="items">

```
<div class="items">  
  <a href="#">Item1</a>  
  <a href="#">Item2</a>  
  <a href="#">Item3</a>  
  <ul>  
    <li><a href="#">Item4</a></li>  
    <li><a href="#">Item5</a></li>  
    <li><a href="#">Item6</a></li>  
  </ul>  
</div>
```



Nested Selectors: Adjacent Sibling

<p> coming after <p>



```
p + p {  
  font-style: italic;  
  font-weight: bold;  
}
```

```
<div>  
  <p>I'm a paragraph</p>  
  <p>I am selected!</p>  
</div>  
<div>  
  <p>I'm a paragraph</p>  
  <h2>Monkey hair</h2>  
  <p>I am NOT selected</p>  
</div>
```

Nested Selectors: Direct Child

** directly contained in a <div>**


```
div > span {  
  background: DodgerBlue;  
}  
span { background: #fff; }
```

Direct child of <div>

```
<div>  
  <span>Span #1, in the div.  
    <span>Span #2, in the span that's...</span>  
  </span>  
</div>  
<span>Span #3, not in the div at all.</span>
```

Span #1, in the div. Span #2,
in the span that's...
Span #3, not in the div at all.

Nested Selectors: Multiple Classes




```
.apple { color: red }  
.orange { color: orange }  
.small { font-size: 16px }  
.apple.orange {  
  font-style: italic;  
}
```

Elements with
both classes

Element with
multiple classes

```
<h2 class="apple orange small">Apple + Orange</h2>  
<h2 class="apple">Apple</h2>  
<h2 class="orange">Orange</h2>
```

Attribute
title="menu"



```
a[title="menu"] {  
  text-decoration: none;  
  color: #962103;  
  font-size: 22px;  
}
```

```
<ul>  
  <li><a href="#">Home</a></li>  
  <li><a href="#">Products</a></li>  
  <li><a href="#" title="menu">Menu</a></li>  
</ul>
```

Multiple Selectors (Element, Element)



```
<h1>Welcome...</h1>
<h2>My name is...</h2>
<p>I live in Duckburg.</p>
<p>My best friend is...</p>
```

```
h1, h2, p {
    background: yellow;
}
```

Combining Multiple Selectors

```
h1#header.intro {  
  text-decoration:  
    underline;  
  color: #C00;  
}
```



```
<h1 id="header" class="intro">HTML and CSS</h1>
```

Problem: Photo Shoot Effect

- You are given a HTML file
- Create a Web page like the screenshot on the right
 - Constraints:
 - You are NOT allowed to change the HTML file
 - Just write the missing CSS



@import  Education

```
"https://fonts.googleapis.com/css?family=Lato:300,400,900";
```

```
* {
  margin: 0;
  padding: 0;
}
body {
  font-family: Arial, sans-serif;
  color: #fcfcfc;
  background-color: #355664;
  width: 960px;
  margin: 0 auto;
}
```



Solution: Photo Shoot Effect – CSS (2)

```
h1, h2, h3 {  
    font-family:  
        forte,Arial,sans-serif;}  
h1 {  
    font-size: 50px;  
    padding: 10px 0 0;  
    text-align: center;  
    text-transform: uppercase}  
h2 {  
    font-size: 40px;  
    letter-spacing: 15px;  
    text-align: center;
```

```
    text-transform: uppercase;  
    border-bottom: 3px solid  
#416371;  
    padding-bottom: 20px;}  
h3 {  
    text-align: right;  
    font-size: 30px;  
    font-weight: normal;  
    margin: 0 0 10px;}  
p {  
    line-height: 20px;  
    padding-bottom: 5px;}
```

Solution: Photo Shoot Effect – CSS (3)

```
figure + p {
    color: #94c258;
}
```

```
img {
    border: none;
    width: 500px;
    height: 300px;
}
div.article-content {
    margin: 15px 0;
}
```

```
nav {
    background: #355664;
    padding: 0 5px;
}
nav ul li {
    display: inline-block;
}
```



Solution: Photo Shoot Effect – CSS (4)

```
nav ul li a {  
    color: #ffffff;  
    display: inline-block;  
    font-size: 30px;  
    margin: 5px 2px;  
    padding: 7px 10px 4px;  
    text-transform: uppercase;}  
nav ul li:first-of-type > a {  
    color: #7CB3E9;  
    font-size: 30px;  
    text-transform: lowercase;  
}
```

```
nav ul a[title="sweet tabs"] {  
    color: #8EC45B;  
    font-size: 30px;  
    text-transform: none;  
}  
  
nav, article,  
nav ul li a, figure {  
    border-radius: 10px;  
}
```

Solution: Photo Shoot Effect – CSS (5)

```
article {  
    background-color: #213E4A;  
    margin: 0 0 10px;  
    padding: 20px;  
    height: 390px;}  
figure {  
    border: 3px solid #142830;  
    float: right;  
    height: 300px;  
    width: 500px;  
    margin-left: 15px;  
}
```

```
footer {  
    border-top: 3px solid  
#142830;  
    padding-top: 15px;  
    margin-bottom: 30px;  
    text-align: center;  
    font-size: 20px;  
}
```



Alliance with **FPT** Education



PSEUDO SELECTORS

Relative to Element Content or State

Pseudo Selector (:hover)


```
<a href="#">Go to Google</a>
```

```
a:hover {  
  color: #D48F29;  
  text-decoration:  
    underline overline;  
}
```




Pseudo Selector (:visited)

```
<a href="#">Go to Google</a>
```




```
a:visited {  
  color:#D48F29;  
}
```




Pseudo Selector (:active)

```
<h2>click anywhere</h2>
```

```
html:active {  
  background: yellow;  
}
```



Pseudo Selector (:first-line)



```
<p>Lorem ipsum dolor  
sit amet, consectetur  
adipiscing elit.  
</p>
```

```
p:first-line {  
  color:blue;  
  background-color: lightblue;  
}
```

Pseudo Selector (::before and ::after)

<h1>CSS Pseudo Selectors</h1>


```
h1::before { /* "« " */  
  content: "\00AB\0020"  
}
```

```
h1::after { /* " »" */  
  content: "\0020\00BB"  
}
```



Structural Pseudo-Classes: nth-child(n)


```
<tr><td>This is first row.</td></tr>  
<tr><td>This is second  
row.</td></tr>  
<tr><td>This is third row.</td></tr>  
<tr><td>This is fourth  
row.</td></tr>  
tr:nth-child(2n) {  
    background: #953113b;  
    color: #fff;  
}
```




Structural Pseudo-Classes: **`nth-child(n+1)`**

```
<tr><td>This is first row.</td></tr>  
<tr><td>This is second row.</td></tr>  
<tr><td>This is third row.</td></tr>  
<tr><td>This is fourth row.</td></tr>
```

```
tr:nth-child(2n+1) {  
  background: #95313b;  
  color: #fff;  
}
```




Structural Pseudo-Classes: nth-of-type(n)

Alliance with  Education

```
<p>This is first paragraph</p>  
<p>This is second paragraph</p>  
<p>This is third paragraph</p>  
<p>This is fourth paragraph</p>  
<div>  
  <p>This is first paragraph</p>  
  <p>This is second paragraph</p>  
</div>
```


```
p:nth-of-type(2) {  
  background: #95313b;  
  color: #fff;  
}
```



Structural Pseudo-Classes: first-of-type

```
<p>This is first paragraph</p>  
<p>This is second paragraph</p>  
<p>This is third paragraph</p>  
<p>This is fourth paragraph</p>  
<div>  
  <p>This is first paragraph</p>  
  <p>This is second paragraph</p>  
</div>
```

```
p:first-of-type {  
  background: #95313b;  
  color: #fff;  
}
```



Problem: Ancient Architecture


- You are given a HTML file:
- Create a Web page like at the screenshot
 - Constraints:
 - Don't change the HTML file
 - Just write the missing CSS




← → ↺

Ancient Roman architecture

Posted on 01.01.2017 by [Someone](#)




Ancient Roman architecture adopted the external language of classical Greek architecture for the purposes of the ancient Romans, but grew so different from Greek buildings as to become a new architectural style. The two styles are often considered one body of classical architecture. Roman architecture flourished in the Roman Republic and even more so under the Empire, when the great majority of surviving buildings were constructed. It used new materials, particularly concrete, and newer technologies such as the arch and the dome to make buildings that were typically strong and well-engineered. Large numbers remain in some form across the empire, sometimes complete and still in use.

 0 COMMENTS


VIEW POST

Ancient Greek architecture

Posted on 01.01.2017 by [Someone](#)




The architecture of ancient Greece is the architecture produced by the Greek-speaking people (Hellenic people) whose culture flourished on the Greek mainland, the Peloponnese, the Aegean Islands, and in colonies in Anatolia and Italy for a period from about 900 BC until the 1st century AD, with the earliest remaining architectural works dating from around 600 BC.[1] Ancient Greek architecture is best known from its temples, many of which are found throughout the region, mostly as ruins but many substantially intact. The second important type of building that survives all over the Hellenic world is the open-air theatre, with the earliest dating from around 525-480 BC.

 0 COMMENTS


VIEW POST

Ancient Indian Architecture

Posted on 01.01.2017 by [Someone](#)



Indian architecture is as old as the history of the civilization. The earliest remains of recognizable building activity in the India dates back to the Indus Valley cities. Among India's ancient architectural remains, the most characteristic are the temples, Chaityas, Viharas, Stupas and other religious structures. In ancient India, temple architecture of high standard developed in almost all regions. The distinct architectural style of temple construction in different parts was a result of geographical, climatic, ethnic, racial, historical and linguistic diversities. The Rock-cut structures present the most spectacular piece of ancient Indian art specimen. Most of the rock-cut structures were related to various religious communities.

 0 COMMENTS

VIEW POST

© Copyright OldWorld by Anonymous. Photos by Anonymous.

Solution: Ancient Architecture – CSS

```
@import
url( 'https://fonts.googleapis.com/cs
s?family=Indie+Flower' );
/* Also import 'Roboto' font */
body {
    font-family: Roboto,sans-serif;
    background: #e2d7aa;
    color: #000000;
    font-size: 16px;
    width: 1180px;
    line-height:24px;
```

```
margin: 0 auto; }

body>div.img-container>img{
    width: 1100px;
    height: 450px;
}

body>div.img-container {
    width: 1600px;
    height: 450px;
    margin-top: 65px;
}
```

Solution: Ancient Architecture – CSS (2)

```
h1 {  
    font-size: 60px;  
    font-family: 'Indie  
Flower', cursive;  
    letter-spacing: 5px;  
    text-align: center;  
    margin-top: 65px;  
}  
a {  
    text-decoration: none;  
}
```

```
nav {  
    margin: 30px;  
    text-align: center;  
}  
  
nav a {  
    text-decoration: none;  
    font-size: 28px;  
    color: #000000;  
}
```

Solution: Ancient Architecture – CSS (3)

```
nav ul li {  
    list-style: none;  
    display: inline;  
    padding: 0 12px 0 12px;}  
nav ul li:first-of-type a,  
nav ul li:last-of-type a {  
    padding-left: 0;  
    color: #0a2d4a;  
    font-weight: bold; }  
article {  
    width: 370px;  
    display: inline-block;}
```

```
main {  
    margin-top: 30px;  
}  
main > article img {  
    width: 350px;  
    height: 200px;  
    margin-bottom: 20px;  
}  
p {  
    width: 345px;  
    text-align: justify;  
    margin-bottom: 20px }
```

Solution: Ancient Architecture – CSS (4)

```
article img + p:first-letter {  
  font-family:  
    EucrosiaUPC sans-serif;  
  text-transform: uppercase;  
  font-size: 40px;}  
.readmore a, .comments a {  
  background:  
url(images/bg2.jpg);  
  color: #ffffff;  
  padding: 10px;  
  margin-top: 10px;  
  text-transform: uppercase;}
```

```
footer {  
  margin: 0;  
  padding: 10px 0 10px 0;  
  text-align: center;}  
article p:last-of-type  
span:first-of-type a::before {  
  content:  
url("images/comment.png");  
  position: relative;  
  padding: 10px;  
  right: 5px;  
  top: 7px;}
```

- CSS Selectors

```
span { background: DodgerBlue; }  
span#identified { color: #EEE; }  
span.sky { color: SkyBlue; }  
p + p { background: red; }
```



- Pseudo selectors

```
:hover, :visited, :active,  
::before, ::after ...
```

- [link one](#)
- [second link](#)
- [link three \(visited\)](#)
- [fourth link](#)