

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Instructors:

Dr. Nguyen An Khuong

Mr. Tran Anh Dung

Dr. Tang Khai Hanh

Dr. Dang Tuan Thuong

Pham Nhat Minh - 1910346, HCMUT.



University of Technology
Ho Chi Minh city

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Table of Contents

1 | 32

1. Introduction
2. DRNG Definition and Survey
3. DVRF Protocol
4. DRNG System for Blockchain-based Applications
5. Experiment and Result
6. Conclusion and Future Work

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Table of Contents

2 | 32

1. Introduction

2. DRNG Definition and Survey

3. DVRF Protocol

4. DRNG System for Blockchain-based Applications

5. Experiment and Result

6. Conclusion and Future Work


Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Motivation

3 | 32

Randomness is very important:

- Used in many applications in life: Gaming, Simulation, Voting, Cryptography, ...
- A reliable source of randomness is required for such applications.



Motivation


4 | 32

Producing randomness is hard.

- True random number generator (TRNG): Produce true random output, but slow and must be stored for testing error.
- Pseudo-random generator (PRNG): Fast, produce pseudo-random outputs. But the owner knows the whole generation process!
- Notorious example of PRNG: The backdoor in Dual EC DRBG of NSA. ¹



PRNG



Dual EC DRBG

¹https://en.wikipedia.org/wiki/Dual_EC_DRBG

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Objectives

6 | 32

In this thesis, we wish to fulfill the following objectives:

- Formally define the syntax and security properties of DRNGs.

In this thesis, we wish to fulfill the following objectives:

- Formally define the syntax and security properties of DRNGs.
- Conduct a systematic literature review and analyze the strengths and weaknesses of existing DRNG constructions.

Objectives

6 | 32

In this thesis, we wish to fulfill the following objectives:

- Formally define the syntax and security properties of DRNGs.
- Conduct a systematic literature review and analyze the strengths and weaknesses of existing DRNG constructions.
- Based on the results of our survey, specify the most suitable DRNG construction tailored for blockchain-based applications.

In this thesis, we wish to fulfill the following objectives:

- Formally define the syntax and security properties of DRNGs.
- Conduct a systematic literature review and analyze the strengths and weaknesses of existing DRNG constructions.
- Based on the results of our survey, specify the most suitable DRNG construction tailored for blockchain-based applications.
- Finally, apply the aforementioned protocol to construct a DRNG system for blockchain-based applications.

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Table of Contents

7 | 32

1. Introduction

2. DRNG Definition and Survey

3. DVRF Protocol

4. DRNG System for Blockchain-based Applications

5. Experiment and Result

6. Conclusion and Future Work

A DRNG consists of two **interactive protocols** **DRNGSetup**, **DRNGGen** and an **algorithm** **DRNGVerify** as follows:

- **DRNGSetup**(1^λ)($\{P\}_{P \in \mathcal{P}}$) : Executed by all participants in \mathcal{P} . Outputs a set **QUAL**, public parameter **pp**, state **st₀** and each **qualified** P_i holds a secret key **sk_i**.

A DRNG consists of two **interactive protocols** **DRNGSetup**, **DRNGGen** and an **algorithm** **DRNGVerify** as follows:

- **DRNGSetup**(1^λ)($\{P\}_{P \in \mathcal{P}}$) : Executed by all participants in \mathcal{P} . Outputs a set **QUAL**, public parameter **pp**, state **st**₀ and each **qualified** P_i holds a secret key **sk** _{i} .
- **DRNGGen**(**st** _{r} , **pp**)($\{P_i(\mathbf{sk}_i)\}_{i \in \mathbf{QUAL}}$) : Executed by all participants in **QUAL** with common inputs **st** _{r} , **pp**. Outputs a value Ω_r , a proof π_r update the state from **st** _{r} to **st** _{$r+1$} .


Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Formal Definition

8 | 32

A DRNG consists of two **interactive protocols** **DRNGSetup**, **DRNGGen** and an **algorithm** **DRNGVerify** as follows:

- **DRNGSetup**(1^λ)($\{P\}_{P \in \mathcal{P}}$) : Executed by all participants in \mathcal{P} . Outputs a set **QUAL**, public parameter **pp**, state **st**₀ and each **qualified** **P**_{*i*} holds a secret key **sk**_{*i*}.
- **DRNGGen**(**st**_{*r*}, **pp**)($\{P_i(\text{sk}_i)\}_{i \in \text{QUAL}}$) : Executed by all participants in **QUAL** with common inputs **st**_{*r*}, **pp**. Outputs a value **Ω**_{*r*}, a proof **π**_{*r*} update the state from **st**_{*r*} to **st**_{*r*+1}.
- **DRNGVerify**(**pp**, **Ω**_{*r*}, **π**_{*r*}, **st**_{*r*}) : Executed by anyone to verify the correctness of **Ω**_{*r*}. Outputs a bit **b** ∈ {0, 1}.



A secure DRNG protocol satisfies the following properties:²

- **Pseudo-randomness:** For any r , the output Ω_r is pseudo-random. More formally, if $(\Omega_r, \pi_r, \mathbf{st}_{r+1}) \leftarrow \text{DRNGGen}(\mathbf{st}_r, \mathbf{pp}) \langle \{P_i(\mathbf{sk}_i)\}_{i \in \text{QUAL}} \rangle$, then for any computational bounded adversaries \mathcal{A} , there is a negligible function **negl** such that

$$| \Pr[\mathcal{A}(\Omega_r, (\Omega_i)_{i=1}^{r-1}) = 1] - \Pr[\mathcal{A}(U, (\Omega_i)_{i=1}^{r-1}) = 1] | \leq \text{negl}(\lambda)$$

where U is **uniformly sampled** in $\{0, 1\}^\lambda$.

²<https://eprint.iacr.org/2019/1320.pdf>

A secure DRNG protocol satisfies the following properties:²

- **Pseudo-randomness**: For any r , the output Ω_r is pseudo-random. More formally, if $(\Omega_r, \pi_r, \mathbf{st}_{r+1}) \leftarrow \text{DRNGGen}(\mathbf{st}_r, \mathbf{pp}) \langle \{P_i(\mathbf{sk}_i)\}_{i \in \text{QUAL}} \rangle$, then for any computational bounded adversaries \mathcal{A} , there is a negligible function **negl** such that

$$|\Pr[\mathcal{A}(\Omega_r, (\Omega_i)_{i=1}^{r-1}) = 1] - \Pr[\mathcal{A}(U, (\Omega_i)_{i=1}^{r-1}) = 1]| \leq \text{negl}(\lambda)$$

where U is **uniformly sampled** in $\{0, 1\}^\lambda$.

- **Unbiasability**: Adversaries cannot control the distribution of the output for their own goal.

²<https://eprint.iacr.org/2019/1320.pdf>

A secure DRNG protocol satisfies the following properties:²

- **Pseudo-randomness**: For any r , the output Ω_r is pseudo-random. More formally, if $(\Omega_r, \pi_r, \mathbf{st}_{r+1}) \leftarrow \text{DRNGGen}(\mathbf{st}_r, \mathbf{pp}) \langle \{P_i(\mathbf{sk}_i)\}_{i \in \text{QUAL}} \rangle$, then for any computational bounded adversaries \mathcal{A} , there is a negligible function negl such that

$$|\Pr[\mathcal{A}(\Omega_r, (\Omega_i)_{i=1}^{r-1}) = 1] - \Pr[\mathcal{A}(U, (\Omega_i)_{i=1}^{r-1}) = 1]| \leq \text{negl}(\lambda)$$

where U is uniformly sampled in $\{0, 1\}^\lambda$.

- **Unbiasability**: Adversaries cannot control the distribution of the output for their own goal.
- **Liveness (Availability)**: The protocol must produce an output. In other words, $\Omega_r \neq \perp$ for all r .

²<https://eprint.iacr.org/2019/1320.pdf>

A secure DRNG protocol satisfies the following properties:²

- **Pseudo-randomness**: For any r , the output Ω_r is pseudo-random. More formally, if $(\Omega_r, \pi_r, \mathbf{st}_{r+1}) \leftarrow \mathbf{DRNGGen}(\mathbf{st}_r, \mathbf{pp})^{\langle \{P_i(\mathbf{sk}_i)\}_{i \in \mathbf{QUAL}} \rangle}$, then for any computational bounded adversaries \mathcal{A} , there is a negligible function \mathbf{negl} such that

$$|\Pr[\mathcal{A}(\Omega_r, (\Omega_i)_{i=1}^{r-1}) = 1] - \Pr[\mathcal{A}(U, (\Omega_i)_{i=1}^{r-1}) = 1]| \leq \mathbf{negl}(\lambda)$$

where U is uniformly sampled in $\{0, 1\}^\lambda$.

- **Unbiasability**: Adversaries cannot control the distribution of the output for their own goal.
- **Liveness (Availability)**: The protocol must produce an output. In other words, $\Omega_r \neq \perp$ for all r .
- **Public Verifiability**: For any r , an external verifier can check the correctness of Ω_r using $\mathbf{DRNGVerify}$.

²<https://eprint.iacr.org/2019/1320.pdf>

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

DRNG Classification

10 | 32

DRNGs are classified through their **cryptographic primitives** as follows:

Cryptographic Primitives	DRNG Constructions
Hash	Proof-of-work, RANDAO.
Publicly verifiable secret sharing	Randshare, SCRAPE, ALBATROSS.
Threshold signature	Drand, DFINITY.
Verifiable random function	Algorand, DVRF.
Homomorphic encryption	Nguyen et al., HERB.
Verifiable delay function	Minimal VDF Beacon, Harmony.

Advantages and disadvantages of DRNG constructions:

	Advantages	Disadvantages
Hash	Achieve $O(n^2)$ communication cost, $O(n)$ computation and verification cost.	Do not achieve Unbiasability and Liveness.
PVSS	Achieve full security properties.	Suffer $O(n^3)$ to $O(n^2 \log^2 n)$ computation and verification cost.
Thres. Sig.	- Achieve full security properties. - Achieve $O(n^2)$ communication cost.	Suffer $O(n \log^2 n)$ computation cost.
VRF	- Achieve $O(n^2)$ communication cost. - DVRF achieves full security properties. - Algorand enjoys $O(n)$ computation cost.	- DVRF suffers $O(n \log^2 n)$ computation cost. - Algorand does not achieve Unbiasability.
HE	- Achieve $O(n^2)$ communication cost. - HERB achieves full security properties. - Nguyen et al. enjoys $O(n)$ computation cost.	- HERB suffers $O(n \log^2 n)$ computation cost. - Nguyen et al. does not achieve Unbiasability.
VDF	- Achieve full security properties. - Achieve $O(n^2)$ communication cost and $O(n)$ verification cost.	Suffer very high computation cost.

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Summary

12 | 32

	Pseudorandom	Unpredictable	Unbiasability	Liveness	Public Ver.	Comm. Cost	Comp. Cost	Verf. Cost	Primitives
Proof-of-work	✗	✓	✗	✗	✓	$\mathcal{O}(n^2)$	very high	$\mathcal{O}(1)$	Hash
RANDAO	✓	✓	✗	✗	✓	$\mathcal{O}(n^2)$	$\mathcal{O}(1)$	$\mathcal{O}(n)$	Hash
RandShare	✓	✓	✓	✓	✓	$\mathcal{O}(n^3)$	$\mathcal{O}(n^3)$	$\mathcal{O}(n^3)$	PVSS
SCRAPE	✓	✓	✓	✓	✓	$\mathcal{O}(n^3)$	$\mathcal{O}(n^2 \log^2 n)$	$\mathcal{O}(n^2 \log^2 n)$	PVSS
ALBATROSS	✓	✓	✓	✓	✓	$\mathcal{O}(n^3)$	$\mathcal{O}(n^2 \log n)$	$\mathcal{O}(1)$	PVSS
Algorand	✗	✓	✗	✗	✓	$\mathcal{O}(n^2)$	$\mathcal{O}(n)$	$\mathcal{O}(1)$	VRF
DVRF	✓	✓	✓	✓	✓	$\mathcal{O}(n^2)$	$\mathcal{O}(n \log^2 n)$	$\mathcal{O}(n \log^2 n)$	VRF
Nguyen19	✓	✓	✗	✓	✓	$\mathcal{O}(n^2)$	$\mathcal{O}(n)$	$\mathcal{O}(n)$	HE
HERB	✓	✓	✓	✓	✓	$\mathcal{O}(n^2)$	$\mathcal{O}(n \log^2 n)$	$\mathcal{O}(n \log^2 n)$	HE
Harmony	✗	✓	✓	✓	✓	$\mathcal{O}(n^2)$	very high	$\mathcal{O}(n)$	VDF
Minimal VDF	✗	✓	✓	✓	✓	$\mathcal{O}(n^2)$	very high	$\mathcal{O}(n)$	VDF
Drand	✗	✓	✓	✓	✓	$\mathcal{O}(n^2)$	$\mathcal{O}(n \log^2 n)$	$\mathcal{O}(n \log^2 n)$	BLS Signature
DFINITY	✗	✓	✓	✓	✓	$\mathcal{O}(n^2)$	$\mathcal{O}(n \log^2 n)$	$\mathcal{O}(n \log^2 n)$	BLS Signature

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Table of Contents


13 | 32

1. Introduction
2. DRNG Definition and Survey
3. DVRF Protocol
4. DRNG System for Blockchain-based Applications
5. Experiment and Result
6. Conclusion and Future Work

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Components


14 | 32



Component: Distributed Key Generation

15 | 32


- Executed jointly by n participants.
- Generate a public-secret key pair $(pk = g^{sk}, sk)$ and a partial public-secret key pair $(pk_i = g^{sk_i}, sk_i)$ for each participant P_i .
- At least $t + 1$ partial secret keys are required to restore sk .



Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Component: VRF Based on Elliptic Curves

16 | 32



ECVRF construction: ³


- The public key pk is $pk = g^{sk}$.
- Let $h = H(X)$ and compute $Y = h^{sk}$.
- Compute the proof π to prove the knowledge of sk such that $pk = g^{sk}$ and $Y = h^{sk}$, then output (Y, π) .

³<https://eprint.iacr.org/2017/099.pdf>


Construction: Setup

17 | 32


DRNGSetup(1^λ) $\langle \{P\}_{P \in \mathcal{P}} \rangle$: For simplicity, see figure below.



$\text{DRNGGen}(\text{st}_r, \text{pp}) \langle \{P_i(\text{sk}_i)\}_{i \in \text{QUAL}} \rangle$: For simplicity, see figure below.



$\text{DRNGGen}(\text{st}_r, \text{pp}) \langle \{P_i(\text{sk}_i)\}_{i \in \text{QUAL}} \rangle$: For simplicity, see figure below.




Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Construction: Generation

20 | 32

DRNGGen(st_r, pp) $\langle \{P_i(\text{sk}_i)\}_{i \in \text{QUAL}} \rangle$: For simplicity, see figure below.




Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Construction: Verification

21 | 32

DRNGVerify(pp, Ω_r , π_r , st_r) : For simplicity, see figure below.



Complexity Analysis

22 | 32

The communication, computation and verification complexity of the protocol depend on the number of participants, denoted by n as follows:

- Communication Complexity: $O(n^2)$.
- Computation Complexity per Participant: $O(n \log^2 n)$.
- Verification Complexity per Verifier: $O(n \log^2 n)$.

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Table of Contents

23 | 32

1. Introduction
2. DRNG Definition and Survey
3. DVRF Protocol
4. DRNG System for Blockchain-based Applications
5. Experiment and Result
6. Conclusion and Future Work

Randomness for Blockchain

24 | 32

- Various blockchain-based games (e.g., Axie Infinity) require randomness for distributing prizes, items.
- Existing blockchain systems employ older DRNGs such as RANDAO → Do not satisfy required security properties.
- We propose to use DRVF protocol above to generate randomness for such applications.





Figure: Axie Infinity ⁴

⁴<https://axieinfinity.com>

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Proposed System Architecture

25 | 32




- **Dapp:** An application wishes to use a random number.

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Proposed System Architecture

25 | 32




- **Dapp**: An application wishes to use a random number.
- **Smart Contract**: Forward random number request from Dapp to DVRF and verify the result from DVRF.

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Proposed System Architecture

25 | 32




- **Dapp**: An application wishes to use a random number.
- **Smart Contract**: Forward random number request from Dapp to DVMF and verify the result from DVMF.
- **DVMF**: Used for generating randomness in a distributed manner.

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Proposed System Workflow

26 | 32



Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Table of Contents

27 | 32

1. Introduction
2. DRNG Definition and Survey
3. DVRF Protocol
4. DRNG System for Blockchain-based Applications
5. Experiment and Result
6. Conclusion and Future Work

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

NIST Test Suite

28 | 32

- Developed and maintained by the U.S. government.

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

NIST Test Suite

28 | 32

- Developed and maintained by the U.S. government.
- Widely used in the industry standard.

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

NIST Test Suite

28 | 32

- Developed and maintained by the U.S. government.
- Widely used in the industry standard.
- Consists of different tests to test the randomness of binary sequences produced by hardware or software-based cryptographic random or pseudo-random number generators following different **statistical tests**.

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

NIST Test Suite

28 | 32

- Developed and maintained by the U.S. government.
- Widely used in the industry standard.
- Consists of different tests to test the randomness of binary sequences produced by hardware or software-based cryptographic random or pseudo-random number generators following different **statistical tests**.
- We use NIST Test Suite to test our implementation with **20** numbers; each number is **100000** bits long.

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Result

29 | 32

Test name	Pass rate
Frequency	20/20
Frequency in a Block	20/20
Run	20/20
Longest Run of Ones in a Block	19/20
Binary Matrix Rank	20/20
Discrete Fourier Transform	20/20
Non-Overlapping Template Matching	20/20
Overlapping Template Matching	20/20
Universal Statistical	20/20
Linear Complexity	19/20
Serial	20/20
Approximate Entropy	19/20
Cumulative Sums	20/20

In the test suite ⁵, for **20** numbers, the acceptable pass rate is equal to $0.99 \pm 3\sqrt{(0.99(1 - 0.99)/20)} = [0.923, 1] \rightarrow$ all test passed.

⁵<https://csrc.nist.gov/pubs/sp/800/22/r1/upd1/final>

Research and Development of a Decentralized Random Number Generation Protocol for Blockchain-based Application

Table of Contents

30 | 32

1. Introduction
2. DRNG Definition and Survey
3. DVRF Protocol
4. DRNG System for Blockchain-based Applications
5. Experiment and Result
6. Conclusion and Future Work

Conclusion.

- A summary of the thesis has been accepted at IUKM 2023. ⁶
- Formally defined the syntax and security properties of DRNGs.
- Conducted a systematic literature review of existing DRNGs.
- Specified a DRNG construction tailored for blockchain-based applications.
- Applied the aforementioned protocol to construct a DRNG system for blockchain-based applications.
- Assessed the security of the system using the NIST test suite.

Future Work.

- Construct DRNGs that are secure against quantum threats.
- Define DRNGs using the Universal Composable Security framework.

⁶<https://www.jaist.ac.jp/IUKM/IUKM2023/>

Research and Development of a Decentralized Random Number Generation
Protocol for Blockchain-based Application

Thank you

32 | 32

Thank You for Listening!