

PORTLAND STATE UNIVERSITY
DEPARTMENT OF ELECTRICAL AND COMPUTER ENGINEERING



2019 ECE CAPSTONE
TEAM 21

FACULTY ADVISOR: ROY KRAVITZ, M.S.

SPONSOR: SIGHTLINE APPLICATIONS

UAV Landing Aid - Design Report

Authors:

KIMBALL S. DAVIS

TAI PHAM

May 14, 2019

Abstract

SightLine Applications has developed a precision visual landing aid for UAV's. The Landing Aid supports autonomous landing operations by automatically finding and tracking an easy to place landing pattern. Integration of the SightLine Landing Aid for end users is problematic. Often drone operators want to just "plug in" a component and fly their mission. Installing software components is acceptable, but any requirement for programming is a barrier to entry or a complete show stopper. Various cables, power, and other electrical connectivity issues are also difficult for vehicle integrators. Rugged or at least robust mechanical enclosures, easy mounting, and environmental reliability are equally important. Lastly, choice of optical system (camera) for the greatest range has caused adoption delays in that it has been a decision left to the integrator. Recognizing the needs from the end-users, Sightline wants to develop a plug and play precision landing aid for UAVs and expect that this new project will be highly valuable to a wide range of multi-copter integrators.

Our solution to the problem involves: I. Selecting, and building a consumer level quadcopter that will be easily customizable for testing II. Designing a camera that will connect directly to the SightLine hardware, distribute power, and facilitate communication III. Research and development of documentation and software to meet plug and play expectations.

The selection, build, and testing of a custom quadcopter is a complicated task with many variables. GPS signal degradation made indoor flight tests impossible, and safe outdoor testing locations were hard to find. We did successfully build, and autonomously fly the Pixhawk 4 controlled quadcopter using QGroundControl mission planning software. In the meantime, a camera for the SightLine hardware was designed utilizing an AR0134CS optical sensor. The camera board was also designed to provide power distribution, and facilitate communication between the Pixhawk 4 flight controller and the SightLine hardware.

Insert SLA1500CAM Test Results summary Here

Insert Software Results summary Here

What are the limitations?

What are the Future implications of the project?

Contents

1 Project Overview	4
1.1 Background	4
1.2 Problem Definition	4
1.3 Solution	4
1.4 Project Management	5
1.4.1 Project Timeline	5
2 Results(Technical Detail)	5
2.1 Quadcopter	5
2.2 Hardware	5
2.3 Software	6
3 Conclusion/What's Left to do	6
4 Appendix	7
4.1 I	7
4.2 II	7
4.3 II	7
4.4 IV	7
4.5 V	7
5 References	8

List of Figures

1	<i>This is a caption for a blank figure</i>	5
2	<i>This is a caption for a blank figure</i>	6
3	<i>This is a caption for a blank figure</i>	6
4	<i>This is a caption for a blank figure</i>	6

1 Project Overview

1.1 Background

SightLine Applications has developed a precision visual landing algorithm that provides an excellent set of benefits:

- Works in degraded and denied GPS environments – Safety and reliability
- Reduces operator training and landing phase complexity.
- Provides detection functions for landing zone safety - detect people, animals, or objects from entering the landing zone
- Provides a rich set of telemetry for flight controllers. 30 Hz data with range, XY offsets, relative azimuth, etc.
- Supports landing on moving platforms - ground vehicles, marine.
- Is not impacted by bright sun or low light conditions.
- Can be used with Thermal (IR) cameras as well as visible (EO) cameras
- Effective range of operation (distance to target) only limited by the size of the landing pattern used

1.2 Problem Definition

Integration of the SightLine Landing Aid for end users is problematic for two main reasons:

1. Connectivity issues with a wide range of cameras.
2. Communication issues with a wide range of flight controller hardware and software.

Currently the end user selects a camera to be used with the SightLine processing hardware. A wide range of cameras must be supported, and custom AB boards must be designed for each one to interface with the SightLine hardware. Each of these AB boards can have cable, power, and electrical connectivity issues that are problematic for the end user. There is also a wide range of flight controller hardware and software, each with a myriad of different communication protocols. Installing software components to facilitate this communication is fine for the end user, but if any programming needs to be done this is usually a complete show stopper.

1.3 Solution

The proposed solution to these problems is to develop an all in one unit (SightLine Hardware + Camera) with plug and play capabilities that can be directly connected to a consumer level flight controller. By doing so camera connectivity and selection problems are eliminated, and communication and software deployment are made much easier for the end user. We will build an off the shelf quadcopter with autonomous flight capabilities to test communication between current SightLine hardware, and our newly designed camera interface.

1.4 Project Management

The project is divided into three sections:

1. Choosing and building an "off the shelf" quadcopter that uses a Pixhawk 4 flight controller that can be used for testing
2. Designing a camera based on the On-Semi AR0134CS optical sensor that connects directly to the SightLine hardware, distributes power, and facilitates communication between the flight controller and SightLine hardware
3. Research and development of documentation and software installers to meet plug and play expectations using QGroundControl flight control and mission planning software

Insert Project Roles and Responsibilities here

1.4.1 Project Timeline

Insert Project Timeline here

2 Results(Technical Detail)

2.1 Quadcopter

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Figure 1: *This is a caption for a blank figure*

2.2 Hardware

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Figure 2: *This is a caption for a blank figure*

2.3 Software

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Figure 3: *This is a caption for a blank figure*

3 Conclusion/What's Left to do

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Figure 4: *This is a caption for a blank figure*

4 Appendix

4.1 I

4.2 II

4.3 II

4.4 IV

4.5 V

5 References

1. Mali, P. (1960). *Magnetic Amplifiers*. New York, NY: John F. Rider.
2. Figure 1. Simple saturable reactor. Reprinted from *Magnetic Amplifiers*(pg. 27), by Paul Mali, 1960, New York, NY, John F. Rider Publisher, Inc.
3. Figure 2. Full-wave self-saturating magnetic amplifier. Reprinted from *Magnetic Amplifiers*(pg. 35), by Paul Mali, 1960, New York, NY, John F. Rider Publisher, Inc.