

[About viralpatel.net](#)[Join Us](#)[Advertise](#)[Search](#)

VIRALPATEL.NET

VEEAM

RECORDED WEBINAR

SQL Server Granular Recovery  
Treat Your Databases Right[Home](#)  
[Android](#)  
[Java](#)  
[Spring](#)  
[Frameworks](#)  
[Database](#)  
[JavaScript](#)  
[Web](#)  
[More...](#)

FOLLOW:



# Spring 4 MVC Tutorial Maven Example – Spring Java Configuration



BY VIRAL PATEL · JUNE 24, 2016



RECENT POSTS

**Spring 4 MVC Tutorial with Eclipse, Maven** – Spring 4 MVC is the newer version of our favorite Java MVC framework. A lot has improved in Spring since the [Spring 3 MVC](#). In this tutorial we will create a simple web application from scratch in Eclipse that will use Spring's latest version 4 MVC framework and Maven configuration. Also we will use Java configuration to configure Spring instead of older XML configuration.

## Getting started with Spring 4 MVC Tutorial

### 1. Create a new Maven project

First things first, we will bootstrap a quick Maven project in Eclipse. Follow these simple steps and create a simple webapplication.



[Spring 4 MVC REST Controller Example \(JSON CRUD Tutorial\)](#)

---

[Spring 4 MVC Tutorial Maven Example – Spring Java Configuration](#)

---

[Find Process ID of Process using a Port in Windows](#)

---


[How to Embed Tomcat within Maven Project – Run Tomcat with Maven](#)

---


[Bootstrap Navbar Menu without JavaScript](#)

---

**1.1** First in Eclipse go to **File -> New** and from New project dialog select **Maven Project**.




**1.2** From New Maven Project dialog, leave the options as shown below and press **Next**.




**1.3** Now select the project Archetype from the options. Type "web" in the filter text and select **maven-archetype-webapp**.







1.4 As shown below, provide the Group Id and Artifact Id. For this example I have given Group Id `net.viralpatel.spring` and Artifact Id as `HelloWorld`.



1.5 Once you press **Finish**, Eclipse should start generating Maven webapp using maven-archetype-webapp. **Progress** view should show the progress of this step.



New project is created with `pom.xml`,  
`WebContent` folder and `src` folder.



## 2. Add Spring 4 MVC Maven dependencies

Project structure is created. Now let's start and add first the maven dependencies for Spring 4 MVC in our `pom.xml` file.

Update `pom.xml` file and add following dependencies.

`pom.xml`

```
<project xmlns="http://maven.apache.org/POM/4.0.0"
  xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
    http://maven.apache.org/maven-v4_0_0.xsd">
  <modelVersion>4.0.0</modelVersion>
  <groupId>net.viralpatel.spring</groupId>
  <artifactId>HelloWorld</artifactId>
  <packaging>war</packaging>
  <version>0.0.1-SNAPSHOT</version>
  <name>HelloWorld Maven Webapp</name>
  <url>http://maven.apache.org</url>
  <properties>
    <java-version>1.7</java-version>
```

12

&lt;/properties&gt;

15

&lt;dependencies&gt;

19

```

</dependency>
<dependency>
  <groupId>javax.servlet
  <artifactId>javax.serv
  <version>3.0.1</versio
  <scope>provided</scope
</dependency>
<dependency>
  <groupId>javax.servlet
  <artifactId>jstl</arti
  <version>1.2</version>
</dependency>
</dependencies>
<build>
  <finalName>HelloWorld</fir
  <pluginManagement>
    <plugins>
      <plugin>
        <groupId>org.a
        <artifactId>ma
        <version>2.3.2
        <configuration>
          <source>$+
          <target>$+
        </configuratio
      </plugin>
      <plugin>
        <groupId>org.a
        <artifactId>ma
        <version>2.4<,
        <configuration>
          <warSource
          <warName>h
          <failOnMis
        </configuratio
      </plugin>
    </plugins>
  </pluginManagement>

```

```
</build>  
</project>
```

After updating pom.xml, Eclipse's maven plugin should start resolving the dependencies.

### 3. Set Annotation based Configuration for Spring 4 MVC tutorial

For this Spring 4 MVC tutorial we are going to use Spring's Java based configuration or annotation based configuration instead of old XML configuration. So now lets add the Java Configuration required to bootstrap Spring 4 MVC example in our webapp.

Create **AppConfig.java** file under **/src** folder. Give appropriate package name to your file.

```
/src/main/java/net/viralpatel/spring  
/config/AppConfig.java
```

```
package net.viralpatel.spring.config;
```


```
import org.springframework.context.an  
import org.springframework.context.an  
import org.springframework.context.an  
import org.springframework.web.servle  
import org.springframework.web.servle  
import org.springframework.web.servle  
import org.springframework.web.servle  
import org.springframework.web.servle  
import org.springframework.web.servle
```

```
@Configuration
@EnableWebMvc
@ComponentScan(basePackages = "net.vi
public class AppConfig extends WebMvc
@Bean
public ViewResolver viewResolver(
    InternalResourceViewResolver
    viewResolver.setViewClass(Jst
    viewResolver.setPrefix("/WEB-
    viewResolver.setSuffix(".jsp"

    return viewResolver;
}

@Override
public void configureDefaultServlet
    configurer.enable();
}

}
```



AppConfig class is annotated with Spring's annotations such as `@Configuration`, `@EnableWebMvc` and `@ComponentScan`.

The `@Configuration` annotation indicates that the class declares one or more `@Bean` methods. These methods are invoked at runtime by Spring to manage lifecycle of the beans. In our case we have defined `@Bean` for view resolver for JSP view.

The `@EnableWebMvc` is equivalent to `<mvc:annotation-driven />` in XML. It enables support for `@Controller` - annotated classes that use



`@RequestMapping` or `@GetMapping` to map incoming requests to certain methods.

The `@ComponentScan` annotation is equivalent to `<context:component-scan>` in XML. It will scan through the given package and register all the Controllers and beans.

The `configureDefaultServletHandling()` method is overridden and we enable default servlet handler. This will let other http request such as .css, .js slip through the usual `DispatcherServlet` and let the container process them. So now we can serve the static files css and javascript from our `WebApp` folder.

The above Annotation based configuration is equivalent to following XML configuration.

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework
xmlns:mvc="http://www.springframe
xmlns:context="http://www.springf
xmlns:xsi="http://www.w3.org/2001
xsi:schemaLocation="
    http://www.springframework.or
    http://www.springframework.or
    http://www.springframework.or
    http://www.springframework.or
    http://www.springframework.or
    http://www.springframework.or

<mvc:annotation-driven />

<context:component-scan base-pack

<bean id="jspViewResolver" class=
```

```

    <property name="viewClass" va
    <property name="prefix" value
    <property name="suffix" value
  </bean>

  <mvc:default-servlet-handler />

</beans>

```

## 4. Set Servlet 3.X Java Configuration

Create `AppInitializer` class under config package. This class will replace web.xml and it will map the spring's dispatcher servlet and bootstrap it.

```

/src/main/java/net/viralpatel/spring
/config/AppInitializer.java

```

```
package net.viralpatel.spring.config;
```

```
import javax.servlet.ServletContext;
import javax.servlet.ServletException
import javax.servlet.ServletRegistrat

```

```
import org.springframework.web.WebApp
import org.springframework.web.context
import org.springframework.web.servle

```

```
public class AppInitializer implement
```

```
public void onStartup(ServletCont
```

```
AnnotationConfigWebApplicatio
ctx.register(AppConfig.class)
ctx.setServletContext(contain

```

```
ServletRegistration.Dynamic s
```

```
servlet.setLoadOnStartup(1);
servlet.addMapping("/");

```

```
}  
  
}
```

We have configured the dispatcher servlet using standard Java based configuration instead of the older `web.xml`. Thus `web.xml` is no longer required and we can simply delete it.

## 5. Create the Controller

Create a sample controller

`HelloController.java` under controller package. This will have a simple `hello()` method that act as starting point. Notice how we have used `@GetMapping` annotation provided as part of Spring 4 MVC. This is equivalent to `@RequestMapping GET`.

```
/src/main/java/net/viralpatel/spring  
/controller/HelloController.java
```

```
package net.viralpatel.spring.control  
  
import org.springframework.stereotype  
import org.springframework.ui.Model;  
import org.springframework.web.bind.a  
  
@Controller  
public class HelloController {  
  
    @GetMapping("/hello")  
    public String hello(Model model)  
  
        model.addAttribute("name", "J  
  
    return "welcome";
```

```
}  
}
```

## 6. Create the View and Stylesheet

**6.1** Create welcome.jsp file under WEB-INF/views folder. This will be our primary view file.

```
/src/main/webapp/WEB-INF/views/welcome.jsp
```

```
<%@taglib uri="http://java.sun.com/jsp" %>  
<!DOCTYPE html>  
<html>  
<head>  
    <title>Spring 4 MVC Hello World E  
    <link rel='stylesheet' href='<c:u  
</head>  
<body>  
    <h2>Hello World, Spring MVC</h2>  
  
    <p>Welcome, ${name}</p>  
</body>  
</html>
```

**6.2** Next create the stylesheet for Spring MVC sample.

```
/src/main/webapp/resources/css/style  
.css
```

```
body {  
    background-color: wheat;  
}
```

## That's All Folks

It's time to execute the project. In Eclipse you can start Tomcat and run the project inside it. Or you can run the project using [Embedded Tomcat](#) using [Maven](#).

Once the application starts successfully, launch the browser and open

<http://localhost:8080/spring4/hello>.



## Download Source Code – Spring 4 MVC Tutorial

Source code of this Spring 4 MVC Hello World tutorial is available in Github.


Download – [spring4-mvc-example.zip](#)  
(6.54 KB)

Github – [spring4-mvc-example.git](#)

## Related Articles

1. [Spring 4 MVC REST Controller Example \(JSON CRUD Tutorial\)](#)
2. [Spring @RequestHeader Annotation example](#)

3. **Change spring-servlet.xml  
Filename (Spring Web Context  
Configuration Filename)**
4. **Spring 3 MVC Interceptor tutorial  
with example**
5. **Tutorial:Create Spring 3 MVC  
Hibernate 3 Example using Maven  
in Eclipse**
6. **Spring MVC Exception Handling  
using @ControllerAdvice  
annotation**
7. **Spring MVC Cookie example**

 Get our Articles via Email. Enter your email address.

Send Me Tutorials

Tags: [apache maven](#) [eclipse](#)

PREVIOUS STORY	NEXT STORY
Find Process ID of Process using a Port in Windows	Spring 4 MVC REST Controller Example (JSON CRUD Tutorial)

 YOU MAY ALSO LIKE...

Spring  
3  
MVC:  
Them  
es in  
Spring  
-  
Tutori  
al  
with  
Exam  
ple

Spring  
MVC  
Excep  
tion  
Handli  
ng  
using  
@Con  
troller  
Advic  
e  
annot  
ation

Spring  
MVC:  
Multip  
le  
Row  
Form  
Submi  
t  
using  
List of  
Beans

---

## 10 COMMENTS

**Nodine** © 22 July, 2016, 20:16

Hello,

Thank you for this usefull tutorial.

Juste a question please, why do you  
put "spring4" in the test URL ?

<http://localhost:8080/spring4/hello>.

Best Regards

Nordine

Reply

**Eddie**

⌚ 28 October, 2016, 10:32

The example is run under  
maven tomcat 7 plugin:

org.apache.tomcat.maven  
tomcat7-maven-plugin

...

/spring4

...

You can check it out in  
pom.xml and the above link  
Embedded Tomcat using  
Maven.

If you build it at war and  
deploy to a standalone  
tomcat instance, you need to  
use the war name as context

Thanks

Eddie

Reply

**Nilesh** ⌚ 1 September, 2016, 15:55

Hello,

This tutorial is not working for me.  
Can you tell me why did you put  
"spring" in the test URL and not the  
actual context name?

Thanks,

Nilesh

Reply

**Sucheta Hardikar**

⌚ 1 September, 2016, 19:37

I have copied your complete project  
for Spring MVC. But value of name  
mapped through Model object is not  
accessible in the JSP view. I tried with  
ELIgnored attribute , by enabling EL



by using page directive in the JSP. But still value of name is not accessible through JSP . What is the reason ?

Reply

**pape**

⌚ 16 September, 2016, 4:50

try with instead of `${name}`

Reply

**pape**

⌚ 16 September, 2016, 4:51

try with `c:out`

`value="${name}"`

Reply

**Aegis** ⌚ 28 September, 2016, 1:58

You need to include spring taglibs in the jsp to get the mapping correct.

Reply

**Anjul Goel** ⌚ 2 October, 2016, 23:03

Hi Sucheta,

The reason the name is not accesible is because you are using an old JSP 1.2 descriptor. Look out for the solution is the below link.

<https://www.mkyong.com/spring-mvc/modelandviews-model-value-is-not-displayed-in-jsp-via-el/>

Reply

**Geetha** ⌚ 13 October, 2016, 18:53

Hello Sir, Thanks for sharing, Good Work.

Reply

**Sandeep** ⌚ 28 October, 2016, 13:27

Could you please tell me why css is not loading in jsp. I am not able to see background color.

Reply

## LEAVE A REPLY

Comment

Name \*

Email \*

Website

Post Comment

---

ViralPatel.net © 2017. All Rights Reserved.

