

Basic JSF Tags

JSF provides a standard HTML tag library. These tags get rendered into corresponding html output. For these tags you need to use the following namespaces of URI in html node.

```
<html
  xmlns="http://www.w3.org/1999/xhtml"
  xmlns:h="http://java.sun.com/jsf/html"
>
```

Following are important *Basic Tags* in JSF 2.0:

S.N.	Tag & Description
1	h:inputText Renders a HTML input of type="text", text box.
2	h:inputSecret Renders a HTML input of type="password", text box.
3	h:inputTextarea Renders a HTML textarea field.
4	h:inputHidden Renders a HTML input of type="hidden".
5	h:selectBooleanCheckbox Renders a single HTML check box.
6	h:selectManyCheckbox Renders a group of HTML check boxes.
7	h:selectOneRadio Renders a single HTML radio button.
8	h:selectOneListbox Renders a HTML single list box.

9

[h:selectManyListbox](#)

Renders a HTML multiple list box.

10

[h:selectOneMenu](#)

Renders a HTML combo box.

11

[h:outputText](#)

Renders a HTML text.

12

[h:outputFormat](#)

Renders a HTML text. It accepts parameters.

13

[h:graphicImage](#)

Renders an image.

14

[h:outputStylesheet](#)

Includes a CSS style sheet in HTML output.

15

[h:outputScript](#)

Includes a script in HTML output.

16

[h:commandButton](#)

Renders a HTML input of type="submit" button.

17

[h:Link](#)

Renders a HTML anchor.

18

[h:commandLink](#)

Renders a HTML anchor.

19

[h:outputLink](#)

Renders a HTML anchor.

20

[h:panelGrid](#)

Renders an HTML Table in form of grid.

21

[h:message](#)

Renders message for a JSF UI Component.

22

[h:messages](#)

Renders all message for JSF UI Components.

23

[f:param](#)

Pass parameters to JSF UI Component.

24

[f:attribute](#)

Pass attribute to a JSF UI Component.

25

[f:setPropertyActionListener](#)

Sets value of a managed bean's property