Rose India TECHNOLOGIES PVT. LTD.

Recommend this on Google

J2me Tutorials

J2ME Tutorial
Image Icon Using Canvas Example
J2ME Hello World Example
J2ME Draw Triangle
Simple Line Canvas Example
Arc MIDlet Example
Text MIDlet Example
Access URL
Kxml Parser Example
KXML Parse Example
J2ME Kxml Connection Example
J2ME Kxml Example
J2ME Kxml Example
J2ME Tutorial
J2ME Draw String
Rectangle Canvas MIDlet Example
Graphics MIDlet Example
J2ME Tutorial
J2ME Servlet Example
J2ME Cookies Example
J2ME Frame Animation2
J2ME Frame Animation
J2ME RMS Read Write
J2ME Record Data Base
J2ME Audio Record
J2ME Record

Get Help MIDlet Example

Get Help MIDlet Example

Share on Google+

Search

Advertisement

Download Wallpapers
MoboGenie.com/Download-Wallpapers
Use Mobogenie to Download Wallpaper Save Data Cost. Download Now!

Ushuaia Ibiza Hotel Deals

Technical WritingTraining

HTML5 Remote Desktop/Apps

This example illustrates how to take help from any other text file which is stored in res folder in your midlet. In this example we are creating a form which name is "New Form". In this form we will add two buttons that are "Help" and "Exit".

Get Help MIDlet Example

Prior Index Next

This example illustrates how to take help from any other text file which is stored in **res** folder in your midlet. In this example we are creating a form which name is **"New Form"**. In this form we will add two buttons that are **"Help"** and **"Exit"**. The **"Exit"** button is used to Exit from current window, but the **"Help"** button is used to call **`helpDATA()`** function. In this function we get the text from **help.txt** file and stored it in a buffer like below:

```
private String helpDATA(){
  InputStream is = getClass().getResourceAsStream("help.txt");
  StringBuffer sb = new StringBuffer();
  try{
  int chars, i = 0;
  while ((chars = is.read()) != -1){
  sb.append((char) chars);
  }
  return sb.toString();
  }catch (Exception e){
  System.out.println("Can't create Buffers");
  }
  return null;
  }
```

The Application is as follows:

Related Latest Frameworks Category

J2ME Tutorial
Image Icon Using Canvas Example
J2ME Hello World Example
J2ME Draw Triangle
Simple Line Canvas Example
Arc MIDlet Example
Text MIDlet Example
Access URL
Kxml Parser Example
KXML Parse Example
>>>More Tutorials in this section...

Listener

J2ME Text Box Example

J2ME Timer Animation

J2ME Vector Example

J2ME Video Control Example

J2ME Event Handling Example

J2ME HashTable Example

J2ME Icon MIDlet Example

J2ME Image Item Example

J2ME Image Example

J2ME Item State Listener Example

J2ME Key Codes Example

J2ME KeyEvent Example

J2ME Label Example

J2ME Random Number

J2ME Read File

J2ME RMS Sorting Example

J2ME Timer MIDlet Example

Custom Item in J2ME

Appending Image into the J2ME Form

J2ME Convert Date To String

Appending string in J2ME Form

J2ME Enumeration Example

J2ME Display Size Example

J2ME Current Date And Time

>>>More Tutorials in this section...



A Complete Source Code of GetHelp.java

```
import java.io.*;
import javax.microedition.midlet.*;
import javax.microedition.lcdui.*;

public class GetHelp extends MIDlet implements CommandListener{
  private Display display;
  private Form form;
  private Command help, exit;
  private Alert alert;

  public void startApp(){
  display = Display.getDisplay(this);
  help = new Command("Help", Command.SCREEN, 1);
  exit = new Command("Exit", Command.EXIT, 1);
  form = new Form("New Form");
  form.addCommand(exit);
  form.addCommand(help);
  form.setCommandListener(this);
  display.setCurrent(form);
  }

  public void pauseApp(){}

  public void destroyApp(boolean unconditional){
  notifyDestroyed();
  }
```

AdChoices

► Java Tutorial
► Java IO
► Java Help

AdChoices

► Create a Database
► Java Applications
► File Java

AdChoices

► Download Java
► Code in Java
► Struts

I Recomme...

Java Swing
Robert Eckst...
INR 635.00

Let Us Java
Yashavant K...
INR 198.00

PROGRAMM...
E Balagurusa...
INR 219.00

Core Java V...
Horstmann C...
INR 585.00

1 2 3 4 > Privacy

```
  public void commandAction(Command c, Displayable s){
  String label = c.getLabel();
  if (label.equals("Help")){
  String string = helpDATA();
  if (string != null){
  alert = new Alert("Help", string, null, null);
  alert.setTimeout(Alert.FOREVER);
  display.setCurrent(alert, form);
  }
  } else if (label.equals("Exit")){
  destroyApp(false);
  }
  }

  private String helpDATA(){
  InputStream is = getClass().getResourceAsStream("help.txt");
  StringBuffer sb = new StringBuffer();
  try{
  int chars, i = 0;
  while ((chars = is.read()) != -1){
  sb.append((char) chars);
  }
  return sb.toString();
  }catch (Exception e){
  System.out.println("Can't create Buffers");
  }
  return null;
  }
}
```

Download Source Code

Advertisement

«Previous Index Next»

Follow us on Twitter, or add us on Facebook or Google Plus to keep you updated with the recent trends of Java and other open source platforms. Connect Me on Google+

Posted on: November 5, 2008 Like 0 Send Tweet 0 Share 0

We're on Follow

+750

Recommend the tutorial

0

Like

6,329 people like this. Be the first of your friends.

Ask Questions? Discuss: Get Help MIDlet Example

Post your Comment

Your Name (*) :

Your Email :

Subject (*):

Your Comment (*):

SUBMIT

COMMENTS

Nishit Dagli
March 7, 2013
Reviews.

Awesome Website. Keep it up. Please don't close it. Really helpful for freshers.

Services

Software Solutions
JSF Development
Outsourcing
ERP
M-Commerce
Flex Development

Website Development
Web Designing
Web Redesigning
Web Development
Logo Design
Web Design Packages
Domain Registration

Web Promotion Services
SEO Services
Search Eng. Optimization
Search Eng. Submission
SEO Tips
SEO Portfolio
Web Promotion Plans

Content Development
Content Development
Article Writing
Blog Writing
News Writing
SEO Copywriting
Technical Documentation
Article Marketing

Web Hosting Services
ASP.NET Hosting
Unix Hosting
E-Commerce Hosting
Windows Hosting
Hosting Plan

E-Commerce Solutions
CRM

Home Privacy Policy
© All Rights are Reserved for Rose India