Categories: PIM on Java ME | File Connection and PIM API (JSR-75) | Code Examples | Symbian | Series 40

Listing contacts in Java ME

This code example demonstrates how to list contacts in Java ME using the PIM API.

To read the contacts, use the method ContactList.items. There are several methods with this name, but in this snippet the one that has no parameters is used. For more information, see the Javadoc for JSR-75 PIM API (http://www.developer.nokia.com/document/Java_Developers_Library_v2/GUID-654A42A3-C453-411A-A153-366C08AEF058/overview-summary.html) .

Preconditions

In order to test this snippet there should be at least one contact in the database. The application also needs permission to read and write PIM database data.

Source

```
/**
  * Instantiates a listContacts.
  */
private void setupContactList() {
    listContacts = new List("Contact list", Choice.IMPLICIT);
    listContacts.addCommand(BACK_COMMAND);
    listContacts.setCommandListener(this);
}
```

```
* Executes the snippet.
private void executeSnippet() {
    openContactList();
 * Fills listContacts fith data read from PIM database and brings
 * the list to the foreground.
private void openContactList() {
    fillContactList();
   display.setCurrent(listContacts);
printString("Done");
 * Reads contacts list from PIM database 'Contacts' and fills listContacts  
* with contact 'name' field value.
private void fillContactList() {
    try {
        } catch (PIMException ex)
        printString(ex.toString());
        return;
    Enumeration contacts = null;
    Contact contact = null;
        printString("Getting contact list items");
        contacts =
                    contactList.items();
    } catch (PIMException ex) {
        releaseContactList();
printString(ex.toString());
        return;
    // Checking contact count
if (!contacts.hasMoreElements()) {
        printString("Contact list IS empty!");
    if (listContacts.size() > 0) {
    while (contacts.hasMoreElements()) {
    contact = (Contact)contacts.nextElement();
        * Closes the contact list if one is opened.
private void releaseContactList() {
```

```
if (contactList != null) {
    try {
        printString("Closing contact list");
        contactList.close();
    } catch (PIMException ex) {
        printString(ex.toString());
    }
}
contactList = null;
}
```

```
/**
  * From CommandListener.
  * Called by the system to indicate that a command has been invoked on a
  * particular displayable.
  * @param command the command that was invoked
  * @param displayable the displayable where the command was invoked
  */
public void commandAction(Command command, Displayable displayable) {
    if (command == BACK_COMMAND) {
        display.setCurrent(mainForm);
        // Close ContactList object instance
        releaseContactList();
    }
}
```

Postconditions

The contacts in the phonebook are listed on the screen.

Supplementary material

This code snippet is part of the stub concept, which means that it has been patched on top of a template application in order to be more useful to developers. The version of the Java ME stub application used as a template in this snippet is v1.1.

- The patched, executable application that can be used to test the features described in this snippet is available for download at Media:ListContacts.zip.
- You can view all the changes that are required to implement the above-mentioned features. The changes are provided in unified diff and colour-coded diff (HTML) formats in Media:ListContacts.diff.zip.
- For general information on applying the patch, see Using Diffs.
- For unpatched stub applications, see Example app stubs with logging framework.

Retrieved from "http://developer.nokia.com/Community/Wiki/index.php?title=Listing_contacts_in_Java_ME&oldid=203340"

This page was last modified on 22 July 2013, at 13:54. 269 page views in the last 30 days.

A Featured links Distribution Community Resources