Latest Tutorials | Questions and Answers | Ask Question

Questio

Search



Recommend this on Google



PHP

Home Java Frameworks Database Technology Web Development **Build/Test Tools** Servers J2ME Frame Animation Home J2me **J2ME Frame Animation J2me Tutorials** Animation J2ME Tutorial Advertisement This application shows to set the Image Icon Using Canvas Example Frame Animation and implement it in J2ME Tutorial the canvas class. In this example we J2ME Hello World are creating a frame using Gauge Example class. J2ME Draw Triangle J2ME Frame Simple Line Canvas **Animation** Example Arc MIDIet Example Text MIDIet Example This application shows to set the Frame Access URL Animation and implement it in the canvas Access URL class. In this example we are creating a frame using Gauge class. When the Kxml Parser Example command action call the "Run" command ,which display the canvas form. In the canvas form we are drawing three blocks, when form's action will run then the blocks separated from each other take place KXML Parse Example and move on the mobile window as shown in figure: J2ME Kxml Connection Example J2ME Kxml Example J2ME Kxml Example J2ME Tutorial J2ME Draw String Rectangle Canvas MIDlet Example Graphics MIDlet Example J2ME Tutorial J2ME Servlet Example J2ME Cookies Example J2ME Frame

Image Icon Using Canvas Example J2ME Hello World Example J2ME Draw Triangle Simple Line Canvas Example Arc MIDIet Example Text MIDIet Example Kxml Parser Example KXML Parse Example >>>More Tutorials in this section...

Animation2 **J2ME Frame** Animation J2ME RMS Read Write

J2ME Record Data

J2ME Audio Record

J2ME Record

Base

J2ME Frame Animation

10/3/13

Listener

J2ME Text Box Example

J2ME Timer Animation

J2ME Vector Example

J2ME Video Control Example

J2ME Event Handling Example

J2ME HashTable Example

J2ME Icon MIDIet Example

J2ME Image Item Example

J2ME Image Example

J2ME Item State Listener Example

J2ME Key Codes Example

J2ME KeyEvent Example

J2ME Label Example

J2ME Random

J2ME Read File

J2ME RMS Sorting Example

J2ME Timer MIDlet Example

Custom Item in J2ME

Appending Image into the J2ME Form

J2ME Convert Date To String

Appending string in J2ME Form

J2ME Enumeration Example

J2ME Display Size Example

J2ME Current Date And Time

>>>More Tutorials in this section...










#### FrameAnimation.java

```
import java.util.Timer;
import java.util.TimerTask;
import javax.microedition.lcdui.*;
import javax.microedition.midlet.*;
public class FrameAnimation extends MIDlet implements CommandListener,
  ItemStateListener{
 private Display display;
 protected boolean started;
 private Command exit, setup, run;
 private Form form;
 private AnimationCanvas canvas;
 private Gauge block, rate;
 private static final int FRAME RATE = 1;
 private static final int BLOCK COUNT = 1;
 protected void startApp() {
 if (!started) {
 display = Display.getDisplay(this);
 form = new Form("Frame Animation");
 rate = new Gauge("Set Frame", true, 10, FRAME_RATE);
 block = new Gauge("Set Blocks", true, 4, BLOCK COUNT);
 form.append(rate);
 form.append(block);
 form.setItemStateListener(this);
 canvas = createAnimationCanvas();
 exit = new Command("Exit", Command.EXIT, 0);
 setup = new Command("Setup", Command.SCREEN, 0);
 run = new Command("Run", Command.SCREEN, 0);
 canvas.addCommand(exit);
 canvas.addCommand(setup);
  form.addCommand(exit);
 form.addCommand(run);
 form.setCommandListener(this):
 canvas.setCommandListener(this);
 display.setCurrent(form);
 started = true;
 protected void pauseApp(){}
 protected void destroyApp(boolean unconditional){}
 public void commandAction(Command c, Displayable d) {
 String label = c.getLabel();
 if (label.equals("Exit")){
 notifyDestroyed();
  } else if (label.equals("Run")) {
 display.setCurrent(canvas);
  } else if (label.equals("Setup")){
 display.setCurrent(form);
```



AdChoices (>

- ► Java for Mobile
- ▶ Java Applications
- ► Java IO

AdChoices D

- ▶ Window Frame
- ▶ Java Applet
- ► Animation Graphics

AdChoices (>

- ▶ A Frame
- ► J2ME
- ► Compare Java Source

## I Recomme...

Effective Ja...



Let Us Java



Java Swing



Android Ap... android James Sheus. INR 344.00

```
1 2 3 4 >
amazonůn Privacy
```

```
public void itemStateChanged(Item item) {
if (item == block) {
int count = block.getValue();
if(count < 1) {
count = 1;
canvas.setBlockCount(count);
} else if (item == rate) {
int count = rate.getValue();
if (count < 1) {
count = 1;
canvas.setFrameRate(count);
protected AnimationCanvas createAnimationCanvas() {
return new AnimationCanvas();
class AnimationCanvas extends Canvas{
protected static final int SIZE = 4;
protected final int[] xSpeeds = { 2, -2, 0, -2 };
protected final int[] ySpeeds = { 2, -2, 2, -0 };
protected int background = display.isColor() ? 0x6699ff : 0xc0c0c0;
protected int foreground = display.isColor() ? 0xff3300 : 0;
protected int width = getWidth();
protected int height = getHeight();
protected int frameRate;
protected Block[] blocks;
protected Timer timer;
protected TimerTask updateTask;
public int getMaxBlocks() {
return blocks.length;
AnimationCanvas() {
setBlockCount(BLOCK COUNT);
setFrameRate(FRAME_RATE);
public void setBlockCount(int count) {
blocks = new Block[count];
createBlocks();
public int getBlockCount(){
return blocks.length;
public void setFrameRate(int frameRate) {
this.frameRate = frameRate;
if (isShown()){
startFrameTimer();
public int getFrameRate(){
return frameRate;
protected void paint(Graphics g) {
g.setColor(background);
```

```
g.fillRect(0, 0, width, height);
g.setColor(foreground);
synchronized (this) {
for (int i = 0, count = blocks.length; i < count; i++) {</pre>
g.fillRect(blocks[i].x, blocks[i].y, SIZE, SIZE);
}
protected void showNotify(){
startFrameTimer();
protected void hideNotify(){
stopFrameTimer();
private void createBlocks() {
int startX = (width - SIZE)/2;
int startY = (height - SIZE)/2;
for (int i = 0, count = blocks.length; i < count; i++) {</pre>
blocks[i] = new Block(startX, startY, xSpeeds[i], ySpeeds[i]);
protected void startFrameTimer(){
timer = new Timer();
updateTask = new TimerTask() {
public void run() {
moveAllBlocks();
long interval = 1000/frameRate;
timer.schedule(updateTask, interval, interval);
protected void stopFrameTimer() {
timer.cancel();
public synchronized void moveAllBlocks() {
for (int i = 0, count = blocks.length; i < count; i++) {</pre>
blocks[i].move();
repaint();
class Block{
int x;
int y;
int xSpeed;
int ySpeed;
Block(int x, int y, int xSpeed, int ySpeed) {
this.x = x;
this.y = y;
this.xSpeed = xSpeed;
this.ySpeed = ySpeed;
void move() {
x += xSpeed;
```

```
if(x <= 0 || x + SIZE >= width) {
    xSpeed = -xSpeed;
}

y += ySpeed;
if(y <= 0 || y + SIZE >= height) {
    ySpeed = -ySpeed;
}
}
}
}
```

## **Download Source Code**


Advertisemen




×

«Previous Index Next»

Follow us on <u>Twitter</u>, or add us on <u>Facebook</u> or <u>Google Plus</u> to keep you updated with the recent trends of Java and other open source platforms. <u>Connect Me on Google+</u>







## **COMMENTS**

# Services

Software Solutions
JSF Development
Outsourcing
ERP
M-Commerce
Flex Development

Website Development
Web Designing
Web Redesigning
Web Development
Logo Design
Web Design Packages
Domain Registration

Web Promotion Services SEO Services Search Eng. Optimization Search Eng. Submission SEO Tips SEO Portfolio Web Promotion Plans Content Development
Content Development
Article Writing
Blog Writing
News Writing
SEO Copywriting
Technical Documentation
Article Marketing

Web Hosting Services ASP.NET Hosting Unix Hosting E-Commerce Hosting Windows Hosting Hosting Plan E-Commerce Solutions

Home Privacy Policy
© All Rights are Reserved for Rose India