

|                              |  |  |  |  |  |  |  |  |  |  |
|------------------------------|--|--|--|--|--|--|--|--|--|--|
| $U_t/\text{mV}$              |  |  |  |  |  |  |  |  |  |  |
| $U_{\text{Super}}/\text{mV}$ |  |  |  |  |  |  |  |  |  |  |
| $U_m/\text{mV}$              |  |  |  |  |  |  |  |  |  |  |

|                              |  |  |  |  |  |  |  |  |  |  |
|------------------------------|--|--|--|--|--|--|--|--|--|--|
| $U_t/\text{mV}$              |  |  |  |  |  |  |  |  |  |  |
| $U_{\text{Super}}/\text{mV}$ |  |  |  |  |  |  |  |  |  |  |
| $U_m/\text{mV}$              |  |  |  |  |  |  |  |  |  |  |

3. 进入超导态后的乱真电势

电压  $U_{\text{Meas1}} = \underline{\hspace{2cm}} \text{mV}$ ,  $U_{\text{Meas2}} = \underline{\hspace{2cm}} \text{mV}$ , 电流  $I = \underline{\hspace{2cm}} \text{mA}$  (电源屏幕显示值)  
乱真电势  $U_{\text{Spur}} = \underline{\hspace{2cm}} \text{mV}$ , 样品电压  $U_{\text{Super}} = \underline{\hspace{2cm}} \text{mV}$ , 样品电阻  $R_{\text{Super}} = \underline{\hspace{2cm}} \Omega$

4. 升温测量

|                              |  |  |  |  |  |  |  |  |  |  |
|------------------------------|--|--|--|--|--|--|--|--|--|--|
| $U_t/\text{mV}$              |  |  |  |  |  |  |  |  |  |  |
| $U_{\text{Super}}/\text{mV}$ |  |  |  |  |  |  |  |  |  |  |
| $U_m/\text{mV}$              |  |  |  |  |  |  |  |  |  |  |

|                              |  |  |  |  |  |  |  |  |  |  |
|------------------------------|--|--|--|--|--|--|--|--|--|--|
| $U_t/\text{mV}$              |  |  |  |  |  |  |  |  |  |  |
| $U_{\text{Super}}/\text{mV}$ |  |  |  |  |  |  |  |  |  |  |
| $U_m/\text{mV}$              |  |  |  |  |  |  |  |  |  |  |

|                              |  |  |  |  |  |  |  |  |  |  |
|------------------------------|--|--|--|--|--|--|--|--|--|--|
| $U_t/\text{mV}$              |  |  |  |  |  |  |  |  |  |  |
| $U_{\text{Super}}/\text{mV}$ |  |  |  |  |  |  |  |  |  |  |
| $U_m/\text{mV}$              |  |  |  |  |  |  |  |  |  |  |