hadoop fs -ls /public

Simple Meaning

This command is used to **list all files and folders inside /public directory** in Hadoop HDFS.

It is similar to Linux:

ls /public

but here it works in **HDFS (Hadoop Distributed File System)**.

Breakdown

- hadoop fs → Use Hadoop file system commands
- -ls → Show files/folders list
- /public → Path of directory you want to check

Example

hadoop fs -ls /public

Output may look like:

```
drwxr-xr-x   - user supergroup          0 2026-04-21 10:00 /public/data
-rw-r--r--   1 user supergroup       2500 2026-04-21 10:05 /public/file1.txt
```

What You Can Understand from Output

Part	Meaning
d	directory (folder)
-	file
permissions	who can read/write
owner	file owner
group	group name
size	file size
date/time	modified time
path	file/folder name

Real Meaning of /public

Usually /public is a shared folder where multiple users can access files.

Example:

- datasets
- common reports
- shared csv files

If Folder Doesn't Exist

You may get:

ls: `/public': No such file or directory

Means /public is not created in HDFS.

Pro Tip

Use:

hadoop fs -ls /

to see root folders first.

Then:

hadoop fs -ls /public

Interview Answer

hadoop fs -ls /public lists all files and directories present inside /public path in HDFS.

mysql -A -u username

Why it Connects Quickly

Because -A means:

--no-auto-rehash

This tells MySQL client:

Do not load table/database names for auto-completion when starting.

So login becomes faster.

What Happens Without -A

Normal command:

mysql -u username -p

When MySQL client starts, it may scan metadata like:

- databases
- tables
- columns

This is used for:

- **TAB auto-completion**
- command-line name suggestions

If server has many databases/tables, startup can be slow.

What -A Does

With:

mysql -A -u username -p

MySQL skips that scanning step.

So:

✅ Faster login
✅ Better for huge production servers
✅ Good for admins

Tradeoff

You lose automatic tab completion initially.

Example:

Typing:

SELECT * FROM emp<TAB>

may not auto-complete.

You can enable later inside mysql:

rehash;

Internal Reason

Without -A, mysql client sends queries to information_schema / metadata to build completion cache.

With -A, it skips metadata fetch.

Less network calls + less parsing = faster connection.

Real World Usage

DBAs often use:

mysql -A -u root -p

on servers with thousands of tables.

Interview Answer

mysql -A connects quickly because it disables auto-rehash, which skips loading database/table metadata used for tab completion during startup.

Easy Memory Trick

A = Avoid metadata loading