Benchmarking Approximate Nearest Neighbour Search: Empirical Trade-offs, Failure Modes, and Mechanistic Analysis

Course: CS4.406 Information Retrieval & Extraction
Monsoon Semester 2026

Abstract

Dense retrieval at scale hinges upon high-throughput Approximate Nearest Neighbour (ANN) search. In this work, we conduct a rigorous, single-threaded comparative benchmark of three prominent vector indexing paradigms—Hierarchical Navigable Small World graphs (**HNSW**), Inverted File Flat (**IVF-Flat**), and Inverted File Product Quantization (**IVF-PQ**)—against an exact FAISS baseline on **SIFT-1M** (128D, Euclidean) and **GloVe-100** (100D, angular). We investigate query latency, memory footprints, and indexing throughput, and evaluate two core failure modes: semantic query difficulty via relative distance contrast on GloVe-100, and the curse of dimensionality under spherical distance concentration on custom synthetic distributions ($d \in [16, 256]$). We demonstrate that while HNSW achieves dominant Pareto throughput on clustered euclidean descriptors, its advantages narrow significantly on semantic hub topologies. Furthermore, we reveal how product quantization imposes a strict structural recall ceiling, and analyze the architectural decision boundary between exact and approximate retrieval under strict memory and latency budgets.

1 Introduction & Hardware Setup

Retrieving the k most similar vectors from an N-element collection forms the computational bottleneck of contemporary semantic search, recommendation engines, and retrieval-augmented generation (RAG). Exact brute-force scan requires $\mathcal{O}(N \cdot d)$ floating-point operations per query, which becomes prohibitive as N scales into millions. Approximate Nearest Neighbour (ANN) search trades a small fraction of retrieval recall for orders-of-magnitude lower query latency.

1.1 Experimental Environment

To eliminate confounding factors such as thread scheduling jitter, NUMA memory migration, and multicore contention, all experiments were conducted in a strictly single-threaded configuration on an isolated physical host.

- **Processor**: Intel(R) Core(TM) i5-1135G7 @ 2.40GHz (4 cores, 8 threads), L1d: 48 KB, L1i: 32 KB, L2: 1.25 MB, L3: 8 MB.
- **Memory**: 16 GB DDR4-3200 DRAM.
- **Operating System**: Linux x86_64 (Kernel 6.16.14).
- **Software Stack**: Python 3.14, FAISS-CPU (1.7.4+), NumPy 1.26+, OpenBLAS backend.
- **Thread Isolation**: Enforced via `OMP_NUM_THREADS=1`, `OPENBLAS_NUM_THREADS=1`, and `faiss.omp_set_num_threads(1)`.

1.2 Datasets & Metric Normalization

We evaluate on two canonical benchmarks from `ann-benchmarks`:

1. **SIFT-1M**: $1,000,000$ 128-dimensional local image descriptors with Euclidean (L_2) distance.
2. **GloVe-100**: $1,183,514$ 100-dimensional word vectors trained on Wikipedia/Gigaword under angular (cosine) distance.

Per assignment mandates, GloVe vectors were L_2-normalized to the unit sphere: $\mathbf{x}' = \mathbf{x}/\|\mathbf{x}\|_2$. For unit vectors $\mathbf{u}, \mathbf{v} \in \mathbb{S}^{d-1}$, the squared Euclidean distance is monotonically related to angular cosine similarity:

$$\|\mathbf{u} - \mathbf{v}\|_2^2 = \|\mathbf{u}\|_2^2 + \|\mathbf{v}\|_2^2 - 2\mathbf{u}^\top \mathbf{v} = 2 - 2\cos(\mathbf{u}, \mathbf{v}) \quad (1)$$

Minimizing Euclidean distance over normalized vectors is strictly isomorphic to minimizing angular distance $D_{\text{ang}} = 1 - \cos(\mathbf{u}, \mathbf{v}) = \frac{1}{2}\|\mathbf{u} - \mathbf{v}\|_2^2$.

Queries ($10,000$ total) were partitioned into $5,000$ validation queries (for tuning) and $5,000$ test queries (for final reported metrics).

2 Part 1: Exact Search Baseline

2.1 Custom Recall@10 with Distance Tie-Handling

In nearest neighbour evaluation, floating-point ties frequently occur at rank $k = 10$, particularly when multiple stored items reside at identical distances from a query. Standard set-intersection recall unfairly penalizes arbitrary tie-breaking by the index.

We implemented a custom metric Recall@k:

$$\text{Recall@}k(q) = \frac{1}{k} \sum_{i=1}^{k} \mathbb{I}\left(\text{ret}_i \in \text{GT}_k \vee \text{dist}(\text{ret}_i, q) \leq D_k(q) + \epsilon\right) \quad (2)$$

where $D_k(q)$ is the distance of the k-th ground-truth neighbour, and $\epsilon = 10^{-3}$ accounts for precision tolerances. The metric was validated with unit tests covering permutations, disjoint sets, partial overlaps, and equidistant boundary ties.

Validating FAISS exact search (`IndexFlatL2`) against the pre-stored ground truth in the HDF5 datasets yielded **100.00% agreement** on both SIFT-1M and GloVe-100.

2.2 Sequential vs. Batch Query Execution

We evaluated exact search speed over $5,000$ queries executed sequentially (1 query per call) versus in a single batched call ($5,000$ queries simultaneously) on full SIFT-1M and GloVe-100 under single-threaded execution.

Table 1: Exact Search Baseline Performance (Single Thread)

Dataset	Mode	Latency (ms)	QPS	Speedup
SIFT-1M	Sequential	27.01	37.0	—
SIFT-1M	Batch	8.48	117.9	**3.19**×
GloVe-100	Sequential	20.80	48.1	—
GloVe-100	Batch	6.22	160.8	**3.34**×

Mechanistic Explanation of the $3.2\times$–$3.3\times$ Speedup:

1. **BLAS GEMM vs. GEMV Arithmetic Intensity**: Sequential execution evaluates 1 query against N vectors, executing a Matrix-Vector product (`GEMV`). GEMV reads $N \times d \times 4$ bytes from memory for only $\mathcal{O}(Nd)$ arithmetic operations (intensity ≈ 0.5 FLOP/byte), stalling on DRAM latency. In contrast, batch execution groups Q queries into a Matrix-Matrix multiplication (`GEMM`), performing $2NQd$ operations over $(N + Q)d$ loaded floats. High arithmetic intensity enables OpenBLAS to tile registers and saturate vector units (AVX2/FMA).
2. **Cache Locality & Memory Bandwidth**: In sequential mode, the entire base matrix ($\approx 500\,\text{MB}$) must be re-read from DRAM $5,000$ times. In batch mode, blocks of the database loaded into the L2/L3 cache are simultaneously evaluated across all Q queries, drastically slashing DRAM bus traffic.
3. **Call Boundary Overhead**: Batching amortizes $5,000$ individual Python/C++ FFI transitions and per-query memory allocations.

3 Part 2: Benchmarking HNSW, IVF-Flat, and IVF-PQ

3.1 Index Architectures & Search sweeps

We benchmarked three representative index families across both datasets:

- **HNSW** (`IndexHNSWFlat`): Multi-layer proximity graph with build parameters $M \in \{16, 32\}$, $efConstruction \in \{40, 100\}$, and search sweep $efSearch \in [10, 512]$.
- **IVF-Flat** (`IndexIVFFlat`): Inverted file index with Voronoi coarse quantizer ($nlist \in \{256, 1024, 4096\}$), sweeping search centroids $nprobe \in [1, 128]$.
- **IVF-PQ** (`IndexIVFPQ`): Inverted file with Product Quantization codes ($nlist = 1024$, $m \in \{16, 32\}$ sub-vectors for SIFT, $m \in \{10, 20\}$ for GloVe, 8 bits/code), sweeping $nprobe \in [1, 128]$.

Every search timing was evaluated sequentially (1 query at a time) across the $5,000$ test queries, repeated, and the median latency recorded.

3.2 Results: QPS and Memory Costs

Table **??** summarizes the queries per second achieved by each index at Recall@10 of 0.90 and 0.95. Table **??** reports index build times, serialized index sizes, and bytes per vector at the operating point achieving Recall ≥ 0.95.

Table 2: Queries Per Second at Target Recall Levels

Dataset	Index	QPS @ Rec 0.90	QPS @ Rec 0.95
SIFT-1M	HNSW	14,648.4	**8,643.1**
SIFT-1M	IVF-Flat	8,880.4	3,368.1
SIFT-1M	IVF-PQ	N/A (< 0.90)	N/A (< 0.95)
GloVe-100	HNSW	2,008.5	N/A (< 0.95)
GloVe-100	IVF-Flat	3,069.9	**414.9**
GloVe-100	IVF-PQ	N/A (< 0.90)	N/A (< 0.95)

Table 3: Build Time and Memory at Recall ≥ 0.95


Dataset	Index	Build (s)	Size (MB)	B / vec	Rec
SIFT-1M	HNSW	166.58	747.8	784.1	0.9723
SIFT-1M	IVF-Flat	99.02	497.9	522.1	0.9762
SIFT-1M	IVF-PQ	15.95	38.8	40.7	0.7325†
GloVe-100	HNSW	261.63	758.7	672.1	0.9091†
GloVe-100	IVF-Flat	1.18	460.6	408.1	0.9692
GloVe-100	IVF-PQ	33.60	32.1	28.4	0.5224†

†Maximum recall achieved across all parameter sweeps (fails to reach 0.95).


3.3 Why Did Certain Indexes Fail to Reach 0.95 Recall?

1. **IVF-PQ Recall Ceiling**: On SIFT-1M, IVF-PQ capped at 0.7325; on GloVe-100, it plateaued at 0.5224. Product Quantization divides vectors into low-dimensional subspaces and assigns each sub-vector to a centroid. While Asymmetric Distance Computation (ADC) is extremely fast, it introduces unavoidable **quantization distortion**. Around the query, true 10-NN vectors frequently have true Euclidean distances that differ by fractions of a percent. The quantization noise swamps these delicate distance differences, causing severe rank-inversion. Without exact re-ranking on uncompressed vectors, increasing $nprobe$ scans more Voronoi cells but cannot overcome this fundamental quantization noise floor.

2. **HNSW Plateau on GloVe-100**: With $M \leq 32$ and $efSearch \leq 256$, HNSW stalled at 0.9091 recall. Word embeddings are characterized by severe **hubness** (certain central words act as nearest neighbours to thousands of other words) and high intrinsic dimensionality. During greedy graph routing, search paths become trapped in hub clusters with high local clustering coefficients, preventing the frontier from penetrating peripheral clusters without excessive link counts ($M \geq 64, efSearch \geq 512$).



(a) SIFT-1M Recall@10 vs. QPS Pareto Trade-off



(b) GloVe-100 Recall@10 vs. QPS Pareto Trade-off

Figure 1: Single-threaded trade-off curves for HNSW, IVF-Flat, and IVF-PQ against the exact baseline. Bold curves depict the optimal Pareto frontier envelope; dashed lines show individual build parameter sweeps.

4 Part 3: Experiment on Query Difficulty

4.1 Hypothesis Formulation

Pre-Committed Hypothesis: *Queries with low relative contrast (where the distance to the 10th neighbour is close to the 1st neighbour) will exhibit lower recall across all approximate indexes. Graph-based indexes (HNSW) will degrade less severely than IVF-Flat because graph routing traverses local cluster bridges, whereas IVF partitions vectors into rigid Voronoi cells that miss neighbours near cell boundaries.*

4.2 Experimental Design & Findings

We quantified query difficulty using **Relative Contrast**:

$$RC(q) = \frac{D_{10}(q)}{D_1(q)} \tag{3}$$

A low RC indicates high ambiguity (the 10th neighbour is nearly as close as the 1st), whereas a high RC indicates isolated, distinct nearest neighbours. The $5,000$ test queries on GloVe-100 were partitioned into 4 equal difficulty quartiles (Q1: Hardest to Q4: Easiest).

Table 4: Recall@10 across Query Difficulty Quartiles on GloVe-100

Index	Overall	Q1 (Hard)	Q2	Q3	Q4 (Easy)
HNSW ($efS = 40$)	0.5859	0.3845	0.5657	0.6824	0.7112
IVF-Flat ($npr = 16$)	0.7960	0.6584	0.7966	0.8627	0.8661
IVF-PQ ($npr = 16$)	0.2971	0.1439	0.2338	0.3493	0.4614




Figure 2: Recall@10 degradation across query difficulty quartiles on GloVe-100.

4.3 Hypothesis Assessment

- **Supported**: All indices degrade dramatically on hard queries. Across Q1, HNSW recall drops by 32.7% and IVF-Flat by 20.8% compared to Q4.
- **Refuted**: Contrary to our hypothesis, HNSW degraded **more severely** than IVF-Flat (spread of 0.3267 vs. 0.2077). In GloVe space, ambiguous queries lie in dense semantic hubs. Greedy routing on HNSW graphs gets trapped in hub vertices whose outgoing edges point to distant clusters, prematurely terminating the beam search. IVF-Flat with $nprobe = 16$ exhaustively checks 16 full Voronoi cells, guaranteeing brute-force evaluation of all points inside those regions regardless of local hub topology.

5 Part 4: Custom Hard Data Experiment

5.1 Hypothesis Formulation

Pre-Committed Hypothesis: *As the intrinsic dimension of uniformly distributed hyperspherical data increases from $d = 16$ to $d = 256$, distance concentration*

($\lim_{d\to\infty} \frac{D_{\max}-D_{\min}}{D_{\min}} \to 0$) will cause IVF-Flat Voronoi cells to lose discriminative partition capability, collapsing recall. Meanwhile, HNSW will experience a steep throughput (QPS) collapse as greedy routing degrades into an exhaustive random walk.

5.2 Experimental Design

We developed a seeded synthetic generator (`seed=42`) generating $100,000$ base vectors and $1,000$ queries uniformly sampled from the unit sphere $\mathbb{S}^{d-1}$ across four dimensionalities: $d \in \{16, 64, 128, 256\}$ ($d = 16$ serving as the unchanged control). We fixed search parameters at standard operating points (HNSW: $efSearch = 32$; IVF-Flat: $nprobe = 8$).

Table 5: The Curse of Dimensionality on Synthetic Spherical Data

d	Role	Contrast	HNSW Rec	HNSW QPS	IVF Rec	IVF QPS
16	Control	2.6137	0.9421	43,177	0.7165	52,988
64	Test	0.7730	0.2487	19,200	0.2835	33,512
128	Test	0.4826	0.1086	14,702	0.1856	14,241
256	Test	0.3171	0.0550	8,956	0.1342	10,575

5.3 Mechanisms & Hypothesis Verification

1. **Distance Concentration**: As proved by Beyer et al., under uniform spherical distributions, distances between all pairs of points concentrate around $\sqrt{2}$. The relative spread $(D_{\max} - D_{\min})/D_{\min}$ collapsed by $\mathbf{87.9}\%$ (from 2.61 at $d = 16$ down to 0.31 at $d = 256$).

2. **Catastrophic Recall Collapse**: With no meaningful distance contrast, Voronoi cell centroids in IVF become equidistant to the query, scattering the true 10-NN across dozens of clusters ($nprobe = 8$ captures only 13.4% of ground truth at $d = 256$). HNSW recall collapsed from 94.2% down to a disastrous **5.5%**, confirming that proximity graphs lose all routing gradient when edge distances become uniform.

3. **Throughput Collapse**: HNSW QPS dropped $4.8\times$ (from 43K to 9K), and IVF QPS dropped $5.0\times$, driven by the $\mathcal{O}(d)$ arithmetic scaling of distance kernels and L1/L2 cache evictions.

4. **Limitations**: We did not evaluate whether manifold learning (PCA/Autoencoders) or sub-space rotation (OPQ) could re-concentrate variance.

6 Part 5: Synthesis & Analytical Responses

6.1 Question 1: Fastest Index at 0.95 Recall

SIFT-1M: HNSW is the decisive winner, delivering **8,643.1 QPS** at Recall 0.95 ($M = 32, efS = 64$), outperforming IVF-Flat ($3,368.1$ QPS, $nlist = 4096, nprobe = 64$) by **2.57**$\times$ and exact baseline by **233.6**$\times$. SIFT descriptors reside on structured low-dimensional image gradient manifolds where Delaunay-like graphs enable logarithmic routing.

GloVe-100: The answer **flips dramatically**. IVF-Flat is the only index to achieve 0.95 recall within our tested sweeps (**414.9 QPS** at $nlist = 256, nprobe = 64$). HNSW failed to reach 0.95, plateauing at 0.909 ($2,008$ QPS). Word embedding spaces possess high intrinsic dimensionality ($\approx$ 30–45) and pronounced hubness. In such topologies, HNSW graphs suffer from short-cutting through hubs, whereas IVF-Flat benefits from exhaustive cluster inspection.

6.2 Question 2: Index Costs and Trade-offs of PQ

Build Time: IVF-Flat is the fastest to construct (1.2 s on GloVe, 99 s on SIFT for $nlist = 4096$) via k-means. HNSW requires intensive link construction and iterative pruning, taking 166 s on SIFT and 262 s on GloVe ($2.6\times$ slower).

Memory Footprint: HNSW requires 748 MB on SIFT and 759 MB on GloVe (672–784 B/vector), representing a **50% memory inflation** over raw uncompressed float arrays (512 B/vec) due to bidirectional neighbor adjacency lists ($2 \times M$ integer pointers per node). IVF-Flat has minimal overhead (+8–22 B/vector, ≈ 4 B/vec for cluster inverted lists).

What PQ Saves vs. Gives Up: IVF-PQ compresses vectors into 16–32 bytes, cutting index size from 512 MB down to **32–38 MB** (a **93% memory reduction**, 28–40 B/vector). It enables blindingly fast lookup ($70,000+$ QPS). However, it **gives up high recall entirely**: due to quantization noise, plain IVF-PQ cannot exceed 0.73 recall on SIFT and 0.52 on GloVe.

6.3 Question 3: Implications of Parts 3 and 4

Parts 3 and 4 demonstrate that headline benchmark metrics (e.g., "95% average recall at $8,000$ QPS") can be deeply misleading:

1. **Semantic Query Inequity**: Averaging recall conceals severe failure on ambiguous queries. In production, high-value exploratory queries (which have low contrast) will receive unacceptable recall ($< 38\%$), even though the overall benchmark claims acceptable service.

2. **Manifold Assumption Failure**: High performance relies on low intrinsic data dimensionality. If embeddings drift toward uniform or higher-dimensional spaces, both graph routing and Voronoi partitioning suffer catastrophic collapse without warning.

6.4 Question 4: Architecture Design Scenario

Constraints: 100 ms per-query SLA, 16 GB RAM budget.
Case A ($N = 150,000$ vectors, $d = 128$):

- Raw data footprint: $150,000 \times 128 \times 4\,\text{B} = 76.8\,\text{MB}$ (negligible).
- Exact search latency: From our baseline (27 ms for 10^6 vectors), search over 150K vectors requires $\approx \mathbf{4.05}$ ms sequentially ($\ll 100$ ms SLA).
- **Decision: Use Exact Search (FAISS IndexFlatL2)**. Zero build time, zero recall loss (100% precision), simple maintenance, and trivially satisfies both constraints.




Figure 3: Part 4: Failure mode analysis on synthetic spherical data. (A) Distance concentration collapses relative contrast $(D_{\max} - D_{\min})/D_{\min}$ and destroys retrieval recall. (B) High-dimensional distance computation overhead collapses query throughput.

Case B ($N = 10,000,000$ **vectors,** $d = 128$):

- Exact search latency scales linearly to $\approx$ **270** ms ($>$ 100 ms SLA). Exact search is ruled out.
- Raw vectors require 5.12 GB RAM.
- HNSW ($M = 32$) requires ≈ 784 B/vector $=$ **7.84** GB, plus allocator overhead, pushing dangerously close to the 16 GB system threshold when concurrent memory buffers are active.
- **Decision: Use IVF-Flat** with $nlist = 16,384$ (2^{14}) and $nprobe = 32$–64. Index size is only $\approx$ **5.16** GB (516 B/vector, easily fitting in 16 GB RAM). Query latency is $\approx$ **8** ms ($\gg 10\times$ faster than the 100 ms SLA) while attaining ≥ 0.95 recall.

6.5 Question 5: Two Ways Our Benchmark Could Be Misleading

1. **Sequential Single-Thread Bias vs. Concurrent Throughput**: We benchmarked strictly 1 query at a time on 1 CPU thread. Production systems serve concurrent queries across multi-core CPUs where memory bus saturation, NUMA cross-socket latency, and L3 cache thrashing severely degrade graph-based indices like HNSW, which rely on random memory pointer indirection. *We did not test multi-threaded concurrency.*

2. **Static Indexing vs. Dynamic Real-Time Updates**: Our benchmark constructed immutable, read-only indices. In real applications, vectors are continuously inserted, updated, and deleted. HNSW graphs suffer structural degradation, orphan nodes, and memory fragmentation under streaming updates, requiring expensive periodic index rebuilding. *We did not test update/churn degradation.*

7 Conclusion

Benchmarking reveals that no single ANN index dominates across all retrieval regimes. HNSW delivers unmatched QPS on well-clustered Euclidean data but incurs heavy memory inflation and struggles in high-hubness angular manifolds. IVF-Flat offers a robust, memory-efficient alternative with fast build times, while IVF-PQ provides extreme compression at the cost of high recall. In high-dimensional and ambiguous regimes, all ANN indexing algorithms degrade severely, underscoring the necessity of workload-specific evaluation beyond aggregate headline numbers.