



<http://algs4.cs.princeton.edu>

1.5 UNION-FIND

- ▶ *dynamic connectivity*
- ▶ *quick find*
- ▶ *quick union*
- ▶ *improvements*
- ▶ *applications*

Subtext of today's lecture (and this course)

Steps to developing a usable algorithm.

- Model the problem.
- Find an algorithm to solve it.
- Fast enough? Fits in memory?
- If not, figure out why not.
- Find a way to address the problem.
- Iterate until satisfied.

The scientific method.

Mathematical analysis.



<http://algs4.cs.princeton.edu>

1.5 UNION-FIND

- ▶ *dynamic connectivity*
- ▶ *quick find*
- ▶ *quick union*
- ▶ *improvements*
- ▶ *applications*

Dynamic connectivity problem

Given a set of N objects, support two operation:

- Connect two objects.
- Is there a path connecting the two objects?

connect 4 and 3

connect 3 and 8

connect 6 and 5

connect 9 and 4

connect 2 and 1

are 0 and 7 connected? ✗

are 8 and 9 connected? ✓


connect 5 and 0

connect 7 and 2

connect 6 and 1


connect 1 and 0

are 0 and 7 connected? ✓



A larger connectivity example

Q. Is there a path connecting p and q ?



A. Yes.

Modeling the objects

Applications involve manipulating objects of all types.

- Pixels in a digital photo.
- Computers in a network.
- Friends in a social network.
- Transistors in a computer chip.
- Elements in a mathematical set.
- Variable names in a Fortran program.
- Metallic sites in a composite system.

When programming, convenient to name objects 0 to $N - 1$.

- Use integers as array index.
- Suppress details not relevant to union-find.




can use symbol table to translate from site names to integers: stay tuned (Chapter 3)

Modeling the connections

We assume "is connected to" is an equivalence relation:

- Reflexive: p is connected to p .
- Symmetric: if p is connected to q , then q is connected to p .
- Transitive: if p is connected to q and q is connected to r , then p is connected to r .

Connected component. Maximal **set** of objects that are mutually connected.



{ 0 } { 1 4 5 } { 2 3 6 7 }




3 connected components

Implementing the operations

Find. In which component is object p ?

Connected. Are objects p and q in the same component?

Union. Replace components containing objects p and q with their union.



Union-find data type (API)

Goal. Design efficient data structure for union-find.

- Number of objects N can be huge.
- Number of operations M can be huge.
- Union and find operations may be intermixed.

```
public class UF
```

```
    UF(int N)
```

*initialize union-find data structure
with N singleton objects (0 to $N - 1$)*

```
    void union(int p, int q)
```

add connection between p and q

```
    int find(int p)
```

component identifier for p (0 to $N - 1$)

```
    boolean connected(int p, int q)
```

are p and q in the same component?

```
public boolean connected(int p, int q)
{ return find(p) == find(q); }
```

1-line implementation of connected()

Dynamic-connectivity client

- Read in number of objects N from standard input.
- Repeat:
 - read in pair of integers from standard input
 - if they are not yet connected, connect them and print out pair

```
public static void main(String[] args)
{
    int N = StdIn.readInt();
    UF uf = new UF(N);
    while (!StdIn.isEmpty())
    {
        int p = StdIn.readInt();
        int q = StdIn.readInt();
        if (!uf.connected(p, q))
        {
            uf.union(p, q);
            StdOut.println(p + " " + q);
        }
    }
}
```

% more tinyUF.txt

10

4 3

3 8

6 5

9 4

2 1

8 9

5 0

7 2

6 1

1 0

6 7

already connected

