



<http://algs4.cs.princeton.edu>

## 2.2 MERGESORT

---

- ▶ *mergesort*
- ▶ *bottom-up mergesort*
- ▶ *sorting complexity*
- ▶ *comparators*
- ▶ *stability*

# Stability

A typical application. First, sort by name; **then** sort by section.

`Selection.sort(a, new Student.ByName());`

Andrews	3	A	664-480-0023	097 Little
Battle	4	C	874-088-1212	121 Whitman
Chen	3	A	991-878-4944	308 Blair
Fox	3	A	884-232-5341	11 Dickinson
Furia	1	A	766-093-9873	101 Brown
Gazsi	4	B	766-093-9873	101 Brown
Kanaga	3	B	898-122-9643	22 Brown
Rohde	2	A	232-343-5555	343 Forbes

`Selection.sort(a, new Student.BySection());`

Furia	1	A	766-093-9873	101 Brown
Rohde	2	A	232-343-5555	343 Forbes
Chen	3	A	991-878-4944	308 Blair
Fox	3	A	884-232-5341	11 Dickinson
Andrews	3	A	664-480-0023	097 Little
Kanaga	3	B	898-122-9643	22 Brown
Gazsi	4	B	766-093-9873	101 Brown
Battle	4	C	874-088-1212	121 Whitman

@#%&@! Students in section 3 no longer sorted by name.

A **stable** sort preserves the relative order of items with equal keys.

# Stability

Q. Which sorts are stable?

A. Need to check algorithm (and implementation).

sorted by time		sorted by location (not stable)		sorted by location (stable)	
Chicago	09:00:00	Chicago	09:25:52	Chicago	09:00:00
Phoenix	09:00:03	Chicago	09:03:13	Chicago	09:00:59
Houston	09:00:13	Chicago	09:21:05	Chicago	09:03:13
Chicago	09:00:59	Chicago	09:19:46	Chicago	09:19:32
Houston	09:01:10	Chicago	09:19:32	Chicago	09:19:46
Chicago	09:03:13	Chicago	09:00:00	Chicago	09:21:05
Seattle	09:10:11	Chicago	09:35:21	Chicago	09:25:52
Seattle	09:10:25	Chicago	09:00:59	Chicago	09:35:21
Phoenix	09:14:25	Houston	09:01:10	Houston	09:00:13
Chicago	09:19:32	Houston	09:00:13	Houston	09:01:10
Chicago	09:19:46	Phoenix	09:37:44	Phoenix	09:00:03
Chicago	09:21:05	Phoenix	09:00:03	Phoenix	09:14:25
Seattle	09:22:43	Phoenix	09:14:25	Phoenix	09:37:44
Seattle	09:22:54	Seattle	09:10:25	Seattle	09:10:11
Chicago	09:25:52	Seattle	09:36:14	Seattle	09:10:25
Chicago	09:35:21	Seattle	09:22:43	Seattle	09:22:43
Seattle	09:36:14	Seattle	09:10:11	Seattle	09:22:54
Phoenix	09:37:44	Seattle	09:22:54	Seattle	09:36:14

*no longer sorted by time*

*still sorted by time*

# Stability: insertion sort

**Proposition.** Insertion sort is **stable**.

```
public class Insertion
{
    public static void sort(Comparable[] a)
    {
        int N = a.length;
        for (int i = 0; i < N; i++)
            for (int j = i; j > 0 && less(a[j], a[j-1]); j--)
                exch(a, j, j-1);
    }
}
```

i	j	0	1	2	3	4
0	0	B <sub>1</sub>	A <sub>1</sub>	A <sub>2</sub>	A <sub>3</sub>	B <sub>2</sub>
1	0	A <sub>1</sub>	B <sub>1</sub>	A <sub>2</sub>	A <sub>3</sub>	B <sub>2</sub>
2	1	A <sub>1</sub>	A <sub>2</sub>	B <sub>1</sub>	A <sub>3</sub>	B <sub>2</sub>
3	2	A <sub>1</sub>	A <sub>2</sub>	A <sub>3</sub>	B <sub>1</sub>	B <sub>2</sub>
4	4	A <sub>1</sub>	A <sub>2</sub>	A <sub>3</sub>	B <sub>1</sub>	B <sub>2</sub>
		A <sub>1</sub>	A <sub>2</sub>	A <sub>3</sub>	B <sub>1</sub>	B <sub>2</sub>

**Pf.** Equal items never move past each other.

# Stability: selection sort

**Proposition.** Selection sort is **not stable**.

```
public class Selection
{
    public static void sort(Comparable[] a)
    {
        int N = a.length;
        for (int i = 0; i < N; i++)
        {
            int min = i;
            for (int j = i+1; j < N; j++)
                if (less(a[j], a[min]))
                    min = j;
            exch(a, i, min);
        }
    }
}
```

i	min	0	1	2
0	2	B <sub>1</sub>	B <sub>2</sub>	A
1	1	A	B <sub>2</sub>	B <sub>1</sub>
2	2	A	B <sub>2</sub>	B <sub>1</sub>
		A	B <sub>2</sub>	B <sub>1</sub>

**Pf by counterexample.** Long-distance exchange can move one equal item past another one.

# Stability: shellsort

**Proposition.** Shellsort sort is **not stable**.

```
public class Shell
{
    public static void sort(Comparable[] a)
    {
        int N = a.length;
        int h = 1;
        while (h < N/3) h = 3*h + 1;
        while (h >= 1)
        {
            for (int i = h; i < N; i++)
            {
                for (int j = i; j > h && less(a[j], a[j-h]); j -= h)
                    exch(a, j, j-h);
            }
            h = h/3;
        }
    }
}
```

h	0	1	2	3	4
	B <sub>1</sub>	B <sub>2</sub>	B <sub>3</sub>	B <sub>4</sub>	A <sub>1</sub>
4	A <sub>1</sub>	B <sub>2</sub>	B <sub>3</sub>	B <sub>4</sub>	B <sub>1</sub>
1	A <sub>1</sub>	B <sub>2</sub>	B <sub>3</sub>	B <sub>4</sub>	B <sub>1</sub>
	A <sub>1</sub>	B <sub>2</sub>	B <sub>3</sub>	B <sub>4</sub>	B <sub>1</sub>

**Pf by counterexample.** Long-distance exchanges.

# Stability: mergesort

---

**Proposition.** Mergesort is **stable**.

```
public class Merge
{
    private static void merge(...)
    { /* as before */ }

    private static void sort(Comparable[] a, Comparable[] aux, int lo, int hi)
    {
        if (hi <= lo) return;
        int mid = lo + (hi - lo) / 2;
        sort(a, aux, lo, mid);
        sort(a, aux, mid+1, hi);
        merge(a, aux, lo, mid, hi);
    }

    public static void sort(Comparable[] a)
    { /* as before */ }
}
```

**Pf.** Suffices to verify that merge operation is stable.

# Stability: mergesort

**Proposition.** Merge operation is **stable**.

```
private static void merge(...)
{
    for (int k = lo; k <= hi; k++)
        aux[k] = a[k];

    int i = lo, j = mid+1;
    for (int k = lo; k <= hi; k++)
    {
        if (i > mid)                a[k] = aux[j++];
        else if (j > hi)            a[k] = aux[i++];
        else if (less(aux[j], aux[i])) a[k] = aux[j++];
        else                        a[k] = aux[i++];
    }
}
```

0	1	2	3	4	5	6	7	8	9	10
A <sub>1</sub>	A <sub>2</sub>	A <sub>3</sub>	B	D	A <sub>4</sub>	A <sub>5</sub>	C	E	F	G

**Pf.** Takes from left subarray if equal keys.



# Sorting summary

	inplace?	stable?	best	average	worst	remarks
selection	✓		$\frac{1}{2} N^2$	$\frac{1}{2} N^2$	$\frac{1}{2} N^2$	$N$ exchanges
insertion	✓	✓	$N$	$\frac{1}{4} N^2$	$\frac{1}{2} N^2$	use for small $N$ or partially ordered
shell	✓		$N \log_3 N$	?	$c N^{3/2}$	tight code; subquadratic
merge		✓	$\frac{1}{2} N \lg N$	$N \lg N$	$N \lg N$	$N \log N$ guarantee; stable
timsort		✓	$N$	$N \lg N$	$N \lg N$	improves mergesort when preexisting order
?	✓	✓	$N$	$N \lg N$	$N \lg N$	holy sorting grail