



<http://algs4.cs.princeton.edu>

1.3 BAGS, QUEUES, AND STACKS

- ▶ *stacks*
- ▶ *resizing arrays*
- ▶ *queues*
- ▶ *generics*
- ▶ *iterators*
- ▶ *applications*

Stack: resizing-array implementation

Problem. Requiring client to provide capacity does not implement API!

Q. How to grow and shrink array?

First try.

- `push()`: increase size of array `s[]` by 1.
- `pop()`: decrease size of array `s[]` by 1.

Too expensive.

- Need to copy all items to a new array, for each operation.
 - Array accesses to insert first N items = $N + (2 + 4 + \dots + 2(N-1)) \sim N^2$.
- infeasible for large N ↓
- ↑ ↑
- 1 array access 2(k-1) array accesses to expand to size k
per push (ignoring cost to create new array)

Challenge. Ensure that array resizing happens infrequently.

Stack: resizing-array implementation

Q. How to grow array?

A. If array is full, create a new array of **twice** the size, and copy items.

"repeated doubling"

```
public ResizingArrayStackOfStrings()
{ s = new String[1]; }

public void push(String item)
{
    if (N == s.length) resize(2 * s.length);
    s[N++] = item;
}

private void resize(int capacity)
{
    String[] copy = new String[capacity];
    for (int i = 0; i < N; i++)
        copy[i] = s[i];
    s = copy;
}
```

Array accesses to insert first $N = 2^i$ items. $N + (2 + 4 + 8 + \dots + N) \sim 3N$.

↑
1 array access
per push

↑
k array accesses to double to size k
(ignoring cost to create new array)

Stack: resizing-array implementation


Q. How to shrink array?

First try.

- `push()`: double size of array `s[]` when array is full.
- `pop()`: halve size of array `s[]` when array is **one-half full**.

Too expensive in worst case.

- Consider push-pop-push-pop-... sequence when array is full.
- Each operation takes time proportional to N .



Stack: resizing-array implementation

Q. How to shrink array?

Efficient solution.

- push(): double size of array `s[]` when array is full.
- pop(): halve size of array `s[]` when array is **one-quarter full**.

```
public String pop()
{
    String item = s[--N];
    s[N] = null;
    if (N > 0 && N == s.length/4) resize(s.length/2);
    return item;
}
```


Invariant. Array is between 25% and 100% full.

Stack resizing-array implementation: performance

Amortized analysis. Starting from an empty data structure, average running time per operation over a worst-case sequence of operations.

Proposition. Starting from an empty stack, any sequence of M push and pop operations takes time proportional to M .

	best	worst	amortized
construct	1	1	1
push	1	N	1
pop	1	N	1
size	1	1	1



doubling and halving operations

order of growth of running time
for resizing stack with N items

Stack resizing-array implementation: memory usage

Proposition. Uses between $\sim 8 N$ and $\sim 32 N$ bytes to represent a stack with N items.

- $\sim 8 N$ when full.
- $\sim 32 N$ when one-quarter full.

```
public class ResizingArrayStackOfStrings
{
    private String[] s; ← 8 bytes × array size
    private int N = 0;
    ...
}
```

Remark. This accounts for the memory for the stack (but not the memory for strings themselves, which the client owns).

Stack implementations: resizing array vs. linked list

Tradeoffs. Can implement a stack with either resizing array or linked list; client can use interchangeably. Which one is better?

Linked-list implementation.

- Every operation takes constant time in the **worst case**.
- Uses extra time and space to deal with the links.

Resizing-array implementation.

- Every operation takes constant **amortized** time.
- Less wasted space.

