



<http://algs4.cs.princeton.edu>

## 2.4 PRIORITY QUEUES


---

- ▶ *API and elementary implementations*
- ▶ *binary heaps*
- ▶ *heapsort*
- ▶ *event-driven simulation*

# Molecular dynamics simulation of hard discs

---

**Goal.** Simulate the motion of  $N$  moving particles that behave according to the laws of elastic collision.



# Molecular dynamics simulation of hard discs

---

**Goal.** Simulate the motion of  $N$  moving particles that behave according to the laws of elastic collision.

## Hard disc model.

- Moving particles interact via elastic collisions with each other and walls.
- Each particle is a disc with known position, velocity, mass, and radius.
- No other forces.

temperature, pressure,  
diffusion constant

motion of individual  
atoms and molecules

**Significance.** Relates macroscopic observables to microscopic dynamics.

- Maxwell-Boltzmann: distribution of speeds as a function of temperature.
- Einstein: explain Brownian motion of pollen grains.


# Warmup: bouncing balls

Time-driven simulation.  $N$  bouncing balls in the unit square.

```
public class BouncingBalls
{
    public static void main(String[] args)
    {
        int N = Integer.parseInt(args[0]);
        Ball[] balls = new Ball[N];
        for (int i = 0; i < N; i++)
            balls[i] = new Ball();
        while(true)
        {
            StdDraw.clear();
            for (int i = 0; i < N; i++)
            {
                balls[i].move(0.5);
                balls[i].draw();
            }
            StdDraw.show(50);
        }
    }
}
```

main simulation loop

% java BouncingBalls 100




# Warmup: bouncing balls

```
public class Ball
{
    private double rx, ry;          // position
    private double vx, vy;          // velocity
    private final double radius;    // radius
    public Ball(...)
    { /* initialize position and velocity */ }

    public void move(double dt)
    {
        if ((rx + vx*dt < radius) || (rx + vx*dt > 1.0 - radius)) { vx = -vx; }
        if ((ry + vy*dt < radius) || (ry + vy*dt > 1.0 - radius)) { vy = -vy; }
        rx = rx + vx*dt;
        ry = ry + vy*dt;
    }
    public void draw()
    { StdDraw.filledCircle(rx, ry, radius); }
}
```

check for collision with walls




**Missing.** Check for balls colliding with **each other**.

- Physics problems: when? what effect?
- CS problems: which object does the check? too many checks?

# Time-driven simulation

---

- Discretize time in quanta of size  $dt$ .
- Update the position of each particle after every  $dt$  units of time, and check for overlaps.
- If overlap, roll back the clock to the time of the collision, update the velocities of the colliding particles, and continue the simulation.




# Time-driven simulation

---


## Main drawbacks.

- $\sim N^2 / 2$  overlap checks per time quantum.
- Simulation is too slow if  $dt$  is very small.
- May miss collisions if  $dt$  is too large.  
(if colliding particles fail to overlap when we are looking)

**dt too small: excessive computation**



**dt too large: may miss collisions**



# Event-driven simulation


---

Change state only when something happens.

- Between collisions, particles move in straight-line trajectories.
- Focus only on times when collisions occur.
- Maintain **PQ** of collision events, prioritized by time.
- Remove the min = get next collision.

**Collision prediction.** Given position, velocity, and radius of a particle, when will it collide next with a wall or another particle?

**Collision resolution.** If collision occurs, update colliding particle(s) according to laws of elastic collisions.






# Particle-wall collision

## Collision prediction and resolution.

- Particle of radius  $s$  at position  $(rx, ry)$ .
- Particle moving in unit box with velocity  $(vx, vy)$ .
- Will it collide with a vertical wall? If so, when?




Predicting and resolving a particle-wall collision

# Particle-particle collision prediction

## Collision prediction.

- Particle  $i$ : radius  $s_i$ , position  $(rx_i, ry_i)$ , velocity  $(vx_i, vy_i)$ .
- Particle  $j$ : radius  $s_j$ , position  $(rx_j, ry_j)$ , velocity  $(vx_j, vy_j)$ .
- Will particles  $i$  and  $j$  collide? If so, when?



# Particle-particle collision prediction

---

## Collision prediction.

- Particle  $i$ : radius  $s_i$ , position  $(rx_i, ry_i)$ , velocity  $(vx_i, vy_i)$ .
- Particle  $j$ : radius  $s_j$ , position  $(rx_j, ry_j)$ , velocity  $(vx_j, vy_j)$ .
- Will particles  $i$  and  $j$  collide? If so, when?

$$\Delta t = \begin{cases} \infty & \text{if } \Delta v \cdot \Delta r \geq 0 \\ \infty & \text{if } d < 0 \\ -\frac{\Delta v \cdot \Delta r + \sqrt{d}}{\Delta v \cdot \Delta v} & \text{otherwise} \end{cases}$$

$$d = (\Delta v \cdot \Delta r)^2 - (\Delta v \cdot \Delta v) (\Delta r \cdot \Delta r - \sigma^2) \quad \sigma = \sigma_i + \sigma_j$$

$$\begin{aligned} \Delta v &= (\Delta vx, \Delta vy) = (vx_i - vx_j, vy_i - vy_j) & \Delta v \cdot \Delta v &= (\Delta vx)^2 + (\Delta vy)^2 \\ \Delta r &= (\Delta rx, \Delta ry) = (rx_i - rx_j, ry_i - ry_j) & \Delta r \cdot \Delta r &= (\Delta rx)^2 + (\Delta ry)^2 \\ & & \Delta v \cdot \Delta r &= (\Delta vx)(\Delta rx) + (\Delta vy)(\Delta ry) \end{aligned}$$

**Important note: This is physics, so we won't be testing you on it!**

# Particle-particle collision resolution

---

**Collision resolution.** When two particles collide, how does velocity change?

$$\begin{aligned} vx_i' &= vx_i + Jx / m_i \\ vy_i' &= vy_i + Jy / m_i \\ vx_j' &= vx_j - Jx / m_j \\ vy_j' &= vy_j - Jy / m_j \end{aligned}$$

← Newton's second law  
(momentum form)

$$Jx = \frac{J \Delta rx}{\sigma}, \quad Jy = \frac{J \Delta ry}{\sigma}, \quad J = \frac{2 m_i m_j (\Delta v \cdot \Delta r)}{\sigma(m_i + m_j)}$$

impulse due to normal force  
(conservation of energy, conservation of momentum)

**Important note:** This is physics, so we won't be testing you on it!

# Particle data type skeleton

---

```
public class Particle
{
    private double rx, ry;          // position
    private double vx, vy;          // velocity
    private final double radius;    // radius
    private final double mass;      // mass
    private int count;              // number of collisions

    public Particle(...) { }

    public void move(double dt) { }
    public void draw()           { }

    public double timeToHit(Particle that) { }
    public double timeToHitVerticalWall() { }
    public double timeToHitHorizontalWall() { }

    public void bounceOff(Particle that) { }
    public void bounceOffVerticalWall() { }
    public void bounceOffHorizontalWall() { }


}
```

← predict collision  
with particle or wall

← resolve collision  
with particle or wall

# Particle-particle collision and resolution implementation

```
public double timeToHit(Particle that)
{
    if (this == that) return INFINITY;
    double dx = that.rx - this.rx, dy = that.ry - this.ry;
    double dvx = that.vx - this.vx; dvy = that.vy - this.vy;
    double dvdr = dx*dvx + dy*dvy;
    if( dvdr > 0) return INFINITY;
    double dvdv = dvx*dvx + dvy*dvy;
    double drdr = dx*dx + dy*dy;
    double sigma = this.radius + that.radius;
    double d = (dvdr*dvdr) - dvdv * (drdr - sigma*sigma);
    if (d < 0) return INFINITY;
    return -(dvdr + Math.sqrt(d)) / dvdv;
}
```



no collision

```
public void bounceOff(Particle that)
{
    double dx = that.rx - this.rx, dy = that.ry - this.ry;
    double dvx = that.vx - this.vx, dvy = that.vy - this.vy;
    double dvdr = dx*dvx + dy*dvy;
    double dist = this.radius + that.radius;
    double J = 2 * this.mass * that.mass * dvdr / ((this.mass + that.mass) * dist);
    double Jx = J * dx / dist;
    double Jy = J * dy / dist;
    this.vx += Jx / this.mass;
    this.vy += Jy / this.mass;
    that.vx -= Jx / that.mass;
    that.vy -= Jy / that.mass;
    this.count++;
    that.count++;
}
```


**Important note: This is physics, so we won't be testing you on it!**

# Collision system: event-driven simulation main loop

## Initialization.

- Fill PQ with all potential particle-wall collisions.
- Fill PQ with all potential particle-particle collisions.

“potential” since collision may not happen if some other collision intervenes



## Main loop.

- Delete the impending event from PQ (min priority =  $t$ ).
- If the event has been invalidated, ignore it.
- Advance all particles to time  $t$ , on a straight-line trajectory.
- Update the velocities of the colliding particle(s).
- Predict future particle-wall and particle-particle collisions involving the colliding particle(s) and insert events onto PQ.

# Event data type

---

## Conventions.

- Neither particle null  $\Rightarrow$  particle-particle collision.
- One particle null  $\Rightarrow$  particle-wall collision.
- Both particles null  $\Rightarrow$  redraw event.

```
private class Event implements Comparable<Event>
{
    private double time;           // time of event
    private Particle a, b;         // particles involved in event
    private int countA, countB;    // collision counts for a and b

    public Event(double t, Particle a, Particle b) { }

    public int compareTo(Event that)
    {    return this.time - that.time;    }

    public boolean isValid()
    {    }
}
```

← create event

← ordered by time

← invalid if  
intervening  
collision



# Collision system implementation: skeleton

---

```
public class CollisionSystem
{
    private MinPQ<Event> pq;           // the priority queue
    private double t = 0.0;           // simulation clock time
    private Particle[] particles;      // the array of particles

    public CollisionSystem(Particle[] particles) { }

    private void predict(Particle a)   add to PQ all particle-wall and particle-
    {                                  particle collisions involving this particle
        if (a == null) return;
        for (int i = 0; i < N; i++)
        {
            double dt = a.timeToHit(particles[i]);
            pq.insert(new Event(t + dt, a, particles[i]));
        }
        pq.insert(new Event(t + a.timeToHitVerticalWall(), a, null));
        pq.insert(new Event(t + a.timeToHitHorizontalWall(), null, a));
    }

    private void redraw() { }

    public void simulate() { /* see next slide */ }
}
```

# Collision system implementation: main event-driven simulation loop

```
public void simulate()
{
```

```
    pq = new MinPQ<Event>();
    for(int i = 0; i < N; i++) predict(particles[i]);
    pq.insert(new Event(0, null, null));
```

← initialize PQ with  
collision events and  
redraw event

```
    while(!pq.isEmpty())
    {
```

```
        Event event = pq.delMin();
        if(!event.isValid()) continue;
        Particle a = event.a;
        Particle b = event.b;
```

← get next event

```
        for(int i = 0; i < N; i++)
            particles[i].move(event.time - t);
        t = event.time;
```

← update positions  
and time

```
        if (a != null && b != null) a.bounceOff(b);
        else if (a != null && b == null) a.bounceOffVerticalWall();
        else if (a == null && b != null) b.bounceOffHorizontalWall();
        else if (a == null && b == null) redraw();
```

← process event

```
        predict(a);
        predict(b);
```


← predict new events  
based on changes

```
    }
}
```

# Particle collision simulation example 1

---


```
% java CollisionSystem 100
```



# Particle collision simulation example 2

---


```
% java CollisionSystem < billiards.txt
```



# Particle collision simulation example 3

---

```
% java CollisionSystem < brownian.txt
```



# Particle collision simulation example 4

---

```
% java CollisionSystem < diffusion.txt
```

