http://algs4.cs.princeton.edu

2.1 Elementary Sorts

- *rules of the game*
- *selection sort*
- *insertion sort*
- *shellsort*
- *shuffling*

Insertion sort demo

- In iteration `i`, swap `a[i]` with each larger entry to its left.



Insertion sort

Algorithm. ↑ scans from left to right.

Invariants.

- Entries to the left of ↑ (including ↑) are in ascending order.
- Entries to the right of ↑ have not yet been seen.

Insertion sort inner loop

To maintain algorithm invariants:

- Move the pointer to the right.

```
i++;
```

- Moving from right to left, exchange `a[i]` with each larger entry to its left.

```
for (int j = i; j > 0; j--)
   if (less(a[j], a[j-1]))
        exch(a, j, j-1);
   else break;
```

Insertion sort: Java implementation

```
public class Insertion
{
   public static void sort(Comparable[] a)
   {
      int N = a.length;
      for (int i = 0; i < N; i++)
         for (int j = i; j > 0; j--)
            if (less(a[j], a[j-1]))
               exch(a, j, j-1);
            else break;
   }

   private static boolean less(Comparable v, Comparable w)
   {  /* as before */  }

   private static void exch(Comparable[] a, int i, int j)
   {  /* as before */  }
}
```

Insertion sort: animation

40 random items





http://www.sorting-algorithms.com/insertion-sort

Insertion sort: animation

40 reverse-sorted items





http://www.sorting-algorithms.com/insertion-sort

Insertion sort: animation

40 partially-sorted items





http://www.sorting-algorithms.com/insertion-sort

Insertion sort: mathematical analysis

Proposition. To sort a randomly-ordered array with distinct keys, insertion sort uses $\sim \frac{1}{4} N^2$ compares and $\sim \frac{1}{4} N^2$ exchanges on average.

Pf. Expect each entry to move halfway back.

		a[]										
i	j	0	1	2	3	4	5	6	7	8	9	10
		S	O	R	T	E	X	A	M	P	L	E
1	0	O	S	R	T	E	X	A	M	P	L	E
2	1	O	R	S	T	E	X	A	M	P	L	E
3	3	O	R	S	T	E	X	A	M	P	L	E
4	0	E	O	R	S	T	X	A	M	P	L	E
5	5	E	O	R	S	T	X	A	M	P	L	E
6	0	A	E	O	R	S	T	X	M	P	L	E
7	2	A	E	M	O	R	S	T	X	P	L	E
8	4	A	E	M	O	P	R	S	T	X	L	E
9	2	A	E	L	M	O	P	R	S	T	X	E
10	2	A	E	E	L	M	O	P	R	S	T	X
		A	E	E	L	M	O	P	R	S	T	X

entries in gray do not move

entry in red is a[j]

entries in black moved one position right for insertion

Trace of insertion sort (array contents just after each insertion)

Insertion sort: trace

a[ ]

i	j	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34
		A	S	O	M	E	W	H	A	T	L	O	N	G	E	R	I	N	S	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
0	0	A	S	O	M	E	W	H	A	T	L	O	N	G	E	R	I	N	S	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
1	1	A	S	O	M	E	W	H	A	T	L	O	N	G	E	R	I	N	S	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
2	1	A	O	S	M	E	W	H	A	T	L	O	N	G	E	R	I	N	S	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
3	1	A	M	O	S	E	W	H	A	T	L	O	N	G	E	R	I	N	S	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
4	1	A	E	M	O	S	W	H	A	T	L	O	N	G	E	R	I	N	S	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
5	5	A	E	M	O	S	W	H	A	T	L	O	N	G	E	R	I	N	S	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
6	2	A	E	H	M	O	S	W	A	T	L	O	N	G	E	R	I	N	S	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
7	1	A	A	E	H	M	O	S	W	T	L	O	N	G	E	R	I	N	S	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
8	7	A	A	E	H	M	O	S	T	W	L	O	N	G	E	R	I	N	S	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
9	4	A	A	E	H	L	M	O	S	T	W	O	N	G	E	R	I	N	S	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
10	7	A	A	E	H	L	M	O	O	S	T	W	N	G	E	R	I	N	S	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
11	6	A	A	E	H	L	M	N	O	O	S	T	W	G	E	R	I	N	S	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
12	3	A	A	E	G	H	L	M	N	O	O	S	T	W	E	R	I	N	S	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
13	3	A	A	E	E	G	H	L	M	N	O	O	S	T	W	R	I	N	S	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
14	11	A	A	E	E	G	H	L	M	N	O	O	R	S	T	W	I	N	S	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
15	6	A	A	E	E	G	H	I	L	M	N	O	O	R	S	T	W	N	S	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
16	10	A	A	E	E	G	H	I	L	M	N	N	O	O	R	S	T	W	S	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
17	15	A	A	E	E	G	H	I	L	M	N	N	O	O	R	S	S	T	W	E	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
18	4	A	A	E	E	E	G	H	I	L	M	N	N	O	O	R	S	S	T	W	R	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
19	15	A	A	E	E	E	G	H	I	L	M	N	N	O	O	R	R	S	S	T	W	T	I	O	N	S	O	R	T	E	X	A	M	P	L	E
20	19	A	A	E	E	E	G	H	I	L	M	N	N	O	O	R	R	S	S	T	T	W	I	O	N	S	O	R	T	E	X	A	M	P	L	E
21	8	A	A	E	E	E	G	H	I	I	L	M	N	N	O	O	R	R	S	S	T	T	W	O	N	S	O	R	T	E	X	A	M	P	L	E
22	15	A	A	E	E	E	G	H	I	I	L	M	N	N	O	O	O	R	R	S	S	T	T	W	N	S	O	R	T	E	X	A	M	P	L	E
23	13	A	A	E	E	E	G	H	I	I	L	M	N	N	N	O	O	O	R	R	S	S	T	T	W	S	O	R	T	E	X	A	M	P	L	E
24	21	A	A	E	E	E	G	H	I	I	L	M	N	N	N	O	O	O	R	R	S	S	S	T	T	W	O	R	T	E	X	A	M	P	L	E
25	17	A	A	E	E	E	G	H	I	I	L	M	N	N	N	O	O	O	O	R	R	S	S	S	T	T	W	R	T	E	X	A	M	P	L	E
26	20	A	A	E	E	E	G	H	I	I	L	M	N	N	N	O	O	O	O	R	R	R	S	S	S	T	T	W	T	E	X	A	M	P	L	E
27	26	A	A	E	E	E	G	H	I	I	L	M	N	N	N	O	O	O	O	R	R	R	S	S	S	T	T	T	W	E	X	A	M	P	L	E
28	5	A	A	E	E	E	E	G	H	I	I	L	M	N	N	N	O	O	O	O	R	R	R	S	S	S	T	T	T	W	X	A	M	P	L	E
29	29	A	A	E	E	E	E	G	H	I	I	L	M	N	N	N	O	O	O	O	R	R	R	S	S	S	T	T	T	W	X	A	M	P	L	E
30	2	A	A	A	E	E	E	E	G	H	I	I	L	M	N	N	N	O	O	O	O	R	R	R	S	S	S	T	T	T	W	X	M	P	L	E
31	13	A	A	A	E	E	E	E	G	H	I	I	L	M	M	N	N	N	O	O	O	O	R	R	R	S	S	S	T	T	T	W	X	P	L	E
32	21	A	A	A	E	E	E	E	G	H	I	I	L	M	M	N	N	N	O	O	O	O	P	R	R	R	S	S	S	T	T	T	W	X	L	E
33	12	A	A	A	E	E	E	E	G	H	I	I	L	L	M	M	N	N	N	O	O	O	O	P	R	R	R	S	S	S	T	T	T	W	X	E
34	7	A	A	A	E	E	E	E	E	G	H	I	I	L	L	M	M	N	N	N	O	O	O	O	P	R	R	R	S	S	S	T	T	T	W	X
		A	A	A	E	E	E	E	E	G	H	I	I	L	L	M	M	N	N	N	O	O	O	O	P	R	R	R	S	S	S	T	T	T	W	X

Insertion sort: analysis

Best case. If the array is in ascending order, insertion sort makes $N-1$ compares and 0 exchanges.

A E E L M O P R S T X

Worst case. If the array is in descending order (and no duplicates), insertion sort makes $\sim \frac{1}{2} N^2$ compares and $\sim \frac{1}{2} N^2$ exchanges.

X T S R P O M L F E A

Insertion sort: partially-sorted arrays

Def. An inversion is a pair of keys that are out of order.

A E E L M O T R X P S

T-R T-P T-S R-P X-P X-S

(6 inversions)

Def. An array is partially sorted if the number of inversions is ≤ $c\,N$.

- Ex 1. A sorted array has 0 inversions.
- Ex 2. A subarray of size 10 appended to a sorted subarray of size N.

Proposition. For partially-sorted arrays, insertion sort runs in linear time.

Pf. Number of exchanges equals the number of inversions.

number of compares = exchanges + (N − 1)

Insertion sort: practical improvements

Half exchanges. Shift items over (instead of exchanging).

- Eliminates unnecessary data movement.
- No longer uses only `less()` and `exch()` to access data.

A C H H I M N N P Q X Y K B I N A R Y

Binary insertion sort. Use binary search to find insertion point.

- Number of compares $\sim N \lg N$.
- But still a quadratic number of array accesses.

A C H H I M N N P Q X Y K B I N A R Y

binary search for first key > K