SwiftDrop

Enterprise System Architecture & Software Design Specification

IN3101 - Enterprise Application Development

Faculty of Information Technology, University of Moratuwa

Development Team & Technical Authors:

K.G.U. Mihiranga (234129P)
W.H. Ashara (234023K)
K.S. Atapattu (234025T)
K.D.N.D. Samarakkodi (234185G)
B.G.S. Sulakma (234200C)
R.K.S. Tharushika (234204R)
M.A.P. Bhagya (235019L)
M.G.K.I. Udithya (234211K)
M.D. Wakishta (234217J)
A.A.P.R. Jayathilaka (234096J)

Conforming to IEEE Std 1016-2009 & ISO/IEC/IEEE 42010 Systems Architecture Standards

DOCUMENT GOVERNANCE & ARCHITECTURAL CHARTER

This document establishes the authoritative System Architecture and Software Design Specification for the SwiftDrop enterprise parcel delivery and courier management platform. It defines the formal system boundaries, architectural trade-offs, modular domain structures, database persistence schemas, security threat models, and integration contracts governing the production implementation. This specification serves as the definitive single source of truth for the platform.

All functional capabilities, transactional guarantees, and non-functional quality attributes defined herein represent the authoritative baseline for engineering, deployment, and operational maintenance. External clients, enterprise logistics partners, and engineering stakeholders shall reference this document for authoritative architectural guidance, contractual interfaces, and technical compliance.

EXECUTIVE SUMMARY

Modern logistics and supply chain management platforms demand rigorous transactional integrity, low-latency parcel lifecycle tracking, reliable asynchronous event dissemination, and secure multi-tenant partner integration. Traditional courier systems frequently suffer from data inconsistencies, race conditions during high-volume courier assignment, and operational opacity due to reliance on manual coordination and legacy architectures. SwiftDrop addresses these systemic challenges by delivering an enterprise-grade, event-driven parcel delivery and courier management platform designed under the principles of Domain-Driven Design (DDD) and Clean Architecture.

The core transactional operations of the platform are implemented as a Go Modular Monolith, strictly partitioned into isolated bounded contexts (Identity, Parcels, Pricing, Dispatch, Delivery, Merchants, Admin, and Events) with single-transaction persistence guarantees. Read-heavy public tracking workloads are offloaded to an independently deployable, read-optimized Server-Sent Events (SSE) tracking service backed by Redis caching and PostgreSQL read replica / connection pools. System-wide reliability is guaranteed via the Transactional Outbox pattern, an asynchronous RabbitMQ message bus with Dead Letter Queues, and an idempotent Event Worker consumer.

This document provides the complete System Architecture and Software Design Specification conforming to IEEE Std 1016-2009 and ISO/IEC/IEEE 42010. To maintain complete engineering transparency, this specification clearly distinguishes between architectural target specifications and verified Release v1.0 prototype codebases. The operational baseline delivered in Release v1.0 includes the Go monolithic wiring, working credential login with Salted SHA-256 (10,000 rounds) key stretching and constant-time verification, HS256 JWT issuance, reusable RBAC authorization middleware, the transactional outbox publishing engine, and an interactive demonstration frontend. Target enterprise enhancements—including pure Go Argon2id memory-hard hashing (TD-SEC-01), asymmetric RS256/EdDSA token signing, federated Google OAuth 2.0 / OIDC, and multi-pod KEDA scaling—are fully specified for subsequent sprint delivery.

TABLE OF CONTENTS

DOCUMENT GOVERNANCE & ARCHITECTURAL CHARTER

EXECUTIVE SUMMARY

TABLE OF CONTENTS

LIST OF FIGURES

LIST OF TABLES

LIST OF ACRONYMS & ABBREVIATIONS

CHAPTER 1: INTRODUCTION

1.1 Project Background

1.1.1 Problem Statement

1.2 Project Scope & Strategic Engineering Objectives

1.3 Enterprise Stakeholder Taxonomy & Actor Responsibilities

1.4 Business Requirements Traceability Matrix (RTM)

CHAPTER 2: GLOBAL REQUIREMENTS ENGINEERING & MASTER USE CASE MODEL

2.1 Functional Requirements Hierarchy

2.2 Non-Functional Requirements (FURPS+ Model Analysis)

2.3 Master Enterprise System Use Case Model

2.4 Inter-Actor Operational Interaction Matrix

CHAPTER 3: GLOBAL SYSTEM ARCHITECTURE PROPOSAL & FUNDAMENTAL TRADE-OFFS

3.1 Architectural Philosophy: The Case for a Modular Monolith with Specialized Services

3.2 High-Level System Topology & Tier Decomposition

3.3 Comparative Architecture Trade-Off Analysis

3.4 Summary of Architectural Decision Records (ADR-001 through ADR-004)

3.5 Authoritative Relational Persistence Philosophy

3.6 High-Precision Financial Computation Strategy

3.7 Technology Stack & Programming Language Selection Justification

CHAPTER 4: IDENTITY, ACCESS CONTROL & SECURITY SUBSYSTEM

4.1 Subsystem Scope & Functional Boundaries

4.2 Architectural Design & Clean DDD Layers

4.3 Dynamic Execution Flows & Drawn Sequence Diagrams

4.4 Input & Output Data Contracts

4.5 Data Modeling & Persistence Schema

4.6 Technical Justifications: Key-Stretching, Token Engineering & Dual-Token Model

4.7 Security Invariants & Defensive Hardening

4.8 Comprehensive Testing Strategy & Acceptance Criteria

CHAPTER 5: PARCEL LIFECYCLE MANAGEMENT & DYNAMIC PRICING SUBSYSTEM

5.1 Subsystem Scope & Physical Boundaries

5.2 Architectural Design: Parcel Aggregate Root Encapsulation

5.3 Dynamic Execution Flows & Drawn Sequence Diagrams

5.4 Input & Output Data Contracts

5.5 Data Modeling & Persistence Schema

5.6 Technical Justifications: State Machine Invariants & Strategy Pattern

5.7 Invariant Guardrails & Prohibited Transitions

5.8 Comprehensive Testing Strategy & Acceptance Criteria

CHAPTER 6: DISPATCH, FLEET MANAGEMENT & PROOF-OF-DELIVERY SUBSYSTEM

6.1 Subsystem Scope & Operational Capabilities

6.2 Architectural Design: Dispatch & Delivery Contexts

6.3 Dynamic Execution Flows & Drawn Sequence Diagrams
6.4 Input & Output Data Contracts
6.5 Data Modeling & Persistence Schema
6.6 Technical Justifications: Advisory Locks & S3 Pre-Signed URLs
6.7 Concurrency Defenses & Failed Delivery Invariants (ADR-004)
6.8 Comprehensive Testing Strategy & Acceptance Criteria

CHAPTER 7: MERCHANT B2B INTEGRATION & WEBHOOK SUBSYSTEM
7.1 Subsystem Scope & Commercial Integration
7.2 Architectural Design: B2B Merchant Context
7.3 Dynamic Execution Flows & Drawn Sequence Diagrams
7.4 Input & Output Data Contracts
7.5 Data Modeling & Persistence Schema
7.6 Technical Justifications: SHA-256 Keys & HMAC-SHA256 Webhooks
7.7 Defensive Security: Tenant Boundaries, Rate Limiting & SSRF Mitigation
7.8 Comprehensive Testing Strategy & Acceptance Criteria

CHAPTER 8: REAL-TIME TRACKING & LIVE PROJECTION SUBSYSTEM
8.1 Subsystem Scope: Read-Heavy Workload Isolation
8.2 Architectural Design: Standalone Microservice Architecture
8.3 Dynamic Execution Flows & Drawn Sequence Diagrams
8.4 Input & Output Data Contracts
8.5 Data Modeling, Read-Replica Views & Redis Caching Fan-Out Strategy
8.6 Technical Justifications: Server-Sent Events vs. WebSockets
8.7 Privacy & Regulatory Safeguards: Public Tracking Redaction Rules
8.8 Comprehensive Testing Strategy & Acceptance Criteria

CHAPTER 9: FRONTEND USER EXPERIENCE & CLIENT APPLICATION SUBSYSTEM
9.1 Subsystem Scope: React/TypeScript Single Page Application (SPA) Portals
9.2 UI/UX Architectural Design: Feature Slicing, Design Tokens & State
9.3 Dynamic User Journeys & Drawn Flowcharts
9.4 Component Contracts & API Integration Layer
9.5 Technical Justifications: React/TypeScript SPA vs. SSR
9.6 Comprehensive Frontend Testing Strategy & Acceptance Criteria
9.7 State Management Architecture & Client-Side Token Storage
9.8 Application Routing Hierarchy & Role-Based Access Matrix
9.9 Component Directory Architecture & Design System Tokens
9.10 Dedicated API Client Service Layer & Interceptors
9.11 Web Accessibility (a11y) & Inclusive Design Practices

CHAPTER 10: EDGE INGRESS, API GATEWAY & TRAFFIC ROUTING SUBSYSTEM
10.1 Subsystem Scope: API Gateway, Dispatcher Portal & Administrative Control
10.2 Architectural Design: Traefik Ingress Controller & Dynamic Routing
10.3 Dynamic Execution Flows & Drawn Architecture Diagrams
10.4 Gateway Routing Rules & Policy Contracts
10.5 Technical Justifications: Traefik vs. NGINX/Kong
10.6 Defensive Security: Header Sanitization, TLS 1.3 Termination & DDoS Defenses
10.7 Comprehensive Testing Strategy & Acceptance Criteria
10.8 Traefik Dynamic Routing Specification & Ingress Middleware Policy
10.9 Admin Authorization Model & Privilege Isolation

CHAPTER 11: ASYNCHRONOUS EVENT-DRIVEN MESSAGING & TRANSACTIONAL OUTBOX SUBSYSTEM
11.1 Subsystem Scope: Reliable Message Broker & Outbox Publisher
11.2 Architectural Design: Transactional Outbox Pattern & AMQP Topology
11.3 Dynamic Execution Flows & Drawn Architecture Diagrams
11.4 Event Contract Specifications
11.5 Data Modeling & Persistence Schema

11.6 Technical Justifications: Transactional Outbox vs. Two-Phase Commit / Debezium CDC
11.7 Defensive Reliability: At-Least-Once Delivery, Idempotency Deduplication & Dead Letter Exchanges
11.8 Comprehensive Testing Strategy & Acceptance Criteria

CHAPTER 12: DEVOPS, CONTAINERIZATION & CLOUD INFRASTRUCTURE PLATFORM

12.1 Subsystem Scope: Automated Deployment, Containerization & Infrastructure As Code
12.2 Multi-Stage Dockerfile Architecture & Container Hardening
12.3 Local Orchestration Platform: Docker Compose Network & Service Topology
12.4 Cloud-Native Kubernetes Infrastructure Platform (ADR-002)
12.5 Observability & Telemetry Infrastructure: Prometheus Metrics, Grafana & Health Probes
12.6 Technical Justifications: Lightweight K3s & Distroless Containers
12.7 Infrastructure Testing: Automated Verification Script (verify.sh) & CI
12.8 Disaster Recovery, Automated Database Backups & Message Bus Durability

CHAPTER 13: GENERATIVE AI DELIVERY ASSISTANT & CROSS-WORKFLOW SUBSYSTEM

13.1 Subsystem Scope: Conversational AI Engine, Tool Calling & System Quality
13.2 Architectural Design: Python/FastAPI Microservice & Model Context Protocol (MCP)
13.3 Dynamic Execution Flows & Drawn Flowcharts
13.4 Tool Specifications & Contracts (get_parcel_status, estimate_delivery_fee)
13.5 Technical Justifications: Read-Only Tool Sandboxing & Zero Direct DB Access
13.6 Defensive Safeguards: Prompt Injection Defenses & Hallucination Prevention
13.7 Comprehensive Testing Strategy & Acceptance Criteria
13.8 AI Safety Guardrails, Hallucination Mitigation & Operational Boundaries
13.9 Resiliency Patterns & Inter-Service Fallback Error Handling

CHAPTER 14: COMPREHENSIVE ENTERPRISE DATA ARCHITECTURE & CANONICAL SCHEMAS

14.1 Master Entity Relationship Diagram (ERD) — Comprehensive 26-Table Relational Schema
14.2 Database Normalization Analysis (3NF Compliance & Integrity Proof)
14.3 Full Table Data Dictionary, Primary Keys, Foreign Keys & Indices
14.4 Canonical 11-Step Sequential Database Migration Plan (000001 through 000011)
14.5 Technical Justifications: Relational Modeling Decisions & Key Constraints

CHAPTER 15: SOFTWARE DESIGN PATTERNS & ENGINEERING PRINCIPLES

15.1 SOLID Principles Applied in Go Backend & TypeScript Frontend
15.2 Gang of Four (GoF) Structural & Behavioral Patterns
15.3 Enterprise Application Patterns

CHAPTER 16: SYSTEM-WIDE SECURITY ARCHITECTURE, THREAT MODELING & PRIVACY

16.1 STRIDE Threat Modeling Analysis Matrix
16.2 Centralized Role-Based Access Control (RBAC) Permission Matrix
16.3 Tenant Isolation & Cross-Account Object Protection (IDOR Prevention)
16.4 Data Protection & PII Compliance

CHAPTER 17: INITIAL CODEBASE VERIFICATION & AUTHENTICATION IMPLEMENTATION

17.1 Milestone Status Overview: Monolith Baseline & Working Authentication
17.2 Backend Identity Module Architecture & Code Artifacts
17.2.1 Database Schema Migration: 000001_create_users_and_roles.up.sql
17.2.2 Password Security, Prototype Key Stretching & Argon2id Migration Strategy
17.2.3 Dual-Token Architecture: In-Memory Access JWT & HttpOnly Refresh Cookies
17.2.4 Reusable RBAC Authorization Middleware in Go
17.3 Operational Authentication Verification & Multi-Role Demonstration Frontend
17.4 Pre-Configured Test Accounts & Demo Scenario Runbook
17.5 Automated Verification Results: Unit Tests, Integration Tests & Linters

CHAPTER 18: WORKLOAD ALLOCATION, MEMBER DELIVERABLES & CONTRIBUTION SHEETS

18.1 10-Member Capability-Based Division Philosophy
18.2 Master Workload Allocation & Dependency Mapping Matrix
18.3 Detailed Individual Contribution Sheets
18.4 Team Collaboration Cadence, Git Flow & Architecture Sign-Off

CHAPTER 19: ARCHITECTURAL EVALUATION, RISK REGISTER & FUTURE ROADMAP

19.1 Milestone Reflection & Architectural Invariants Preserved
19.2 Risk Register & Technical Debt Ledger
19.3 Phase 2 Roadmap: Core Parcel Booking, Live Tracking & Outbox Relay

REFERENCES

APPENDIX A: REST API ENDPOINT CONTRACTS & SPECIFICATION INDEX

APPENDIX B: RBAC ROLE-PERMISSION MATRIX & SYSTEM ENTITLEMENTS

LIST OF FIGURES

Figure 2.1: Master Enterprise System Use Case Diagram
Figure 3.1: SwiftDrop High-Level System Topology Diagram
Figure 4.1: Identity, Access Management & RBAC Subsystem UML Use Case Model
Figure 4.2: Layered & Hexagonal Architecture Component Layout for Identity Subsystem
Figure 4.3: Password Login & JWT Issuance Sequence Diagram
Figure 4.4: Federated Google OAuth 2.0 & OpenID Connect (OIDC) Sequence Flow
Figure 4.5: Identity, User Roles & Authentication Relational Entity-Relationship Diagram
Figure 5.1: Parcel Management & Dynamic Pricing Subsystem UML Use Case Model
Figure 5.2: Clean Architecture Component Layout for Parcel & Pricing Subsystems
Figure 5.3: Dynamic Delivery Fee Estimation Activity Workflow
Figure 5.4: Dynamic Tariff Calculation & 15-Minute Quote Sequence Flow
Figure 5.5: Customer Parcel Booking Activity Workflow
Figure 5.6: Atomic Parcel Booking & Status History Commit Sequence Flow
Figure 5.7: Canonical 9-State Parcel Lifecycle State Machine (FSM)
Figure 5.8: Parcel & Pricing Relational Entity-Relationship Diagram (ERD)
Figure 6.1: Dispatch, Fleet & POD Subsystem UML Use Case Model
Figure 6.2: Clean Architecture Component Layout for Dispatch & Delivery
Figure 6.3: Dispatcher Courier Assignment Sequence Diagram
Figure 6.4: Courier Proof-of-Delivery Attachment Flow
Figure 6.5: Failed Delivery Attempt Decision Flowchart (ADR-004)
Figure 6.6: Dispatch & Delivery Relational Entity-Relationship Diagram (ERD)
Figure 7.1: Clean Architecture Package Layout for Merchant Module
Figure 7.2: Merchant Approval State Machine Flowchart
Figure 7.3: B2B Merchant Automated Order Creation via Secured API
Figure 7.4: Outbound Webhook Delivery & Exponential Backoff Retry Flow
Figure 7.5: Merchant Persistence Schema Relational Entity-Relationship Diagram
Figure 7.6: Cryptographic API Key Authentication & Constant-Time Verification Pipeline Flowchart
Figure 7.7: Webhook Registration Validation & SSRF Prevention Pipeline Flowchart
Figure 7.8: Outbound Webhook Dispatch, Exponential Backoff & Dead Letter Queue Flowchart
Figure 8.1: Tracking & Real-Time Projections Subsystem UML Use Case Model
Figure 8.2: Clean Hexagonal Architecture & Modular Layers for Tracking Subsystem
Figure 8.3: Distributed Multi-Pod Deployment & Kubernetes Infrastructure Topology
Figure 8.4: Real-Time Server-Sent Events (SSE) Stream & Distributed Fan-Out Sequence Flow
Figure 8.5: Public Tracking Lookup & SEC-009 Privacy Masking Sequence Flow
Figure 8.6: SSE Client Reconnection & Exponential Backoff Activity Workflow
Figure 8.7: Resilient 30-Second REST Polling Degradation Flowchart
Figure 8.8: Read-Optimized Tracking Projection Schema & ER Diagram
Figure 9.1: Customer 4-Step Parcel Booking Wizard Journey Flowchart
Figure 9.2: Public Real-Time Tracking Live View Journey
Figure 10.1: Traefik Dynamic Ingress Routing Architecture
Figure 10.2: Edge Rate Limiting & Denial-of-Service Defense Flow
Figure 11.1: Asynchronous Event-Driven Messaging & Outbox Relay Architecture
Figure 11.2: RabbitMQ Topic Exchange & Dead-Letter Broker Topology
Figure 11.3: Transactional Outbox Persistence & Polling Relay Loop
Figure 11.4: Dead-Letter Queue (DLQ) Routing & Operator Replay Pipeline
Figure 11.5: Merchant Webhook Delivery & SSRF-Hardened Egress Pipeline
Figure 11.6: Server-Side Request Forgery (SSRF) Egress Defense Decision Flowchart
Figure 12.1: Docker Compose Multi-Container Orchestration Topology
Figure 12.2: Kubernetes Cluster Architecture, Services & Ingress
Figure 12.3: Continuous Integration & Automated Deployment Quality Gate Pipeline

Figure 13.1: SwiftDrop AI Delivery Assistant & FastMCP Service UML Use Case Model
Figure 13.2: High-Level AI Delivery Assistant & FastMCP System Architecture Overview
Figure 13.3: Conversational Intent Parsing, Tariff Estimation & Action Directive Flow (SEQ-AI-02)
Figure 13.4: FastMCP Tool Discovery & Protocol Execution Sequence (SEQ-AI-05/06)
Figure 13.5: Cross-Workflow Quality & E2E Test Harness Architecture Topology
Figure 13.6: Cross-Workflow Quality & E2E Acceptance Testing Use Case Model
Figure 13.7: Webhook Transient Failure, Backoff Retries & Dead-Letter Queue Pipeline (SEQ-QA-04)
Figure 14.1: Master Relational Entity-Relationship Diagram (26 Canonical Tables)
Figure 14.2: Canonical Sequential Database Migration Dependency Chain (Migrations 000001 through 000011)
Figure 17.1: SwiftDrop Unified Authentication Portal (Demonstration Prototype Login Screen)
Figure 17.2: Administrator Operations & Governance Console (Role: ADMIN — RBAC Demonstration)
Figure 17.3: Central Dispatcher Operations Console (Role: DISPATCHER — RBAC Demonstration)
Figure 17.4: Courier Mobile Driver Route & POD Console (Role: COURIER — RBAC Demonstration)
Figure 17.5: B2B Merchant Logistics & Shipping Console (Role: MERCHANT — Tenant Scoping Demonstration)
Figure 17.6: Customer Self-Service Parcel Portal (Role: CUSTOMER — RBAC Demonstration)

LIST OF TABLES

Table 1.1: Comprehensive Business Requirements Traceability Matrix
Table 1.2: Specification Chapter Ownership and 10-Member Subsystem Mapping
Table 3.1: Comparative Analysis of Architecture Patterns
Table 3.2: Technical Evaluation of Core Backend Programming Languages
Table 4.1: Identity Subsystem Security Hardening & Threat Mitigation Matrix
Table 5.1: Comparative Analysis of Parcel Lifecycle & State Management Strategies
Table 6.1: Technical Justification for Concurrency Control during Parcel Assignment
Table 7.1: Architectural Evaluation of Webhook Delivery & Integration Patterns
Table 8.1: Comparison of Real-Time Push Technologies
Table 9.1: Architectural Justification for Frontend Framework
Table 9.2: Frontend Application Route Hierarchy and Role Access Matrix
Table 10.1: Technical Justification for Ingress Controller
Table 10.2: Traefik Ingress Gateway Dynamic Route Mappings and Middleware Policy
Table 11.1: Technical Justification for Outbox Pattern
Table 11.2: Comparative Evaluation of Enterprise Message Brokers
Table 11.3: Messaging Subsystem Architectural Decision Records (ADR-005 through ADR-010)
Table 12.1: Technical Evaluation of Hosting & Orchestration Platforms
Table 13.1: Technical Comparison of LLM Integration Architectures
Table 14.1: Comprehensive Relational Table Specifications & Key Constraints
Table 16.1: STRIDE Threat Analysis & Architectural Mitigations Matrix
Table 16.2: Centralized RBAC Endpoint Authorization Matrix
Table 17.1: Pre-Configured Evaluation Test Accounts & Role Credentials
Table 17.2: Platform Component Implementation & Milestone Delivery Status Matrix
Table 18.1: Master 10-Member Capability Workload Allocation Matrix
Table 19.1: Project Architectural Risk Register & Mitigation Strategy
Table A.1: Master REST API Endpoint Contracts & Specification Index
Table B.1: Comprehensive RBAC Permission Matrix & System Entitlements

LIST OF ABBREVIATIONS & SYSTEM GLOSSARY

ACID: Atomicity, Consistency, Isolation, Durability

ADR: Architectural Decision Record

AMQP: Advanced Message Queuing Protocol

API: Application Programming Interface

BFF: Backend for Frontend

CDC: Change Data Capture

CORS: Cross-Origin Resource Sharing

DDD: Domain-Driven Design

DLQ: Dead Letter Queue

DLX: Dead Letter Exchange

ERD: Entity Relationship Diagram

FSM: Finite State Machine

FURPS: Functionality, Usability, Reliability, Performance, Supportability

HMAC: Hash-based Message Authentication Code

HPA: Horizontal Pod Autoscaler

IDOR: Insecure Direct Object Reference

JWT: JSON Web Token

K3s: Lightweight Certified Kubernetes Distribution

KEDA: Kubernetes Event-driven Autoscaling

LKR: Sri Lankan Rupee (ISO 4217 Currency Code)

MCP: Model Context Protocol

OIDC: OpenID Connect

PDPA: Personal Data Protection Act (Sri Lanka No. 9 of 2022)

PII: Personally Identifiable Information

POD: Proof of Delivery

RBAC: Role-Based Access Control

REST: Representational State Transfer

RTM: Requirements Traceability Matrix

SKIP LOCKED: Non-Blocking Concurrent Row Selection Engine (PostgreSQL)

SOLID: Single responsibility, Open-closed, Liskov substitution, Interface segregation, Dependency inversion

SPA: Single Page Application

SRS: Software Requirements Specification

SSE: Server-Sent Events

SSRF: Server-Side Request Forgery

TLS: Transport Layer Security

TTL: Time to Live

UML: Unified Modeling Language

UUIDv7: Universally Unique Identifier Version 7 (Time-Ordered Epoch)

CHAPTER 1

INTRODUCTION

1.1 Project Background

1.1.1 Problem Statement

In contemporary parcel logistics and urban courier ecosystems, efficiency, transparency, and data integrity represent foundational competitive differentiators. SwiftDrop currently manages parcel bookings, fleet routing, and merchant interactions through fragmented, semi-automated manual channels—predominantly unencrypted phone communication, paper waybills, and uncoordinated spreadsheet entries. This operational posture introduces critical vulnerabilities, including catastrophic parcel misplacements, untracked delivery failures, courier dispatch deadlocks, billing discrepancies, and an absolute lack of real-time shipment visibility for end-customers and enterprise merchants.

As shipment volumes scale linearly, manual workflows fail exponentially. Multiple dispatchers simultaneously assign parcels to the same overburdened courier without visibility into vehicle load capacities or delivery zones, resulting in courier fatigue, missed delivery service-level agreements (SLAs), and customer dissatisfaction. Furthermore, third-party merchants lack programmatic API access to submit bulk orders or receive automated delivery status notifications, creating severe communication bottlenecks.

To permanently resolve these systemic inefficiencies, the engineering team has architected SwiftDrop. SwiftDrop replaces disparate legacy workflows with an authoritative, event-driven digital platform delivering automated booking, dynamic pricing calculation, optimized dispatch boards, live SSE tracking projections, cryptographic proof of delivery, and seamless B2B partner integration.

1.2 Project Scope & Strategic Engineering Objectives

The overarching objective of the SwiftDrop project is to design, implement, secure, containerize, and formally specify an enterprise-grade parcel delivery and courier management platform. In accordance with IEEE Std 1016-2009 and ISO/IEC/IEEE 42010 architecture frameworks, the platform encompasses the following strategic technical objectives:

1. Architectural Rigor & Clean Domain Boundaries: Implement a Domain-Driven Design (DDD) Go Modular Monolith for core business domains (Identity, Parcels, Pricing, Dispatch, Delivery, Merchants) coupled with specialized deployable services (Tracking SSE API, Outbox Relay daemon, Event Worker consumer, and Generative AI assistant), ensuring zero circular dependencies and clean layer isolation.

2. Absolute Transactional Integrity: Guarantee strict ACID transactions across all parcel lifecycle state transitions, eliminating data anomalies via aggregate root encapsulation, PostgreSQL advisory locking, and single-transaction audit history and outbox event commits.

3. Asynchronous Resilience & At-Least-Once Delivery: Construct a reliable asynchronous integration backbone utilizing the Transactional Outbox pattern, an AMQP RabbitMQ message broker with Dead Letter Queues (DLQ), and idempotent consumer processing.

4. Defensive Enterprise Security & Multi-Tenancy: Enforce defense-in-depth security featuring an enterprise credential hashing architecture targeting Argon2id (ADR-003, with a verified Salted SHA-256 10,000-round prototype baseline and transparent re-hashing upgrade path under TD-SEC-01), dual-token JWT authentication with sliding refresh sessions (HS256 in v1.0 prototype; RS256/EdDSA target), centralized RBAC middleware, strict IDOR tenant isolation, SSRF defenses on external webhooks, and PII masking on public endpoints.

5. Production Readiness & Verifiable Quality: Provide multi-container Docker Compose orchestration for local development, production-ready Kubernetes (K3s) deployment manifests (including PostgreSQL, RabbitMQ, and KEDA worker autoscaling), automated test suites, and deliver a working Release v1.0 authentication baseline with pre-seeded test accounts.

To provide unambiguous accountability across the multi-member engineering team, Table 1.2 maps the primary domain capability, ownership lead, and chapter responsibilities across all 10 members:

Table 1.2: Specification Chapter Ownership and 10-Member Subsystem Mapping

Chapter Number & Title	**Primary Owner**	**Domain Responsibility & Scope**
Chapter 4: Identity, Access Control & Security Architecture	Member 1: K.G.U. Mihiranga (234129P)	Authentication, JWT, roles, permissions, tenant validation, security architecture

Chapter Number & Title	Primary Owner	Domain Responsibility & Scope
Chapter 5: Parcel Lifecycle Management & Dynamic Pricing Subsystem	Member 2: K.K.D.A.N. Ashara (234017V)	Parcel aggregate root, 9-state booking lifecycle, dimension validation, dynamic tariff engine
Chapter 6: Courier Dispatching, Route Optimization & Delivery Execution	Member 3: W.A.A.S. Atapattu (234024M)	Dispatcher board, advisory lock courier assignment, mobile driver manifest, proof of delivery
Chapter 7: Merchant Tenant Integration & Automated B2B Subsystem	Member 4: K.A.S.S. Samarakkodi (234200X)	Commercial tenant onboarding, SHA-256 API keys, webhook subscriptions, constant-time verification
Chapter 8: Real-Time Shipment Tracking & Streaming Updates Subsystem	Member 5: H.K.S. Sulakma (234208B)	Standalone Go SSE service, read-optimized tracking projections, public sanitized lookup
Chapter 9: Frontend User Experience & Client Application Subsystem	Member 6: W.T.D. Tharushika (234210G)	React/TypeScript SPA, customer/merchant portal, 4-step booking wizard, tracking journey
Chapter 10: Edge Ingress, API Gateway & Traffic Routing Subsystem	Member 7: H.M.B.N. Bhagya (234035B)	Traefik v3 reverse proxy, path-based routing, edge rate limiting, TLS 1.3 termination, Admin backend
Chapter 11: Asynchronous Event-Driven Messaging & Transactional Outbox Subsystem	Member 8: M.G.K.I. Udithya (234211K)	Transactional outbox writer, singleton relay daemon, RabbitMQ topic topology, idempotent worker
Chapter 12: DevOps, Containerization & Cloud Infrastructure Platform	Member 9: L.H.S.N. Wakishta (234215D)	Multi-stage distroless Dockerfiles, docker-compose orchestration, K3s Kubernetes, CI verify pipeline
Chapter 13: Generative AI Delivery Assistant & Cross-Workflow Subsystem	Member 10: T.A. Jayathilaka (234076C)	Python/FastAPI assistant, Model Context Protocol (FastMCP) tool calling, end-to-end quality harness

1.3 Enterprise Stakeholder Taxonomy & Actor Responsibilities

SwiftDrop establishes a formal taxonomy of five primary human actors and four automated system actors, defining unambiguous boundaries of operational responsibility:

1. Customer: Public individuals who register accounts, generate dynamic delivery quotes, book parcel shipments, manage address books, cancel uncollected parcels, and monitor live shipment milestones through responsive web interfaces.

2. Merchant: Commercial B2B enterprise tenants who onboard onto the platform, generate SHA-256 encrypted API keys, ingest high-volume batch shipment orders programmatically, configure webhook endpoints, and receive signed delivery notifications.

3. Courier: Field delivery personnel who access mobile-optimized delivery manifests, accept assigned parcel pickup routes, update transit status milestones, record failed delivery attempt justifications, and capture cryptographic proof of delivery (photo uploads and customer signatures).

4. Dispatcher: Operational logistics supervisors who manage regional delivery zones, monitor active courier capacity and vehicle loads, execute parcel dispatch assignments via interactive cockpit boards, and resolve failed delivery escalations.

5. System Administrator: Platform operations personnel who manage system-wide tariff configuration rules, oversee merchant business approvals, maintain user account security, audit security logs, and inspect infrastructure telemetry.

6. Automated System Actors: The Outbox Relay Daemon (polling committed outbox events and publishing to RabbitMQ as a strict singleton), the Event Worker Service (consuming events, dispatching webhooks, and persisting notifications), the Reconciler Tool (scheduled background cron job performing retention pruning and dead-letter replay), and the Generative AI Assistant (parsing natural language customer inquiries and executing read-only MCP tool calls).

1.4 Business Requirements Traceability Matrix (RTM)

The Requirements Traceability Matrix (RTM) establishes bidirectional traceability between high-level enterprise business requirements, subsystem module ownership, database schemas, and verification criteria across the software development lifecycle. Cross-cutting persistence stores—including audit_logs (security auditing), idempotency_keys (mutation replay protection), and ai_conversations (session context)—serve all operational domains.

Table 1.1 documents the comprehensive traceability matrix for SwiftDrop:

Table 1.1: Comprehensive Business Requirements Traceability Matrix

Req ID	Strategic Business Requirement	Responsible Subsystem & Member	Persistent Data Store	Verification & Acceptance Criteria
BR-01	Secure User Authentication & RBAC	K.G.U. Mihiranga (234129P, Member 1) — Identity & Security	users, roles, user_roles, refresh_tokens, oauth_identities	Unit tests for Salted SHA-256 key stretching & constant-time verification; integration tests verifying JWT token issuance and HTTP 403 on role mismatch.
BR-02	Dynamic Pricing & Parcel Booking	W.H. Ashara (234023K, Member 2) — Parcels & Pricing	parcels, parcel_status_history, pricing_rules, pricing_quotes, parcel_addresses	Unit tests validating weight/dimension formulas; atomic transaction tests committing parcel and outbox records.
BR-03	Courier Assignment & Proof of Delivery	K.S. Atapattu (234025T, Member 3) — Dispatch & Delivery	couriers, courier_assignments, delivery_attempts	Concurrency tests validating PostgreSQL advisory locks during courier assignment; S3 pre-signed URL upload tests.
BR-04	Merchant Onboarding & Webhooks	K.D.N.D. Samarakkodi (234185G, Member 4) — Merchant Integration	merchants, merchant_api_credentials, webhook_endpoints	Integration tests asserting SHA-256 API key hashing and HMAC-SHA256 signature headers on outbound webhook payloads.
BR-05	Low-Latency Live Public Tracking	B.G.S. Sulakma (234200C, Member 5) — Tracking & SSE	PostgreSQL Read Replica / Pool, Redis Pub/Sub	Load test target verifying up to 5,000 concurrent streaming connections (benchmarked at 1,000+); automated tests confirming PII redaction on public queries.
BR-06	Unified Responsive Web Portals	R.K.S. Tharushika (234204R, Member 6) — Customer/Merchant Web	Local Storage / React Query Cache	End-to-end Playwright tests verifying 4-step booking wizard and live tracking map updates.
BR-07	Ingress Control & Dispatcher Console	M.A.P. Bhagya (235019L, Member 7) — Dispatcher/Admin & Gateway	Traefik Dynamic Configuration	Automated curl tests verifying IP rate limiting (5 req/min burst 3 on login, 120 req/min on merchant API) and path-prefix routing.

Req ID	Strategic Business Requirement	Responsible Subsystem & Member	Persistent Data Store	Verification & Acceptance Criteria
BR-08	Guaranteed Event Relaying & Workers	M.G.K.I. Udithya (234211K, Member 8) — Event Messaging & Outbox	outbox_events, processed_events, notification_deliveries, webhook_deliveries, webhook_delivery_attempts, RabbitMQ, swiftdrop.dlq	End-to-end integration tests asserting at-least-once outbox publishing and worker idempotency deduplication.
BR-09	Cloud-Native Deployment & Telemetry	M.D. Wakishta (234217J, Member 9) — DevOps & Kubernetes	Docker Compose, K3s, Prometheus	CI pipeline running scripts/verify.sh; Kubernetes readiness/liveness probe assertions.
BR-10	Natural Language Support & Quality	A.A.P.R. Jayathilaka (234096J, Member 10) — AI Assistant & Quality	Read-Only MCP Tool Interface	Pytest suite validating tool parameter constraints and deterministic fallbacks on backend timeouts.

CHAPTER 2

GLOBAL REQUIREMENTS ENGINEERING & MASTER USE CASE MODEL

2.1 Functional Requirements Hierarchy

The functional capabilities of SwiftDrop are structured into a formal three-tier functional decomposition hierarchy comprising Authentication & Access Control (F-01 to F-05), Parcel Lifecycle & Tariff Calculations (F-06 to F-12), Fleet Dispatch & Milestone Tracking (F-13 to F-18), Merchant B2B Integration (F-19 to F-23), and Platform Intelligence & Administration (F-24 to F-28).

Tier 1: Core Transactional Capabilities encompass customer and merchant user registration, multi-factor credential authentication, parcel quotation generation based on physical dimensions and delivery zones, parcel booking with atomic outbox event persistence, dispatcher courier matching, and courier milestone recording.

Tier 2: Real-Time Communication & Outbound Integration encompass public shipment tracking via Server-Sent Events, Redis-backed event fan-out, outbound HMAC-SHA256 signed webhook delivery to merchant URLs, and asynchronous email notification triggers via RabbitMQ consumer workers.

Tier 3: Platform Governance & Intelligence encompass administrator pricing rule configuration, operational delivery zone and postal code prefix management (zone_postal_codes), courier fleet performance metrics, dead-letter queue inspection, and conversational parcel tracking via the Generative AI assistant.

2.2 Non-Functional Requirements (FURPS+ Model Analysis)

To guarantee enterprise-grade operational quality and architectural compliance, non-functional requirements are modeled in strict alignment with the FURPS+ taxonomy (Functionality, Usability, Reliability, Performance, Supportability, plus Design and Implementation Constraints) with concrete, verifiable metrics:

1. Functionality (Security & Authorization): The system must enforce granular Role-Based Access Control (RBAC) across all administrative, operational, and customer endpoints.

Authentication must validate JWT claims on every protected request with zero trust, completely preventing privilege escalation and Insecure Direct Object Reference (IDOR) attacks across merchant tenants.

2. Usability & User Experience: Web interfaces must be fully responsive across desktop, tablet, and mobile form factors, achieving Google Lighthouse accessibility scores exceeding 90. The customer parcel booking wizard must enable end-to-end shipment creation in under four interactive wizard steps with real-time client-side dimension validation.

3. Reliability & Availability: The transactional core must maintain a 99.5% uptime target during operational dispatch hours. The Transactional Outbox pattern guarantees at-least-once delivery with zero message loss during transient network partitions or broker restarts. Downstream message consumers must achieve 100% idempotent deduplication via database ledgers.

4. Performance & Latency Targets: Core API REST endpoints must maintain sub-200 millisecond response times at the 95th percentile ($p95 < 200$ ms) under a sustained nominal load of 100 concurrent active users. The read-optimized Tracking SSE service must broadcast milestone status updates with an end-to-end latency below 100 milliseconds ($p95 < 100$ ms) while supporting up to 5,000 concurrent streaming connections with memory utilization below 256 megabytes.

5. Scalability & Elasticity: The Go Core API monolith handles up to 250 requests per second per container replica. Dedicated background Event Workers must scale horizontally from 1 to 3 Kubernetes pods based on RabbitMQ queue depth backlog exceeding 50 pending messages, preventing queue buildup during commercial dispatch surges.

6. Supportability & Observability: All microservices and modular monolith components must output structured JSON logs using uber-go/zap, propagating correlation IDs (X-Correlation-ID) across distributed boundaries. All services must export Prometheus metrics on /metrics and provide standardized Kubernetes health probes on /healthz (liveness) and /readyz (readiness), kept strictly internal to the cluster network.

7. Design & Implementation Constraints: The Core API must be implemented in pure Go (version 1.22+) adhering strictly to Clean Architecture layer isolation. Domain models must possess zero external framework dependencies. All monetary values must be represented

strictly as 64-bit signed integers storing minor currency units (cents in Sri Lankan Rupees - LKR) to permanently prevent binary floating-point rounding errors.

2.3 Master Enterprise System Use Case Model

Figure 2.1 illustrates the master UML use case model for SwiftDrop, establishing the behavioral boundaries between the primary human actors, automated background daemons, and system subsystems.




Figure 2.1: Master Enterprise System Use Case Diagram

The master use case model explicitly captures cross-cutting dependencies. Use Case UC-03 (Book Parcel) includes UC-02 (Calculate Pricing Quote) to enforce that bookings cannot proceed without a valid, cryptographically signed quote reference. Furthermore, UC-10 (Assign Courier) triggers an asynchronous notification workflow executed by UC-18 and UC-19, ensuring that courier assignments immediately reflect on courier mobile devices and merchant dashboards.

2.4 Inter-Actor Operational Interaction Matrix

The inter-actor interaction matrix models the transactional and asynchronous handoffs occurring between system participants across the parcel lifecycle.

When a Customer or Merchant books a parcel (UC-03 / UC-07), the Core API creates a parcel record in CREATED status and writes a corresponding outbox event. The Dispatcher observes the unassigned parcel on the real-time dispatch board (UC-09) and assigns an active Courier (UC-10), transitioning the aggregate status to ASSIGNED. This state mutation generates an assignment event, prompting the Outbox Relay to publish a message to RabbitMQ.

The Courier inspects their mobile daily manifest via the Courier Portal (UC-12) and scans the physical package at pickup, transitioning the state to PICKED_UP (UC-13). As the courier navigates transit milestones, the Outbox Relay publishes event messages to the RabbitMQ topic exchange (swiftdrop.events.topic); the Tracking API consumes q.tracking.updates directly to stream live Server-Sent Events (SSE) to the customer (UC-04), while the Event Worker consumes q.notifications.worker and q.webhooks.dispatcher to trigger signed merchant webhooks and customer email notifications upon delivery (UC-14).

CHAPTER 3

GLOBAL SYSTEM ARCHITECTURE PROPOSAL & FUNDAMENTAL TRADE-OFFS

3.1 Architectural Philosophy: The Case for a Modular Monolith with Specialized Services

The architecture of SwiftDrop is defined as a Domain-Driven Design (DDD) Go Modular Monolith complemented by specialized deployable services for read-heavy and asynchronous workloads (governed by ADR-002).

During architectural planning, the engineering team rigorously evaluated three competing structural paradigms: a Distributed Microservices Mesh (10 independent services), a Traditional Monolithic Application, and a Modular Monolith with Targeted Standalone Services. While pure microservices offer extreme independent scaling, they introduce severe operational complexities for an enterprise logistics platform: distributed transaction failures, network latency overhead, complex two-phase commit (2PC) rollbacks across parcel assignment boundaries, and difficult local developer workflows.

Conversely, a monolithic architecture without boundaries rapidly degenerates into a tangled 'big ball of mud', where database tables are updated across modules without invariant validation. SwiftDrop combines the strengths of both approaches: core business operations (Identity, Parcels, Pricing, Dispatch, Delivery, Merchants) reside within a single modular Go binary with strictly enforced internal package boundaries, sharing a single authoritative PostgreSQL database. Meanwhile, read-intensive public tracking (Tracking SSE API), heavy outbox publication (Outbox Relay), long-running asynchronous webhook execution (Event Worker), and Python-based NLP processing (AI Assistant) are partitioned into dedicated deployable binaries. Operationally, the Outbox Relay runs as a strict singleton process (exactly one replica) to guarantee sequential polling without distributed lock contention, whereas the Event Worker scales horizontally via KEDA based on queue backlog.

3.2 High-Level System Topology & Tier Decomposition

Figure 3.1 illustrates the five functional tiers comprising the SwiftDrop enterprise system topology.




Figure 3.1: SwiftDrop High-Level System Topology Diagram

The five functional tiers operate with strict dependency isolation. Tier 1 clients communicate solely through Tier 2 (Traefik Ingress Controller). The Core API (Tier 3A) executes state transitions within atomic PostgreSQL transactions (Tier 5), committing updated entity states and outbox event records simultaneously. The Asynchronous Backbone (Tier 4) guarantees at-least-once message delivery to downstream consumers without distributed two-phase locking.

3.3 Comparative Architecture Trade-Off Analysis

Table 3.1 presents the comparative architectural trade-off analysis evaluated by the engineering team, providing technical justification for the selected hybrid topology:

Table 3.1: Comparative Analysis of Architecture Patterns

Architectural Dimension	**Distributed Microservices Mesh**	**Pure Monolithic Application**	**SwiftDrop Hybrid Topology (Selected)**
Data Consistency	Eventual consistency; complex 2PC / Sagas across service boundaries.	ACID guaranteed via shared local database transactions.	ACID guaranteed for all core parcel transitions; eventual consistency for read tracking.

Architectural Dimension	Distributed Microservices Mesh	Pure Monolithic Application	SwiftDrop Hybrid Topology (Selected)
Operational Complexity	Very High: Requires service mesh, distributed tracing, complex CI/CD.	Low: Single build artifact, simple deployment.	Moderate: Go Modular Monolith + 4 specialized deployable services (Tracking API, Outbox Relay, Event Worker, AI Assistant) plus Reconciler CronJob.
Deployment Independence	High: Every service deploys independently.	Zero: Any bug requires full system redeployment.	Targeted: High-churn tracking and messaging deploy independently from Core API.
Network Latency Overhead	High: Cascading HTTP/gRPC hops across microservices.	Zero: In-process Go function calls across internal packages.	Minimal: In-process function calls within Core API; high-speed AMQP for async tasks.
Failure Blast Radius	Isolated to individual microservices.	High: Memory leak or crash halts entire platform.	Protected: Outbox poller and SSE service run in isolated memory spaces.
Resource Footprint	Heavy: Substantial CPU/RAM overhead per container.	Very Low: Single process overhead.	Optimized: Go Modular Monolith consumes < 60MB RAM; K3s cluster fits in 2GB RAM.

API & Event Versioning Strategy: SwiftDrop implements explicit URI-based versioning for all HTTP REST interfaces (/api/v1/*), ensuring strict backward compatibility for mobile clients and merchant enterprise integrations. Additive schema enhancements (new JSON fields, optional query parameters) are supported without version increments. If a non-backward-compatible change is required in a future release, a new URI namespace (/api/v2/*) will be introduced concurrently, accompanied by a mandatory 6-month deprecation notice communicated via standard HTTP Sunset (RFC 8594) and Deprecation response headers. Decoupled from HTTP endpoints, asynchronous event schemas enforce contract versioning through canonical suffix identifiers (<aggregate>.<action>.v1), guaranteeing that downstream workers and merchant webhooks deserialize versioned payloads deterministically without breaking on internal domain refactorings.

3.4 Summary of Architectural Decision Records (ADR-001 through ADR-004)

The architectural governance of SwiftDrop is codified in four authoritative, binding Architectural Decision Records (ADRs):

1. ADR-001: Traefik as Ingress Controller & Reverse Proxy. Traefik was selected over NGINX and Kong due to its native Docker/Kubernetes service discovery, seamless TLS Let's Encrypt automation, low latency, and built-in middleware for IP-based rate limiting and path rewrites.

2. ADR-002: Modular Monolith with Dedicated Deployable Workload Services. Core business logic is encapsulated in a Go modular monolith, while read-heavy public tracking, outbox publishing, event processing, and AI tools are partitioned into standalone services hosted on lightweight Kubernetes (K3s).

3. ADR-003: Dual-Token JWT & Authentication Architecture. User authentication targets Argon2id password hashing (memory-hard, resistant to GPU/ASIC attacks; implemented as Salted SHA-256 with 10,000 rounds in the Phase 1 prototype baseline with transparent migration scheduled under TD-SEC-01), dual-token JWT sessions (target architecture specifies RS256/EdDSA with public JWKS; Phase 1 operational prototype uses HMAC-SHA256), and federated Google OAuth 2.0 / OIDC.

4. ADR-004: Failed Delivery Attempt Semantics & Max 3 Attempt Limit. Couriers are permitted a maximum of three delivery attempts per parcel, each requiring explicit reason classification (Customer Unavailable, Incorrect Address, Refused, Restricted Access). Upon the third failure, the parcel aggregate automatically transitions to RETURNED, prohibiting further field assignments.

3.5 Authoritative Relational Persistence Philosophy

PostgreSQL 16 was selected as the sole authoritative persistence engine for SwiftDrop. While NoSQL document stores provide schema flexibility, parcel logistics operations inherently require strict relational integrity, foreign key cascading constraints, ACID transactional guarantees, and concurrency serialization.

PostgreSQL fulfills these enterprise requirements through support for declarative foreign keys, partial B-Tree indexing, JSONB storage for unstructured webhook payloads, row-level locking (SELECT ... FOR UPDATE SKIP LOCKED) for outbox relay workers, and session-level Advisory Locks to eliminate race conditions during simultaneous courier dispatch assignments.

3.6 High-Precision Financial Computation Strategy

In accordance with international banking software standards and SwiftDrop Engineering Standards §3.2, all monetary figures—including delivery fees, distance surcharges, weight tariffs, and merchant discounts—are strictly represented as 64-bit signed integers (BIGINT) storing minor currency units (cents in Sri Lankan Rupees - LKR).

This architectural invariant permanently eliminates IEEE 754 binary floating-point rounding errors common in commercial software (e.g., 0.1 + 0.2 != 0.3). In database schemas, fee columns use BIGINT NOT NULL paired with a currency VARCHAR(3) NOT NULL DEFAULT 'LKR' column. In Go domain models, fees use int64 types. Conversions to major currency units (Rupees) occur strictly at the presentation boundary in frontend formatters.

3.7 Technology Stack & Programming Language Selection Justification

The selection of programming languages, execution runtimes, and core platforms across SwiftDrop is guided by strict operational requirements: sub-100ms response latencies, minimal memory overhead for high-density container packing on economic infrastructure, compile-time type safety, and clean domain boundary isolation.

Table 3.2 documents the comparative evaluation and architectural justification for the core backend programming language selected for the Modular Monolith:

Table 3.2: Technical Evaluation of Core Backend Programming Languages

Criteria	Java / Spring Boot	Node.js / NestJS	Go (Golang 1.22+) (Selected)	Architectural Justification
Concurrency Model	Heavyweight OS threads (1MB stack per thread); Project Loom virtual threads still maturing.	Single-threaded event loop; CPU-bound cryptographic operations block asynchronous I/O.	Lightweight Goroutines (2KB initial stack, multiplexed on M:N scheduler).	Handles thousands of concurrent parcel status updates and SSE connections with sub-millisecond response.
Memory Footprint	Heavy: 400MB to 800MB baseline RSS per JVM container.	Moderate: 150MB to 250MB RSS per V8 process.	Minimal: Under 45MB baseline RSS (<60MB under production load).	Enables running the complete SwiftDrop cluster on an economical single-node VPS (ADR-002) within 2GB RAM.

Criteria	Java / Spring Boot	Node.js / NestJS	Go (Golang 1.22+) (Selected)	Architectural Justification
Compilation & Deployability	Fat JAR requires heavy JVM container image (>250MB).	Requires Node.js runtime and node_modules directory (>300MB).	Compiles to single static binary with zero runtime dependencies. Distroless image <20MB.	Drastically accelerates CI/CD pipelines, minimizes container attack surface, and eliminates runtime dependency drift.
Domain Clean Architecture	Relies heavily on reflection, dynamic proxies, and annotation magic.	Dynamic typing requires runtime validators; decorators add framework coupling.	Enforces explicit error handling, compile-time interfaces, and strict package isolation.	Pure domain entities cannot accidentally import infrastructure or HTTP packages, preserving DDD layer purity.

For specialized satellite services, language choices are optimized for specific domain capabilities: Python 3.11 was selected for the AI Assistant Service (Chapter 13) to leverage the native FastMCP SDK and comprehensive machine learning ecosystem, while TypeScript (strict mode) with React 18 was selected for the frontend (Chapter 9) to enforce end-to-end type parity with backend API DTOs.

CHAPTER 4

IDENTITY, ACCESS CONTROL & SECURITY SUBSYSTEM

4.1 Subsystem Scope & Functional Boundaries

The Identity, Access Control & Security Subsystem serves as the authoritative security perimeter and trust anchor for the SwiftDrop enterprise platform. Engineered within core-api/internal/identity/ as a production-ready module following Clean Architecture principles, this subsystem encapsulates user credential authentication, iterative key-stretched password hashing, constant-time verification, dual-token JWT lifecycle management, in-memory access token security, HttpOnly refresh cookie rotation, and Role-Based Access Control (RBAC) authorization enforcement.

The subsystem runtime leverages pure Go 1.22+ standard library primitives, deliberately avoiding external web framework bloat to maintain maximum execution performance, auditability, and memory efficiency. Relational persistence is anchored in PostgreSQL 16 using parameterized ACID transactions via github.com/lib/pq. Database migrations execute inside transactional blocks managed by an embedded Go migrator (embed.FS) that tracks schema versioning in the authoritative schema_migrations ledger.

Functional boundaries strictly dictate that the Identity subsystem owns the users and refresh_tokens tables. It provides reusable authentication middleware to all other Core API modules while strictly isolating internal credential structures (password hashes, refresh session tokens, and cryptographic keys) from external callers. Subsystems such as Parcels, Dispatch, Pricing, and Merchants are strictly prohibited from mutating user roles or bypassing token verification.

Figure 4.1 illustrates the comprehensive UML Use Case model for the Identity, Access Management & Security Subsystem, detailing authentication, session management, role verification, and access control capabilities across platform actors:




Figure 4.1: Identity, Access Management & RBAC Subsystem UML Use Case Model

Traceability & SRS Requirements: Subsystem capabilities map to formal requirements: FR-AUTH-001 (User Account Registration), FR-AUTH-002 (Password Authentication & JWT Issuance), FR-AUTH-003 (Token Refresh with Family Revocation), and FR-AUTH-004 (Role-Based Access Control Enforcement).

4.2 Architectural Design & Clean DDD Layers

In strict compliance with Clean Architecture and Domain-Driven Design principles, the Identity subsystem is decoupled into four isolated architectural layers with unidirectional inward dependency flow:

1. Domain Layer (internal/identity/domain/): Contains pure domain entities, value objects, and domain errors with zero external dependencies (importing neither database/sql nor net/http):

- Email Value Object: Validates email strings against an RFC 5322 compliant regular expression, rejecting empty inputs or lengths exceeding 254 characters (ErrInvalidEmail), while automatically trimming whitespace and normalizing to lowercase.
- Password Policy (ValidatePlaintextPassword): Enforces strict complexity invariants—length between 8 and 128 characters, with mandatory inclusion of at least one uppercase letter (A-Z), one lowercase letter (a-z), one numeric digit (0-9), and one special symbol or punctuation character (@$!%*?&...). Non-compliant inputs immediately return ErrWeakPassword.

- Canonical Roles (Role Value Object): Authoritatively governs the 5 platform roles—ADMIN, DISPATCHER, COURIER, MERCHANT, and CUSTOMER. Roles are parsed case-insensitively with whitespace normalization; unrecognized values trigger ErrInvalidRole.
- Account Status Invariants: The user.IsActive() domain guard prevents suspended or disabled accounts from receiving valid authentication tokens, immediately halting execution with ErrUserSuspended.

2. Application Layer (internal/identity/application/): Orchestrates authentication use cases via AuthService and UserService. Defines repository interfaces (UserRepository, RefreshTokenRepository) and cryptographic abstractions (PasswordHasher, TokenService).

3. Infrastructure Layer (internal/identity/infrastructure/): Implements persistence interfaces using parameterized PostgreSQL queries, salted key-stretched SHA-256 hashing (10,000 rounds, 16-byte random salt, colon-delimited storage), and HMAC-SHA256 symmetric JWT signing.

4. Transport Layer (internal/identity/transport/): Thin HTTP handlers mapping JSON requests to application command DTOs, validating inputs, executing cookie management, and providing context propagation middleware (Authenticate, RequireRole, RequireTenant) and retrieval helpers (transport.GetUser(ctx), transport.GetTenantID(ctx)).

Figure 4.2 depicts the layered and hexagonal architecture of the Identity subsystem, showcasing the strict Ports and Adapters boundary isolating core domain business invariants from external transport handlers and relational persistence drivers:




Figure 4.2: Layered & Hexagonal Architecture Component Layout for Identity Subsystem

4.3 Dynamic Execution Flows & Drawn Sequence Diagrams

The Identity subsystem executes secure authentication through an iterative key-stretched password hashing pipeline and a dual-token lifecycle with refresh token family rotation.

Figure 4.3 illustrates the dynamic password authentication lifecycle, detailing credential retrieval, iterative salted key stretching, constant-time verification, in-memory access token issuance, and HttpOnly refresh token rotation (the architectural target and Phase 1 prototype baseline are formally analyzed in Section 4.6):




Figure 4.3: Password Login & JWT Issuance Sequence Diagram

Figure 4.4 illustrates the planned federated Google OAuth 2.0 / OpenID Connect (OIDC) authentication architecture design, detailing social identity verification and account provisioning in the platform roadmap:




Figure 4.4: Federated Google OAuth 2.0 & OpenID Connect (OIDC) Sequence Flow

4.4 Input & Output Data Contracts

The Identity module exposes public and protected REST endpoints adhering strictly to SwiftDrop API conventions (JSON snake_case, standard { "status": "success", "data": ... } envelopes):

1. User Login: POST /api/v1/auth/login (Public)

Request Headers: Content-Type: application/json

Request Body:

```
{
  "email": "admin@swiftdrop.local",
  "password": "AdminPassword123!"
}
```

Success Response (200 OK):

Response Headers:

```
Set-Cookie: refresh_token=...; Path=/api/v1/auth; HttpOnly; Secure; SameSite=Strict;
Max-Age=604800
```

Response Body:

```
{
  "status": "success",
  "data": {
    "access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...",
    "token_type": "Bearer",
    "expires_in": 900,
    "user": {
      "id": "usr_01HADMIN00000000000000001",
      "email": "admin@swiftdrop.local",
      "display_name": "System Administrator",
      "role": "ADMIN",
      "tenant_id": ""
    }
  }
}
```

Error Status Codes:

- 400 Bad Request: Malformed JSON or blank input fields.
- 401 Unauthorized: Invalid email address or incorrect password.
- 403 Forbidden: Account is suspended or inactive (user.IsActive() == false).

2. Current User Identity: GET /api/v1/auth/me (Protected)

Request Headers:

Authorization: Bearer <access_token>

Success Response (200 OK):

```
{
  "status": "success",
  "data": {
    "user": {
      "id": "usr_01HADMIN00000000000000001",
      "email": "admin@swiftdrop.local",
      "display_name": "System Administrator",
      "role": "ADMIN",
      "tenant_id": ""
    }
  }
}
```

Error Status Codes:

- 401 Unauthorized: Missing, malformed, or expired access token.

4.5 Data Modeling & Persistence Schema

The Identity module owns migration 000001_create_users_and_roles.up.sql, establishing the core user identity and session persistence structures:

1. users Table: Authoritative user account directory. Columns: id (VARCHAR(32) PRIMARY KEY, prefixed with usr_), email (VARCHAR(255) UNIQUE NOT NULL), password_hash (TEXT NOT NULL, formatted as <salt_hex>:<iterations>:<hash_hex>), role (VARCHAR(32) NOT NULL CHECK (role IN ('ADMIN', 'DISPATCHER', 'COURIER', 'MERCHANT', 'CUSTOMER'))), tenant_id (VARCHAR(64) NULL, indexed, populated with mrc_ for commercial merchants), display_name (VARCHAR(255) NOT NULL), status (VARCHAR(32) DEFAULT 'ACTIVE'), email_verified (BOOLEAN DEFAULT FALSE), created_at (TIMESTAMPTZ NOT NULL), updated_at (TIMESTAMPTZ NOT NULL).

2. refresh_tokens Table: Secure session family and token revocation ledger. Columns: id (VARCHAR(32) PRIMARY KEY), user_id (VARCHAR(32) REFERENCES users(id) ON DELETE CASCADE), token_hash (VARCHAR(64) UNIQUE NOT NULL), family_id (VARCHAR(32) NOT NULL, indexed), is_revoked (BOOLEAN DEFAULT FALSE), expires_at (TIMESTAMPTZ NOT NULL), created_at (TIMESTAMPTZ NOT NULL).

The relational database is pre-seeded with five canonical test accounts covering all platform roles to facilitate integration verification:
- Administrator: admin@swiftdrop.local / AdminPassword123! (Role: ADMIN)
- Dispatcher: dispatcher@swiftdrop.local / Dispatcher123! (Role: DISPATCHER)
- Courier: courier@swiftdrop.local / CourierPassword123! (Role: COURIER)
- Commercial Merchant: merchant@vendor.com / Merchant123! (Role: MERCHANT, Tenant: mrc_01HMERCHANTTENANT00001)
- Customer: customer@swiftdrop.local / CustomerPassword123! (Role: CUSTOMER)

Figure 4.5 illustrates the relational entity-relationship structure owned by the Identity subsystem, detailing the primary key indexes, foreign key cascading constraints, and session family associations:




Figure 4.5: Identity, User Roles & Authentication Relational Entity-Relationship Diagram

4.6 Technical Justifications: Key-Stretching, Token Engineering & Dual-Token Model

Table 4.1 details the security hardening matrix and defensive countermeasures engineered into the Identity subsystem:

Table 4.1: Identity Subsystem Security Hardening & Threat Mitigation Matrix

Threat Vector	Mitigation Strategy	Implementation Detail
Rainbow Table Attacks	Salted key stretching (Phase 1: Salted SHA-256 10,000 rounds; Phase 2 Target: Argon2id)	Unique 16-byte random salt per user prevents precomputed hash lookups; transparent re-hashing upgrade path defined under TD-SEC-01.
Timing Attacks	Constant-time equality checks	crypto/subtle.ConstantTimeCompare prevents response latency password probing.
XSS Token Theft	In-memory token storage	Access token resides strictly in application memory; never exposed to browser storage.
CSRF Exploitation	Strict Cookie isolation	Refresh tokens use SameSite=Strict, HttpOnly, and Secure flags.
SQL Injection	Parameterized queries	Prepared statements ($1, $2) ensure user inputs are never concatenated into SQL.
Token Replay	Short expiration & unique jti	Access tokens expire in 15 minutes and include distinct cryptographic UUIDs.
Session Hijacking	Refresh token family rotation	Reuse of a revoked token invalidates all associated active sessions immediately.

Password Hashing Architectural Target vs. Phase 1 Implementation Baseline: The target security architecture for SwiftDrop specifies Argon2id (RFC 9106, memory-hard, m=64MB, t=3, p=4), recognized by OWASP and NIST as the industry gold standard for resistance against specialized ASIC and GPU brute-force cracking rigs. In the Phase 1 operational prototype baseline, credential verification was implemented using standard-library Salted SHA-256 with 10,000 iterative key-stretching rounds and 16-byte cryptographically random salt entropy (crypto/rand), serialized as <salt_hex>:<iterations>:<hash_hex>. During login, comparisons execute strictly via crypto/subtle.ConstantTimeCompare() to eliminate side-channel timing attacks.

Cryptographic Technical Debt & Phase 2 Migration Path (TD-SEC-01): From an objective threat-modeling standpoint, 10,000 rounds of SHA-256 is acknowledged as an architectural concession and technical debt item (TD-SEC-01). While selected in the initial prototype to enforce a strict zero-external-dependency standard library implementation during initial container bring-up and isolated test execution, current OWASP Password Storage guidance requires either Argon2id (available in pure Go via golang.org/x/crypto/argon2) or at least 600,000 rounds of PBKDF2-HMAC-SHA256. Because SwiftDrop's Clean Architecture strictly encapsulates credential processing behind the PasswordHasher domain interface (internal/identity/domain/ports.go), migrating to Argon2id requires zero modifications to domain entities or HTTP transport handlers. Under milestone Sprint 3 (TD-SEC-01), the platform introduces the Argon2id adapter with a transparent 're-hash on authenticate' pipeline: when an existing user logs in, the authentication service verifies the legacy SHA-256 hash, computes the Argon2id hash, and atomically updates the users.password_hash record in PostgreSQL. A supplementary background worker is scheduled to handle dormant accounts.

Symmetric HMAC-SHA256 Token Signing: Within the Go modular monolith, the authentication issuer and all authorization middleware verifiers execute within the same protected internal runtime environment. Symmetric HMAC-SHA256 (HS256) provides maximum computational throughput, sub-millisecond validation latency, and minimal memory overhead via a secure 256-bit server secret (JWT_SECRET). This design achieves optimal performance without the computational overhead of asymmetric RSA operations, while maintaining a clean modular architecture that can seamlessly transition to asymmetric RS256/EdDSA if services are decoupled into distributed microservices.

Dual-Token Lifecycle & Storage Architecture: To protect against Cross-Site Scripting (XSS) and Cross-Site Request Forgery (CSRF), SwiftDrop enforces a dual-token architecture. The short-lived Access Token (15-minute expiration) is held strictly in application memory (React Context state) and transmitted via Authorization: Bearer <token>, completely preventing script-based token exfiltration from localStorage or sessionStorage. The long-lived Refresh Token (7-day lifespan) is stored in an HttpOnly, Secure, SameSite=Strict cookie scoped to /api/v1/auth. Refresh tokens are tracked in PostgreSQL under a shared family_id; when refreshed, the current token is atomically revoked and a new pair is issued. Presentation of an already revoked token triggers instant breach detection, revoking the entire token family and requiring full re-authentication.

4.7 Security Invariants & Defensive Hardening

The Identity module strictly enforces the following architectural security invariants:

1. Role-Based Access Control (RBAC) & Context Propagation: The Authenticate middleware validates incoming Bearer JWT tokens, verifies signatures and expiration claims, and injects the authenticated *domain.User entity and TenantID directly into the Go request context.Context. Downstream handlers access identity attributes via clean helper functions (transport.GetUser(ctx) and transport.GetTenantID(ctx)).

2. Granular Role & Tenant Guards: The RequireRole(...roles) middleware halts unauthorized callers with HTTP 403 Forbidden before execution reaches business use cases. The RequireTenant middleware enforces strict data boundaries for multi-tenant merchant operations, ensuring merchants can only query data matching their verified tenant_id (mrc_...).

3. RFC 7519 Token Claims Construction: Standardized token claims encapsulate sub (unique user ID), email, role (canonical role string), tenant_id, iat (issued at timestamp), exp (expiration timestamp), and jti (unique cryptographically random UUID per token for replay protection).

4.8 Comprehensive Testing Strategy & Acceptance Criteria

Verification is achieved through automated unit tests in internal/identity/domain/ asserting RFC 5322 email regex compliance, password complexity rules (uppercase, lowercase, numeric, symbol), role normalization, and active status invariants.

Cryptographic unit tests assert 16-byte random salt generation, 10,000-round key-stretched SHA-256 computation, and constant-time equality evaluation via crypto/subtle.ConstantTimeCompare().

Integration tests execute against PostgreSQL using the embedded migrator, verifying authentication flows across all 5 pre-seeded role accounts (ADMIN, DISPATCHER, COURIER, MERCHANT, CUSTOMER), validating HttpOnly cookie issuance, asserting 401 Unauthorized for malformed/expired credentials, and confirming that RequireRole middleware blocks privilege escalation with HTTP 403 Forbidden.

Acceptance criteria require 100% test pass rates across all authentication routes, zero plaintext credential persistence, zero hardcoded secrets in version control, and full compliance with SwiftDrop Engineering Standards v1.0.

CHAPTER 5

PARCEL LIFECYCLE MANAGEMENT & DYNAMIC PRICING SUBSYSTEM

5.1 Subsystem Scope & Physical Boundaries

The Parcel Lifecycle Management & Dynamic Pricing Subsystem serves as the core operational heartbeat of SwiftDrop, governing the complete parcel lifecycle state machine, dimensional and zone-pair tariff calculation engine, customer and merchant booking workflows, and atomic persistence orchestration. It encapsulates all domain rules regarding parcel weight and dimensional classifications, dynamic tariff quoting, and lifecycle state transitions across the delivery journey.

Physical boundaries dictate that all parcel state mutations MUST execute through the Parcel aggregate root in internal/parcels/domain/parcel.go within an atomic PostgreSQL transaction. Direct database updates bypassing the aggregate root or outbox event logger are strictly prohibited, guaranteeing that the immutable audit history in parcel_status_history and published integration events in outbox_events are always synchronized.

Subsystem ownership boundaries are strictly partitioned across engineering leads:
- Member 2 (Parcel Management & Pricing): Authoritative owner of the Parcel Aggregate Root, 9-state lifecycle authority, status transition validation, dynamic pricing engine, quote generation, and booking orchestration.
- Member 3 (Dispatch & Delivery): Coordinates courier assignment, mobile manifests, delivery attempts, and proof-of-delivery (POD). Member 3 invokes parcel lifecycle methods via the application use case interface (IParcelUseCase) within transactional boundaries, and never executes direct SQL updates on parcel status.
- Member 5 (Tracking): Consumes parcel lifecycle milestones and publishes read-optimized Server-Sent Events (SSE) and sanitized public tracking projections without modifying domain state.
- Member 7 (Admin & API Gateway): Manages delivery zones (zone_postal_codes) and administrative tariff configuration.
- Member 8 (Event Publishing): Provides the shared transactional outbox infrastructure and asynchronous RabbitMQ relay worker.

Figure 5.1 outlines the subsystem UML use case model, specifying functional interactions across Customer, Merchant Client, and Administrator actors with delivery fee estimation, customer booking, merchant parcel creation, booking cancellation, parcel details retrieval, status history audit, and tariff configuration:




Figure 5.1: Parcel Management & Dynamic Pricing Subsystem UML Use Case Model

Traceability & SRS Requirements: Subsystem capabilities map to formal requirements: FR-PRC-001 (Dynamic Tariff Estimation), FR-PRC-002 (15-Minute Guaranteed Quote Window), FR-PCL-001 (Customer Parcel Booking), FR-PCL-002 (Canonical 9-State Lifecycle Transitions), and FR-PCL-003 (Idempotent Parcel Cancellation).

5.2 Architectural Design: Parcel Aggregate Root Encapsulation

The subsystem adheres to strict Domain-Driven Design aggregate root boundaries:

1. Parcel Aggregate Root (internal/parcels/domain/parcel.go): Encapsulates physical dimensions (length_cm, width_cm, height_cm), actual weight (weight_kg), chargeable weight (chargeable_weight_kg), immutable JSONB address snapshots (pickup_address, dropoff_address), origin and destination zone identifiers, current lifecycle status (9-state FSM), assigned courier ID, attempt counter (attempt_count, max 3 attempts per ADR-004), and optimistic concurrency version (version INT NOT NULL DEFAULT 1). All state transitions evaluate domain invariants prior to database commits.

2. Pricing Engine Strategy Pattern (internal/pricing/domain/calculator.go): Resolves applicable tariffs based on origin/destination zone pairs (delivery_zones) and billable weight bands. Applies industry-standard volumetric weight pricing (L * W * H / 5000) with billable weight max(actual_weight, volumetric_weight). Calculates deterministic delivery fees strictly in 64-bit integer minor currency units (fee_cents in LKR) with 15-minute guaranteed validity windows persisted in pricing_quotes.

3. Atomic Persistence Orchestrator (internal/parcels/application/booking_service.go): Atomically commits the parcel entity, append-only audit record in parcel_status_history, integration event in outbox_events (parcel.booked.v1), and cached result in idempotency_keys within a single PostgreSQL transaction. Asynchronous message publication to RabbitMQ is handled strictly by Member 8's Outbox Relay after transaction commit.

Figure 5.2 illustrates the Clean Architecture modular layout for the Parcel and Pricing subsystems, detailing the decoupling between HTTP transport handlers, application use cases, pure domain aggregates, and PostgreSQL/outbox persistence adapters conforming to the 9-state lifecycle:




Figure 5.2: Clean Architecture Component Layout for Parcel & Pricing Subsystems

5.3 Dynamic Execution Flows & Drawn Sequence Diagrams

The parcel subsystem executes two foundational workflows: dynamic quotation generation and atomic parcel booking, governed by an authoritative 9-state lifecycle state machine.

Figure 5.3 illustrates the dynamic delivery fee estimation activity workflow, detailing zone-pair tariff resolution, volumetric weight calculation, applicable weight band mapping, and 15-minute quote generation with persistence in pricing_quotes:




Figure 5.3: Dynamic Delivery Fee Estimation Activity Workflow

Figure 5.4 depicts the dynamic tariff calculation and 15-minute quote sequence flow across transport handlers, pricing use case orchestrators, zone-pair tariff lookups, and quote persistence layers:




Figure 5.4: Dynamic Tariff Calculation & 15-Minute Quote Sequence Flow

Figure 5.5 illustrates the customer parcel booking activity workflow, tracing input validation, idempotent token resolution, quote expiration guards, aggregate construction, and transactional outbox persistence across five clean swimlanes:




Figure 5.5: Customer Parcel Booking Activity Workflow

Figure 5.6 details the atomic parcel booking and outbox commit sequence flow, ensuring that aggregate state persistence, status audit history, outbox event generation, and idempotency status update execute within a single ACID transaction:




Figure 5.6: Atomic Parcel Booking & Status History Commit Sequence Flow

Figure 5.7 depicts the canonical 9-state parcel lifecycle state machine (FSM), illustrating authoritative state transitions from CREATED through terminal DELIVERED, RETURNED, or CANCELLED milestones:




Figure 5.7: Canonical 9-State Parcel Lifecycle State Machine (FSM)

Events are persisted atomically using the Transactional Outbox pattern (see §11.3 for details), guaranteeing zero lost events during broker partitions.

5.4 Input & Output Data Contracts

The Parcel and Pricing subsystems expose the following primary REST contracts:

1. Generate Delivery Quote: POST /api/v1/pricing/quote (Authenticated Customer / Merchant)

Request Headers: Content-Type: application/json, Authorization: Bearer <JWT>

Request Payload:

```
{
  "pickup_zone_id": "ZONE_COLOMBO_03",
  "destination_zone_id": "ZONE_COLOMBO_07",
  "weight_kg": 2.50,
  "length_cm": 20.00,
  "width_cm": 20.00,
  "height_cm": 20.00,
  "service_level": "STANDARD"
}
```

Success Response (201 Created):

```
{
  "status": "success",
  "data": {
    "quote_id": "770e8400-e29b-41d4-a716-446655440099",
    "pricing_rule_id": "prc_colombo_intra_v1",
    "service_level": "STANDARD",
    "actual_weight_kg": 2.50,
    "volumetric_weight_kg": 1.60,
    "chargeable_weight_kg": 2.50,
    "fee_cents": 55000,
    "currency": "LKR",
    "expires_at": "2026-10-28T10:15:00Z"
  }
}
```

Error Status Codes:

- 400 Bad Request: Missing mandatory fields, negative weight/dimensions, or unsupported service level.
- 422 Unprocessable Entity: Weight exceeds 30 kg, dimensions exceed 150 cm, or unsupported zone pair.

2. Book Parcel: POST /api/v1/parcels (Authenticated Customer / Merchant)

Request Headers: Content-Type: application/json, Authorization: Bearer <JWT>, Idempotency-Key: 9b1deb4d-3b7d-4bad-9bdd-2b0d7b3dcb6d

Request Payload:

```
{
  "quote_id": "770e8400-e29b-41d4-a716-446655440099",
  "pickup": {
    "contact_name": "Alice Perera",
    "phone": "+94771234567",
    "zone_id": "ZONE_COLOMBO_03",
    "address_line1": "No 45 Galle Road",
    "city": "Colombo 03",
    "postal_code": "00300"
  },
  "dropoff": {
    "contact_name": "Bob Fernando",
    "phone": "+94719876543",
    "zone_id": "ZONE_COLOMBO_07",
    "address_line1": "No 12 Gregory's Road",
    "city": "Colombo 07",
    "postal_code": "00700"
  },
  "weight_kg": 2.50,
  "dimensions": {
    "length_cm": 20.00,
    "width_cm": 20.00,
    "height_cm": 20.00
  },
  "service_level": "STANDARD"
}
```

Success Response (201 Created):

```
{
  "status": "success",
  "data": {
    "parcel_id": "990e8400-e29b-41d4-a716-446655440111",
    "tracking_number": "SD-20261028-A3X9K7",
    "status": "CREATED",
    "fee_cents": 55000,
    "currency": "LKR",
    "created_at": "2026-10-28T10:02:15Z"
  }
}
Error Status Codes:
- 400 Bad Request: Malformed JSON syntax or missing required contact fields.
- 409 Conflict: Idempotency payload mismatch (same key submitted with altered payload).
- 422 Unprocessable Entity: Quoted price expired, dimensions mismatch quote snapshot,
or invalid zone.
```

5.5 Data Modeling & Persistence Schema

The Parcel and Pricing subsystems own migrations 000004_create_pricing_rules.up.sql, 000005_create_parcels_and_quotes.up.sql, and 000010_create_idempotency_keys.up.sql, establishing the following relational tables:

1. parcels: Authoritative parcel aggregate table. Columns: id (UUID PRIMARY KEY DEFAULT gen_random_uuid()), tracking_number (VARCHAR(32) UNIQUE NOT NULL), sender_id (UUID NOT NULL REFERENCES users(id) ON DELETE RESTRICT),

merchant_id (UUID NULL REFERENCES merchants(id) ON DELETE RESTRICT), current_status (VARCHAR(32) NOT NULL DEFAULT 'CREATED' CHECK (current_status IN ('CREATED', 'ASSIGNED', 'PICKED_UP', 'IN_TRANSIT', 'OUT_FOR_DELIVERY', 'DELIVERED', 'ATTEMPT_FAILED', 'RETURNED', 'CANCELLED'))), service_level (VARCHAR(32) NOT NULL DEFAULT 'STANDARD'), weight_kg (NUMERIC(6,2) NOT NULL CHECK (weight_kg > 0 AND weight_kg <= 30.0)), chargeable_weight_kg (NUMERIC(6,2) NOT NULL), price_cents (BIGINT NOT NULL CHECK (price_cents >= 0)), currency (VARCHAR(3) NOT NULL DEFAULT 'LKR'), pricing_rule_id (VARCHAR(64) NOT NULL), pricing_rule_version (INT NOT NULL), pickup_address (JSONB NOT NULL), dropoff_address (JSONB NOT NULL), recipient_name (VARCHAR(120) NOT NULL), recipient_phone (VARCHAR(32) NOT NULL), attempt_count (INT NOT NULL DEFAULT 0 CHECK (attempt_count >= 0 AND attempt_count <= 3)), version (INT NOT NULL DEFAULT 1 CHECK (version >= 1)), created_at (TIMESTAMPTZ NOT NULL DEFAULT NOW()), updated_at (TIMESTAMPTZ NOT NULL DEFAULT NOW()).

2. pricing_rules: Configurable zone-pair tariff matrix. Columns: id (VARCHAR(64) NOT NULL), version (INT NOT NULL), name (VARCHAR(128) NOT NULL), pickup_zone_id (VARCHAR(64) NOT NULL REFERENCES delivery_zones(id) ON DELETE RESTRICT), destination_zone_id (VARCHAR(64) NOT NULL REFERENCES delivery_zones(id) ON DELETE RESTRICT), weight_band_id (INT NOT NULL), min_weight_kg (NUMERIC(6,2) NOT NULL), max_weight_kg (NUMERIC(6,2) NOT NULL), fee_cents (BIGINT NOT NULL CHECK (fee_cents >= 0)), currency (VARCHAR(3) NOT NULL DEFAULT 'LKR'), effective_from (TIMESTAMPTZ NOT NULL DEFAULT NOW()), effective_to (TIMESTAMPTZ NULL), is_active (BOOLEAN NOT NULL DEFAULT TRUE), created_at (TIMESTAMPTZ NOT NULL DEFAULT NOW()), PRIMARY KEY (id, version).

3. pricing_quotes: Persisted fee estimates with 15-minute TTL. Columns: id (UUID PRIMARY KEY DEFAULT gen_random_uuid()), pricing_rule_id (VARCHAR(64) NOT NULL), pricing_rule_version (INT NOT NULL), service_level (VARCHAR(32) NOT NULL), fee_cents (BIGINT NOT NULL CHECK (fee_cents >= 0)), currency (VARCHAR(3) NOT NULL DEFAULT 'LKR'), input_snapshot (JSONB NOT NULL), expires_at (TIMESTAMPTZ NOT NULL), accepted_parcel_id (UUID NULL REFERENCES parcels(id) ON DELETE SET NULL), created_at (TIMESTAMPTZ NOT NULL DEFAULT NOW()).

4. parcel_status_history: Append-only immutable audit trail. Columns: id (UUID PRIMARY KEY DEFAULT gen_random_uuid()), parcel_id (UUID NOT NULL REFERENCES parcels(id) ON DELETE RESTRICT), from_status (VARCHAR(32) NULL), to_status (VARCHAR(32) NOT NULL), actor_id (UUID NULL REFERENCES users(id) ON DELETE SET NULL), actor_role (VARCHAR(32) NOT NULL), reason_code (VARCHAR(64) NULL), note (TEXT NULL), parcel_version (INT NOT NULL), occurred_at (TIMESTAMPTZ NOT NULL DEFAULT NOW()). The ON DELETE RESTRICT constraint guarantees that parcel audit records can never be erased.

5. idempotency_keys: Platform-wide idempotency cache. Columns: caller_hash (VARCHAR(64) NOT NULL), idempotency_key (VARCHAR(128) NOT NULL), endpoint (VARCHAR(128) NOT NULL), request_hash (VARCHAR(64) NOT NULL), status_code (INT NOT NULL), response_payload (JSONB NOT NULL), created_at (TIMESTAMPTZ NOT NULL DEFAULT NOW()), expires_at (TIMESTAMPTZ NOT NULL), PRIMARY KEY (caller_hash, idempotency_key).

Figure 5.8 provides the relational Entity-Relationship Diagram (ERD) for the parcel and pricing subsystem, depicting relational constraints, foreign keys, and audit relationships between parcels, parcel_status_history, pricing_rules, pricing_quotes, and idempotency_keys:




Figure 5.8: Parcel & Pricing Relational Entity-Relationship Diagram (ERD)

5.6 Technical Justifications: State Machine Invariants & Strategy Pattern

Table 5.1 provides the technical justification for the domain aggregate root pattern and lifecycle management strategy selected for SwiftDrop:

Table 5.1: Comparative Analysis of Parcel Lifecycle & State Management Strategies

Architectural Pattern	**Direct Database CRUD Updates**	**Distributed Saga Choreography**	**Domain Aggregate Root FSM (Selected)**
Business Invariant Enforcement	Poor: Validation scattered across multiple controllers; prone to illegal state transitions via raw SQL.	Complex: Asynchronous compensating actions require eventual consistency; vulnerable to intermediate state exposure.	Maximum: Invariants evaluated strictly in-memory by pure domain models before any database mutation occurs.
Audit Trail Guarantees	Optional / Manual: Logging requires explicit secondary SQL queries, risking dropped audit events.	High overhead: Requires distributed tracing and event store to reconstruct aggregate history.	Atomic: Single PostgreSQL transaction commits entity mutation, append-only history row, and outbox event simultaneously.

Architectural Pattern	Direct Database CRUD Updates	Distributed Saga Choreography	Domain Aggregate Root FSM (Selected)
Concurrency Isolation	Low: Prone to dirty reads and lost updates during simultaneous courier and customer interactions.	Moderate: Eventual consistency introduces temporal anomalies where parcels appear unassigned while assigned.	Strict ACID: PostgreSQL row locks and aggregate boundaries prevent concurrent conflicting mutations.
Testability & Purity	Low: Unit tests require active database connections and mock SQL drivers.	Difficult: Requires complex asynchronous event brokers and integration harnesses.	Exceptional: 100% pure Go domain tests with zero dependencies on database/sql or net/http.

Zone-Pair Tariff Matrix & Volumetric Pricing: SwiftDrop evaluates delivery fees through a deterministic zone-pair tariff model (Pickup Zone + Destination Zone + Weight Band -> Fee). In accordance with international air and courier freight standards (IATA), physical parcel charges are computed using the Volumetric Weight Divisor (5000): Volumetric Weight = (Length * Width * Height) / 5000. Chargeable weight represents the exact maximum between physical scale weight and volumetric displacement, preventing light, bulky parcels from consuming vehicle cargo capacity without appropriate tariff compensation.

Persisted Quote Lifecycle & Price Freezing: To eliminate financial arbitrage and protect customer quotes against real-time fuel and traffic fluctuations, SwiftDrop implements a 15-Minute Guaranteed Quote Window backed by persisted records in pricing_quotes. When a quote is calculated, its input snapshot, rule version, and fee are stored in PostgreSQL. Upon booking, the quote ID is verified for expiration (NOW() <= expires_at) and parameter congruence. The accepted price is frozen into the parcel aggregate snapshot (price_cents, pricing_rule_id, pricing_rule_version), insulating historical bookings against future tariff changes.

Optimistic Concurrency Control (version Column): To prevent lost updates during simultaneous operations (e.g. a dispatcher assigning a courier while a customer requests cancellation), the parcels table enforces an optimistic locking version column (version INT NOT NULL DEFAULT 1). Every state mutation executes UPDATE parcels SET current_status = $1, version = version + 1 WHERE id = $2 AND version = $3. If another transaction has concurrently updated the record, zero rows are affected and the domain raises ErrOptimisticLockConflict, mapped to HTTP 409 Conflict.

Idempotency Key Architecture: To guarantee network resiliency across unreliable mobile client connections, all parcel bookings mandate an Idempotency-Key HTTP header. The Core API stores idempotency keys, request body SHA-256 hashes, and cached HTTP responses in PostgreSQL with a 24-hour time-to-live. Repeated submissions with identical payloads return the cached HTTP 201 response directly. If a client reuses an idempotency key with an altered request payload, the engine rejects the transaction with HTTP 409 Conflict (IDEMPOTENCY_PAYLOAD_MISMATCH).

5.7 Invariant Guardrails & Prohibited Transitions

The subsystem enforces the following strict operational guardrails:

1. Prohibited State Transitions & ADR-004 Semantics: DELIVERED, RETURNED, and CANCELLED represent immutable terminal states with zero outbound transitions. Couriers are permitted a maximum of three delivery attempts per parcel. Only a DISPATCHER or ADMIN can authorize a reattempt from ATTEMPT_FAILED back to OUT_FOR_DELIVERY. Upon the third failed attempt (attempt_count >= 3), the parcel automatically transitions to RETURNED. Customer cancellations are permitted strictly while the parcel is in CREATED or ASSIGNED status prior to courier pickup.

2. Physical Dimension & Weight Validation Limits: Parcels exceeding 30.0 kg (weight_kg > 30.0), single dimensions exceeding 150.0 cm (length_cm, width_cm, or height_cm > 150.0), or below minimum billable weight (0.1 kg / 100g) are rejected at the domain boundary with ErrParcelLimitExceeded (mapped to HTTP 422 Unprocessable Entity).

3. Quote Expiration & Single-Use Consumption: Any parcel booking referencing an expired quote (NOW() > expires_at) or a previously accepted quote is rejected with ErrQuoteInvalidOrExpired (HTTP 422), preventing tariff arbitrage and quote reuse.

4. Direct Database Update Prohibition: All status transitions must execute through parcel.TransitionTo(...) within an active PostgreSQL transaction that atomically appends to parcel_status_history and outbox_events. Raw SQL updates bypassing domain aggregate guards are strictly forbidden.

5.8 Comprehensive Testing Strategy & Acceptance Criteria

Unit tests in internal/parcels/domain/parcel_test.go assert all valid and prohibited transitions across the 9-state state machine, verifying the 3-attempt ceiling, cancellation guards, and optimistic concurrency version increments.

Integration tests in tests/integration/booking_test.go execute concurrent parcel bookings using test transaction rollbacks, asserting that parcels, immutable status history records (ON DELETE RESTRICT), outbox events, and idempotency cache records commit simultaneously within an atomic database transaction.

CHAPTER 6

DISPATCH, FLEET MANAGEMENT & PROOF-OF-DELIVERY SUBSYSTEM

6.1 Subsystem Scope & Operational Capabilities

The Dispatch, Fleet Management & Proof-of-Delivery Subsystem governs regional courier assignments, vehicle capacity enforcement, transit milestone tracking, photographic proof-of-delivery ingestion, and delivery attempt failure lifecycles under ADR-004. It coordinates operational logistics across regional hubs, ensuring balanced workload distribution and secure execution.

Operational boundaries dictate that dispatchers assign couriers to parcels only when vehicle load thresholds and delivery zones permit, leveraging transactional locking mechanisms to prevent double-assignment race conditions during peak operating windows.

Figure 6.1 outlines the subsystem UML use case model, specifying functional interactions across dispatchers, couriers, and automated workers managing zone routes, vehicle load assignments, and delivery attempt logging.




Figure 6.1: Dispatch, Fleet & POD Subsystem UML Use Case Model

Traceability & SRS Requirements: Subsystem capabilities map to formal requirements: FR-DSP-001 (Advisory-Locked Courier Assignment), FR-DSP-002 (Mobile Driver Manifest), FR-DLV-001 (3-Attempt Failure Classification ADR-004), and FR-DLV-002 (Cryptographic S3 Proof of Delivery Attachment).

6.2 Architectural Design: Dispatch & Delivery Contexts

The subsystem is structured into two clean bounded contexts sharing cohesive database schemas:

1. Dispatch Context (internal/dispatch/): Manages courier availability, zone boundaries, dispatch board queries, and concurrent assignment transactions protected by PostgreSQL session-level advisory locks.

2. Delivery Context (internal/delivery/): Enforces delivery attempt lifecycles, ADR-004 retry thresholds (maximum 3 attempts), photographic proof-of-delivery attachments via AWS S3 pre-signed URLs, and failure classifications.

Figure 6.2 illustrates the Clean Architecture component layout for the Dispatch and Delivery contexts, detailing the decoupling between HTTP handlers, application use cases, pure domain entities, and PostgreSQL/S3 persistence adapters.




Figure 6.2: Clean Architecture Component Layout for Dispatch & Delivery

6.3 Dynamic Execution Flows & Drawn Sequence Diagrams

The subsystem executes two primary operational flows: dispatcher courier assignment with advisory concurrency locks, and courier proof-of-delivery execution with photographic verification.

Figure 6.3 illustrates the dispatcher courier assignment sequence flow, detailing role verification, PostgreSQL advisory lock acquisition, courier capacity validation, and atomic transactional outbox commit.




Figure 6.3: Dispatcher Courier Assignment Sequence Diagram

Figure 6.4 illustrates the courier delivery attempt and photographic proof-of-delivery attachment sequence, showing S3 pre-signed URL issuance and immutable audit recording.




Figure 6.4: Courier Proof-of-Delivery Attachment Flow

Figure 6.5 depicts the ADR-004 Failed Delivery Attempt decision flowchart, tracing attempt counter incrementation, failure classification, and automated transition to RETURNED upon the third failed attempt.




Figure 6.5: Failed Delivery Attempt Decision Flowchart (ADR-004)

6.4 Input & Output Data Contracts

1. Assign Courier: POST /api/v1/dispatch/assignments (Dispatcher Role)

Request Payload:

```
{
  "parcel_id": "990e8400-e29b-41d4-a716-446655440111",
  "courier_id": "110e8400-e29b-41d4-a716-446655440222",
  "scheduled_pickup_at": "2026-10-28T14:00:00Z"
}
```

Success Response (200 OK):

```
{
  "data": {
    "assignment_id": "330e8400-e29b-41d4-a716-446655440333",
    "parcel_id": "990e8400-e29b-41d4-a716-446655440111",
    "courier_id": "110e8400-e29b-41d4-a716-446655440222",
    "status": "ASSIGNED",
    "assigned_at": "2026-10-28T10:30:00Z"
  }
}
```

2. Complete Delivery with Proof: POST /api/v1/deliveries/{id}/complete (Courier Role)

Request Payload:

```
{
  "proof_type": "SIGNATURE_AND_PHOTO",
  "signature_data": "...",
  "photo_key": "pod/2026/10/28/photo_990e8400.jpg",
  "received_by_name": "A. B. Silva",
  "notes": "Delivered to front reception."
}
```

Success Response (200 OK):

```
{
  "data": {
    "parcel_id": "990e8400-e29b-41d4-a716-446655440111",
    "status": "DELIVERED",
    "completed_at": "2026-10-28T14:45:00Z"
  }
}
```

3. Record Delivery Failure: POST /api/v1/deliveries/{id}/failed (Courier Role)

Request Payload:

```
{
  "reason_code": "RECIPIENT_UNAVAILABLE",
  "notes": "Front gate locked; no response to intercom buzzer.",
  "latitude": 6.9271,
  "longitude": 79.8612
}
```

Success Response (200 OK):

```
{
  "data": {
    "attempt_id": "440e8400-e29b-41d4-a716-446655440444",
    "parcel_id": "990e8400-e29b-41d4-a716-446655440111",
    "attempt_number": 1,
    "status": "ATTEMPT_FAILED"
  }
}
```

6.5 Data Modeling & Persistence Schema

The Dispatch and Delivery subsystems own migrations 000006_create_couriers.up.sql and 000007_create_dispatch_and_delivery.up.sql, establishing the following relational tables:

1. couriers: Fleet personnel profiles. Columns: id (UUID PK), user_id (UUID FK -> users.id UNIQUE), vehicle_type (VARCHAR(20)), max_capacity_grams (INT), current_zone_id (UUID FK -> delivery_zones.id), is_active (BOOLEAN), created_at.

2. courier_assignments: Operational assignment records. Columns: id (UUID PK), parcel_id (UUID FK -> parcels.id), courier_id (UUID FK -> couriers.id), assigned_by_user_id (UUID FK), status (VARCHAR(20)), assigned_at, completed_at.

3. delivery_attempts: Delivery audit history. Columns: id (UUID PK), parcel_id (UUID FK -> parcels.id), attempt_number (INT CHECK 1..3), status (VARCHAR(20)), failure_reason (VARCHAR(50) nullable), proof_photo_url (TEXT nullable), signature_url (TEXT nullable), attempted_at.

Figure 6.6 provides the relational Entity-Relationship Diagram (ERD) for the dispatch and delivery subsystem, showing constraints, foreign keys, and audit trails across couriers, courier_assignments, and delivery_attempts.




Figure 6.6: Dispatch & Delivery Relational Entity-Relationship Diagram (ERD)

6.6 Technical Justifications: Advisory Locks & S3 Pre-Signed URLs

Table 6.1 outlines the technical justification for concurrency control strategies evaluated for high-volume courier dispatch:

Table 6.1: Technical Justification for Concurrency Control during Parcel Assignment

Evaluation Metric	**Optimistic Concurrency Control (OCC)**	**Distributed Redis Redlock**	**PostgreSQL Advisory Locks (Selected)**
Lock Contention Handling	High failure rate: Concurrent writes abort transactions, forcing heavy client retry loops.	Low: Distributed in-memory lock acquisition before database commit.	Zero abort cascades: Non-blocking try-lock immediately returns HTTP 409 without database deadlocks.
Infrastructure Overhead	Zero: Relies on table version column (version = version + 1).	High: Requires Redis cluster management, sentinel failover, and clock drift synchronization.	Zero extra infrastructure: Utilizes native PostgreSQL connection engine and hashtext hash functions.

Evaluation Metric	Optimistic Concurrency Control (OCC)	Distributed Redis Redlock	PostgreSQL Advisory Locks (Selected)
Split-Brain / Lease Expiry	None: Relies on SQL transaction serialization.	High risk: Slow network or garbage collection pauses can cause lock lease expiration while transaction is active.	Safe: Advisory locks are transaction-bound (pg_advisory_xact_lock) and automatically release on commit or rollback.

During high-volume logistics dispatch, two regional dispatchers might attempt to assign different couriers to the exact same parcel simultaneously. Standard optimistic locking checks fail if reads occur concurrently. SwiftDrop implements PostgreSQL Session-Level Advisory Locks (pg_try_advisory_lock(hashtext('parcel:' || parcel_id))). If an assignment is in progress, the second dispatcher's request immediately aborts with HTTP 409 Conflict, permanently eliminating double-dispatch anomalies.

Uploading photographic proof of delivery directly through the Go Core API would saturate server network bandwidth and RAM. SwiftDrop utilizes AWS S3 Pre-Signed URLs (valid for 5 minutes). The courier's mobile client uploads multi-megabyte image binaries directly to S3 storage, and only submits the validated S3 object key to the Core API, maintaining high backend throughput.

Furthermore, the separation of the delivery_attempts entity from the parcels aggregate root under ADR-004 addresses a critical logistics design flaw: naive systems overwrite delivery attempt status directly onto parcel rows, permanently erasing physical audit history. In SwiftDrop, every attempt creates an immutable historical row capturing the courier ID, GPS coordinates, failure reason classification, and photo evidence. Establishing an authoritative ceiling of exactly three attempts prevents perpetual reattempt loops and vehicle fuel waste, while requiring explicit dispatcher authorization for rescheduling guarantees operational governance over damaged or unreachable shipments.

6.7 Concurrency Defenses & Failed Delivery Invariants (ADR-004)

ADR-004 establishes strict delivery failure invariants: couriers can execute at most three delivery attempts per parcel. Every failed attempt must select an authoritative classification from the enum (CUSTOMER_UNAVAILABLE, INCORRECT_ADDRESS,

CUSTOMER_REFUSED, RESTRICTED_ACCESS). Attempt records must include GPS coordinates recorded at the customer location.

Upon the third recorded failure (or upon explicit customer refusal REFUSED_BY_RECIPIENT), the application service automatically transitions the parcel status to RETURNED, unassigns the courier, and triggers a return-to-sender workflow. Any subsequent delivery attempt on that parcel is strictly blocked by the domain state machine.

6.8 Comprehensive Testing Strategy & Acceptance Criteria

Concurrency tests in tests/integration/dispatch_concurrency_test.go launch 50 parallel goroutines attempting to assign different couriers to a single parcel. The test asserts that exactly one assignment succeeds, 49 requests receive HTTP 409 Conflict, and exactly one outbox event is created.

Unit tests in internal/delivery/domain/attempt_test.go assert that the 4th attempt is rejected with ErrMaxDeliveryAttemptsExceeded and verify that successful delivery requires a non-empty photo URL or signature SVG.

CHAPTER 7

MERCHANT B2B INTEGRATION & WEBHOOK SUBSYSTEM

7.1 Subsystem Scope & Commercial Integration

The Merchant B2B Integration & Webhook Subsystem (owned by K.D.N.D. Samarakkodi [234185G] — Member 4) enables enterprise e-commerce merchants and third-party logistics aggregators to integrate programmatically with SwiftDrop. Located in core-api/internal/merchants/, this module manages merchant business onboarding, administrative verification workflows, cryptographic API key issuance (with SHA-256 storage), outbound webhook endpoint subscriptions, and HMAC-SHA256 signature generation.

Commercial boundaries dictate that merchants can ingest high-volume batch parcels, query bulk status histories, and configure custom webhook callback URLs. The subsystem enforces strict multi-tenant data isolation, ensuring merchants can never access, query, or cancel parcels belonging to other tenants.

Traceability & SRS Requirements: Subsystem capabilities map to formal requirements: FR-MER-001 (Commercial Merchant Onboarding & Approval), FR-MER-002 (SHA-256 API Key Provisioning), and FR-MER-003 (HMAC-SHA256 Signed Webhook Dispatches).

7.2 Architectural Design: B2B Merchant Context

The merchant module adheres to clean DDD isolation:

1. Merchant Aggregate Root (internal/merchants/domain/merchant.go): Encapsulates commercial profile data, business registration numbers, approval status (PENDING -> APPROVED / REJECTED / SUSPENDED), and API key associations.

2. Webhook Engine: Manages webhook event subscriptions and outbound delivery queues. Validates customer URLs against SSRF private IP filters.

Figure 7.1 illustrates the Clean Architecture package layout and DDD layer decomposition for the Merchant Integration module within the Go Modular Monolith:




Figure 7.1: Clean Architecture Package Layout for Merchant Module

7.3 Dynamic Execution Flows & Drawn Sequence Diagrams

Figure 7.2 depicts the Merchant Administrative Approval lifecycle state machine, illustrating the valid transitions across PENDING, APPROVED, SUSPENDED, REJECTED, and DISABLED states, as well as the administrative actions and side-effects enforced by the domain aggregate:




Figure 7.2: Merchant Approval State Machine Flowchart

Figure 7.3 illustrates the automated B2B order ingestion flow, detailing API key authentication, constant-time HMAC hash verification, idempotency checking, aggregate booking validation, and atomic transactional outbox commitment:




Figure 7.3: B2B Merchant Automated Order Creation via Secured API

Figure 7.4 illustrates the outbound webhook delivery sequence across distributed subsystems, depicting parcel outbox event publication to RabbitMQ, consumption by the Event Worker, cryptographic AES-256-GCM secret decryption, HMAC-SHA256 signature generation, zero-trust HTTP POST delivery, exponential backoff retries with jitter, and Dead-Letter Queue (DLQ) routing:




Figure 7.4: Outbound Webhook Delivery & Exponential Backoff Retry Flow

Events are persisted atomically using the Transactional Outbox pattern (see §11.3 for details).

7.4 Input & Output Data Contracts

1. Generate Merchant API Key: POST /api/v1/merchants/api-keys (Merchant Admin)

Request Payload:

```
{
  "label": "Production E-Commerce Backend",
  "expires_in_days": 365
}
```

Success Response (201 Created):

```
{
  "data": {
    "key_id": "660e8400-e29b-41d4-a716-446655440777",
    "api_key": "swd_live_8f3a9b2c1d4e5f6a7b8c9d0e1f2a3b4c",
    "key_prefix": "swd_live_8f3a9b2c",
    "created_at": "2026-10-28T11:00:00Z"
  }
}
Note: The raw api_key is returned exactly once during creation and is never retrievable
again.
```

```
2. Configure Webhook URL: POST /api/v1/merchants/webhooks (Merchant Admin)
Request Payload:
{
  "url": "https://api.merchantshop.com/webhooks/swiftdrop",
  "subscribed_events": [
    "parcel.created",
    "parcel.assigned",
    "parcel.picked_up",
    "parcel.delivered",
    "parcel.failed_attempt"
  ]
}
Success Response (201 Created):
{
  "data": {
    "webhook_id": "880e8400-e29b-41d4-a716-446655440888",
    "url": "https://api.merchantshop.com/webhooks/swiftdrop",
    "signing_secret": "whsec_99a8b7c6d5e4f3a2b1c0d9e8f7a6b5c4",
    "enabled": true
  }
}
```

7.5 Data Modeling & Persistence Schema

The Merchant subsystem owns migration 000003_create_merchants_and_credentials.up.sql, establishing the commercial tenant profiles, cryptographic API credentials, and outbound webhook delivery targets.

Figure 7.5 illustrates the relational persistence schema and cross-module foreign key relationships for the Merchant Integration subsystem:




Figure 7.5: Merchant Persistence Schema Relational Entity-Relationship Diagram

1. merchants: Commercial tenant profiles. Columns: id (UUID PK), user_id (UUID FK -> users.id UNIQUE), business_name (VARCHAR(255) NOT NULL), registration_number (VARCHAR(100) UNIQUE NOT NULL), status (VARCHAR(50) DEFAULT 'PENDING' CHECK (status IN ('PENDING', 'APPROVED', 'REJECTED', 'SUSPENDED', 'DISABLED'))), rejection_reason (TEXT), version (INT NOT NULL DEFAULT 1), created_at (TIMESTAMPTZ DEFAULT NOW()), updated_at (TIMESTAMPTZ DEFAULT NOW()).

2. merchant_api_credentials: API credential store. Columns: id (UUID PK), merchant_id (UUID FK -> merchants.id ON DELETE CASCADE), key_prefix (VARCHAR(16) NOT NULL), key_hash (VARCHAR(64) NOT NULL UNIQUE), label (VARCHAR(100)), expires_at (TIMESTAMPTZ), is_active (BOOLEAN DEFAULT TRUE). Indices: CREATE INDEX idx_api_keys_lookup ON merchant_api_credentials(key_prefix, is_active).

3. webhook_endpoints: Webhook delivery endpoints. Columns: id (UUID PK), merchant_id (UUID FK -> merchants.id ON DELETE CASCADE), url (TEXT NOT NULL), secret_ciphertext (BYTEA NOT NULL), secret_key_version (INT NOT NULL DEFAULT 1), secret_last4 (VARCHAR(4) NOT NULL), subscribed_event_types (TEXT[] NOT NULL), enabled (BOOLEAN DEFAULT TRUE), created_by (UUID NULL), deleted_at (TIMESTAMPTZ NULL), created_at (TIMESTAMPTZ NOT NULL DEFAULT NOW()), updated_at (TIMESTAMPTZ NOT NULL DEFAULT NOW()). Indices: CREATE INDEX idx_webhooks_merchant ON webhook_endpoints(merchant_id);

7.6 Technical Justifications: SHA-256 Keys & HMAC-SHA256 Webhooks

Table 7.1 details the comparative architectural evaluation defending the asynchronous webhook worker pattern selected for B2B partner integration:

Table 7.1: Architectural Evaluation of Webhook Delivery & Integration Patterns

Criteria	Client Polling (GET /parcels)	Synchronous HTTP POST in Transaction	Asynchronous Worker with DLQ (Selected)
Network Resource Utilization	Highly inefficient: 90%+ queries return unchanged 304/200 data, saturating database pools.	Risky: Merchant endpoint latency or outages directly hold PostgreSQL connections open, causing connection pool exhaustion.	Optimal: Events dispatched from RabbitMQ workers; zero transactional impact on core OLTP database.

Criteria	Client Polling (GET /parcels)	Synchronous HTTP POST in Transaction	Asynchronous Worker with DLQ (Selected)
Delivery Guarantees	None: Merchant must implement continuous polling loops and handle missing data.	Poor: If merchant server drops connection or times out, the entire booking transaction rolls back.	At-least-once: Bounded jittered retries (0s, 30s, 2m, 10m, 30m; 5 attempts) recorded in webhook_deliveries; terminal FAILED rows retained for audit/manual replay; swiftdrop.dlq isolates unparseable poison messages.
Data Freshness & Latency	Delayed by polling interval (e.g. 60 seconds).	Real-time, but destabilizes Core API throughput.	Near real-time (<250ms event latency from outbox publication to webhook execution).
Security & Verification	Standard Bearer token or API key query parameter.	Vulnerable to network eavesdropping and replay attacks without cryptographic signatures.	HMAC-SHA256 non-repudiation signature header with Unix timestamp, immune to payload tampering and replay attacks.

Storing plaintext API keys in databases creates severe compromise risks during database dumps. SwiftDrop issues 32-byte cryptographically secure random API keys prefixed with swd_live_ and a unique 8-character lookup prefix. The database stores strictly the SHA-256 hash of the key. Incoming requests are authenticated in O(1) time by querying the index on key_prefix and comparing SHA-256 hashes in constant time, preventing timing attacks.

Figure 7.6 illustrates the multi-stage cryptographic API key authentication and constant-time verification pipeline:




Figure 7.6: Cryptographic API Key Authentication & Constant-Time Verification Pipeline Flowchart

Outbound webhook delivery requires non-repudiation and payload integrity verification. Every webhook HTTP POST request includes the header X-SwiftDrop-Signature: t=1698480000,v1=abcdef... containing an HMAC-SHA256 digest computed over the signature string "{t}.{raw_body}" using the merchant's private signing secret, accompanied by X-SwiftDrop-Timestamp, X-SwiftDrop-Event-ID, and X-SwiftDrop-Delivery-ID headers.

Because merchant webhook URLs represent arbitrary user-supplied external endpoints, they introduce critical Server-Side Request Forgery (SSRF) vulnerabilities. To immunize internal infrastructure against lateral penetration, SwiftDrop implements a two-tier SSRF defense: Member 4 executes pre-flight DNS validation during endpoint registration, and Member 8's

Event Worker re-validates DNS and dials the verified IP at every delivery attempt via a custom DialContext, strictly blocking RFC 1918 private subnets (10/8, 172.16/12, 192.168/16), carrier-grade NAT (100.64/10), local loopback (127/8), link-local/cloud metadata (169.254/16), and IPv6 unique local/link-local ranges, completely neutralizing DNS rebinding attacks.

7.7 Defensive Security: Tenant Boundaries, Rate Limiting & SSRF Mitigation

The merchant module enforces rigorous defensive security:

1. Server-Side Request Forgery (SSRF) Defense: When a merchant registers a webhook URL, internal/merchants/infrastructure/ssrf_validator.go resolves the DNS hostname and parses the IP address against blacklisted private/loopback CIDRs (127.0.0.0/8, 10.0.0.0/8, 172.16.0.0/12, 192.168.0.0/16, 169.254.0.0/16). Attempts to register internal network URLs are rejected with HTTP 422 Unprocessable Entity.

Figure 7.7 illustrates the multi-stage URL validation and pre-flight DNS SSRF defense pipeline executed during webhook registration:




Figure 7.7: Webhook Registration Validation & SSRF Prevention Pipeline Flowchart

2. Insecure Direct Object Reference (IDOR) Defense: All parcel retrieval queries execute with WHERE merchant_id = $auth_merchant_id, preventing multi-tenant data exfiltration.

3. Outbound Webhook Resiliency & Failure Logging: As depicted in Figure 7.8, the Event Worker enforces strict timeout boundaries (5.0s per attempt), jittered exponential backoffs (0s, 30s, 2m, 10m, 30m; 5 attempts total), and updates the webhook_deliveries record to FAILED after the 5th attempt for operational audit and manual replay via the Admin API. Webhook delivery failures never route to swiftdrop.dlq, which is reserved strictly for unparseable poison messages rejected from the message broker:




Figure 7.8: Outbound Webhook Dispatch, Exponential Backoff & Dead Letter Queue Flowchart

7.8 Comprehensive Testing Strategy & Acceptance Criteria

Unit tests in internal/merchants/domain/webhook_url_test.go assert that URLs pointing to 127.0.0.1, localhost, and AWS metadata endpoints (169.254.169.254) are rejected.

Integration tests in tests/integration/merchant_api_test.go verify that unapproved merchants (status=PENDING) receive HTTP 403 Forbidden when attempting to book parcels, and confirm that webhook HMAC signatures match the expected payload hash.

CHAPTER 8

REAL-TIME TRACKING & LIVE PROJECTION SUBSYSTEM

8.1 Subsystem Scope: Read-Heavy Workload Isolation

The Real-Time Tracking & Live Projection Subsystem provides high-concurrency, read-optimized status projections and reactive milestone updates for customers, merchant platforms, and public consumers across web and mobile touchpoints. Designed as a standalone, horizontally scalable microservice (services/tracking/ listening on port :8081), it operates completely decoupled from the core monolithic API to isolate read-heavy traffic and prevent high-volume tracking queries from degrading transactional booking and dispatch workflows.

Public tracking queries generate over 85% of total system HTTP traffic, as anxious customers and recipients frequently refresh tracking links. To ensure sub-100ms response latencies and protect the authoritative PostgreSQL database from connection exhaustion, the subsystem relies on read-only database views, Redis in-memory Pub/Sub fan-out, and reactive Server-Sent Events (SSE) streaming connections.

Figure 8.1 outlines the subsystem UML use case model, specifying functional interactions for public visitors, authenticated customer accounts, and internal background consumers querying public statuses, subscribing to real-time SSE event streams, and ingesting asynchronous status updates.




Figure 8.1: Tracking & Real-Time Projections Subsystem UML Use Case Model

Traceability & SRS Requirements: Subsystem capabilities map to formal requirements: FR-TRK-001 (Public Sanitized Milestone Lookup) and FR-TRK-002 (Real-Time Server-Sent Events Streaming).

8.2 Architectural Design: Standalone Microservice Architecture

The tracking microservice utilizes a streaming reactive architecture:

1. Server-Sent Events (SSE) Stream Engine: Maintains open HTTP streaming connections (text/event-stream) with clients, streaming incremental milestone payloads in real time as delivery events occur.

2. Redis Pub/Sub Event Distribution: In a multi-replica deployment, the Tracking API consumes events directly from RabbitMQ queue q.tracking.updates (bound to topic exchange swiftdrop.events.topic with routing keys parcel.# and courier.#) and broadcasts them across Redis channel tracking.events. All connected Tracking API pods subscribe to this Redis channel to fan out updates to active client SSE streams regardless of which pod holds the client connection, eliminating database polling entirely.

3. Read-Replica Projections: Queries asynchronous PostgreSQL read replicas for initial tracking history upon initial page load, completely insulating primary transactional write workloads.

Figure 8.2 illustrates the Clean Hexagonal Architecture modular layout for the Tracking subsystem, detailing strict decoupling between HTTP/SSE transport handlers, application use cases, pure domain aggregates, and PostgreSQL/Redis/RabbitMQ infrastructure adapters.




Figure 8.2: Clean Hexagonal Architecture & Modular Layers for Tracking Subsystem

Figure 8.3 illustrates the distributed multi-pod deployment topology and Kubernetes infrastructure, highlighting Traefik API Gateway edge ingress, HPA autoscaling (2 to 4 pods), multi-pod cross-broadcasting via Redis 7 Pub/Sub, and RabbitMQ message ingestion.




Figure 8.3: Distributed Multi-Pod Deployment & Kubernetes Infrastructure Topology

8.3 Dynamic Execution Flows & Drawn Sequence Diagrams

Figure 8.4 illustrates the end-to-end Server-Sent Events (SSE) connection and distributed live event fan-out lifecycle across client browsers, Traefik edge gateway, tracking service pods, RabbitMQ message queues, and Redis in-memory broadcast buses.




Figure 8.4: Real-Time Server-Sent Events (SSE) Stream & Distributed Fan-Out Sequence Flow

Figure 8.5 details the Public Tracking Query Sanitization and SEC-009 Privacy Masking sequence flow, enforcing strict rate limiting, regex validation, and irreversible redaction of sensitive recipient PII before public egress.




Figure 8.5: Public Tracking Lookup & SEC-009 Privacy Masking Sequence Flow

Figure 8.6 illustrates the client-side SSE connection resilience workflow, detailing stream initialization, keepalive heartbeat pings, and exponential backoff reconnection loops when encountering network interruptions.




Figure 8.6: SSE Client Reconnection & Exponential Backoff Activity Workflow

Figure 8.7 depicts the automated fallback degradation flowchart, detailing the transition to 30-second REST polling when SSE retries are exhausted, and terminating polling once terminal delivery milestones are reached.




Figure 8.7: Resilient 30-Second REST Polling Degradation Flowchart

8.4 Input & Output Data Contracts

1. Connect Live Tracking Stream: GET /api/v1/tracking/public/{trackingNumber}/stream (Public / Customer)

Response Headers:

```
Content-Type: text/event-stream
Cache-Control: no-cache
Connection: keep-alive
```

Stream Data Payload (SSE Event):

```
event: status_update
data: {"tracking_number":"SD-20261028-
A3X9K7","status":"OUT_FOR_DELIVERY","status_description":"Courier is out for delivery
in your
zone.","timestamp":"2026-10-28T14:30:00Z","estimated_delivery":"2026-10-28T16:00:00Z"}
```

2. Public Tracking Query: GET /api/v1/tracking/public/{trackingNumber} (Public)

Success Response (200 OK):

```
{
  "data": {
    "tracking_number":"SD-20261028-A3X9K7",
    "current_status": "OUT_FOR_DELIVERY",
    "origin_city": "Colombo 03",
    "destination_city": "Kandy",
    "milestones": [
      { "status": "CREATED", "timestamp": "2026-10-28T10:02:15Z" },
      { "status": "PICKED_UP", "timestamp": "2026-10-28T11:45:00Z" },
      { "status": "OUT_FOR_DELIVERY", "timestamp": "2026-10-28T14:30:00Z" }
    ]
  }
}
```

8.5 Data Modeling, Read-Replica Views & Redis Caching Fan-Out Strategy

The Tracking service does not own migration tables; it queries an optimized SQL view (vw_public_tracking) constructed over the authoritative parcels and parcel_status_history tables on a dedicated PostgreSQL read replica.

When an event is published, the Tracking API consumes messages directly from RabbitMQ queue q.tracking.updates (bound to topic exchange swiftdrop.events.topic with routing keys parcel.# and courier.#). In a multi-replica deployment, tracking instances utilize internal Redis Pub/Sub (channel tracking.events) to fan out updates to active client SSE connections matching the tracking_number. The Event Worker maintains zero direct Redis connectivity, strictly dedicating its operational scope to transactional webhook delivery and notification dispatching.

Figure 8.8 provides the relational Entity-Relationship Diagram (ERD) for the tracking projection data layer, showing relationships between read-only parcels projections, tracking_milestones history, redacted parcel_addresses, and the processed_events consumer deduplication table.




Figure 8.8: Read-Optimized Tracking Projection Schema & ER Diagram

8.6 Technical Justifications: Server-Sent Events vs. WebSockets

Table 8.1 provides the technical comparison between Server-Sent Events (SSE) and WebSockets for real-time tracking:

Table 8.1: Comparison of Real-Time Push Technologies

Technical Criteria	WebSockets	Server-Sent Events (SSE - Selected)	Architectural Justification
Communication Direction	Full-duplex (bidirectional).	Unidirectional (server-to-client).	Tracking updates are strictly outbound. Clients never send real-time streams to the tracking API.
Protocol & Transport	Custom ws:// protocol, requires protocol upgrade handshake.	Standard HTTP/1.1 or HTTP/2. Traverses firewalls, CDNs, and proxies seamlessly.	Traefik natively routes HTTP SSE without custom TCP tuning. Zero firewall blockages.
Auto-Reconnection	Requires custom client reconnect & backoff logic.	Built-in native browser reconnection with Last-Event-ID header.	Browsers automatically reconnect and resume missed milestones without extra client code.
Server Overhead	High: Requires stateful protocol connections and binary framing.	Extremely low: Standard persistent chunked HTTP response streaming.	Enables supporting 5,000 concurrent viewers on a minimal 256MB container.

8.7 Privacy & Regulatory Safeguards: Public Tracking Redaction Rules

Public tracking queries allow anyone with a tracking number to view shipment progress. To comply with data privacy regulations (GDPR/APPI) and prevent physical reconnaissance or customer stalking, the service enforces strict PII Redaction Rules:

1. Customer Phone Numbers and Email Addresses are 100% stripped from public payloads.

2. Physical Street Addresses are redacted to City/Region level (e.g. 'Colombo 03' instead of 'No 45/A, Galle Road, Colombo 03').

3. Courier Internal Notes and driver personal identifiers are strictly omitted from public views.

8.8 Comprehensive Testing Strategy & Acceptance Criteria

Load testing using k6 simulates 2,000 concurrent SSE subscribers over a 10-minute duration, validating that memory consumption remains below 150MB and 99% of status events are delivered in under 50 milliseconds.

Automated unit tests in services/tracking/sanitizer_test.go assert that all raw database fields containing phone numbers, street names, and recipient identities are completely removed from JSON output.

CHAPTER 9

FRONTEND USER EXPERIENCE & CLIENT APPLICATION SUBSYSTEM

9.1 Subsystem Scope: React/TypeScript Single Page Application (SPA) Portals

The Frontend User Experience & Client Application Subsystem provides the public and client-facing digital interfaces for SwiftDrop. Located in web/, this subsystem is constructed as a modern Single Page Application (SPA) utilizing React 18, TypeScript (in strict mode), Vite, and Tailwind CSS.

The frontend encapsulates three dedicated operational portals: the Customer Shipment Portal (booking wizard, address management, live parcel tracking), the Merchant Self-Service Console (bulk CSV order upload, API key management, webhook endpoint tester), and Public Anonymous Tracking (instant milestone lookups without login). All interactions execute against approved REST APIs; client-side evaluation of domain business logic or independent tariff calculation is strictly prohibited.

9.2 UI/UX Architectural Design: Feature Slicing, Design Tokens & State

The client architecture follows Feature-Sliced Design (FSD) to maintain scalability across multiple developer teams:

1. Shared Layer (web/src/shared/): Generic UI primitives (Button, Modal, Input, Table), design tokens (Tailwind color scales, spacing, typography), and Axios HTTP client instances configured with JWT interceptors.

2. Entities Layer (web/src/entities/): Domain entity models (Parcel, Quote, User, Merchant) and TypeScript type definitions.

3. Features Layer (web/src/features/): Self-contained functional flows: booking-wizard, live-tracking, auth-login, merchant-onboarding, and dispatcher-admin (housing the logistics dispatch board, courier mobile manifest, and administrative operations detailed in Chapter 10).

4. Pages & Routing (web/src/pages/): Route guards mapping user role claims (CUSTOMER, MERCHANT) to client portal layouts, along with /ops/* (ADMIN, DISPATCHER) and /courier/* (COURIER) protected routes via React Router v6.

9.3 Dynamic User Journeys & Drawn Flowcharts

Figure 9.1 depicts the 4-step interactive Customer Parcel Booking Wizard journey, modeling client-side schema validation, asynchronous quote estimation, quote expiration handling, and idempotent transaction confirmation:




Figure 9.1: Customer 4-Step Parcel Booking Wizard Journey Flowchart

Figure 9.2 models the real-time Public Tracking Live View journey, illustrating anonymous shipment lookup, privacy masking (SEC-009), Server-Sent Events (SSE) notification streaming, authoritative refetching, and bounded polling fallback:




Figure 9.2: Public Real-Time Tracking Live View Journey

9.4 Component Contracts & API Integration Layer

All API requests are encapsulated in dedicated service modules (src/services/api/parcels.ts, auth.ts, merchants.ts). The client configures an Axios interceptor that automatically attaches the Bearer token from in-memory state. When a 401 Unauthorized response is received, the interceptor transparently calls POST /api/v1/auth/refresh to rotate the session using the HttpOnly cookie and retries the original request, creating a frictionless user experience.

9.5 Technical Justifications: React/TypeScript SPA vs. SSR

Table 9.1 provides the architectural rationale for selecting a client-rendered React/TypeScript SPA over Server-Side Rendering (Next.js/Remix):

Table 9.1: Architectural Justification for Frontend Framework

Evaluation Metric	Server-Side Rendering (Next.js)	React 18 + Vite SPA (Selected)	Architectural Justification
Deployment Simplicity	Requires dedicated Node.js server runtime to render HTML pages.	Compiles to pure static HTML/CSS/JS assets served by NGINX or Traefik.	Massively simplifies Kubernetes operations; zero Node.js memory leaks in production.
Real-Time SSE Handling	Complex server middleware needed for long-lived SSE connections.	Native browser EventSource API connects directly to the Go Tracking API.	Bypasses unnecessary frontend server hops, reducing streaming latency.
Type Safety & Contracts	Shared types require monorepo toolchains.	Strict TypeScript mode with Zod schemas mirrored from OpenAPI contracts.	Catches API contract mismatches during build time before deployment.

9.6 Comprehensive Frontend Testing Strategy & Acceptance Criteria

Frontend UI specifications include validation for package dimensions and dynamic quote countdown timer updates in the booking wizard, designed for client-side form controls prior to API submission.

End-to-end integration tests using Playwright simulate a complete user journey: logging in as customer, completing all four booking wizard steps, verifying that a tracking number is generated, and confirming that the live tracking stepper transitions upon simulated SSE status events.

9.7 State Management Architecture & Client-Side Token Storage

The React/TypeScript Single Page Application separates client-side state across three distinct operational layers:

1. Ephemeral Client UI State (React Context & Zustand): Wizard progression across the 4-step parcel booking journey, active modal visibility, sidebar collapse toggles, and user theme preferences reside in lightweight Zustand stores. Zustand was selected over Redux for its boilerplate-free API, native TypeScript type inference, and minimal 1.2 KB bundle footprint.

2. Server Cache State (TanStack Query): Server data synchronization, REST response caching, and query deduplication are governed by TanStack Query (React Query). Queries are configured with a 5-minute stale-time window and automatic background re-validation on window focus. Successful mutations (such as booking creation or courier assignment)

immediately invalidate target query keys, ensuring zero-latency UI updates without full page reloads.

3. Client Authentication & Token Security: In strict adherence to OWASP Single Page Application security guidelines, sensitive JWT access tokens are stored exclusively in browser memory (JavaScript closure scope) to permanently eliminate Cross-Site Scripting (XSS) token exfiltration via localStorage or sessionStorage. Long-lived refresh tokens are stored in secure, HttpOnly, SameSite=Strict cookies inaccessible to client scripts. A silent token refresh cycle is executed automatically 60 seconds prior to token expiration or upon receiving an HTTP 401 response via a shared Promise mutex.

9.8 Application Routing Hierarchy & Role-Based Access Matrix

Application navigation is orchestrated via React Router v6, implementing nested layout routes protected by high-order AuthGuard components that evaluate user role claims prior to rendering protected views:

Table 9.2: Frontend Application Route Hierarchy and Role Access Matrix

Route Path	Target Feature Component	Access Entitlement	Route Protection Strategy
/login	LoginForm	Public (Unauthenticated)	Open access; redirects authenticated users to their home dashboard.
/register	RegisterForm	Public (Unauthenticated)	Self-service customer registration; redirects to login upon success.
/tracking	PublicTrackingView	Public (Anonymous)	Public milestone lookup; returns sanitized PII-redacted shipment status.
/customer/dashboard	CustomerDashboard	ROLE_CUSTOMER	Protected; requires valid Customer JWT; displays active shipments.
/customer/book	BookingWizard (4-Step)	ROLE_CUSTOMER	Protected; guides address entry, dimension validation, and quote freezing.
/customer/parcels	ParcelHistoryList	ROLE_CUSTOMER	Protected; paginated list of booked parcels with live tracking links.
/merchant/dashboard	MerchantConsole	ROLE_MERCHANT	Protected; B2B shipping analytics, volume metrics, and order ingestion.
/merchant/api-keys	ApiKeyManagement	ROLE_MERCHANT	Protected; provision, inspect prefixes, and revoke SHA-256 API credentials.

Route Path	Target Feature Component	Access Entitlement	Route Protection Strategy
/merchant/webhooks	WebhookConfigView	ROLE_MERCHANT	Protected; configure webhook URLs, subscribed event types, and view secrets.
/dispatcher/board	DispatcherCockpit	ROLE_DISPATCHER	Protected; live zone dispatch board, courier capacity, and advisory locks.
/courier/portal	CourierManifestView	ROLE_COURIER	Protected; mobile manifest, stop navigation, delivery attempt, and POD photo.
/admin/zones	ZoneManagementView	ROLE_ADMIN	Protected; delivery zone polygons, postal prefix mappings, and tariff matrix.
/admin/system	SystemSettingsView	ROLE_ADMIN	Protected; system parameters, fee rules, outbox status, and audit logs.

9.9 Component Directory Architecture & Design System Tokens

The frontend codebase follows a strict feature-sliced architecture organized under web/src/:
- components/ui/: Houses reusable atomic UI primitives (Button, Card, Dialog, Input, Table, Badge, Alert) styled via Tailwind CSS utility classes and Radix UI accessible primitives.
- components/layout/: Shared structural shells including AppNavbar, SidebarNav, Footer, and responsive AppShell containers.
- features/*: Self-contained domain modules co-locating components, hooks, and types (e.g. features/booking/ containing BookingWizard.tsx, StepAddress.tsx, StepDimensions.tsx, StepQuote.tsx; features/tracking/ containing LiveTrackingStepper.tsx, EventTimeline.tsx).
- services/: Dedicated singleton API client services isolating HTTP communication from UI components.
- hooks/: Custom React hooks encapsulate state logic (useAuth, useParcels, useSSETracking, useDebounce).

Component naming conventions strictly enforce PascalCase for component files (e.g. BookingWizard.tsx) and camelCase for hooks and utility functions (e.g. useSSETracking.ts, formatCurrency.ts).

9.10 Dedicated API Client Service Layer & Interceptors

All backend communication is centralized in a singleton ApiClient service (services/apiClient.ts):

- Request Interceptors: Automatically injects the Authorization: Bearer <token> header, attaches a unique X-Correlation-ID UUIDv4 header for distributed request tracing, and sets Content-Type: application/json.
- Response Interceptors: Translates backend standardized RFC 7807 Problem Details error envelopes into typed JavaScript domain exceptions (ApiError), exposing structured error codes and field-level validation errors to UI forms.
- Concurrency Mutex for Token Refresh: When a protected endpoint returns HTTP 401 Unauthorized, the response interceptor pauses all concurrent outbound requests, initiates a single refresh request to /api/v1/auth/refresh, updates the in-memory access token, and transparently replays the queued requests without disrupting the user session.

9.11 Web Accessibility (a11y) & Inclusive Design Practices

The client application adheres to WCAG 2.1 Level AA accessibility standards:

- Semantic HTML5: Layouts strictly utilize semantic landmarks (<main>, <header>, <nav>, <section>, <article>) to ensure screen readers navigate content logically.
- ARIA Attributes: Dynamic elements incorporate explicit ARIA roles: aria-live='polite' on the live tracking status stepper to announce SSE milestone updates, aria-describedby linking form inputs to validation error spans, and role='progressbar' on the booking wizard header.
- Keyboard Navigation: All interactive controls are fully keyboard-navigable with visible high-contrast focus rings (focus-visible:ring-2 ring-primary). Modal dialogs implement active focus traps to prevent focus escaping to background elements while open.

CHAPTER 10

EDGE INGRESS, API GATEWAY & TRAFFIC ROUTING SUBSYSTEM

10.1 Subsystem Scope: API Gateway, Dispatcher Portal & Administrative Control

The Edge Ingress, API Gateway & Traffic Routing Subsystem provides the single ingress entrypoint, edge traffic security, and operational administration control for the SwiftDrop enterprise platform. Located across deploy/gateway/ and core-api/internal/admin/, this module configures the Traefik v3 API Gateway and provides administrative Core API capabilities (operational delivery zones, postal code prefixes in zone_postal_codes, runtime system settings, system-wide delivery reports, and immutable audit log inspection, with merchant approval coordination via internal/merchants). Operational courier fleet management belongs to Member 3 (internal/dispatch/), and container health probes are managed directly by Kubernetes readiness checks.

Furthermore, this subsystem provides the central Dispatcher Fleet Cockpit and the Courier Mobile Web Manifest in web/src/features/dispatcher-admin/, enabling logistics supervisors to manage regional fleet assignments and couriers to execute daily delivery tasks.

10.2 Architectural Design: Traefik Ingress Controller & Dynamic Routing

In accordance with ADR-001, Traefik v3 serves as the unified reverse proxy and ingress controller:

1. Dynamic Route Matching & Router Hierarchy: Traefik evaluates declarative routers configured with explicit priorities:
- Public Tracking SSE Stream (/api/v1/tracking/public/{trackingNumber}/stream): Priority 100, buffer-free streaming with 15-second heartbeat.
- AI Assistant MCP Stream (/api/v1/ai/mcp/sse): High-priority streaming channel for agent tooling.
- Authentication Login (/api/v1/auth/login): Isolated entrypoint protected by dedicated brute-force rate limiting.
- Courier Proof Photo Upload (/api/v1/deliveries/{id}/proof-photo): Multipart form route with

an elevated 10 MB request body limit.
- Merchant B2B API (/api/v1/merchants/*): Protected tenant API with dedicated rate limiting.
- Core API Modular Monolith (/api/v1/*): General operational API routes with standard 1 MB JSON body limit.
- AI Assistant Chat (/api/v1/ai/chat): Conversational assistant queries with 60-second read timeout.
- Public Delivery Zones (/api/v1/zones): Unauthenticated endpoint returning active zones and postal code prefix lookups.
- Single Page Application (/): Routes public web traffic to the React frontend.
- Internal Management Dashboard (:8090): Internal-only observability dashboard inaccessible from external networks.

2. Multi-Tier Edge Rate Limiting Middleware (R-13): Token bucket rate limiters are applied per client IP:
- Authentication Login: Strictly 5 requests per minute with a burst allowance of 3 on /api/v1/auth/login to prevent credential stuffing and brute-force attacks.
- Merchant API: 120 requests per minute with a burst allowance of 20 on /api/v1/merchants/*.
- Public Tracking: 30 requests per minute with a burst allowance of 10 on /api/v1/tracking/public/*.
- AI Assistant: 10 requests per minute with a burst allowance of 2 on /api/v1/ai/*.
- Concurrent Streams: Maximum 5 concurrent open streaming connections per client IP.
- General Core API traffic (/api/v1/*) carries no static gateway rate limiter; Core API authenticates the caller token and enforces fine-grained tenant boundaries.

3. Security Header Injection & CORS: Automatically injects HSTS, X-Frame-Options: DENY, X-Content-Type-Options: nosniff, Content-Security-Policy (CSP), and validates CORS pre-flight OPTIONS requests.




Figure 10.1: Traefik Dynamic Ingress Routing Architecture

10.3 Dynamic Execution Flows & Drawn Architecture Diagrams

Figure 10.2 illustrates the multi-tier Edge Rate Limiting, identity header sanitization, payload size enforcement, and denial-of-service defense flow. Gateway policies enforce a 1 MB maximum payload on standard JSON requests and up to 10 MB for courier POD photo uploads, with upstream execution timeouts budgeted at 30 seconds for Core API and 60 seconds for AI Assistant queries, with automated retries disabled on mutating write operations:




Figure 10.2: Edge Rate Limiting & Denial-of-Service Defense Flow

10.4 Gateway Routing Rules & Policy Contracts

Traefik dynamic configuration rules are codified in deploy/gateway/traefik/dynamic-routes.yml (paired with static configuration in traefik.yml). The configuration defines explicit path prefixes, strips caller-spoofed identity headers, maps upstream Docker/K8s service hostnames, and integrates with Cloudflare edge proxying. Upstream pod readiness and healthy target rotation are managed natively by Kubernetes readiness probes, avoiding unnecessary gateway-level active polling.

```
Dynamic Router Hierarchy & Priority Rules: Traefik processes ingress traffic against a
strict priority-ordered router hierarchy:
- Priority 100: Public Tracking SSE Stream (/api/v1/tracking/public/
{trackingNumber}/stream) routed directly to services/tracking/ with proxy buffering
disabled (flushInterval: -1) and persistent connection keepalive.
- Priority 90: AI Assistant SSE Stream & FastMCP (/api/v1/ai/stream) routed to
services/ai-assistant/ with 60-second timeouts.
- Priority 85: Proof of Delivery Photo Upload (POST /api/v1/deliveries/{id}/proof-
photo) configured with an expanded 10 MB multipart payload ceiling.
- Priority 80: Authentication Login (POST /api/v1/auth/login) governed by strict 5
req/min (burst 3) token bucket rate limiting.
- Priority 70: Merchant B2B API (/api/v1/merchant/*) governed by 120 req/min (burst 20)
token bucket rate limiting.
- Priority 50: General Operational Core API (/api/v1/*) routed to core-api with 1 MB
payload limits and 30-second request timeouts.
- Priority 40: API Version Fallback (/api/*) catching unrecognized paths and returning
structured HTTP 404 JSON responses.
- Priority 20: Web Frontend (/) serving React Single Page Application assets with
client-side index.html fallback routing.
- Internal Management: Traefik Dashboard and Prometheus metrics listening on internal
port :8090, restricted to cluster-local CIDRs.
```

Request Timeout & Circuit Breaker Contracts: Gateway timeouts enforce deterministic SLA boundaries. Upstream response timeouts are capped at 30 seconds for transactional Core API endpoints and 60 seconds for generative AI inference. To protect transactional consistency, non-idempotent HTTP methods (POST, PUT, PATCH, DELETE) strictly forbid automatic gateway retries, preventing duplicate parcel bookings or repeated payment debits during transient network interruptions.

10.5 Technical Justifications: Traefik vs. NGINX/Kong

Table 10.1 outlines the technical justification for selecting Traefik over NGINX and Kong:

Table 10.1: Technical Justification for Ingress Controller

Criteria	NGINX	Kong Gateway	Traefik v3 (Selected)
Service Discovery	Requires manual configuration reloading (nginx -s reload) or Lua scripts.	Requires external PostgreSQL database for gateway state storage.	Native automatic service discovery via Docker API and Kubernetes Ingress CRDs.
Configuration Overhead	Static text configuration files; error-prone during container scaling.	Heavyweight; complex plugin architecture and DB migrations.	Clean YAML dynamic configuration; hot-reloads in milliseconds without restarting.
Streaming Protocols	Good, but requires custom buffering tweaks (proxy_buffering off).	Complex WebSocket/SSE configuration plugins.	First-class out-of-the-box support for Server-Sent Events (SSE) and HTTP/2 multiplexing.

10.6 Defensive Security: Header Sanitization, TLS 1.3 Termination & DDoS Defenses

In production, Cloudflare terminates client TLS connections and absorbs volumetric network-layer DDoS floods before traffic reaches the cluster ingress. Traefik listens on port 443 for direct development and local container environments, with Go's standard library TLS 1.3 engine dynamically negotiating secure, forward-secrecy cipher suites.

To protect against header manipulation and IP spoofing, Traefik inspects the rightmost client IP from the X-Forwarded-For header (depth 1, populated by Cloudflare). Furthermore, Traefik strictly strips spoofable caller identity headers (X-User-Role, X-User-ID, X-Tenant-ID) from incoming client requests. Caller identity and tenant scope can only be asserted by Core API through cryptographically validated JWT access tokens.

10.7 Comprehensive Testing Strategy & Acceptance Criteria

Automated perimeter verification suites validate gateway routing, rate-limiting enforcement, and security policies:

1. Rate Limiting Verification: Automated test harnesses execute rapid request bursts against the gateway:
- Authentication Endpoint: 5 consecutive POST requests to /api/v1/auth/login are processed; the 6th rapid attempt immediately triggers HTTP 429 Too Many Requests with a Retry-After header, confirming brute-force protection.
- Merchant API: Rapid query batches exceeding 120 requests/minute (burst 20) on /api/v1/merchant/* return HTTP 429, shielding backend database pools.
- Streaming Limit: Attempting to establish more than 5 concurrent SSE streams from a single client IP triggers HTTP 429, preventing connection starvation.

2. Defensive Header & Payload Enforcement:
- Header Stripping: Requests injected with spoofed headers (X-User-Role: ADMIN, X-User-ID: usr_fake, X-Tenant-ID: mrc_fake) are verified at the upstream backend to ensure all spoofable headers are stripped by Traefik before reaching Core API.
- Real IP Extraction: Tests simulate Cloudflare forwarding by injecting multi-hop X-Forwarded-For headers, verifying that Traefik strictly extracts the depth-1 IP for rate-limiting and audit logging.
- Payload Ceilings: Standard API POST requests with payloads exceeding 1 MB are

intercepted with HTTP 413 Payload Too Large, while multipart photo uploads up to 10 MB on /api/v1/deliveries/{id}/proof-photo succeed without truncation.

10.8 Traefik Dynamic Routing Specification & Ingress Middleware Policy

Traefik v3 serves as the edge reverse proxy and ingress controller, routing traffic across Core API, Tracking API, AI Assistant, and the frontend SPA:

Table 10.2: Traefik Ingress Gateway Dynamic Route Mappings and Middleware Policy

Path Prefix / Rule	Target Upstream Service	Rate Limiting Threshold	Security & Middleware Policy
PathPrefix(`/api/v1/auth/login`)	service-core-api:8080	5 req/min (Burst: 3)	Token Bucket per client IP; brute-force credential stuffing mitigation; TLS 1.3.
PathPrefix(`/api/v1/auth/*`)	service-core-api:8080	Gateway pass-through	Token refresh and registration; Core API internal rate check; strips Server header.
PathPrefix(`/api/v1/merchant/*`)	service-core-api:8080	120 req/min (Burst: 20)	Token Bucket per merchant API key prefix; B2B programmatic quota enforcement.
PathPrefix(`/api/v1/tracking/public/{trackingNumber}/stream`)	service-tracking:8081	30 req/min (Burst: 10)	Max 5 open streaming connections per IP; SSE response buffer bypass; keep-alive.
PathPrefix(`/api/v1/tracking/public/*`)	service-tracking:8081	30 req/min (Burst: 10)	Public read-only milestone query; PII redacted; response caching enabled.
PathPrefix(`/api/v1/ai/*`)	service-ai-assistant:8000	10 req/min (Burst: 2)	Token Bucket per IP; rate limit prevents LLM cost exhaustion; strips internal proxy headers.
PathPrefix(`/api/v1/*`)	service-core-api:8080	Gateway pass-through	Core API transactional operations; mandatory JWT bearer token validation; CORS.
PathPrefix(`/`)	web:80	200 req/min (Burst: 50)	Serves compiled React static assets; fallback to index.html for SPA client-side routes.

The Traefik edge middleware chain enforces comprehensive security controls: strict Cross-Origin Resource Sharing (CORS) with pre-flight handling, automated TLS 1.3 termination utilizing modern forward-secret cipher suites (TLS_AES_128_GCM_SHA256,

TLS_AES_256_GCM_SHA384), and mandatory response header hardening including HSTS (Strict-Transport-Security: max-age=31536000; includeSubDomains), X-Frame-Options: DENY, and X-Content-Type-Options: nosniff.

10.9 Admin Authorization Model & Privilege Isolation

Administrative capabilities are restricted to authenticated users possessing the ROLE_ADMIN entitlement, enforced server-side via Core API RBAC middleware:

- Delivery Zone Administration (admin:zones:write): Authorizes administrators to create and update delivery zone boundaries (delivery_zones) and configure postal code prefix mappings (zone_postal_codes) required for dynamic tariff calculations.
- System Parameter Management (admin:settings:write): Controls system-wide operational parameters, including fuel surcharge percentages and default currency rules in system_settings.
- Messaging Infrastructure Telemetry (admin:events:read): Enables administrators to inspect transactional outbox publishing backlog and query dead-letter queue (swiftdrop.dlq) status.
- Audit Log Review (admin:audit:read): Grants read-only access to immutable system-wide security logs in audit_logs.

Refer to Appendix A and Appendix B for the comprehensive endpoint-to-permission mapping.

CHAPTER 11

ASYNCHRONOUS EVENT-DRIVEN MESSAGING & TRANSACTIONAL OUTBOX SUBSYSTEM

11.1 Subsystem Scope: Reliable Message Broker & Outbox Publisher

The Asynchronous Event-Driven Messaging & Transactional Outbox Subsystem establishes the guaranteed enterprise messaging backbone for SwiftDrop. Partitioned across core-api/internal/events/ (outbox writer library and event schemas) and services/messaging/ (the standalone messaging daemon suite), this subsystem eliminates distributed dual-write inconsistencies via the Transactional Outbox pattern, operates the autonomous singleton Outbox Relay publisher, configures the RabbitMQ AMQP message broker topology, manages the resilient Event Worker consumer, and provides administrative reconciliation tools.

Messaging boundaries mandate that Core API use cases NEVER publish directly to RabbitMQ inside HTTP transaction handlers. All integration events MUST be written to the outbox_events table within the exact same database transaction that commits the domain aggregate mutation. This architectural guarantee ensures that events are published to downstream subscribers if and only if the authoritative database transaction successfully commits.

11.2 Architectural Design: Transactional Outbox Pattern & AMQP Topology

The messaging architecture comprises four decoupled operational components:

1. Outbox Writer Contract (core-api/internal/events/writer.go & repository.go): Exposes the OutboxWriter.Write(ctx, tx *sql.Tx, ...AnyEnvelope) contract executed within Core API transactions to atomically stage versioned event envelopes into the outbox_events table.

2. Singleton Outbox Relay Daemon (services/messaging/cmd/relay & internal/relay): An autonomous Go daemon running strictly as a single replica (singleton). The relay claims pending outbox rows in atomic batches of 50 via SELECT ... FOR UPDATE SKIP LOCKED with a 60-second visibility lease (next_attempt_at = now() + lease), publishes messages to

RabbitMQ with AMQP publisher confirms outside the transaction, and marks committed rows as PUBLISHED upon broker acknowledgment.

3. RabbitMQ AMQP Broker Topology: Establishes a durable topic exchange swiftdrop.events.topic, binding routing keys using '#' wildcards (parcel.#, courier.#, merchant.#) to durable subscriber queues: q.notifications.worker (parcel.#), q.webhooks.dispatcher (parcel.#, courier.#, merchant.#), and q.tracking.updates (parcel.#, courier.#). Unparseable poison messages are routed to Dead Letter Exchange swiftdrop.dlq.exchange (fanout) and isolated in dead-letter queue swiftdrop.dlq with a 30-day message TTL.

4. Idempotent Consumer Worker (services/messaging/cmd/worker & internal/{consumer,notification,webhook,delivery}): Consumes AMQP messages, enforces two-tier idempotency via the processed_events table, dispatches HMAC-SHA256 signed webhooks to merchant endpoints, and delivers customer notification emails via SMTP (Mailpit in local environments). Unlike the singleton relay, the worker scales horizontally via KEDA based on queue backlog.

5. Reconciler Tool (services/messaging/cmd/reconcile & internal/reconciler): An autonomous maintenance tool executing stale-outbox audits, expired visibility lease resets, database retention pruning (7-day published outbox events, 30-day notification and webhook delivery rows, 35-day processed-events ledger), and controlled dead-letter queue replays (cmd/reconcile dlq-replay --limit N).

Figure 11.1 depicts the overall containerized messaging subsystem layout, illustrating the decoupled interactions between Core API transactions, the singleton Outbox Relay daemon, PostgreSQL, RabbitMQ, and external endpoints:




Figure 11.1: Asynchronous Event-Driven Messaging & Outbox Relay Architecture

Figure 11.2 illustrates the RabbitMQ AMQP broker topology, detailing topic exchanges, routing keys, durable consumer queues, and dead-letter channels:




Figure 11.2: RabbitMQ Topic Exchange & Dead-Letter Broker Topology

[Note on Broker Queue Bindings: In Figure 11.2, q.webhooks.dispatcher is bound to topic exchange swiftdrop.events.topic with wildcard routing keys parcel.#, courier.#, and merchant.#, ensuring that merchant webhook subscribers receive parcel lifecycle, courier dispatch, and merchant administrative events.]

11.3 Dynamic Execution Flows & Drawn Architecture Diagrams

Figure 11.3 models the Outbox Relay Polling Loop and RabbitMQ Publisher Confirm lifecycle. The poller claims pending rows in batches of 50 in a short transaction that sets a 60-second visibility lease (next_attempt_at = now() + 60s). Broker publication occurs strictly outside any database transaction; on broker confirmation (ACK), the row is marked PUBLISHED. On publication failure, attempt_count is incremented with exponential backoff; if attempts reach 5, the row is marked FAILED. A crash after broker publish can result in duplicate delivery, which downstream consumers handle idempotently:




Figure 11.3: Transactional Outbox Persistence & Polling Relay Loop

Figure 11.4 models the Dead-Letter Queue (DLQ) Routing, poison message isolation, and operator replay flow. Unparseable or poisoned messages are rejected with basic.nack(requeue=false) and routed to swiftdrop.dlq. Operator replay via cmd/reconcile dlq-

replay reads messages from swiftdrop.dlq and republishes directly to swiftdrop.events.topic with header x-replayed-from: swiftdrop.dlq, acking the dead-letter message only after broker confirmation (never writing back to outbox_events):




Figure 11.4: Dead-Letter Queue (DLQ) Routing & Operator Replay Pipeline

Figure 11.5 depicts the end-to-end Merchant Webhook Delivery and SSRF-hardened egress pipeline, illustrating AES-256-GCM secret decryption with endpoint-id AAD, pre-dial DNS validation, and HMAC-SHA256 signature generation:




Figure 11.5: Merchant Webhook Delivery & SSRF-Hardened Egress Pipeline

11.4 Event Contract Specifications

All integration events adhere to the standardized SwiftDrop event envelope (CloudEvents-inspired) with canonical naming pattern <aggregate>.<action>.v1 (e.g. parcel.booked.v1, parcel.assigned.v1, parcel.picked_up.v1, parcel.out_for_delivery.v1, parcel.delivered.v1, parcel.delivery_failed.v1, parcel.returned.v1, parcel.cancelled.v1):

```
{
  "event_id": "0192e4a1-9999-7abc-8def-0123456789ab",
  "producer": "core-api",
  "occurred_at": "2026-10-28T15:00:00Z",
  "correlation_id": "0192e4a1-8888-7abc-8def-0123456789ab",
  "aggregate_type": "parcel",
  "aggregate_id": "0192e4a1-0001-7abc-8def-0123456789ab",
  "aggregate_version": 7,
  "event_type": "parcel.delivered.v1",
  "schema_version": "1.0.0",
  "payload": {
    "parcel_id": "0192e4a1-0001-7abc-8def-0123456789ab",
    "tracking_number": "SD-20261028-00912",
    "merchant_id": "0192e4a1-5555-7abc-8def-0123456789ab",
    "status": "DELIVERED",
    "proof_type": "PHOTO",
    "proof_id": "0192e4a1-7777-7abc-8def-0123456789ab",
    "delivered_at": "2026-10-28T14:59:45Z",
    "notify": {
      "recipient_name": "Bob Fernando",
      "recipient": "bob@example.lk"
    }
  }
}
```

Event payloads strictly exclude raw S3 storage URLs, courier personal telephone numbers, and internal operational notes. Recipient contact information resides exclusively within an optional notify block, which the Event Worker strips before dispatching webhook payloads to external merchant endpoints.

11.5 Data Modeling & Persistence Schema

Migration steps 1–11 are the logical dependency order. In the repository all migrations live in core-api/migrations/ and use timestamped filenames, because the embedded migrator sorts by filename. Steps 8 and 9 are 20261101000050_create_outbox_events and 20261101000500_create_worker_dedup_and_webhooks. services/messaging contains no migrations.

1. outbox_events: Relational outbox buffer. Columns: id UUID PK; producer VARCHAR(64) DEFAULT 'core-api'; occurred_at TIMESTAMPTZ; correlation_id VARCHAR(128); aggregate_type VARCHAR(64); aggregate_id UUID; aggregate_version INT >= 1; event_type VARCHAR(128) matching ^[a-z_]+.[a-z_]+.v[0-9]+$; schema_version VARCHAR(16) DEFAULT '1.0.0'; payload JSONB; status PENDING|PUBLISHED|FAILED; attempt_count INT; next_attempt_at TIMESTAMPTZ; last_error TEXT; created_at TIMESTAMPTZ; published_at TIMESTAMPTZ. Index: idx_outbox_pending ON (created_at ASC) WHERE status='PENDING'.

2. processed_events: Consumer idempotency ledger. Columns: consumer_name VARCHAR(64), event_id UUID, processed_at TIMESTAMPTZ; PRIMARY KEY (consumer_name, event_id).

3. notification_deliveries: Customer email and SMS delivery audit. Columns: id UUID PK; event_id UUID; recipient VARCHAR(255); channel EMAIL|SMS; template_name VARCHAR(64); status PENDING|IN_PROGRESS|SUCCESS|FAILED; attempt_count INT; next_attempt_at TIMESTAMPTZ; lease_expires_at TIMESTAMPTZ; provider_message_id VARCHAR(255); last_error TEXT; created_at TIMESTAMPTZ; delivered_at TIMESTAMPTZ; plus event_type, aggregate_id, aggregate_version, payload; UNIQUE (event_id, channel, recipient). No foreign key to outbox_events (outbox rows are purged at 7 days, delivery rows at 30).

4. webhook_deliveries: Merchant webhook execution ledger. Columns: id UUID PK; endpoint_id FK to webhook_endpoints(id) ON DELETE RESTRICT; event_id UUID; status PENDING|IN_PROGRESS|SUCCESS|FAILED; attempt_count INT; next_attempt_at TIMESTAMPTZ; lease_expires_at TIMESTAMPTZ; response_status_code INT; response_body_snippet VARCHAR(500); last_error TEXT; created_at TIMESTAMPTZ; delivered_at TIMESTAMPTZ; plus event_type, aggregate_id, aggregate_version, occurred_at, payload; UNIQUE (endpoint_id, event_id).

5. webhook_delivery_attempts: Append-only audit history of every HTTP webhook attempt. Columns: id UUID PK; delivery_id FK to webhook_deliveries(id) ON DELETE CASCADE; attempt_no INT; started_at TIMESTAMPTZ; response_status_code INT; response_body_snippet VARCHAR(500); error_class VARCHAR(64); error_message TEXT; next_attempt_at TIMESTAMPTZ; created_at TIMESTAMPTZ.

11.6 Technical Justifications: Transactional Outbox vs. Two-Phase Commit / Debezium CDC

Table 11.1 provides the technical comparison between messaging reliability strategies:

Table 11.1: Technical Justification for Outbox Pattern

Pattern	Two-Phase Commit (2PC)	Debezium CDC (Log Mining)	Transactional Outbox Poller (Selected)
Reliability	Prone to coordinator locking deadlocks and blocking during network splits.	High: Reads PostgreSQL Write-Ahead Log (WAL) directly.	100% Reliable: Leverages PostgreSQL standard ACID transaction commit.
Operational Overhead	Very High: Requires XA-compliant database drivers and coordinator.	High: Requires Apache Kafka, Kafka Connect, and WAL decoding plugins.	Low: Lightweight Go daemon running alongside PostgreSQL. Zero extra Java runtimes.
Payload Filtering	N/A	Exposes raw table row mutations rather than formal domain events.	Perfect: Publishes versioned, application-level domain event envelopes.

Table 11.2 documents the technical evaluation defending the selection of RabbitMQ as SwiftDrop's enterprise message broker:

Table 11.2: Comparative Evaluation of Enterprise Message Brokers

Criteria	Apache Kafka	AWS SQS / SNS	RabbitMQ (AMQP 0-9-1) (Selected)
Messaging Semantics	Log-centric distributed streaming; designed for append-only time-series partitions.	Cloud-proprietary queue service; opaque message lifecycle.	Broker-centric queue routing; rich topic exchanges, direct routing keys, and dead letter exchanges (DLX).
Consumer Acknowledgment	Offset-based; failures in one message block entire partition or require complex dead-letter topics.	Per-message visibility timeout; delayed re-queuing.	Native per-message acknowledgment (basic.ack / basic.nack) with immediate DLQ routing.
Resource Footprint	Heavy: Requires JVM, high RAM (>1GB), and cluster coordination (Zookeeper / KRaft).	Zero on-premise, but incurs high operational cloud costs and vendor lock-in.	Lightweight: Minimal container memory footprint in production environments.
Local Dev & Testing Parity	Complex: Requires local Kafka test containers; high startup latency in CI pipelines.	Impossible offline: Requires LocalStack emulation with fidelity discrepancies.	Flawless: Official Docker image spins up rapidly in Docker Compose and GitHub Actions CI.

In parcel logistics workflows, integration messages represent distinct transactional business events (e.g. parcel.booked.v1, parcel.assigned.v1, parcel.delivery_failed.v1). Because each

parcel must be acknowledged, processed, and tracked independently, RabbitMQ's per-message AMQP 0-9-1 delivery semantics provide an optimal architectural fit over Kafka's partition-based batch streaming.

To establish formal architectural traceability, Table 11.3 codifies the module-level architectural decision records (ADR-005 through ADR-010) governing messaging reliability, broker topology, and fault recovery:

Table 11.3: Messaging Subsystem Architectural Decision Records (ADR-005 through ADR-010)

Decision ID	Decision Title	Selected Technical Strategy	Invariants & Justification	Status
ADR-005	Transactional Outbox Pattern	PostgreSQL outbox_events with SELECT ... FOR UPDATE SKIP LOCKED	Guarantees atomic business mutation and event staging in single ACID transaction without 2PC or CDC.	Accepted
ADR-006	RabbitMQ AMQP Broker Topology	Topic Exchange (swiftdrop.events.topic) with wildcard routing	Lightweight container footprint, AMQP publisher confirms, and granular topic routing vs. heavyweight Kafka.	Accepted
ADR-007	Jittered Exponential Backoff Webhooks	5 retry attempts: 0s, 30s, 2m, 10m, 30m with ±20% random jitter	Prevents thundering-herd effect on merchant endpoints; deterministic status code classification.	Accepted
ADR-008	Pre-Dial Egress SSRF Defense	Custom net.Dialer verifying DNS resolution against IP blocklist	Neutralizes DNS rebinding attacks at every outbound connection attempt; blocks private and cloud metadata CIDRs.	Accepted
ADR-009	Dead-Letter Channel & Poison Isolation	Dedicated DLX (swiftdrop.dlq.exchange) and queue (swiftdrop.dlq)	Prevents unparseable corrupt messages from halting consumer queues; 30-day retention for operator replay.	Accepted
ADR-010	Autonomous Database Reconciler	Scheduled maintenance tool: 7d outbox, 30d delivery, 35d processed	Prevents relational table bloat while retaining audit logs; automated visibility lease recovery on worker crash.	Accepted

11.7 Defensive Reliability: At-Least-Once Delivery, Idempotency Deduplication & Dead Letter Exchanges

Delivery Guarantees & Idempotency: SwiftDrop provides an authoritative delivery guarantee of at-least-once delivery with idempotent processing; exactly-once delivery across distributed networks is provably impossible. The Event Worker enforces lease-based task execution: upon receiving an event, it creates or claims an in-progress delivery row with a visibility lease (lease_expires_at). The external side-effect (HTTP webhook dispatch or SMTP transmission) is executed while holding the lease. Only after the execution outcome is deterministically known does the worker commit the terminal delivery state and insert the deduplication record into processed_events (consumer_name, event_id) in a single database transaction. If a worker crashes mid-flight before committing, the lease expires and the Reconciler re-queues the task for retry—guaranteeing that crash faults result in safe retries rather than silently lost messages.

Webhook Delivery Mechanics & Failure Classification: Outbound webhooks execute with a 5-second per-attempt timeout and an explicit 5-attempt jittered backoff schedule: 0s, 30s, 2m, 10m, and 30m (±20% random jitter). Response status codes are classified deterministically:
- 2xx: Success. Marked SUCCESS in webhook_deliveries.
- 408, 429, 5xx, or network timeouts: Transient error. Scheduled for next retry attempt.
- Other 4xx, redirects (webhooks never follow HTTP redirects), or SSRF blocks: Terminal failure. Immediately marked FAILED without further attempts.
- After 5 unsuccessful attempts, the delivery row transitions to FAILED for audit and manual replay via the Admin API. Webhook delivery failures never route to the dead-letter queue.

Poison Message Isolation via Dead-Letter Queue (swiftdrop.dlq): Messages that cannot be parsed due to corrupt JSON schemas or unrecoverable broker deserialization errors are rejected via basic.nack(requeue=false). The broker routes these messages through swiftdrop.dlq.exchange (fanout) into swiftdrop.dlq with a 30-day message TTL, preventing hot poison-message processing loops.

Egress SSRF Defense via Custom DialContext: When dispatching external webhooks, the Event Worker's custom DialContext resolves DNS once and evaluates all resolved IP addresses against an extensive blocklist before establishing a TCP socket: RFC 1918 private subnets (10/8, 172.16/12, 192.168/16), carrier-grade NAT (100.64/10), loopback (127/8), link-local/cloud metadata (169.254/16), reserved (240.0.0.0/4), current network (0.0.0.0/8), IETF protocol assignments (192.0.0.0/24), benchmark testing (198.18.0.0/15), multicast

(224.0.0.0/4, ff00::/8), IPv6 unique-local (fc00::/7), IPv4-IPv6 translation (64:ff9b::/96), and IPv4-mapped IPv6 forms of these. The client dials the verified IP directly while preserving the original TLS SNI header, neutralizing DNS rebinding attacks at every delivery attempt.

Figure 11.6 illustrates the SSRF Defense decision flowchart executed by the worker transport prior to dispatching any external HTTP webhook request:




Figure 11.6: Server-Side Request Forgery (SSRF) Egress Defense Decision Flowchart

11.8 Comprehensive Testing Strategy & Acceptance Criteria

Automated verification of the messaging subsystem spans multiple test harnesses:

- Unit Tests: core-api/internal/events/*_test.go validates event envelope serialization, required correlation_id propagation, and golden JSON format matching. services/messaging/internal/sqlguard and core-api/migrations/sql_guard_test.go verify that every column referenced in SQL string literals exists in the migration DDL.

- Consumer & Worker Tests: services/messaging/internal/{relay,consumer,delivery,notification,webhook,reconciler}/*_test.go verify state machines,

retry schedules, HMAC signature headers, SSRF CIDR rejection tables, and lease recovery.

- Integration & E2E Tests: services/messaging/tests/ runs end-to-end lifecycle verification requiring Docker containers (executed via INTEGRATION=1). The suite confirms that database transaction rollbacks leave zero outbox rows, 10 duplicate message deliveries produce exactly one external webhook call, unparseable poison messages route to swiftdrop.dlq without looping, and expired visibility-lease reset is covered by unit and SQL-contract tests (TestResetExpiredLeases).

CHAPTER 12

DEVOPS, CONTAINERIZATION & CLOUD INFRASTRUCTURE PLATFORM

12.1 Subsystem Scope: Automated Deployment, Containerization & Infrastructure As Code

The DevOps, Containerization & Cloud Infrastructure Platform (owned by M.D. Wakishta [234217J] — Member 9) provides the automated build pipelines, local multi-container development environment, production Kubernetes orchestration, and continuous telemetry monitoring for SwiftDrop. Located across deploy/ and .github/workflows/, this module maintains Dockerfiles, docker-compose.yaml, Helm deployment charts, and automated verification test harnesses (scripts/verify.sh).

Operational boundaries mandate that all deployable services package into hardened, minimal container images with non-root security contexts, and pass automated CI checks before merging into main.

12.2 Multi-Stage Dockerfile Architecture & Container Hardening

All Go backend services utilize hardened multi-stage Docker builds designed to minimize container attack surfaces and optimize cold-start performance. The compilation stage utilizes golang:1.22-alpine to fetch dependencies with cached layer hashing (go mod download) and compiles statically linked binaries via CGO_ENABLED=0 GOOS=linux go build -ldflags="-s -w -extldflags '-static'", stripping all debug symbol tables and DWARF data to achieve minimal binary size.

Core API and other services target distroless (gcr.io/distroless/static-debian12:nonroot, UID 65532: nonroot); the messaging image currently uses alpine:3.19 (UID 10001). Distroless images contain solely the compiled Go binary, CA root certificates, and timezone data—omitting shell interpreters (/bin/sh, /bin/bash), package managers (apt, apk), and core utilities. This permanently eliminates arbitrary command execution and container breakout vulnerabilities (CWE-78). Across the messaging deployment, five binaries are packaged: relay, worker, reconcile (production) and devemit, fake-receiver (development tools). Containers

enforce readOnlyRootFilesystem: true and drop all Linux kernel capabilities (cap_drop: [ALL]).

For messaging and background integration workloads (services/messaging), the runtime container is built upon alpine:3.19 executing under an unprivileged, non-root user swiftdrop (UID 10001:10001). This hardened multi-binary container packages the Outbox Relay (cmd/relay), the Event Worker consumer (cmd/worker), and the administrative Reconciler CLI (cmd/reconcile), retaining necessary CA certificates and timezone assets while dropping all Linux capabilities.

12.3 Local Orchestration Platform: Docker Compose Network & Service Topology

Figure 12.1 depicts the complete 10-service local development topology defined in docker-compose.yaml:




Figure 12.1: Docker Compose Multi-Container Orchestration Topology

12.4 Cloud-Native Kubernetes Infrastructure Platform (ADR-002)

Figure 12.2 depicts the production Kubernetes (K3s) deployment architecture:




Figure 12.2: Kubernetes Cluster Architecture, Services & Ingress

12.5 Observability & Telemetry Infrastructure: Prometheus Metrics, Grafana & Health Probes

Every deployable service exposes Prometheus instrumentation at /metrics, publishing multi-dimensional metrics across key system dimensions:

- HTTP Request Metrics: http_request_duration_seconds (histogram buckets from 10ms to 10s) and http_requests_total (partitioned by status code, HTTP method, and route path).

- Domain Transition Metrics: parcel_status_transitions_total counter tracking real-time parcel state machine transitions across all 9 canonical statuses.

- Asynchronous Messaging Metrics: swiftdrop_outbox_pending_events (gauge measuring pending outbox rows awaiting publication), swiftdrop_outbox_oldest_pending_age_seconds (gauge tracking lag of oldest uncommitted outbox event), swiftdrop_outbox_published_total (counter of broker-confirmed published events), and swiftdrop_dlq_depth_gauge (measuring dead-letter queue depth on swiftdrop.dlq), alongside broker queue depths for q.notifications.worker, q.webhooks.dispatcher, and q.tracking.updates.

- Real-Time Streaming Gauges: tracking_active_sse_connections measuring concurrent SSE tracking client streams.

Health Probe Invariants & Traffic Isolation: Health endpoints are strictly decoupled from external public edge ingress, accessible exclusively to internal Kubernetes kubelet agents and cluster-local monitoring scrapers (R-07):
- Liveness Probe (/health/live): Lightweight check validating that the Go HTTP runtime process is operational, responding within 2 seconds.
- Readiness Probe (/health/ready): Deep dependency check asserting active PostgreSQL database connection pool viability and RabbitMQ broker socket reachability. If database connection saturation occurs, /health/ready immediately returns HTTP 503 Service Unavailable, prompting Kubernetes to dynamically withdraw the pod from the IngressRoute endpoints without restarting the process.

Startup Probes allow a 30-second initialization grace period for database schema migrations and connection pool warming before liveness monitoring initiates, eliminating premature container restart loops during cold deployments.

Dedicated Messaging Health & Telemetry Endpoints: The Outbox Relay poller daemon exposes internal Kubernetes health probes and Prometheus metrics on port :8082 (/health/live, /health/ready, /metrics). The Event Worker consumer exposes identical health and telemetry endpoints on port :8083 (/health/live, /health/ready, /metrics). These diagnostic ports are purely cluster-local and strictly isolated from the Traefik public ingress route.

12.6 Technical Justifications: Lightweight K3s & Distroless Containers

Table 12.1 outlines the architectural justification for the container hosting platform and runtime environment selected for SwiftDrop:

Table 12.1: Technical Evaluation of Hosting & Orchestration Platforms

Criteria	Managed Cloud K8s (AWS EKS / GKE)	Standalone Docker Compose on VM	K3s on Ubuntu VPS + Cloudflare (Selected)
Cost & Infrastructure Efficiency	High Overhead: Managed control plane fees ($75+/month per cluster) plus multi-node overhead for small-to-medium deployments.	Extremely low: Single VM, but lacks declarative Kubernetes API, ingress CRDs, and automated self-healing.	Optimal Efficiency: High-density lightweight VPS hosts CNCF-certified Kubernetes control plane, worker, and stateful storage with minimal operational overhead.

Criteria	Managed Cloud K8s (AWS EKS / GKE)	Standalone Docker Compose on VM	K3s on Ubuntu VPS + Cloudflare (Selected)
Kubernetes API Fidelity	100% upstream Kubernetes API; standard manifests and ingress resources.	0%: Uses Compose YAML; incompatible with production cloud deployments.	100% CNCF Certified: Identical Deployments, StatefulSets, IngressRoutes, and CronJobs run seamlessly.
Resource Footprint	Heavy: Node agents and cloud controllers consume 1.5GB to 2GB RAM per node.	Minimal: Zero container orchestration overhead.	Extremely lightweight: Control plane and agent packaged in a single 50MB binary consuming <512MB RAM.
Edge Security & Ingress	Requires cloud load balancers ($25/mo per ingress) and external WAF addons.	Requires manual reverse proxy setup; no native Let's Encrypt certificate automation.	Cloudflare edge proxy terminates public TLS and filters DDoS, passing encrypted traffic to Traefik via strict UFW firewall rules.

In accordance with ADR-002, SwiftDrop adopts a single Ubuntu VPS running K3s paired with Cloudflare edge proxy for staging and production hosting. K3s provides complete Kubernetes API fidelity while eliminating cloud control plane expenses. The host firewall (UFW) restricts inbound ports 80 and 443 strictly to Cloudflare's published CIDR ranges, protecting the server origin against direct IP discovery and volumetric DDoS attacks.

To minimize container vulnerabilities and accelerate CI/CD build pipelines, Go service Dockerfiles adopt multi-stage builds. Core API and other services target distroless (gcr.io/distroless/static-debian12 with USER nonroot:nonroot), while the messaging image currently uses alpine:3.19 (UID 10001). The application compiles inside a full golang:1.22-alpine builder image with CGO_ENABLED=0. Production images omit shell interpreters and package managers, effectively eliminating CVE vulnerabilities and preventing remote command injection attacks. The messaging build packages five distinct binaries: relay, worker, reconcile (production) and devemit, fake-receiver (development tools).

Finally, local developer workflows maintain 100% architectural parity with production Kubernetes manifests. The local deploy/docker-compose.yml file mirrors all environment variable schemas, port bindings, database credentials, and network topologies defined in deploy/kubernetes/, ensuring that features verified locally run identically on the production K3s cluster.

12.7 Infrastructure Testing: Automated Verification Script (verify.sh) & CI

The repository provides scripts/verify.sh and verify.ps1, executing: 1. Code formatting check (gofmt), 2. Static analysis and depguard linter (golangci-lint), 3. Race condition detection and unit tests (go test -race ./...), 4. Strict TypeScript compilation (tsc --noEmit), and 5. Docker container boot health assertions.

Figure 12.3 illustrates the automated Continuous Integration and Continuous Deployment (CI/CD) quality gate pipeline governed by Member 9, detailing both the pull request validation workflow (ci.yml) and the zero-downtime production deployment workflow (deploy.yml):




Figure 12.3: Continuous Integration & Automated Deployment Quality Gate Pipeline

As depicted in Figure 12.3, every pull request triggers automated secret scanning with TruffleHog to guarantee zero credential leaks, followed by Go static analysis and depguard module boundary enforcement. Upon successful merge to the main branch, container images are built and tagged with immutable Git commit SHAs, pushed to GitHub Container Registry (GHCR), and rolled out to the Kubernetes cluster preceded by an atomic database migration Job with backoffLimit: 0. If synthetic health probes fail, an automated rollback is immediately initiated.

12.8 Disaster Recovery, Automated Database Backups & Message Bus Durability

To protect operational continuity against hardware catastrophic failures and data corruption, SwiftDrop establishes a multi-tiered disaster recovery strategy across authoritative data stores and messaging brokers:

1. PostgreSQL Backup & Point-in-Time Recovery (PITR): Database state is protected via automated daily full logical dumps (pg_dump -Fc) executed at 02:00 UTC, complemented by continuous PostgreSQL Write-Ahead Log (WAL) archiving shipped to off-site encrypted S3 object storage. Snapshots follow a 30-day rolling retention policy. In disaster recovery scenarios, the point-in-time recovery runbook enables restoring database state to any specific timestamp within the retention window with sub-15-minute Recovery Point Objective (RPO < 15 min) and sub-1-hour Recovery Time Objective (RTO < 60 min).

2. RabbitMQ Durability & Message Persistence: The message broker guarantees persistence across container and node crashes. The primary topic exchange (swiftdrop.events.topic), dead-letter exchange (swiftdrop.dlq.exchange), and all consumer queues (q.notifications.worker, q.webhooks.dispatcher, q.tracking.updates, swiftdrop.dlq) are provisioned with durable: true. All messages published by the Outbox Relay specify AMQP delivery mode 2 (persistent), ensuring message payloads are written to disk before broker publisher confirmations are issued.

3. Database Restoration & Message Replay Consistency: If PostgreSQL is restored from a historical backup, the transactional outbox and consumer ledgers roll back to a consistent snapshot. Upon startup, the Outbox Relay poller queries all outbox_events records where status = 'PENDING', republishing them to RabbitMQ. Downstream Event Workers safely absorb re-delivered messages due to unique constraints in processed_events (consumer_name, event_id) and webhook_deliveries (endpoint_id, event_id), completely neutralizing duplicate execution risks.

CHAPTER 13

GENERATIVE AI DELIVERY ASSISTANT & CROSS-WORKFLOW SUBSYSTEM

13.1 Subsystem Scope: Conversational AI Engine, Tool Calling & System Quality

The Generative AI Delivery Assistant & Cross-Workflow Subsystem (owned by A.A.P.R. Jayathilaka [234096J] — Member 10) provides an intelligent conversational assistant and oversees system-wide cross-workflow integration quality. Located in services/ai-assistant/, this subsystem is implemented in Python 3.11 using FastAPI and the Model Context Protocol (MCP).

The assistant allows customers and merchants to query parcel delivery milestones, calculate complex shipping fee estimates, and explain return policies in natural language. In accordance with SwiftDrop Security Standards §8.0, the assistant operates within a strict read-only sandbox: it is permanently prohibited from possessing direct database credentials, executing SQL queries, mutating parcel state, or accessing private customer data.

Figure 13.1 illustrates the comprehensive UML Use Case model for the SwiftDrop AI Delivery Assistant and FastMCP Service (Module 01), detailing all 24 conversational and tool capabilities spanning public parcel lookups, dynamic fee quotes, authenticated shipment disambiguation, FastMCP tool discovery, guardrails, and health probes:




Figure 13.1: SwiftDrop AI Delivery Assistant & FastMCP Service UML Use Case Model

13.2 Architectural Design: Python/FastAPI Microservice & Model Context Protocol (MCP)

The AI subsystem architecture decouples intent parsing from business execution across five clean layers:

1. FastAPI Ingress & Security: Authenticates user sessions, validates input hygiene, and enforces Token Bucket rate limiting (20 RPM).

2. Domain Orchestrator & Envelopes: Normalizes incoming prompts, manages in-memory LRU session histories, and coordinates LLM inference.

3. Sandboxed Read-Only Tool Registry: Strictly exposes approved read-only tools with zero state mutation and zero direct database connectivity.

4. Universal LLM Provider Adapter: Supports live inference (OpenAI, OpenRouter, NVIDIA NIM) with deterministic mock fallback (TEST_MODE=true) for offline CI environments.

5. Dual-Channel FastMCP Transports: Exposes tools locally via standard stdio JSON-RPC 2.0 and remotely via HTTP Server-Sent Events (SSE).

Figure 13.2 illustrates the high-level architecture and system integration topology of the Python/FastAPI AI Delivery Assistant service, showcasing edge routing through the Traefik API Gateway, the FastMCP integration server, the sandboxed read-only tool registry, and downstream REST communication with the SwiftDrop Core API:




Figure 13.2: High-Level AI Delivery Assistant & FastMCP System Architecture Overview

13.3 Dynamic Execution Flows & Drawn Flowcharts

Figure 13.3 depicts the end-to-end conversational intent parsing, function tool execution, dynamic shipping tariff estimation, and 1-click action directive generation sequence flow (SEQ-AI-02):




Figure 13.3: Conversational Intent Parsing, Tariff Estimation & Action Directive Flow (SEQ-AI-02)

Figure 13.4 illustrates the FastMCP tool discovery and protocol execution sequence (SEQ-AI-05/06), showing how external AI developer clients (Claude Desktop, Cursor IDE) interact via standard stdio JSON-RPC 2.0 pipes and remote HTTP Server-Sent Events (SSE) streams:




Figure 13.4: FastMCP Tool Discovery & Protocol Execution Sequence (SEQ-AI-05/06)

13.4 Tool Specifications & Contracts (get_parcel_status, estimate_delivery_fee)

The assistant exposes two authoritative MCP tool schemas:

```
1. Tool: get_parcel_status
Description: Retrieves current delivery milestone and sanitised status for a tracking number.
Parameters Schema:
{
  "type": "object",
  "properties": {
    "tracking_number": {
      "type": "string",
      "pattern": "^SD-[0-9]{8}-[A-Z0-9]{6}$",
      "description": "Canonical SwiftDrop tracking number"
    }
  },
  "required": ["tracking_number"]
}
```

```
2. Tool: estimate_delivery_fee
Description: Estimates shipping fee based on physical dimensions, weight, and delivery zones.
Parameters Schema:
{
  "type": "object",
  "properties": {
    "pickup_zone": { "type": "string" },
    "dropoff_zone": { "type": "string" },
    "weight_grams": { "type": "integer", "minimum": 1, "maximum": 50000 },
    "length_cm": { "type": "integer", "maximum": 200 },
    "width_cm": { "type": "integer", "maximum": 200 },
    "height_cm": { "type": "integer", "maximum": 200 }
  },
  "required": ["pickup_zone", "dropoff_zone", "weight_grams"]
}
```

13.5 Technical Justifications: Read-Only Tool Sandboxing & Zero Direct DB Access

Table 13.1 provides the technical justification defending the Model Context Protocol (FastMCP) and read-only tool sandboxing architecture selected for the AI Assistant service:

Table 13.1: Technical Comparison of LLM Integration Architectures

Evaluation Metric	Direct SQL Query Generation (Text-to-SQL)	Unbounded LangChain Agent	Model Context Protocol / FastMCP (Selected)
Security & Injection Risk	Catastrophic: LLM can execute DROP TABLE, UPDATE status, or bypass tenant WHERE clauses via prompt injection.	High: Agent has arbitrary code execution or open HTTP access across internal networks.	Maximum Security: Assistant has zero database access, zero shell access, and can invoke strictly pre-approved read-only schemas.
Data Accuracy & Hallucination	High hallucination: LLM invents SQL schema columns or calculates fictitious pricing formulas.	Unpredictable: Multi-hop reasoning loops often get stuck or invent operational answers.	Zero Hallucination: Pricing calculations and tracking status queries execute on authoritative Go Core APIs.
Interface Standardization	Custom proprietary prompt templates; brittle across model upgrades.	Framework lock-in to Python LangChain ecosystem.	Open Standard: FastMCP implements JSON-RPC 2.0 tool discovery, decoupled from specific model providers (Gemini / Claude / OpenAI).

Evaluation Metric	Direct SQL Query Generation (Text-to-SQL)	Unbounded LangChain Agent	Model Context Protocol / FastMCP (Selected)
Auditability & Telemetry	Impossible: Raw generated SQL strings are difficult to audit for compliance.	Complex: Agent internal thought traces must be captured.	Structured: Every tool call is an explicit JSON-RPC invocation logged with user ID, input schema, and execution latency.

Direct database access from an LLM service introduces catastrophic SQL injection and unauthorized data exfiltration vulnerabilities. Sandboxing the AI assistant to consume strictly read-only Core REST APIs enforces all existing database connection pooling, tenant isolation filters, and PII masking rules. The LLM cannot hallucinate arbitrary pricing rates because the tool execution directly evaluates the authoritative pricing engine.

Furthermore, the adoption of the Model Context Protocol (FastMCP) standardizes tool discovery and schema validation across the platform. Tools expose formal JSON Schema parameter definitions, allowing the model to validate types (e.g. integer gram weights between 1 and 50,000) prior to execution. In the event of model failure, network timeout, or third-party API degradation, the assistant gracefully falls back to deterministic rule-based JSON responses, ensuring that customers always receive accurate tracking statuses without experiencing conversational downtime.

13.6 Defensive Safeguards: Prompt Injection Defenses & Hallucination Prevention

The AI Assistant incorporates defense-in-depth safeguards across input, tool invocation, and inference generation boundaries:

1. Delimiter Isolation & Jailbreak Filtering: Untrusted user input is encapsulated within semantic XML delimiters (<user_prompt>...</user_prompt>) to prevent instruction hijacking. Ingress guardrails evaluate incoming text against a heuristic regex library detecting adversarial injection patterns (e.g., 'ignore all previous instructions', 'system override', 'you are now database administrator'). Injections are halted immediately with canned rejection envelopes.

2. Pydantic Parameter Validation & Grounding: FastMCP tool invocations strictly validate arguments against Pydantic schema contracts prior to calling Core API endpoints. Out-of-

bounds parameters (e.g., negative parcel weight or malformed tracking tokens) trigger client-side validation errors without consuming backend resources. To permanently eliminate hallucinations, system instructions forbid the model from predicting delivery dates or courier names without explicit, verified tool output data.

3. Deterministic Mock Fallback (TEST_MODE=true): To insulate automated CI pipelines and local developers from external third-party LLM outages (OpenAI, NVIDIA NIM) or rate-limit saturation, the service features an automated mock provider that serves deterministic JSON responses matching live API contracts.

13.7 Comprehensive Testing Strategy & Acceptance Criteria

Pytest suites in services/ai-assistant/tests/test_tools.py verify parameter schema validation, assert that invalid tracking numbers return clean JSON errors, and test prompt injection defenses against 50 adversarial attack vectors with a 100% defense rate.

A.A.P.R. Jayathilaka (234096J — Member 10) is additionally responsible for Cross-Workflow Quality, End-to-End System Verification, and Live Demo Readiness (Module 02). Figure 13.5 illustrates the comprehensive cross-workflow quality and end-to-end testing topology under Member 10 ownership, showcasing the automated test orchestrator, mock webhook receiver, RabbitMQ assertion harness, and live demo verification dashboard:




Figure 13.5: Cross-Workflow Quality & E2E Test Harness Architecture Topology

Figure 13.6 illustrates the Master Cross-Workflow Quality and Acceptance Testing Use Case Model (Module 02), governing all 39 automated E2E test journeys, mandatory enterprise acceptance criteria, chaos vulnerability injections, and live demo verification artifacts:




Figure 13.6: Cross-Workflow Quality & E2E Acceptance Testing Use Case Model

Figure 13.7 illustrates the transactional webhook failure, exponential backoff retries, and dead-letter queue routing sequence flow (SEQ-QA-04):




Figure 13.7: Webhook Transient Failure, Backoff Retries & Dead-Letter Queue Pipeline (SEQ-QA-04)

13.8 AI Safety Guardrails, Hallucination Mitigation & Operational Boundaries

To ensure that natural language interactions cannot compromise enterprise data integrity or invent fictional operational commitments, the Generative AI Assistant operates under strict architectural guardrails:

1. Hallucination Mitigation via Structured Tool Calling: Operational facts (parcel delivery milestones, tariff fees, and courier states) are never generated from free-text LLM completions. The model is constrained strictly to invoking approved FastMCP tools (get_parcel_status, estimate_delivery_fee). The tool output schemas are strictly validated by Pydantic v2 models before the LLM synthesizes natural language summaries.

2. Input Validation & Parameter Sanitization: FastMCP tool arguments undergo rigorous syntactic and semantic validation before dispatching Core API requests: tracking numbers must conform strictly to ^SD-[0-9]{8}-[A-Z0-9]{6}$, delivery zone identifiers are verified against registered zones, and package dimensions/weights are bounded to physical limits

(weight <= 30 kg, dimensions <= 150 cm). Malformed arguments and prompt injection strings are rejected immediately with descriptive error responses.

3. Strict Operational Prohibitions: In strict compliance with the architectural sandbox, the AI service operates under an immutable read-only contract: zero direct database connectivity (no database drivers or connection pools provisioned), zero state mutation endpoints (cannot book parcels, cancel orders, or modify courier assignments), zero shell or container command execution capabilities, and zero arbitrary external internet access.

13.9 Resiliency Patterns & Inter-Service Fallback Error Handling

The AI Assistant handles inter-service communication failures and upstream disruptions gracefully:

- Core API Unreachability: If the Core API monolith is unavailable or returns HTTP 503 during maintenance, the AI service intercepts the connection error and outputs a deterministic fallback message: 'The logistics core is temporarily unavailable for real-time status queries. Please check back shortly or access the public tracking portal directly.'
- Tool Execution Timeouts: All outbound HTTP requests dispatched to Core API endpoints enforce a strict 5-second timeout cap. If a query times out, the assistant terminates the call cleanly rather than hanging user conversation threads.
- Upstream LLM Rate Limiting (HTTP 429): If external LLM API rate limits are exhausted, the assistant falls back to local heuristic intent matching or requests the user to retry after a short delay.

CHAPTER 14

COMPREHENSIVE ENTERPRISE DATA ARCHITECTURE & CANONICAL SCHEMAS

14.1 Master Entity Relationship Diagram (ERD) — Comprehensive 26-Table Relational Schema

Figure 14.1 depicts the master Entity Relationship Diagram (ERD) for SwiftDrop, defining the comprehensive 26-table relational data architecture modeling all 10 member domains:




Figure 14.1: Master Relational Entity-Relationship Diagram (26 Canonical Tables)

14.2 Database Normalization Analysis (3NF Compliance & Integrity Proof)

All relational schemas strictly satisfy Third Normal Form (3NF):

1. First Normal Form (1NF): All attributes contain strictly atomic, scalar values (UUIDs, integers, timestamps, text). Composite addresses are normalized or encapsulated as validated JSONB documents with schema check constraints.

2. Second Normal Form (2NF): All non-key attributes depend entirely on the primary key, eliminating partial dependencies. In user_roles, role permissions are factored into the roles table rather than duplicated.

3. Third Normal Form (3NF): Zero transitive dependencies exist. For example, couriers store current_zone_id rather than denormalizing zone names, city, or tariff rates, guaranteeing that zone configuration changes propagate consistently.

14.3 Full Table Data Dictionary, Primary Keys, Foreign Keys & Indices

Table 14.1 documents the authoritative 26-table relational data dictionary:

Table 14.1: Comprehensive Relational Table Specifications & Key Constraints

Table Name	Primary Key	Foreign Keys & Target	Key Columns & Data Types	Critical Indexes
users	`id (UUID)`	None	email (VARCHAR(255) UNIQ), password_hash (TEXT), role (VARCHAR(50)), tenant_id (VARCHAR(100)), display_name (VARCHAR(255)), phone (VARCHAR(50)), status (VARCHAR(32)), created_at (TIMESTAMPTZ), updated_at (TIMESTAMPTZ)	UNIQUE(email), idx_users_tenant(tenant_id)
roles	`id (VARCHAR(50))`	None	description (TEXT), created_at (TIMESTAMPTZ)	PRIMARY KEY(id)
user_roles	(user_id, role_id)	user_id -> users, role_id -> roles	Composite PK	idx_user_roles(user_id, role_id)
oauth_identities	`id (UUID)`	user_id -> users.id	provider (VARCHAR(32)), provider_subject (VARCHAR(255)), email (VARCHAR(255))	UNIQUE(provider, provider_subject)

Table Name	Primary Key	Foreign Keys & Target	Key Columns & Data Types	Critical Indexes
refresh_tokens	id (UUID)	user_id -> users.id	token_hash (VARCHAR(255) UNIQ), family_id (VARCHAR(100)), is_revoked (BOOL), expires_at (TIMESTAMPTZ), created_at (TIMESTAMPTZ)	idx_refresh_family(family_id)
delivery_zones	id (VARCHAR(32))	None	code (VARCHAR(32) UNIQ), name (VARCHAR(128)), base_surcharge_cents (BIGINT), currency (VARCHAR(3) DEFAULT 'LKR'), enabled (BOOL), boundary_polygon (JSONB)	UNIQUE(code), idx_zones_enabled(enabled)
zone_postal_codes	prefix (VARCHAR(10))	zone_id -> delivery_zones.id	zone_id (VARCHAR(32)), created_at (TIMESTAMPTZ)	PRIMARY KEY (prefix), idx_postal_zone(zone_id)
system_settings	key (VARCHAR(64))	None	value (JSONB), value_type (VARCHAR(32)), description (TEXT), updated_by (VARCHAR(32)), updated_at (TIMESTAMPTZ)	PRIMARY KEY (key)
pricing_rules	(id, version)	pickup_zone_id -> delivery_zones.id, destination_zone_id -> delivery_zones.id	weight_band_id (INT), min_weight_kg (NUMERIC(6,2)), max_weight_kg (NUMERIC(6,2)), fee_cents (BIGINT), currency (VARCHAR(3))	idx_pricing_lookup(pickup_zone_id, destination_zone_id, is_active)
pricing_quotes	id (UUID)	accepted_parcel_id -> parcels.id	pricing_rule_id, service_level, fee_cents (BIGINT), currency (VARCHAR(3)), input_snapshot (JSONB), expires_at (TIMESTAMPTZ)	idx_quotes_expiry(expires_at)

Table Name	Primary Key	Foreign Keys & Target	Key Columns & Data Types	Critical Indexes
parcels	`id (UUID)`	sender_id -> users.id, merchant_id -> merchants.id	tracking_number (VARCHAR(32) UNIQ), current_status (VARCHAR(32)), weight_kg (NUMERIC(6,2)), price_cents (BIGINT), currency (VARCHAR(3)), version (INT)	UNIQUE(tracking_number), idx_parcels_status(current_status)
parcel_status_history	`id (UUID)`	parcel_id -> parcels.id (ON DELETE RESTRICT), actor_id -> users.id	from_status, to_status, actor_role, reason_code, parcel_version (INT), occurred_at (TIMESTAMPTZ)	idx_history_parcel(parcel_id, occurred_at)
parcel_addresses	`id (UUID)`	parcel_id -> parcels.id (ON DELETE CASCADE)	address_type (VARCHAR(16)), recipient_name (VARCHAR(128)), street_line1 (VARCHAR(255)), city (VARCHAR(64)), postal_code (VARCHAR(16)), phone (VARCHAR(32))	idx_addresses_parcel(parcel_id)
couriers	`id (UUID)`	user_id -> users.id, zone_id -> delivery_zones.id	vehicle_type, license_plate (VARCHAR(32)), max_capacity_grams (INT), is_active (BOOL)	UNIQUE(user_id), idx_courier_zone(zone_id)
courier_assignments	`id (UUID)`	parcel_id -> parcels.id, courier_id -> couriers.id	status (VARCHAR(32)), assigned_by_user_id (UUID), assigned_at (TIMESTAMPTZ), completed_at (TIMESTAMPTZ)	UNIQUE(parcel_id), idx_assign_courier(courier_id)
delivery_attempts	`id (UUID)`	parcel_id -> parcels.id, courier_id -> couriers.id	attempt_number (INT CHECK 1..3), status, failure_reason, proof_photo_url, signature_url, attempted_at	idx_attempt_parcel(parcel_id)
merchants	`id (UUID)`	user_id -> users.id	business_name (VARCHAR(255)), registration_number (VARCHAR(64) UNIQ), status (VARCHAR(32)), contact_email (VARCHAR(255))	UNIQUE(user_id), UNIQUE(registration_number)

Table Name	Primary Key	Foreign Keys & Target	Key Columns & Data Types	Critical Indexes
merchant_api_credentials	`id (UUID)`	merchant_id -> merchants.id	key_prefix (VARCHAR(16)), key_hash (VARCHAR(64) UNIQ), is_active (BOOL), expires_at (TIMESTAMPTZ)	idx_api_keys_lookup(key_prefix, is_active)
webhook_endpoints	`id (UUID)`	merchant_id -> merchants.id	url (TEXT), secret_ciphertext (BYTEA), secret_key_version (INT), secret_last4 (VARCHAR(4)), subscribed_event_types (TEXT[]), enabled (BOOL), created_by (UUID), deleted_at (TIMESTAMPTZ), created_at (TIMESTAMPTZ), updated_at (TIMESTAMPTZ)	idx_webhooks_merchant (merchant_id)
outbox_events	`id (UUID)`	None	producer (VARCHAR(64) DEFAULT 'core-api'), occurred_at (TIMESTAMPTZ), correlation_id (VARCHAR(128)), aggregate_type (VARCHAR(64)), aggregate_id (UUID), aggregate_version (INT >= 1), event_type (VARCHAR(128)), schema_version (VARCHAR(16) DEFAULT '1.0.0'), payload (JSONB), status (VARCHAR(32) CHECK (status IN ('PENDING','PUBLISHED','FAILED'))), attempt_count (INT), next_attempt_at (TIMESTAMPTZ), last_error (TEXT), created_at (TIMESTAMPTZ), published_at (TIMESTAMPTZ)	idx_outbox_pending(created_at ASC) WHERE status='PENDING'
processed_events	(consumer_name, event_id)	None	consumer_name (VARCHAR(64)), event_id (UUID), processed_at (TIMESTAMPTZ DEFAULT NOW())	PRIMARY KEY (consumer_name, event_id), idx_processed_events_time(processed_at)

Table Name	Primary Key	Foreign Keys & Target	Key Columns & Data Types	Critical Indexes
notification_deliveries	`id (UUID)`	None (no FK to outbox_events; outbox purged at 7d, deliveries at 30d)	event_id (UUID), recipient (VARCHAR(255)), channel (VARCHAR(32) CHECK (channel IN ('EMAIL','SMS'))), template_name (VARCHAR(64)), status (VARCHAR(32) CHECK (status IN ('PENDING','IN_PROGRESS','SUCCESS','FAILED'))), attempt_count (INT), next_attempt_at (TIMESTAMPTZ), lease_expires_at (TIMESTAMPTZ), provider_message_id (VARCHAR(255)), last_error (TEXT), event_type (VARCHAR(128)), aggregate_id (UUID), aggregate_version (INT), payload (JSONB), created_at (TIMESTAMPTZ), delivered_at (TIMESTAMPTZ)	UNIQUE(event_id, channel, recipient), idx_notify_status(status)
webhook_deliveries	`id (UUID)`	endpoint_id -> webhook_endpoints.id ON DELETE RESTRICT	event_id (UUID), status (VARCHAR(32) CHECK (status IN ('PENDING','IN_PROGRESS','SUCCESS','FAILED'))), attempt_count (INT), next_attempt_at (TIMESTAMPTZ), lease_expires_at (TIMESTAMPTZ), response_status_code (INT), response_body_snippet (VARCHAR(500)), last_error (TEXT), event_type (VARCHAR(128)), aggregate_id (UUID), aggregate_version (INT), occurred_at (TIMESTAMPTZ), payload (JSONB), created_at (TIMESTAMPTZ), delivered_at (TIMESTAMPTZ)	UNIQUE(endpoint_id, event_id), idx_wh_deliveries_pending(status, next_attempt_at)

Table Name	Primary Key	Foreign Keys & Target	Key Columns & Data Types	Critical Indexes
webhook_delivery_attempts	`id (UUID)`	delivery_id -> webhook_deliveries.id ON DELETE CASCADE	attempt_no (INT), started_at (TIMESTAMPTZ), response_status_code (INT), response_body_snippet (VARCHAR(500)), error_class (VARCHAR(64)), error_message (TEXT), next_attempt_at (TIMESTAMPTZ), created_at (TIMESTAMPTZ)	idx_wh_attempts_delivery(delivery_id)
idempotency_keys	(caller_hash, idempotency_key)	None	request_hash (VARCHAR(64)), status_code (INT), response_payload (JSONB), expires_at (TIMESTAMPTZ)	PRIMARY KEY (caller_hash, idempotency_key), idx_idempotency_expiry (expires_at)
audit_logs	`id (UUID)`	None	actor_id (VARCHAR(64)), actor_role (VARCHAR(32)), action (VARCHAR(64)), target_type (VARCHAR(64)), target_id (VARCHAR(64)), previous_state (JSONB), new_state (JSONB), client_ip (VARCHAR(45)), request_id (VARCHAR(64)), created_at (TIMESTAMPTZ)	PRIMARY KEY (id), idx_audit_actor(actor_id), idx_audit_time(created_at)

14.4 Canonical 11-Step Sequential Database Migration Plan (000001 through 000011)

Migration steps 1–11 are the logical dependency order. In the repository all migrations live in core-api/migrations/ and use timestamped filenames, because the embedded migrator sorts by filename. Steps 8 and 9 are 20261101000050_create_outbox_events and 20261101000500_create_worker_dedup_and_webhooks. services/messaging contains no migrations.

1. 000001_create_users_and_roles: Establishes users, roles, user_roles, and oauth_identities tables.

2. 000002_create_delivery_zones: Establishes operational delivery zones (delivery_zones), postal code prefix mappings (zone_postal_codes), and runtime configuration toggles (system_settings).

3. 000003_create_merchants_and_credentials: Creates merchants, merchant_api_credentials, and webhook_endpoints tables.

4. 000004_create_pricing_rules: Creates dynamic zone-pair tariff calculation rules and fee matrixes in BIGINT cents.

5. 000005_create_parcels_and_quotes: Creates parcels, immutable parcel_status_history audit table (ON DELETE RESTRICT), and expiring pricing_quotes cache.

6. 000006_create_couriers: Creates courier fleet profiles and vehicle capacity thresholds.

7. 000007_create_dispatch_and_delivery: Creates courier_assignments and delivery_attempts audit tables.

8. 20261101000050_create_outbox_events (logical step 8): Creates the transactional outbox table (outbox_events) with partial indexing on PENDING status (created_at ASC) and lease retry metadata.

9. 20261101000500_create_worker_dedup_and_webhooks (logical step 9): Creates consumer message deduplication table (processed_events), notification delivery registry (notification_deliveries), and webhook dispatch tracking tables (webhook_deliveries, webhook_delivery_attempts).

10. 000010_create_idempotency_keys: Creates client idempotency cache table (idempotency_keys) with request body SHA-256 hashing and 24-hour expiration.

11. 000011_create_audit_logs: Creates immutable system-wide security and administrative audit event logs.

Figure 14.2 illustrates the canonical sequential database migration dependency chain across the modular monolith modules, showing how migrations 000001 through 000011 execute sequentially to maintain foreign key integrity across bounded contexts without cyclic dependencies.




Figure 14.2: Canonical Sequential Database Migration Dependency Chain (Migrations 000001 through 000011)

14.5 Technical Justifications: Relational Modeling Decisions & Key Constraints

The data architecture incorporates three foundational persistence decisions designed to preserve transactional integrity and long-term legal compliance:

1. UUIDv4 & UUIDv7 Primary Identifiers vs. Sequential BIGINT: Adopting 128-bit cryptographically secure UUIDs (UUIDv4 for entity identities and time-ordered UUIDv7 for outbox events) permanently eliminates enumeration and IDOR scraping vulnerabilities (attackers cannot guess subsequent parcel URLs by incrementing IDs). Furthermore, UUIDs prevent business intelligence leakage, ensuring competitors cannot infer daily parcel shipment volumes from consecutive database sequence gaps. Distributed UUID generation allows application servers to mint primary keys in-memory before committing transactions, eliminating database sequence locks during high-volume parcel ingestion.

2. Point-in-Time Address Immutability (parcel_addresses Table & Snapshot Isolation): When a parcel is booked, delivery addresses are persisted into the immutable parcel_addresses table (linked via parcel_id with ON DELETE CASCADE) and captured as a point-in-time JSONB snapshot on the parcel aggregate. Normalizing delivery addresses into a mutable customer profile table would mean that if a customer updates their residential address next month, previously delivered or in-transit waybill records would retroactively mutate. Dedicated immutable address records guarantee legal non-repudiation, courier route proof, and insurance audit validity.

3. High-Performance Partial B-Tree Indexing on Transactional Outbox: To ensure the Outbox Relay poller queries unpublished events in sub-millisecond time, SwiftDrop implements a partial B-Tree index: CREATE INDEX idx_outbox_pending ON outbox_events(created_at ASC) WHERE status = 'PENDING'. This partial index excludes the millions of historical PUBLISHED records, maintaining an ultra-compact memory footprint in PostgreSQL buffer cache and eliminating full-table sequential scans.

CHAPTER 15

SOFTWARE DESIGN PATTERNS & ENGINEERING PRINCIPLES

15.1 SOLID Principles Applied in Go Backend & TypeScript Frontend

SwiftDrop enforces the five SOLID software engineering principles across both backend Go and frontend TypeScript codebases:

1. Single Responsibility Principle (SRP): Each Go struct and TypeScript component possesses a single reason to change. In the Identity subsystem, Hasher solely hashes passwords, TokenProvider solely mints JWTs, and AuthService coordinates transactions without directly generating crypto tokens.

2. Open/Closed Principle (OCP): The pricing subsystem is open for extension but closed for modification. New tariff formulas (e.g. holiday surge pricing) implement the PriceCalculator interface without modifying existing parcel booking code.

3. Liskov Substitution Principle (LSP): Repository port interfaces (e.g. UserRepository) can be substituted transparently with PostgreSQL pgx implementations or in-memory mock implementations in unit tests without altering use case behavior.

4. Interface Segregation Principle (ISP): Go interfaces are kept small and focused (e.g. events.OutboxWriter exposing solely Write(ctx, tx *sql.Tx, envelopes ...AnyEnvelope) error). Handlers do not depend on massive god-interfaces.

5. Dependency Inversion Principle (DIP): High-level domain use cases depend strictly on abstract port interfaces, never on low-level technical drivers (database/sql, net/http, or AWS S3 clients).

15.2 Gang of Four (GoF) Structural & Behavioral Patterns

The platform leverages foundational Gang of Four design patterns:

1. Strategy Pattern (Specified): Applied in internal/pricing/ to interchange distance-based, dimensional, and merchant-discount pricing algorithms dynamically at runtime without altering booking workflows.

2. Observer Pattern: Applied via RabbitMQ topic exchange pub/sub and in services/tracking/ where parcel status transitions broadcast to Redis Pub/Sub channels and push real-time events to active browser SSE listeners.

3. Factory Pattern (Specified): Applied in internal/parcels/domain/parcel.go (NewParcel(...)) to enforce that valid parcels cannot be instantiated with negative weights, missing zones, or invalid addresses.

4. Adapter Pattern: Applied in infrastructure layers to adapt concrete technical drivers—such as the Salted SHA-256 hasher, JWT token provider, PostgreSQL pgx/sql repositories, SMTP mailer, and AMQP RabbitMQ publisher—into pure domain port abstractions.

15.3 Enterprise Application Patterns

The architecture incorporates high-reliability enterprise application patterns:

1. Transactional Outbox Pattern: Solves the dual-write problem by atomically committing business state and outbox events in a single PostgreSQL transaction.

2. Repository & Unit of Work Pattern (platform/db.WithTx): Abstracts relational SQL queries behind clean Go domain repository ports, while platform/db.WithTx encapsulates atomic database transaction lifecycles, ensuring aggregate updates, status history logs, and outbox rows commit or roll back as an indivisible unit.

3. Idempotency Key Pattern: Clients supply unique Idempotency-Key headers on mutating requests, preventing duplicate billing or double parcel bookings under transient network retries.

4. Idempotent Consumer & Dead Letter Channel Patterns: Applied in services/messaging where consumers record processed message identifiers atomically in processed_events (consumer_name, event_id) before executing side effects. Poison messages failing schema validation are rejected via basic.nack(requeue=false) routing directly into the dead-letter exchange swiftdrop.dlq without blocking worker thread execution.

CHAPTER 16

SYSTEM-WIDE SECURITY ARCHITECTURE, THREAT MODELING & PRIVACY

16.1 STRIDE Threat Modeling Analysis Matrix

Table 16.1 documents the formal STRIDE threat modeling analysis and architectural countermeasures implemented across SwiftDrop:

Table 16.1: STRIDE Threat Analysis & Architectural Mitigations Matrix

Threat Category	Attack Vector & Scenario	Impact Severity	Architectural Countermeasure Implemented
Spoofing	Attacker forges JWT claims or impersonates another user or merchant.	Critical	HS256/RS256 cryptographic signature validation with secret rotation; HS256/RS256 cryptographic signature validation with secret rotation; SHA-256 (Phase 1) password hashing with planned migration to Argon2id (TD-SEC-01 transparent rehashing on login).
Tampering	Attacker intercepts webhook payloads or alters parcel delivery status in transit.	High	TLS 1.3 encryption on all ingress; HMAC-SHA256 signature headers on outbound webhooks; AES-256-GCM encryption for stored webhook secrets with endpoint ID AAD; aggregate root FSM validation.
Repudiation	Courier denies delivering package or claims customer was unavailable falsely.	High	Cryptographic proof-of-delivery photos uploaded via S3 pre-signed URLs; immutable GPS timestamped parcel_status_history.
Information Disclosure & SSRF	Public tracking queries expose customer phone numbers; malicious merchant webhook URLs trigger SSRF against internal cluster metadata.	Critical	Public Tracking Projection masks addresses to city level and strips recipient PII; Webhook Dispatcher enforces strict pre-dial SSRF DNS validation (net.Dialer.Control rejecting RFC1918, loopback, link-local, and 169.254.169.254 on every delivery attempt); recipient email header injection defense strips CRLF sequences.
Denial of Service	Distributed HTTP flood exhausts database connection pools during peak dispatch hours.	High	Traefik Edge Token Bucket Rate Limiting (5 req/min burst 3 on login, 120 req/min burst 20 on merchant API, 30 req/min burst 10 on tracking, 10 req/min burst 2 on AI, max 5 open streams per IP); read-heavy tracking decoupled to SSE microservice.

Threat Category	Attack Vector & Scenario	Impact Severity	Architectural Countermeasure Implemented
Elevation of Privilege	Customer alters role claim in JWT to gain Dispatcher or Admin privileges.	Critical	Server-side RBAC middleware validates verified token claims; user_roles table is authoritative on token issuance.

16.2 Centralized Role-Based Access Control (RBAC) Permission Matrix

Table 16.2 specifies the centralized RBAC endpoint authorization matrix across all system subsystems:

Table 16.2: Centralized RBAC Endpoint Authorization Matrix

API Resource Endpoint	Method	Anonymous Public	Customer	Merchant	Courier	Dispatcher	Admin
`/api/v1/auth/login`	POST	**ALLOW**	**ALLOW**	**ALLOW**	**ALLOW**	**ALLOW**	**ALLOW**
`/api/v1/auth/me`	GET	**DENY**	**ALLOW**	**ALLOW**	**ALLOW**	**ALLOW**	**ALLOW**
`/api/v1/quotes`	POST	**DENY**	**ALLOW**	**ALLOW**	**DENY**	**ALLOW**	**ALLOW**
`/api/v1/parcels`	POST	**DENY**	ALLOW (Own)	ALLOW (Own)	**DENY**	**ALLOW**	**ALLOW**
`/api/v1/parcels/{id}`	GET	**DENY**	ALLOW (Own)	ALLOW (Own)	ALLOW (Assigned)	**ALLOW**	**ALLOW**
`/api/v1/dispatch/assignments`	POST	**DENY**	**DENY**	**DENY**	**DENY**	**ALLOW**	**ALLOW**
`/api/v1/courier/parcels`	GET	**DENY**	**DENY**	**DENY**	ALLOW (Own)	**ALLOW**	**ALLOW**
`/api/v1/courier/shift`	POST	**DENY**	**DENY**	**DENY**	ALLOW (Own)	**DENY**	**ALLOW**

API Resource Endpoint	Method	Anonymous Public	Customer	Merchant	Courier	Dispatcher	Admin
`/api/v1/deliveries/{id}/proof-photo`	POST	**DENY**	**DENY**	**DENY**	ALLOW (Assigned)	**DENY**	**ALLOW**
`/api/v1/deliveries/{id}/complete`	POST	**DENY**	**DENY**	**DENY**	ALLOW (Assigned)	**DENY**	**ALLOW**
`/api/v1/deliveries/{id}/failed`	POST	**DENY**	**DENY**	**DENY**	ALLOW (Assigned)	**DENY**	**ALLOW**
`/api/v1/merchants/api-keys`	POST	**DENY**	**DENY**	ALLOW (Own)	**DENY**	**DENY**	**ALLOW**
`/api/v1/zones`	GET	**ALLOW**	**ALLOW**	**ALLOW**	**ALLOW**	**ALLOW**	**ALLOW**
`/api/v1/admin/zones`	GET, POST, PUT, DELETE	**DENY**	**DENY**	**DENY**	**DENY**	ALLOW (GET)	**ALLOW**
`/api/v1/admin/pricing-rules`	GET, POST, PUT	**DENY**	**DENY**	**DENY**	**DENY**	**DENY**	**ALLOW**
`/api/v1/admin/settings`	GET, PUT	**DENY**	**DENY**	**DENY**	**DENY**	**DENY**	**ALLOW**
`/api/v1/admin/audit-logs`	GET	**DENY**	**DENY**	**DENY**	**DENY**	**DENY**	**ALLOW**
`/api/v1/admin/reports/deliveries`	GET	**DENY**	**DENY**	**DENY**	**DENY**	**ALLOW**	**ALLOW**
`/api/v1/admin/merchants/{id}/approve`	POST	**DENY**	**DENY**	**DENY**	**DENY**	**DENY**	**ALLOW**
`/api/v1/tracking/public/{number}`	GET	**ALLOW**	**ALLOW**	**ALLOW**	**ALLOW**	**ALLOW**	**ALLOW**
`/api/v1/tracking/public/{number}/stream`	GET	**ALLOW**	**ALLOW**	**ALLOW**	**ALLOW**	**ALLOW**	**ALLOW**

16.3 Tenant Isolation & Cross-Account Object Protection (IDOR Prevention)

Insecure Direct Object Reference (IDOR) attacks are eliminated by scoping all queries with the authenticated caller's tenant_id and user_id. For merchant endpoints, the core API resolves tenant_id as a merchant UUID and returns HTTP 404 Not Found for any records belonging to foreign tenants (note: in Phase 1 mock accounts, seeded tenant_id strings such as mrc_... are normalized to merchant UUIDs in production migrations). An authenticated Customer querying a parcel belonging to another customer receives HTTP 404 Not Found, permanently preventing cross-tenant data leaks.

16.4 Data Protection & PII Compliance

Customer telephone numbers, recipient names, and physical street addresses are classified as sensitive PII governed by the Sri Lanka Personal Data Protection Act (PDPA), No. 9 of 2022 and international privacy standards (GDPR). Defensive measures include: (1) TLS 1.3 encryption in transit across all edges; (2) public tracking milestone projection masking addresses to city level and stripping all recipient phone numbers; (3) structured application logging redaction (customer email addresses masked as b***@domain and passwords/tokens completely omitted); (4) outbound webhook sanitization stripping recipient contact info (the notify payload block) before dispatch; and (5) session cookie hardening using HttpOnly, SameSite=Strict, and Secure flags (enforced in production HTTPS deployments).

CHAPTER 17

INITIAL CODEBASE VERIFICATION & AUTHENTICATION IMPLEMENTATION

17.1 Milestone Status Overview: Monolith Baseline & Working Authentication

In accordance with the Release v1.0 engineering baseline, the engineering team has delivered the initial operational codebase. This milestone establishes the Go Modular Monolith project wiring (core-api/cmd/api/main.go), canonical PostgreSQL database migrations (000001 through 000011), the core Identity & Access Management authentication logic with pre-seeded credentials, reusable RBAC authorization middleware, and an interactive demonstration frontend prototype.

It is important to state the precise operational scope of this milestone: the working authentication subsystem currently implements simple credential-based login using pre-seeded user accounts with Role-Based Access Control (RBAC) capabilities. Advanced identity workflows—such as self-service customer registration (POST /api/v1/auth/register), federated Google OAuth 2.0 / OpenID Connect (OIDC) callback exchange, and self-service password reset flows—represent formal architectural specifications designed in Chapter 4 and scheduled for implementation in subsequent delivery phases.

17.2 Backend Identity Module Architecture & Code Artifacts

17.2.1 Database Schema Migration: 000001_create_users_and_roles.up.sql

The migration defines the users and refresh_tokens tables, establishing 128-bit UUID primary keys for users, tenant_id VARCHAR(100) indexed to support merchant tenant isolation (e.g. mrc_...), canonical role validation (ADMIN, DISPATCHER, COURIER, MERCHANT, CUSTOMER), and an append-only refresh token ledger (family_id). Database migrations execute inside atomic transactions managed by an embedded Go migrator (embed.FS) tracking versioning in schema_migrations.

17.2.2 Password Security, Prototype Key Stretching & Argon2id Migration Strategy

Implemented in internal/identity/infrastructure/, the Phase 1 prototype protects credentials using 16 bytes of cryptographically secure pseudo-random salt generated via crypto/rand and subjected to iterative key stretching across 10,000 rounds of SHA-256. Passwords are saved in PostgreSQL in the canonical format sdsha256$<salt_hex>$<hash_hex> with 10,000 iterations fixed in code. Verification executes in constant CPU clock cycles via crypto/subtle.ConstantTimeCompare(), completely neutralizing side-channel timing attacks.

To resolve cryptographic technical debt (TD-SEC-01) and attain strict OWASP/NIST compliance, the identity module specifies the pure Go Argon2id adapter (golang.org/x/crypto/argon2) configured with memory-hard parameters: m=65,536 KiB (64 MB), iterations t=3, parallelism p=4, 16-byte salt, and 32-byte key. The AuthService incorporates a transparent dual-verifier migration pipeline: during login, the service detects whether the stored hash begins with $argon2id$; if a legacy SHA-256 hash is detected and verified, the service immediately computes the Argon2id hash and atomically updates users.password_hash in PostgreSQL within the same request lifecycle. This guarantees a seamless, zero-downtime migration to state-of-the-art memory-hard hashing without disrupting active users.

17.2.3 Dual-Token Architecture: In-Memory Access JWT & HttpOnly Refresh Cookies

The authentication subsystem implements a strict dual-token lifecycle. The short-lived 15-minute Access Token (JWT, signed with HMAC-SHA256 using server secret JWT_SECRET) embeds verified claims (sub, role, tenant_id, jti, iat, exp) and resides strictly in application memory (React Context state) transmitted via Authorization: Bearer <token>, preventing script-based XSS theft. The 7-day Refresh Token is delivered via a Secure, HttpOnly, SameSite=Strict cookie scoped to /api/v1/auth. PostgreSQL tracks refresh tokens under a family_id; upon refresh, the token is revoked and rotated. Presentation of an already revoked token triggers immediate family invalidation, preventing session hijacking.

17.2.4 Reusable RBAC Authorization Middleware in Go

Implemented in internal/identity/transport/, the middleware layer intercepts incoming HTTP requests: Authenticate verifies Bearer JWT signatures, claims, and active status (user.IsActive()), injecting *domain.User and TenantID into request context.Context; RequireRole(...roles) validates caller roles, halting unauthorized access with HTTP 403

Forbidden; and RequireTenant enforces merchant data isolation. Context helper functions (transport.GetUser(ctx) and transport.GetTenantID(ctx)) provide clean retrieval for downstream service handlers.

17.3 Operational Authentication Verification & Multi-Role Demonstration Frontend

The functional implementation of the authentication subsystem in the current codebase release is specifically scoped to a simple login workflow utilizing pre-seeded credentials with Role-Based Access Control (RBAC) capabilities. The backend identity module (core-api/internal/identity/) verifies submitted credentials against pre-seeded database accounts using Salted SHA-256 password hashing with 10,000 iterative key-stretching rounds and constant-time verification (crypto/subtle.ConstantTimeCompare), issues signed JWT access tokens embedding the user's authoritative role and tenant_id claims, and enforces role boundaries via reusable Go HTTP middleware.

Architectural Alignment Note: The architectural diagrams in Chapter 4 (Figures 4.2 and 4.3) specify the abstract Ports and Adapters boundaries and theoretical design baseline. In the operational Release v1.0 codebase, the PasswordHasher port is concretely realized via Salted SHA-256 with 10,000 iterative key-stretching rounds and constant-time verification (crypto/subtle.ConstantTimeCompare), and the TokenProvider port is realized via symmetric HMAC-SHA256 (HS256) with a 256-bit server secret. This provides optimal memory and CPU throughput within the monolithic Go runtime while preserving strict interface boundaries for future microservice decoupling.

To visually demonstrate that this simple login logic and RBAC routing operate reliably end-to-end, the engineering team constructed an interactive demonstration frontend prototype (React + TypeScript). This frontend is not the final consumer production outcome; rather, it serves as an operational demonstration harness designed to verify credential submission, token issuance, and dynamic role-based view routing using the pre-seeded evaluation accounts.

Figure 17.1 illustrates the unified authentication sign-in portal constructed for the demonstration interface, featuring the credential login form (along with visual layout placeholders for future OIDC integration):




Figure 17.1: SwiftDrop Unified Authentication Portal (Demonstration Prototype Login Screen)

Upon submitting valid pre-seeded credentials, the backend validates the email and password hash, generates a 15-minute access token embedding the user's authoritative role and tenant_id claims, and sets an HttpOnly refresh cookie. The demonstration client application decodes the token payload and automatically routes the authenticated user to their role-specific operational dashboard.

Figure 17.2 demonstrates successful administrative authentication and governance access for the pre-seeded System Administrator account (admin@swiftdrop.local), presenting the Administrator Operations & Governance Console:




Figure 17.2: Administrator Operations & Governance Console (Role: ADMIN — RBAC Demonstration)

As depicted in Figure 17.2, the Admin Console provides system-wide operational governance, displaying illustrative mock demonstration data generated for frontend interface layout testing

(including simulated synthetic metrics such as 1,428 registered accounts, 14 delivery zones, and illustrative uptime telemetry). The console provides Delivery Zones & System Settings configuration (defining operational delivery zones with postal code prefix mappings in zone_postal_codes, system runtime toggles, and delivery reporting; fee evaluation logic is strictly governed by Member 2's pricing rules). Centralized user account directory administration is scheduled for implementation under the Platform Governance Roadmap (jointly assigned to Member 1 and Member 7).

Figure 17.3 demonstrates successful authentication and RBAC routing for the pre-seeded Regional Dispatcher account (dispatcher@swiftdrop.local), presenting the Central Dispatch & Courier Operations Board:




Figure 17.3: Central Dispatcher Operations Console (Role: DISPATCHER — RBAC Demonstration)

As shown in Figure 17.3, the Dispatcher Console displays illustrative mock operational metrics, including an unassigned parcel queue (3 bookings), active courier fleet roster, and high-level delivery milestone counters (84 in-transit parcels, 210 completed drops) designed to verify responsive cockpit view layouts.

Figure 17.4 demonstrates the mobile-responsive driver workflow when authenticated under the pre-seeded Field Courier account (courier@swiftdrop.local):




Figure 17.4: Courier Mobile Driver Route & POD Console (Role: COURIER — RBAC Demonstration)

As illustrated in Figure 17.4, the Courier Console restricts access exclusively to the courier's assigned delivery manifest, displaying active shift status (ON DUTY), stop-by-stop delivery run in Colombo 03–05, Cash on Delivery (COD) collection records, and action triggers for electronic Proof of Delivery (POD) capture and failed attempt logging.

Figure 17.5 demonstrates multi-tenant B2B isolation when authenticated under the pre-seeded Commercial Merchant account (merchant@vendor.com):




Figure 17.5: B2B Merchant Logistics & Shipping Console (Role: MERCHANT — Tenant Scoping Demonstration)

Figure 17.5 verifies that merchant tenant scoping is actively enforced by the backend (displaying Tenant ID mrc_01HMERCHANTTENANT00001). The console provides self-service bulk parcel ingestion via CSV drag-and-drop, monthly shipment analytics (842 parcels

shipped, 99.1% delivery success), B2B API secret key management, and webhook subscription event monitoring.

Figure 17.6 demonstrates customer-level self-service tracking when authenticated as the pre-seeded Retail Customer account (customer@swiftdrop.local):




Figure 17.6: Customer Self-Service Parcel Portal (Role: CUSTOMER — RBAC Demonstration)

As demonstrated in Figure 17.6, customer accounts receive a streamlined, self-service tracking view highlighting active shipments, real-time milestone progress (SD-20261030-99801 assigned to courier Kamal Perera), delivery history (14 completed deliveries), cumulative shipping expenditure (LKR 9,450), and saved delivery addresses.

17.4 Pre-Configured Test Accounts & Demo Scenario Runbook

Table 17.1 details the pre-configured test evaluation accounts seeded into the database for demonstration and grading verification:

[SECURITY NOTICE: The plaintext credentials listed in Table 17.1 are strictly provisioned for academic evaluation, local integration test execution, and grading demonstration in isolated test environments. These credentials are valid in the mock-storage fallback. With PostgreSQL, the seeded password hashes must be generated by StandardPasswordHasher before login succeeds. Production deployments strictly forbid pre-seeded default credentials; all administrative and operational accounts must undergo mandatory password rotation, multi-factor authentication enrollment, and credential vault ingestion prior to release.]

Table 17.1: Pre-Configured Evaluation Test Accounts & Role Credentials

Role Assigned	Pre-Seeded Email	Plaintext Password	Primary Demonstration Capabilities
System Administrator	admin@swiftdrop.local	AdminPassword123!	System-wide operational governance, delivery zone and postal code prefix management (zone_postal_codes), system settings, operational delivery reports, and security audit logs.
Regional Dispatcher	dispatcher@swiftdrop.local	Dispatcher123!	Central dispatch cockpit, unassigned parcel queue, courier fleet capacity matching, and live delivery metrics.
Field Courier	courier@swiftdrop.local	CourierPassword123!	Mobile driver manifest, daily delivery runs in Colombo, stop-by-stop route execution, and electronic Proof of Delivery (POD).
Commercial Merchant	merchant@vendor.com	Merchant123!	Multi-tenant logistics console (Tenant: mrc_01HMERCHANTTENANT00001), bulk parcel ingestion, B2B API keys, and webhook subscriptions.
Retail Customer	customer@swiftdrop.local	CustomerPassword123!	Customer self-service tracking portal, active shipment milestones, delivery history, and saved delivery addresses.

Table 17.2 provides an authoritative architectural cross-reference detailing the implementation status of every platform component, distinguishing operational Release v1.0 software from formal Phase 2 architectural specifications:

Table 17.2: Platform Component Implementation & Milestone Delivery Status Matrix

Platform Component & Directory	Primary Owner	Architectural Specification	Release v1.0 Implementation Status	Target Milestone Delivery
Core API Monolith Wiring (cmd/api/, internal/platform/)	Member 1 & 9	Designed & Verified	Operational Baseline: Single binary wiring, PostgreSQL pool, graceful shutdown, config parser.	Release v1.0 (Complete)
Identity, Auth & RBAC (internal/identity/)	Member 1 (Mihiranga)	Designed & Verified	Operational Prototype: Salted SHA-256 (10k rounds), dual-token JWT (HS256), RBAC middleware.	Sprint 3 (TD-SEC-01 Argon2id & OIDC)

Platform Component & Directory	Primary Owner	Architectural Specification	Release v1.0 Implementation Status	Target Milestone Delivery
Parcel Aggregate & State Machine (internal/parcels/)	Member 2 (Ashara)	Designed (Chapter 5)	Architectural Specification: Domain models, 9-state FSM, and booking invariants codified.	Sprint 1 (Milestone M1)
Dynamic Pricing & Tariffs (internal/pricing/)	Member 2 (Ashara)	Designed (Chapter 5)	Architectural Specification: Weight/dimension pricing formulas and 15-min signed quotes designed.	Sprint 1 (Milestone M1)
Dispatch & Advisory Locking (internal/dispatch/)	Member 3 (Atapattu)	Designed (Chapter 6)	Architectural Specification: Session-level advisory locking algorithms and fleet roster queries designed.	Sprint 2 (Milestone M2)
Delivery Execution & POD (internal/delivery/)	Member 3 (Atapattu)	Designed (Chapter 6)	Architectural Specification: 3-attempt failure semantics (ADR-004) and S3 photo contracts designed.	Sprint 2 (Milestone M2)
Merchant Integration & Webhooks (internal/merchants/)	Member 4 (Samarakkodi)	Designed (Chapter 7)	Architectural Specification: Tenant profiles, SHA-256 API key hashing, and HMAC signatures designed.	Sprint 2 (Milestone M2)
Real-Time Tracking SSE Service (services/tracking/)	Member 5 (Sulakma)	Designed (Chapter 8)	Architectural Specification: Standalone Go SSE service, Redis pub/sub, and PII masking pipeline.	Sprint 3 (Milestone M3)
Customer & Merchant Frontend (web/src/features/customer-merchant/)	Member 6 (Tharushika)	Designed & Verified	Demonstration Prototype: Role-based routing, customer dashboard, and merchant UI layout verified.	Sprint 1 & 2 (Milestones M1/M2)

Platform Component & Directory	Primary Owner	Architectural Specification	Release v1.0 Implementation Status	Target Milestone Delivery
Traefik Ingress Gateway (deploy/gateway/)	Member 7 (Bhagya)	Architectural Specification	Specified: Traefik v3 reverse proxy, 10 routers, multi-tier rate limits, header sanitization.	Sprint 4 (Milestone M4)
Admin Backend Module & Zones (internal/admin/)	Member 7 (Bhagya)	Architectural Specification	Specified: Zone postal prefix matching (zone_postal_codes), settings, reports, audit logs.	Sprint 4 (Milestone M4)
Transactional Outbox & Event Worker (internal/events/, services/messaging/)	Member 8 (Udithya)	Designed (Chapter 11)	Implemented: outbox library, relay, worker (email + webhooks), reconciler, ops API + Swagger hub, platform packages. Unit tests pass; Docker-based integration tests run with INTEGRATION=1. Remaining (Phase 2): integration with the producers (Members 2, 3, 4) and Kubernetes deployment.	Phase 2 (Integration & K8s)
DevOps, K3s Kubernetes & CI (deploy/, scripts/verify.sh)	Member 9 (Wakishta)	Designed & Verified	Operational Baseline: Distroless Dockerfiles, docker-compose 10-service stack, verify.sh pipeline.	Release v1.0 (Complete)
AI Assistant & Quality Harness (services/ai-assistant/, test harnesses)	Member 10 (Jayathilaka)	Architectural Specification	Specified: Python FastMCP service, read-only tools, mock fallback, test harnesses.	Sprint 4 (Milestone M4)

17.5 Automated Verification Results: Unit Tests, Integration Tests & Linters

Terminal test execution logs confirm passing test suites across all packages:

go test -v ./internal/identity/... executes with zero failures, asserting token issuance, invalid password rejection, and RBAC rejection. Unit tests in core-api/internal/events/... (go test -v ./internal/events/...) verify event envelope serialization, UUIDv7 generation, correlation_id propagation, and outbox schema validation. Services/messaging tests verify worker idempotency, HMAC signing, SSRF dialer filtering, and reconciler recovery.

CHAPTER 18

WORKLOAD ALLOCATION, MEMBER DELIVERABLES & CONTRIBUTION SHEETS

18.1 10-Member Capability-Based Division Philosophy

SwiftDrop partitions engineering responsibilities across 10 engineering domain leads based on functional capability ownership. This division guarantees strict domain isolation, clear bounded-context ownership, and rapid parallel engineering velocity.

18.2 Master Workload Allocation & Dependency Mapping Matrix

Table 18.1 outlines the primary domain assignments across all 10 members:

Table 18.1: Master 10-Member Capability Workload Allocation Matrix

Engineering Lead & Author	Primary Domain Capability	Owned Code Paths & Schemas	Key Deliverables for Release v1.0 Baseline
K.G.U. Mihiranga (234129P, Member 1)	Identity, Access & Security	internal/identity/, users, roles, user_roles	Operational credential login (Salted SHA-256 prototype baseline with TD-SEC-01 Argon2id migration path), JWT provider, RBAC middleware, and security unit tests.
W.H. Ashara (234023K, Member 2)	Parcel Management & Pricing	internal/parcels/, internal/pricing/, parcels, quotes	Parcel aggregate root, 9-state lifecycle FSM, dynamic pricing strategy, and booking validation.
K.S. Atapattu (234025T, Member 3)	Dispatch, Fleet & Delivery	internal/dispatch/, internal/delivery/, couriers	Dispatch board queries, advisory locks, ADR-004 delivery proof, and failure classification.
K.D.N.D. Samarakkodi (234185G, Member 4)	Merchant B2B Integration	internal/merchants/, merchants, merchant_api_keys	Merchant onboarding, SHA-256 API keys, HMAC-SHA256 webhook contracts, and tenant isolation.
B.G.S. Sulakma (234200C, Member 5)	Tracking API & Real-Time Updates	services/tracking/, Redis pub/sub	Standalone SSE tracking microservice, public tracking PII sanitization, and load verification.

Engineering Lead & Author	Primary Domain Capability	Owned Code Paths & Schemas	Key Deliverables for Release v1.0 Baseline
R.K.S. Tharushika (234204R, Member 6)	Customer & Merchant Frontend	web/src/features/customer-merchant/	React/TypeScript SPA, 4-step booking wizard, live SSE tracking view, and responsive design tokens.
M.A.P. Bhagya (235019L, Member 7)	Dispatcher/Admin Frontend & Gateway	deploy/gateway/, internal/admin/, web/src/features/dispatcher-admin/	Traefik API Gateway, multi-tier rate limiting, dispatcher fleet cockpit UI, courier mobile web manifest, and admin backend module (zones, settings, audit).
M.G.K.I. Udithya (234211K, Member 8)	Event-Driven Backend & Messaging	internal/events/, services/messaging/, outbox_events	Transactional Outbox Writer (Write method), Outbox Relay poller (singleton daemon), RabbitMQ topic exchange topology (swiftdrop.events.topic), idempotent Event Worker (processed_events), Reconciler tool, and swiftdrop.dlq dead-letter handling. Also delivered: ops/admin API (/api/v1/admin/events/*, /api/v1/merchant/webhook-deliveries*), Swagger hub (/swagger/), shared platform packages (internal/platform/db, httpx, middleware, config), and the cross-module integration test harness (core-api/tests).
M.D. Wakishta (234217J, Member 9)	DevOps, Kubernetes & Observability	deploy/, docker-compose.yaml, K3s manifests	Docker Compose 10-service stack, Kubernetes manifests, scripts/verify.sh CI, and Prometheus metrics.
A.A.P.R. Jayathilaka (234096J, Member 10)	AI Assistant & Cross-Workflow Quality	services/ai-assistant/, test harnesses	Python FastAPI AI service, MCP tool schemas, end-to-end integration tests, and demo scenarios.

18.3 Detailed Individual Contribution Sheets

1. Member 1: K.G.U. Mihiranga (Index: 234129P) — Identity, Access Control & Security: Authored Chapter 4 specification. Implemented the core-api/internal/identity/ module, including credential authentication (with Salted SHA-256 prototype baseline and TD-SEC-01

Argon2id target architecture), dual-token JWT provider, RBAC authorization middleware protecting all operational endpoints, and automated security test suites.

2. Member 2: W.H. Ashara (Index: 234023K) — Parcel Lifecycle Management & Dynamic Pricing: Authored Chapter 5 specification. Designed and implemented the Parcel aggregate root in core-api/internal/parcels/, the canonical 9-state lifecycle finite state machine, dynamic tariff calculation formulas, and 15-minute price quote generation.

3. Member 3: K.S. Atapattu (Index: 234025T) — Dispatch, Fleet Management & Proof-of-Delivery: Authored Chapter 6 specification. Implemented courier dispatch boards in core-api/internal/dispatch/ using PostgreSQL session-level advisory locks to eliminate double-assignment race conditions, and proof-of-delivery (POD) verification in core-api/internal/delivery/ conforming to ADR-004.

4. Member 4: K.D.N.D. Samarakkodi (Index: 234185G) — Merchant B2B Integration & Webhook Subsystem: Authored Chapter 7 specification. Implemented core-api/internal/merchants/ with merchant onboarding verification, SHA-256 API key issuance, outbound webhook subscriptions, and HMAC-SHA256 signature generation enforcing multi-tenant isolation.

5. Member 5: B.G.S. Sulakma (Index: 234200C) — Real-Time Tracking & Live Projection Subsystem: Authored Chapter 8 specification. Implemented the standalone read-optimized tracking microservice in services/tracking/ utilizing Server-Sent Events (SSE), Redis Pub/Sub, and public tracking PII sanitization in accordance with ADR-002.

6. Member 6: R.K.S. Tharushika (Index: 234204R) — Frontend User Experience & Client Web Portals: Authored Chapter 9 specification. Implemented the React 18 / TypeScript SPA in web/, including the 4-step parcel booking wizard, live SSE tracking viewer, customer dashboard, and merchant self-service management console.

7. Member 7: M.A.P. Bhagya (Index: 235019L) — Edge Ingress, API Gateway, Dispatcher/Admin Portal & Operations Module: Authored Chapter 10 specification. Implemented Traefik v3 API Gateway configurations in deploy/gateway/traefik/ (path-prefix routing, header sanitization, IP-based token bucket rate limiting: 5 RPM burst 3 on login, 120 RPM burst 20 on merchant API, 30 RPM burst 10 on tracking, 10 RPM burst 2 on AI, and 5 concurrent streams/IP), the Dispatcher Fleet Cockpit UI and Courier Mobile Web Manifest in web/src/features/dispatcher-admin/, and the core-api/internal/admin/ backend module

(delivery zones, postal code prefixes, runtime system settings, operational delivery reports, and immutable audit logs).

8. Member 8: M.G.K.I. Udithya (Index: 234211K) — Asynchronous Event-Driven Messaging & Transactional Outbox Subsystem: Authored Chapter 11 specification. Designed the Transactional Outbox pattern and Outbox Writer in core-api/internal/events/ (writer.go, repository.go), implemented the Outbox Relay poller daemon in services/messaging/cmd/relay and internal/relay, configured the RabbitMQ topic exchange topology (swiftdrop.events.topic), implemented the idempotent Event Worker in services/messaging/cmd/worker and internal/{consumer,notification,webhook,delivery}, authored the operational Reconciler tool (cmd/reconcile), and maintained migrations 000008 and 000009 across all 5 messaging and delivery tables. Also delivered: ops/admin API (/api/v1/admin/events/*, /api/v1/merchant/webhook-deliveries*), Swagger hub (/swagger/), shared platform packages (internal/platform/db, httpx, middleware, config), and the cross-module integration test harness (core-api/tests).

9. Member 9: M.D. Wakishta (Index: 234217J) — DevOps, Containerization & Cloud Infrastructure Platform: Authored Chapter 12 specification. Implemented multi-stage distroless Dockerfiles, docker-compose.yaml local orchestration, production Kubernetes (K3s) manifests with cgroup quotas, and the automated verification harness in scripts/verify.sh.

10. Member 10: A.A.P.R. Jayathilaka (Index: 234096J) — Generative AI Delivery Assistant & Cross-Workflow Quality Subsystem: Authored Chapter 13 specification. Implemented the Python/FastAPI AI Assistant service in services/ai-assistant/ using FastMCP with sandboxed read-only tool calling, and designed the cross-workflow quality and end-to-end integration test harness (Module 02).

18.4 Team Collaboration Cadence, Git Flow & Architecture Sign-Off

To coordinate parallel development across 10 engineering leads without architectural regression, the engineering team instituted a rigorous development governance protocol conforming to IEEE standards. The team adopted a Git Flow branching model where all feature work occurs on short-lived branches (feature/<member-id>-<capability>), requiring passing CI checks (scripts/verify.sh executing gofmt, golangci-lint, and unit tests) and mandatory peer review approvals from at least two domain leads before merging into the main integration branch.

Architectural boundaries and inter-service contracts were formally established through structured technical synchronization meetings. These sessions produced 13 binding Architectural Agreements (A1 through A13) and 12 coordinated Database Migration Decisions (D1 through D12) cataloged in docs/architecture/, ensuring clean foreign key sequences and zero circular schema dependencies across the modular monolith and independent services. Branch protection rules require passing CI verification (scripts/verify.sh) and CODEOWNERS review approvals before merging.

CHAPTER 19

ARCHITECTURAL EVALUATION, RISK REGISTER & FUTURE ROADMAP

19.1 Milestone Reflection & Architectural Invariants Preserved

The Release v1.0 milestone establishes the foundational architecture, canonical data schemas, and baseline security controls for the SwiftDrop logistics platform, delivering working authentication, RBAC authorization, and the transactional messaging pipeline while establishing clear architectural contracts for subsequent domain implementations. By enforcing domain invariants through aggregate roots, guaranteeing atomic state updates via single PostgreSQL transactions, and decoupling public read-heavy tracking streams from transactional writes, the design mitigates common distributed systems failure modes. However, maintaining architectural integrity through subsequent implementation phases requires vigilant management of the technical debt and delivery risks identified in this evaluation.

19.2 Risk Register & Technical Debt Ledger

Table 19.1 details identified project risks, current operational status, likelihood, severity, and architectural mitigations across the system lifecycle:

Table 19.1: Project Architectural Risk Register & Mitigation Strategy

Risk ID	Identified Risk Description	Probability	Severity	Status & Architectural Mitigation Strategy
RSK-01	Cryptographic Technical Debt in Prototype Password Hashing (TD-SEC-01).	Medium	High	In Progress: Salted SHA-256 (10,000 rounds) is sufficient for initial isolated testing but below OWASP production standards. Mitigated in Phase 2 Sprint 3 via transparent re-hashing to Argon2id upon user login.
RSK-02	Third-Party LLM Provider Latency & API Rate Limits.	High	Medium	Open / Planned: AI assistant relies on external cloud LLM inference (OpenAI/NVIDIA NIM), which may introduce high latency or transient rate-limiting (HTTP 429). Mitigated via local deterministic mock fallback (TEST_MODE=true), response caching, and client timeout caps (60 s).

Risk ID	Identified Risk Description	Probability	Severity	Status & Architectural Mitigation Strategy
RSK-03	External Identity Provider (Google OAuth/OIDC) Downtime.	Low	Medium	Open / Planned: Outage or API deprecation from Google Identity platform could prevent federated sign-in. Mitigated by retaining authoritative local email/password authentication as an independent, primary login mechanism.
RSK-04	Implementation Gap & Synchronization Drift Across 10 Team Members.	High	High	In Progress: With 10 developers concurrently implementing modular contexts, uncoordinated contract drift could break integration. Mitigated by mandatory living documentation (README.md, API.md), ADR governance, and automated CI verification (scripts/verify.sh).
RSK-05	Merchant Webhook Receiver Downtime Causing Message Bus Backlog.	Medium	Medium	Mitigated by design: Misconfigured or offline merchant receivers do not block message processing. Webhook retries are managed in PostgreSQL via webhook_deliveries with exponential backoff (0s, 30s, 2m, 10m, 30m with ±20% jitter) marking exhaustion as FAILED; poison AMQP broker messages route to swiftdrop.dlq via basic.nack(requeue=false).
RSK-06	Courier Double-Assignment Concurrency Race Conditions.	Medium	High	Mitigated by design: Simultaneous dispatchers assigning the same parcel could create conflicting assignments. Mitigated by session-level PostgreSQL Advisory Locks (pg_try_advisory_xact_lock) on parcel IDs.
RSK-07	Outbox Relay Polling Contention Under High-Volume Writes.	Low	Medium	Mitigated by design: Heavy concurrent parcel creation could cause row contention or duplicate publishing. Mitigated by strict singleton deployment of Outbox Relay (1 replica), batch leases with SKIP LOCKED, and publishing outside the database transaction.
RSK-08	Tracking SSE Service Memory Growth During Viral Tracking Spikes.	Medium	High	Mitigated by design: Thousands of concurrent browser SSE connections could exhaust API Gateway or core-api RAM. Mitigated by decoupling into a standalone Go tracking microservice that ingests q.tracking.updates from RabbitMQ and uses Redis Pub/Sub for inter-pod SSE connection broadcast.

19.3 Phase 2 Roadmap: Core Parcel Booking, Live Tracking & Outbox Relay

To transition the SwiftDrop platform from the verified Release v1.0 prototype baseline to a full production deployment, the engineering team has scheduled a structured, 4-Sprint Milestone Delivery Roadmap spanning 8 weeks of iterative development:

Sprint 1 (Weeks 1–2): Core Parcel Booking, Dynamic Pricing & Schema Expansion
- Primary Owners: Member 2 (Parcels & Pricing), Member 6 (Customer Web UI), Member 9 (Database Migrations).
- Objectives: Operationalize the Parcel aggregate root, implement the 9-state finite state machine (FSM), deploy the dynamic tariff calculation engine with 15-minute cryptographically signed quotes, and construct the 4-step customer booking wizard in React.
- Key Deliverables: Merged internal/parcels/ application use cases, migration scripts 000003 through 000005 executed in PostgreSQL, and passing unit test suites for dimension and weight boundary validation.

Sprint 2 (Weeks 3–4): Courier Dispatch Cockpit, Mobile Driver Manifest & Proof-of-Delivery
- Primary Owners: Member 3 (Dispatch & Delivery), Member 7 (Dispatcher Cockpit UI), Member 4 (Merchant B2B API).
- Objectives: Operationalize courier assignment with PostgreSQL session advisory locks, deliver the mobile driver manifest with stop-by-stop route navigation, implement ADR-004 delivery attempt failure classifications (max 3 attempts), and provide S3 pre-signed URL upload for electronic Proof of Delivery (POD) photos.
- Key Deliverables: Merged internal/dispatch/ and internal/delivery/ modules, courier mobile web manifest (PWA), merchant B2B API key provisioning, and automated concurrency race-condition tests.

Sprint 3 (Weeks 5–6): Asynchronous Outbox Relay, RabbitMQ Event Worker & Security Hardening (TD-SEC-01)
- Primary Owners: Member 8 (Messaging & Outbox), Member 1 (Identity & Security), Member 5 (Tracking SSE Service).
- Objectives: Activate asynchronous event publishing via the Outbox Relay poller (SELECT ... FOR UPDATE SKIP LOCKED), deploy RabbitMQ topic exchange topology and the idempotent Event Worker, decouple the read-heavy Tracking microservice with Redis Pub/Sub, and execute Technical Debt item TD-SEC-01 (transparent re-hashing to Argon2id

upon user authentication and federated Google OIDC verification).

- Key Deliverables: Deployable services/messaging/ and services/tracking/ containers, zero-downtime password migration pipeline, and SSE connection load tests verifying 1,000+ concurrent streams.

Sprint 4 (Weeks 7–8): AI Assistant Integration, End-to-End System Hardening & Live Production Staging

- Primary Owners: Member 10 (AI Assistant & QA Lead), Member 9 (DevOps & K3s Platform), All Members.
- Objectives: Connect the Python/FastAPI AI Assistant service to live Core API endpoints via FastMCP tool calling, execute the master 39-scenario automated cross-workflow integration test harness, provision staging infrastructure on a single Ubuntu VPS running K3s with Cloudflare edge ingress, and conduct final security and performance sign-offs.
- Key Deliverables: Passing E2E test runs across all business scenarios (customer booking to merchant webhook receipt), verified Traefik edge rate limiting, Grafana monitoring dashboards, and production readiness certification.

REFERENCES

[1] IEEE Computer Society, "IEEE Standard for Information Technology—Systems Design—Software Design Descriptions," IEEE Std 1016-2009, 2009.

[2] ISO/IEC/IEEE, "Systems and software engineering — Architecture description," ISO/IEC/IEEE 42010:2011, 2011.

[3] E. Evans, "Domain-Driven Design: Tackling Complexity in the Heart of Software," Addison-Wesley Professional, 2003.

[4] R. C. Martin, "Clean Architecture: A Craftsman's Guide to Software Structure and Design," Prentice Hall, 2017.

[5] G. Hohpe and B. Woolf, "Enterprise Integration Patterns: Designing, Building, and Deploying Messaging Solutions," Addison-Wesley, 2003.

[6] M. Fowler, "Patterns of Enterprise Application Architecture," Addison-Wesley, 2002.

[7] A. Biryukov, D. Dinu, and P. Khovratovich, "Argon2: New Generation of Memory-Hard Functions for Password Hashing and Other Applications," IEEE European Symposium on Security and Privacy (EuroS&P), 2016.

[8] M. Jones, J. Bradley, and N. Sakimura, "JSON Web Token (JWT)," RFC 7519, IETF, May 2015.

[9] D. Hardt, "The OAuth 2.0 Authorization Framework," RFC 6749, IETF, October 2012.

[10] SwiftDrop Engineering Team, "SwiftDrop Parcel Delivery & Courier Management System — Software Requirements Specification (SRS)," Version 1.0, docs/intial/SwiftDrop_SRS_v1.0.docx, Oct. 2026.

[11] SwiftDrop Architecture Board, "Architectural Decision Records (ADR-001 through ADR-004)," docs/architecture/, Oct. 2026.

[12] RabbitMQ Documentation, "AMQP 0-9-1 Model Explained, Topic Exchanges, and Dead Letter Exchanges," Broadcom Inc., 2024.

[13] PostgreSQL Global Development Group, "PostgreSQL 16 Documentation — Concurrency Control, Advisory Locks, and Partial Indexing," 2024.

[14] Parliament of the Democratic Socialist Republic of Sri Lanka, "Personal Data Protection Act, No. 9 of 2022," Certified on 19th March, 2022.

APPENDIX A: REST API ENDPOINT CONTRACTS & SPECIFICATION INDEX

Table A.1 serves as the master quick-reference index of all authoritative REST API contracts across the SwiftDrop modular monolith and dedicated microservices:

Table A.1: Master REST API Endpoint Contracts & Specification Index

Method & Path	Subsystem & Owner	Description	Required Role / Auth	Request Body / Parameters	Success Code	Error Status Codes
POST /api/v1/auth/register	Identity (Member 1)	Register retail customer account	Public	email, password, display_name, phone	201 Created	400 Bad Request, 409 Conflict
POST /api/v1/auth/login	Identity (Member 1)	Authenticate user credentials & issue JWT	Public (5 req/min)	email, password	200 OK	400 Bad Request, 401 Unauthorized, 429 Too Many Requests
POST /api/v1/auth/refresh	Identity (Member 1)	Rotate access token via refresh token	Public (Cookie)	None (HttpOnly cookie)	200 OK	401 Unauthorized
POST /api/v1/auth/logout	Identity (Member 1)	Revoke refresh token family	Authenticated	None	204 No Content	401 Unauthorized
POST /api/v1/pricing/quote	Pricing (Member 2)	Generate 15-minute guaranteed delivery tariff	Authenticated	pickup_zone_id, destination_zone_id, weight_kg, dimensions	201 Created	400 Bad Request, 422 Unprocessable Entity

Method & Path	Subsystem & Owner	Description	Required Role / Auth	Request Body / Parameters	Success Code	Error Status Codes
POST /api/v1/parcels	Parcels (Member 2)	Book parcel shipment with quote ID	ROLE_CUSTOMER / MERCHANT	quote_id, sender_address, recipient_address, service_level	201 Created	400 Bad Request, 409 Conflict (Idempotency)
GET /api/v1/parcels/{id}	Parcels (Member 2)	Retrieve parcel details and status	ROLE_CUSTOMER / MERCHANT	Parcel ID (UUID path)	200 OK	401 Unauthorized, 404 Not Found
POST /api/v1/parcels/{id}/cancel	Parcels (Member 2)	Cancel uncollected parcel shipment	ROLE_CUSTOMER / MERCHANT	Parcel ID (UUID path), reason	200 OK	400 Bad Request, 409 Conflict (Illegal State)
POST /api/v1/dispatch/assignments	Dispatch (Member 3)	Assign courier to parcel via advisory lock	ROLE_DISPATCHER	parcel_id, courier_id, zone_id	200 OK	400 Bad Request, 409 Conflict (Double Assignment)
GET /api/v1/courier/manifest	Dispatch (Member 3)	Retrieve daily delivery manifest	ROLE_COURIER	Courier ID (from JWT)	200 OK	401 Unauthorized, 403 Forbidden

Method & Path	Subsystem & Owner	Description	Required Role / Auth	Request Body / Parameters	Success Code	Error Status Codes
POST /api/v1/courier/pickup/{id}	Delivery (Member 3)	Confirm parcel physical pickup	ROLE_COURIER	Parcel ID (UUID path), location	200 OK	409 Conflict (Invalid Transition)
POST /api/v1/courier/deliver/{id}	Delivery (Member 3)	Complete delivery with POD attachment	ROLE_COURIER	Parcel ID (UUID path), proof_type, proof_photo_url	200 OK	400 Bad Request, 422 Unprocessable Entity
POST /api/v1/merchants/api-keys	Merchants (Member 4)	Provision SHA-256 API key	ROLE_MERCHANT	label, expires_in_days	201 Created	401 Unauthorized, 403 Forbidden
POST /api/v1/merchants/webhooks	Merchants (Member 4)	Configure outbound webhook endpoint	ROLE_MERCHANT	url, subscribed_events (array)	201 Created	400 Bad Request (SSRF validation failed)
POST /api/v1/merchant/parcels/bulk	Merchants (Member 4)	Batch ingest parcel shipments	ROLE_MERCHANT (API Key)	JSON array of parcel shipment items	202 Accepted	401 Unauthorized, 422 Unprocessable Entity
GET /api/v1/tracking/public/{trackingNumber}	Tracking (Member 5)	Public sanitized milestone tracking	Public	Tracking Number (path)	200 OK	404 Not Found

Method & Path	Subsystem & Owner	Description	Required Role / Auth	Request Body / Parameters	Success Code	Error Status Codes
GET /api/v1/tracking/public/{trackingNumber}/stream	Tracking (Member 5)	Real-time SSE status event stream	Public	Tracking Number (path)	200 OK (text/event-stream)	404 Not Found, 429 Too Many Requests
POST /api/v1/ai/chat	AI Assistant (Member 10)	Natural language query via FastMCP	Authenticated	prompt, conversation_id	200 OK	400 Bad Request, 503 Service Unavailable
GET /api/v1/admin/zones	Admin (Member 7)	Query configured delivery zones	ROLE_ADMIN	None	200 OK	401 Unauthorized, 403 Forbidden
POST /api/v1/admin/zones	Admin (Member 7)	Provision or update delivery zone	ROLE_ADMIN	code, name, postal_code_prefixes	201 Created	400 Bad Request, 409 Conflict
GET /api/v1/admin/events/outbox	Messaging (Member 8)	Inspect pending outbox publishing queue	ROLE_ADMIN	status, limit, offset	200 OK	401 Unauthorized, 403 Forbidden
GET /api/v1/admin/events/dlq	Messaging (Member 8)	Query dead-letter queue messages	ROLE_ADMIN	limit, offset	200 OK	401 Unauthorized, 403 Forbidden
POST /api/v1/admin/events/reconcile	Messaging (Member 8)	Trigger autonomous lease reset and cleanup	ROLE_ADMIN	dry_run, limit	200 OK	401 Unauthorized, 403 Forbidden

APPENDIX B: RBAC ROLE-PERMISSION MATRIX & SYSTEM ENTITLEMENTS

Table B.1 provides the comprehensive, authoritative Role-Based Access Control (RBAC) permission entitlement matrix enforced by the Core API and Traefik edge ingress controller:

Table B.1: Comprehensive RBAC Permission Matrix & System Entitlements

Permission / Capability	Customer	Commercial Merchant	Courier	Dispatcher	System Administrator	Public
auth:register / auth:login	Yes	Yes	Yes	Yes	Yes	Yes
pricing:quote (Tariff Calculation)	Yes	Yes	No	Yes	Yes	Yes
parcels:create (Book Shipment)	Yes (Personal)	Yes (Tenant Scoped)	No	No	Yes	No
parcels:read (View Own Details)	Yes (Own Only)	Yes (Tenant Scoped)	Yes (Assigned)	Yes (All Zone)	Yes (All)	Sanitized
parcels:cancel (Cancel Uncollected)	Yes (Own Only)	Yes (Tenant Scoped)	No	Yes (Zone)	Yes (All)	No
dispatch:assign (Advisory Lock)	No	No	No	Yes	Yes	No
courier:manifest (Daily Route)	No	No	Yes	Yes (Zone)	Yes (All)	No
delivery:attempt / delivery:pod	No	No	Yes	No	Yes	No
merchant:api-keys (Manage Credentials)	No	Yes	No	No	Yes	No
merchant:webhooks (Manage Endpoints)	No	Yes	No	No	Yes	No
tracking:stream (SSE Real-Time Push)	Yes	Yes	No	Yes	Yes	Yes (Sanitized)
ai:assistant:chat (Read-Only Tool)	Yes	Yes	Yes	Yes	Yes	Yes (Tracking only)

Permission / Capability	Customer	Commercial Merchant	Courier	Dispatcher	System Administrator	Public
admin:zones:write (Configure Zones)	No	No	No	No	Yes	No
admin:settings:write (Tariff Rules)	No	No	No	No	Yes	No
admin:events:read / dlq:manage	No	No	No	No	Yes	No
admin:audit:read (Audit Log Inspection)	No	No	No	No	Yes	No