

# CS2124 Exam One

2017 Fall

Note that I have omitted any `#includes` or `"using namespace std;"` statements in all questions, in order to save space and to save your time thinking about them. You may assume that all such statements that are needed are present. And you don't have to write them either!!!

Please, read all questions carefully!

Answering the short-answer questions, in particular, require that you read and *understand* the programs shown. You need to read them *carefully* if you are going to understand them.

If a question asks you to write a class or a function and shows you test code, be sure your class / function works with that test code.

If a question asks you to write a class or a function and shows you output, be sure your class / function generates that output, unless the spec states otherwise.

Questions	Points
1-6	4
7	10
8	10
9	20
10	40

Answer questions 1–8 in **this exam book**. For multiple choice questions, circle the correct answer. There should be only one correct answer / question.


Answer questions 9 and 10 in your **blue book**.

Place your name and id on every page in this book before the end of the exam. You will **lose four points** if you have not done so when we call "time to put your pens / pencils down." Sorry to be punitive, but some students seem to want to get that small advantage over their classmates.

For multiple choice questions, circle one answer!

1. [Extra credit] Who created C++?

- a) Gosling
- b) Hopper
- c) Ritchie
- ☒ d) Stroustrup



- e) Thompson
- f) van Rosum
- g) Wall
- h) None of the above

2. The expression  $p \rightarrow x$  means the same thing as:

- a)  $*p.x$
- b)  $*(p.x)$
- ☒ c)  $(*p).x$

- d) (a) and (c)
- e) all of the above
- f) none of the above

3. Given a class called Thing and the code

```
Thing thingOne, thingTwo;
```

What function call is the following line equivalent to?

```
thingTwo = thingOne;
```

- a) `Thing& Thing::operator=(const Thing& rhs)`
- b) `operator=(thingTwo, thingOne)`
- ☒ c) `thingTwo.operator=(thingOne)`
- ☒ d) Either (a) or (b), depending on how the programmer chose to implement the operator.
- e) None of the above because it is using the Thing copy constructor.
- f) None of the above

4. Given:

```
void foo(int x) {  
    int* (const) p = &x;    // line A  
    x = 17;                // line B  
    cout << *p << ' ';    // line C  
    *p = 28;               // line D  
}
```

```
int main() {  
    int y = 42;  
    foo(y);  
    cout << y << endl;  
}
```

circled  
change  
end of  
p → x = 42  
x = 17  
p → 28

17 42

2

n

What is the result of compiling and running the above code? (Circle only one answer)

- a) The program will have a compilation error at line A
- b) The program will have a compilation error at line B
- c) The program will have a compilation error at line C
- d) The program will have a compilation error at line D
- e) The program will have a runtime error (or undefined behavior) at line D.
- f) The program will print out: 17 17
- ☒ g) The program will print out: 17 42
- h) The program will print out: 42 17
- ☒ i) The program will print out: 42 42
- j) The program will print out: 17 28
- k) The program will print out: 42 28
- l) All of the above
- m) None of the above.

5. Given the following code:

```
class Holodeck {
public:
    Holodeck(int val) : program(val) {}
    void display() { cout << "Holodeck program: " << program << endl; }
private:
    int program = 17;
};

class Galaxy {
public:
    void display() { cout << "Galaxy class ship\n"; }
private:
    Holodeck something;
};

int main() {
    Galaxy nc1701d;
    nc1701d.display();
}
```

What is the result of compiling and running the above code?

- |  |  |
|--|--|
| a) Outputs:<br>Holodeck program: 17                      | d) Outputs:<br>Galaxy class ship<br>Holodeck program: 17                   |
| b) Outputs:<br>Galaxy class ship                         | e) Compile time error  |
| c) Outputs:<br>Holodeck program: 17<br>Galaxy class ship | <input checked="" type="radio"/> f) Run time error (or undefined behavior) |
|  | g) None of the above.  |

6. Using the ranged for (also known as the "foreach"), display the vector of ints called intVec (No, do not put this in a function.)

*-2 ranged-for*  
~~for (size\_t i = 0; i < intVec.size(); i++) {~~  
for (size\_t i = 0; i < intVec.size(); i++) {  
    cout << intVec[i] << endl;  
}

7. Given:

```
class ShuttleCraft {
public:
    ShuttleCraft(string s) : s(s) {}
    // ... possibly other methods
private:
    string s;
    // ... possibly other fields
};

class Orville {
public:
    Orville(string s) : p(new ShuttleCraft(s)) {}
    ~Orville() { delete p; }
private:
    ShuttleCraft* p;
};
```

Implement an appropriate assignment operator, i.e. a deep copy, for the class Orville. Write it below.  
(Oh, yes, the class ShuttleCraft supports copy control.)

<sup>-2 cond -1</sup>  
~~Orville~~ (Orville & secOr) { self-assignment check -2  
~~orville~~ = new secOr; No deep copy -2  
delete secOr; return \*this -2  
}

8. Given:

```
vector<int*> vip;
```

In the following three parts modify the vector that is defined above.  
(And no, you do not need to put your code in functions.)

- a) First, fill vip with the addresses of 100 ints that you have allocated on the heap. Each one will have the value 28.

```
int x = 0;  
int* num = new int(28);  
while (x < 100) {  
    vip.pushback(num);  
    x++;  
}
```

-1

- b) Now, modify those values in the vector by adding the index of the entry to the value that was stored on the heap, e.g. add 17 to integer pointed to by vip[17].

```
for (int i = 0; i < vip.size(); i++) {  
    vip[i] = *vip[i] + i;  
}
```

-2

- c) Finally, free up all of the entries on the heap. Do not leave any dangling pointers.

```
for (int i = 0; i < vip.size(); i++) {  
    delete vip[i];  
    vip[i] = nullptr;  
}
```

-2

Blue book

Answer questions 9 and 10 in your blue book.

9. [~12 lines of code] Given the type Thing:

```
struct Thing {  
    vector<int> stuff;  
};
```

write the following two functions,

**fill:** fills a vector with data from a file stream.

- The lines of the file each
  - start with a string "one", "two" or "three".
  - And then have that many ints on the rest of the line.
  - Example file:  
three 2 4 6  
one 12  
two 6 28  
one 8
- The vector holds Things, as defined above. Put the ints that show up on a single line into the vector in a Thing object. There should be one Thing object for each line in the file.
- Note the stream is already open, so you don't have to worry about that.

**totalStuff:**

- Passed the vector of Things. Computes and returns a single int which is the total of all the ints in all of Things in the the vector.
- For the above sample input file the function would return the sum  $2+4+6+12+6+28+8$  which I think is 66.

Below is an example program in which fill and totalStuff are called from main.

- Note that neither fill nor totalStuff are *methods*.
- Do not modify the Thing struct.

```
int main() {  
    ifstream ifs("stuff.txt");  
    vector<Thing> things;           // Note, not Thing pointers  
    fill(ifs, things);             // Implement this function  
    ifs.close();  
    cout << "Total stuff: "  
          << totalStuff(things)    // Implement this function  
          << endl;  
}
```

Answer in the blue book!!!

10. [~24 lines of code] These days the company that CS students all want to work for is *SnackChat*: this start-up knows that everyone likes to snack and to chat. They are not quite sure what their product will be, but that isn't going to stop them from seeking employees and investors!

Part of what makes working there so nice is the flexibility they provide in picking what group you get to work with. It's completely up to you! Not only that, but at the same time you are working as a member of one group, you can also be leading another group! Everyone can be a leader!

So, how does this all work?

- Well, if you want to *join* a group, all you do is say that you want to join the *leader* of that group. For example, `john.join(george)`, would result in john joining the team that george is in charge of. Remember, in this flexible company, george can also be a member of someone *else's* group. Work is never boring! (and there are plenty of snacks!)
- Naturally there are some issues to address. First, if you are already part of one group and then decide to instead join a different group your original will have to be notified and remove you. Again, if we remember john from our earlier example, who joined with george, if he now chooses to blend with mary, i.e. `john.join(mary)`, that call needs to remove him from george's group before adding him to mary's.
- By the way, we don't care about the order of the members in a group. After all, they're just all chatting together, anyway! (If that makes it easier for you to write your code, great. If not, don't worry about it.)
- A couple of cases we want to avoid:
  - Joining with yourself would be uninteresting, so we won't allow that to occur.
  - Also, it would be confusing if first george joined with mary and then mary joined with george. If they had meetings, how would they know who was in charge?!? Can't have that, so you can't join with someone who is currently already joined with you. (i.e. you can't join the group of someone who is in the group that you lead.)
  - And of course, we don't want people joining a group that they are already in. That would result in confusing duplication if allowed or annoying paperwork for the human resources department. So, trying to join with the leader of your current group doesn't work.
- Finally, we really should have *some* error checking code. Our `join` method will return `true` if we successfully joined with the leader and `false` otherwise. This way we won't "fail silently".

Below is a sample scenario. **Your job is just to define the Chip class**, together with its constructor, a `display` method and the `join` method. (Yes people who work there call themselves Chips. They tried very hard to find a word that connecting snacking and chatting and this was the best they could do. I hope they are more successful with their product.)

Note the `display` method's output. Your class's definition should generate the output as shown, except possibly for the order of the Chips in a group. (Remember, we don't care about order.)

And finally, no, this problem does not involve copy control or the heap.



### Test Code:

```
int main() {
    Chip moe("Moe");
    Chip larry("Larry");
    Chip curly("Curly");
    Chip curly2("Curly");

    moe.join(larry);    // Returns true
    larry.display();
    curly.join(larry); // Returns true
    curly2.join(larry); // Returns true. Now we have two Chips named Curly in the group
    larry.display();
    larry.join(moe);    // Returns false
    moe.join(moe);      // Returns false
    moe.join(larry);    // Returns false
    curly2.join(moe);   // Returns true. Curly2 has switched allegiance.
    moe.display();
    larry.display();
    curly2.display();
}
```

### Output:

```
Name: Larry; Leader: none; Chips: Moe.
Name: Larry; Leader: none; Chips: Moe Curly Curly.
Name: Moe; Leader: Larry; Chips: Curly.
Name: Larry; Leader: none; Chips: Moe Curly.
Name: Curly; Leader: Moe; Chips: none.
```

Write your answer in the Blue Book!

Chip {  
    name  
    leaders array  
    vector of string of chips

void

Q(-3)



9) fill ifstream ifs, vector<Thing> & things) {

string number

int num, num1, num2;

while (ifs >> number) {

if (number == "one") {

ifs >> num;

~~things.stuff.pushback(num);~~

Thing block;

block.stuff.pushback(num);

things.pushback(block);

}

else if (number == "two") {

ifs >> num >> num1;

Thing block;

block.stuff.pushback(num);

block.stuff.pushback(num1);

things.pushback(block); }

else if (number == "three") {

ifs >> num >> num1 >> num2;

Thing block;

block.stuff.pushback(num);

block.stuff.pushback(num1);

block.stuff.pushback(num2);

things.pushback(block);

}

}

}

9

## CONST REF (-2)

```
int totalStuff (vector<Thing> things){  
    int count = 0;  
    for (int i = 0; i < things.size(); i++){  
        for (int j = 0; j < things[i].stuff.size(); j++){  
            count += things[i].stuff[j];  
        }  
    }  
    return count;  
}
```

6

12

10) class Chip {

4

public:

Chip(const string& name): name(name) {}

2

void display { ~~const~~ (-5)

cout << "Name: " << name << "; leader: " <<

leader << "; chips: " << display-chips() << endl;

} with get-name() const { return name; }

void display-chips() {

for (int i = 0; i < vector-of-chips.size(); i++) {

cout << vector-of-chips[i] << " ";

}

}

6

bool join(Chip& chip2) { 4 + 0 2

~~chip2.name~~

for (int i = 0; i < vector-of-chips.size(); i++)

if (chip2.get-name() != name) {

vector-of-chips.pushback(chip2.get-name());

chip2.leader = this;

return true;

}

~~return false;~~

~~return false;~~

} }

return false;

}

→ private:

0

string name; ~~no up r~~

string leader = "none";

vector<string> vector-of-chips;