

PHARMARIDGE WEB â MAINTENANCE AND DEPLOYMENT GUIDE

Repository: 'https://github.com/pharmaridge/web'

Live site: 'https://pharmaridge.github.io/web/'

1. One-time Windows / PowerShell / VS Code setup

Install Git for Windows and VS Code. In PowerShell, configure your Git identity:

```
git config --global user.name "Your Name"
git config --global user.email "you@example.com"
```

Use the current GitHub SSH key. If the key is already registered with GitHub, test it:

```
ssh -T git@github.com
```

A successful response normally says that GitHub authenticated you. Never paste a GitHub personal access token into the repository, a script, or a remote URL.

If a key has not been created yet:

```
ssh-keygen -t ed25519 -C "you@example.com"
Get-Content $HOME\.ssh\id_ed25519.pub | Set-Clipboard
```

Add the copied public key at GitHub: ****Settings â SSH and GPG keys â New SSH key****.

2. Pull the current website over SSH

Clone it once:

```
cd $HOME\Documents
git clone git@github.com:pharmaridge/web.git
cd .\web
code .
```

If the folder already exists, switch to the deployed branch and pull safely:

```
cd $HOME\Documents\web
git remote set-url origin git@github.com:pharmaridge/web.git
git switch main
git pull --ff-only origin main
code .
```

Confirm the remote is using SSH:

```
git remote -v
```

It should show 'git@github.com:pharmaridge/web.git' for fetch and push.

3. Make and preview a change in VS Code

This is a static site. The main files are:

- â€¢ 'index.html' â€” page content and structure
- â€¢ 'styles.css' â€” layout, responsive design, animation and visual styling
- â€¢ 'app.js' â€” carousels, admin drawer, client showcase and browser storage
- â€¢ 'assets/' â€” only the image assets used by the public site

Run a local preview from the VS Code terminal:

```
python -m http.server 4173
```

Open 'http://localhost:4173' in a browser. Stop the server with 'Ctrl+C'.

Before committing, check the change:

```
git status
git diff
```

4. Commit, push and redeploy

GitHub Pages redeploys automatically after a push to 'main' through
'github/workflows/pages.yml'.

```
git add index.html styles.css app.js assets PHARMARIDGE_SETUP.md .github\workflows\pages.yml
git commit -m "Describe the change"
git push origin main
```

Monitor deployment at:

<https://github.com/pharmaridge/web/actions>

After the workflow succeeds, allow a minute or two for cache refresh and then open:

<https://pharmaridge.github.io/web/>

If a push is rejected, do not use a personal access token in the remote URL. Confirm that the SSH key belongs to a GitHub account with write access to 'pharmaridge/web'.

5. Admin workspace

The admin entry point is intentionally discreet and is not displayed in the main navigation.

Find it at the very bottom of the public website footer:

****Privacy • Terms • Workspace access****

Click ****Workspace access**** to open the admin drawer.

Current credentials

There are currently ****no username or password credentials****. This project contains a front-end demo admin drawer, not a secured production admin backend. Its edits are stored in the browser's 'localStorage' and are only visible in that browser.

The drawer currently supports editing:

- â€ Support email
- â€ Phone number
- â€ Head office
- â€ Plan pricing
- â€ Announcement message
- â€ Client name

- â€¢ Client logo upload
- â€¢ Client story
- â€¢ Removing client showcase entries

Important production note

Do not use the current browser-only admin for real customer, pricing or client data. Before launch, add a real authentication and backend service with:

- â€¢ Server-side sessions or a managed identity provider
- â€¢ Password reset and MFA
- â€¢ Role-based permissions
- â€¢ Database-backed settings and client profiles
- â€¢ Secure image storage
- â€¢ Audit logs
- â€¢ Server-side validation

The current admin is suitable for design review and static-site demonstrations only.

6. Production admin portal

The production admin portal is available at:

<https://pharmaridge.github.io/web/admin.html>

It is powered by Supabase and supports:

- â€¢ Email/password authentication
- â€¢ Authenticated client management
- â€¢ Client logo uploads to Supabase Storage
- â€¢ Public client showcase publishing
- â€¢ Client removal
- â€¢ Row-level security policies

Supabase setup

1. Create a Supabase project.
2. Run 'supabase-schema.sql' in the Supabase SQL Editor.
3. In Supabase Authentication, create the first admin user under **Authentication â€¢ Users**.
4. In the GitHub repository, open **Settings â€¢ Secrets and variables â€¢ Actions**.
5. Add these repository secrets:

SUPABASE_URL=https://your-project.supabase.co
SUPABASE_ANON_KEY=your-public-anon-key

6. Push to 'main' or manually run the Pages workflow.
7. Open '/web/admin.html' and sign in with the Supabase admin user.

The Supabase anon key is designed to be exposed in a browser. Never put the Supabase service-role key in GitHub Pages, JavaScript, or the repository. The SQL policies are the security boundary.

The current client showcase in 'app.js' is retained as a local fallback for design preview, while 'public-data.js' reads published client profiles from Supabase in production.

Changeable public site details

After running the updated 'supabase-schema.sql', sign in at '/web/admin.html'. The **Public site settings** panel lets an authenticated administrator change:

- â€¢ Contact email
- â€¢ Contact number
- â€¢ Head office
- â€¢ Top announcement
- â€¢ Essential plan price
- â€¢ Partner plan price

Changes are stored in Supabase and read by the public website. Do not edit these values in the browser developer tools; use the authenticated admin portal so the database remains the source of truth.

Video and document libraries

Run 'supabase-media-extension.sql' in Supabase SQL Editor to create:

- â€¢ 'video_library' for YouTube videos
- â€¢ 'resource_library' for Google Docs and other Google document links

From the admin portal, choose **YouTube video** or **Google document link** in the content type selector. Enter a title, a dynamic category, the YouTube/Google URL and a description.

Published videos appear in the public video library with YouTube key-frame thumbnails and play links. Categories become filter buttons automatically. Published documents appear in the resource library and open in a new tab.

Website enquiries

The contact form stores each enquiry in Supabase table 'inquiries' with:

- â€ Email
- â€ Enquiry type
- â€ Message
- â€ Status ('new', 'in_progress', 'resolved', 'archived')
- â€ Created and updated timestamps

Run 'supabase-inquiries.sql' in Supabase SQL Editor. Then open the admin portal and choose ****Enquiries****. Admins can review, change status or delete enquiries.

The public form does not expose private admin data. Visitors have insert-only access; only authenticated admins can read, update or delete the inbox. For email notifications, connect a Supabase Edge Function or an automation service such as Resend after the insert trigger.