

```
In [1]: import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
```

```
In [2]: #function to calculate the loss of a model
def get_loss(x, y, theta):
    """x is input data (m x n)
        y is ground truths (m x 1)
        theta is model params (n x 1)"""
    h = x.dot(theta)
    error = np.subtract(h, y)
    sqError = np.square(error)
    sumSqError = np.sum(sqError)
    avgSqError = sumSqError / (2 * len(y))
    return avgSqError
```

```
In [3]: #Function to run the gradient descent algorithm
def gradient_descent(x, y, theta, a, iterations):
    """x is input data (m x n)
        y is ground truths (m x 1)
        theta is model params (n x 1)
        a is learn rate (scalar)
        iterations. duh. (scalar)"""
    losses = np.zeros(iterations)
    for i in range(iterations):
        h = x.dot(theta)
        error = np.subtract(h, y)
        delta = x.transpose().dot(error)
        grad = delta / len(y)
        theta = theta - (a * grad)
        losses[i] = get_loss(x, y, theta)
    return theta, losses
```

```
In [4]: #Read in the CSV into a dataframe
csvData = pd.read_csv("./D3.csv")

csvData.head(5)
```

Out[4]:

| | X1 | X2 | X3 | Y |
|---|----------|----------|----------|----------|
| 0 | 0.000000 | 3.440000 | 0.440000 | 4.387545 |
| 1 | 0.040404 | 0.134949 | 0.888485 | 2.679650 |
| 2 | 0.080808 | 0.829899 | 1.336970 | 2.968490 |
| 3 | 0.121212 | 1.524848 | 1.785455 | 3.254065 |
| 4 | 0.161616 | 2.219798 | 2.233939 | 3.536375 |

```
In [5]: #Begin Part A Code
```

```
In [6]: #SETTINGS for Part A
# Learn rate
LEARN_RATE = 0.025
# Gradient descent iterations
ITERATIONS = 1000
```

```
In [7]: #convert the dataframe into formatted np arrays

csvCols = len(csvData.columns)
csvRows = len(csvData)

y = csvData.values[:,csvCols-1].reshape(csvRows, 1)

y[0:5,:]
```

```
Out[7]: array([[4.38754501],
               [2.6796499 ],
               [2.96848981],
               [3.25406475],
               [3.53637472]])
```

```
In [8]: #format x1 values
x1 = np.ones((csvRows, 1))
col1 = csvData.values[:,0].reshape(csvRows, 1)
x1 = np.hstack((x1, col1))

x1[0:5,:]
```

```
Out[8]: array([[1.          , 0.          ],
               [1.          , 0.04040404],
               [1.          , 0.08080808],
               [1.          , 0.12121212],
               [1.          , 0.16161616]])
```

```
In [9]: #format x2 values
x2 = np.ones((csvRows, 1))
col2 = csvData.values[:,1].reshape(csvRows, 1)
x2 = np.hstack((x2, col2))

x2[0:5,:]
```

```
Out[9]: array([[1.          , 3.44        ],
               [1.          , 0.1349495 ],
               [1.          , 0.82989899],
               [1.          , 1.52484848],
               [1.          , 2.21979798]])
```

```
In [10]: #format x3 values
x3 = np.ones((csvRows, 1))
col3 = csvData.values[:,2].reshape(csvRows, 1)
x3 = np.hstack((x3, col3))

x3[0:5,:]
```


```
Out[10]: array([[1.      , 0.44      ],
 [1.      , 0.88848485],
 [1.      , 1.3369697 ],
 [1.      , 1.78545454],
 [1.      , 2.23393939]])
```

```
In [11]: #Run the gradient descent
theta1 = np.zeros((2,1))
theta1, loss1 = gradient_descent(x1,y,theta1,LEARN_RATE,ITERATIONS)

print("Converged Loss for h(X1): {0:.3f}".format(loss1[ITERATIONS-1]))
print("Trained Model for h(X1) = {0:.3f} X1 + {1:.3f}".format(theta1[1,0],theta1[0,0]))

plt.rcParams["figure.figsize"] = (10,5)
plt.grid()
plt.xlabel('Number of iterations')
plt.ylabel('Loss (J)')
plt.title('Convergence of gradient descent for X1 at a={}'.format(LEARN_RATE))
plt.plot(range(1, ITERATIONS + 1),loss1, color='blue');
```

Converged Loss for h(X1): 0.985
 Trained Model for h(X1) = -2.030 X1 + 5.905




```
In [12]: #Run the gradient descent
theta2 = np.zeros((2,1))
theta2, loss2 = gradient_descent(x2,y,theta2,LEARN_RATE,ITERATIONS)

print("Converged Loss for h(X2): {0:.3f}".format(loss2[ITERATIONS-1]))
print("Trained Model for h(X2) = {0:.3f} X2 + {1:.3f}".format(theta2[1,0],theta2[0,0]))

plt.rcParams["figure.figsize"] = (10,5)
plt.grid()
plt.xlabel('Number of iterations')
plt.ylabel('Loss (J)')
plt.title('Convergence of gradient descent for X2 at a={}'.format(LEARN_RATE))
plt.plot(range(1, ITERATIONS + 1),loss2, color='blue');
```

Converged Loss for h(X2): 3.599

Trained Model for h(X2) = 0.558 X2 + 0.734




```
In [13]: #Run the gradient descent
theta3 = np.zeros((2,1))
theta3, loss3 = gradient_descent(x3,y,theta3,LEARN_RATE,ITERATIONS)

print("Converged Loss for X3: {0:.3f}".format(loss3[ITERATIONS-1]))
print("Trained Model for h(X3) = {0:.3f} X3 + {1:.3f}".format(theta3[1,0],theta3[0,0]))

plt.rcParams["figure.figsize"] = (10,5)
plt.grid()
plt.xlabel('Number of iterations')
plt.ylabel('Loss (J)')
plt.title('Convergence of gradient descent for X3 at a={}'.format(LEARN_RATE))
plt.plot(range(1, ITERATIONS + 1),loss3, color='blue');
```

Converged Loss for X3: 3.629

Trained Model for $h(X3) = -0.517 X3 + 2.862$



```
In [14]: #End Part A Code,
#Begin Part B code
```

```
In [15]: #SETTINGS for Part B
# Learn rate
LEARN_RATE = 0.055
# Gradient descent iterations
ITERATIONS = 1000
```

In [16]: *#convert the dataframe into formatted np arrays*

```
#initialize some variables
csvCols = len(csvData.columns)
csvRows = len(csvData)

x = np.ones((csvRows, 1))
y = csvData.values[:,csvCols-1].reshape(csvRows, 1)
for i in range(0,csvCols-1): #populate x
    col = csvData.values[:,i].reshape(csvRows, 1)
    x = np.hstack((x, col))

print("first two X")
print(x[0:2,:])
print("first two Y")
print(y[0:2,:])
```

first two X

```
[[1.          0.          3.44          0.44          ]
 [1.          0.04040404 0.1349495  0.88848485]]
```

first two Y

```
[[4.38754501]
 [2.6796499 ]]
```


```
In [17]: #Run the gradient descent
theta = np.zeros((csvCols,1))
theta, loss = gradient_descent(x,y,theta,LEARN_RATE,ITERATIONS)
print("Converged Loss J = {:.3f}".format(loss[ITERATIONS-1]))
print("Trained Model h(X1,X2,X3) = {0:.3f} X1 + {1:.3f} X2 + {2:.3f} X3 + {3:.3f} X4".format(float(theta[1]),float(theta[2]),float(theta[3]),float(theta[0])))

plt.rcParams["figure.figsize"] = (10,5)
plt.grid()
plt.xlabel('Number of iterations')
plt.ylabel('Loss (J)')
plt.title('Convergence of gradient descent for a={}'.format(LEARN_RATE))
plt.plot(range(1, ITERATIONS + 1),loss, color='blue')
```

Converged Loss J = 0.738

Trained Model $h(X_1, X_2, X_3) = -2.001 X_1 + 0.536 X_2 + -0.262 X_3 + 5.293$

Out[17]: [matplotlib.lines.Line2D at 0x1ec395bd1f0<]



```
In [18]: XV = np.array([[1, 1, 1],[2, 0, 4],[3, 2, 1]])
XV = np.hstack((np.ones((3, 1)), XV))
print("XV")
print(XV)
H = XV.dot(theta)
print("h(XV)")
print(H)
```

```
XV
[[1. 1. 1. 1.]
 [1. 2. 0. 4.]
 [1. 3. 2. 1.]]
h(XV)
[[3.56577916]
 [0.24153226]
 [0.10042608]]
```

